


$L^*/Y_{\text{intendert}}$ (absolutt)	18.0/18.0	37.3/37.3	56.7/56.7	76.1/76.0	95.4/95.4	N_0 (min.)	W_1 (max.)
$w^* = l^*_{\text{CIE LAB}, r}$ (relativ)							
w^*_{input} w^*_{output}	0,000	0,250	0,500	0,750	1,000	N_0 (min.)	W_1 (max.)

L^*/Y_i intendert (absolutt)	18.0/18.0	23.2/23.2	28.3/28.3	33.5/33.5	38.6/38.6	43.8/43.8	49.0/49.0	54.1/54.1	59.3/59.3	64.4/64.4	69.6/69.6	74.8/74.8	79.9/79.9	85.1/85.1	90.2/90.2	95.4/95.4
Nr. og Hex-code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$W^*=L^*_{CIE LAB, r}$ (relativ)																
W^*_{input} W^*_{output}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000

5-113130-F0



kode: omfelt-ring

TN721-1, Figur C4Wde: Element D: Landoltringer W-N; PS operator: *rgb/cmy0*



TN721-3, Figur C5Wde: Element E: Linjeraster med 45° (eller 135°); PS operator: *rgb/cmy0*



TN721-5, Figur C6Wde: Element F: Linjeraster med 90° (eller 0°); PS operator: *rgb/cmy0*