

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für E00, $Y_w=100$, $Y_m=520_770$, LINYAB-Daten													%
i_1, λ_1	i_2, λ_2	Y_{100}	A_{100}	B_{100}	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	%	
1	405	32	564	57.42	-24.95	-16.34	29.83	0.5653	-0.6845	213.2	16 484 38 592	Cm	%
6	435	33	565	57.91	-29.14	-7.99	30.22	0.4967	-0.538	195.3	17 488 45 627		%
10	450	33	566	58.45	-35.13	5.29	35.53	0.3988	-0.3094	171.4	19 498 -1 498c		%
12	460	33	568	59.28	-37.54	11.81	39.35	0.3666	-0.2007	162.5	21 507 -1 507c		%
13	465	33	569	60.14	-38.45	14.78	41.19	0.3606	-0.1541	158.9	22 514 -1 514c		%
14	470	34	571	61.52	-38.94	17.52	42.7	0.3669	-0.1152	155.7	24 522 -1 522c		%
14	475	35	575	64.53	-39.14	18.72	43.38	0.3934	-0.1098	154.4	25 525 -1 525c	Gm	%
16	480	36	581	68.21	-38.3	23.26	44.81	0.4385	-0.0589	148.7	27 538 -1 538c		%
17	485	39	595	76.7	-34.16	27.66	43.96	0.5546	-0.0393	140.9	29 549 -1 549c		%
18	490	-1	490c	94.54	-11.19	35.56	37.28	0.8815	-0.0238	107.4	33 568 11 459	max	%
19	495	-1	495c	93.18	-9.88	35.6	36.94	0.8939	-0.0179	105.5	33 568 12 461		%
19	500	-1	499c	93.18	-9.88	35.6	36.94	0.8939	-0.0179	105.5	33 568 12 461		%
22	510	-1	510c	86.74	-3.57	34.08	34.26	0.9587	-0.0071	95.9	34 571 13 469		%
24	520	-1	520c	80.14	2.4	31.74	31.83	1.0299	-0.0038	85.6	34 574 14 473	Ym	%
26	530	-1	530c	72.11	8.87	28.69	30.03	1.123	-0.0021	72.8	35 577 15 477		%
28	540	-1	540c	63.21	15.04	25.21	29.35	1.2379	-0.0011	59.1	36 581 15 479		%
29	545	-1	545c	58.59	17.8	23.38	29.39	1.3039	-0.0009	52.7	36 583 16 480		%
29	550	-1	549c	58.59	17.8	23.38	29.39	1.3039	-0.0009	52.7	36 583 16 480		%
30	555	-1	554c	53.92	20.26	21.53	29.56	1.3757	-0.0007	46.7	37 585 16 482		%
32	560	-1	560c	44.64	23.98	17.83	29.88	1.5372	-0.0005	36.6	38 590 16 483		%
	380	770	100.0	0.0	0.0	0.0	0.01	1.0	-0.4	0.0			%
Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für E00, $Y_w=100$, $Y_m=770_520$, LINYAB komplementär%													%
i_1, λ_1	i_2, λ_2	Y_{100}	A_{100}	B_{100}	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	%	
32	564	1	405	42.57	24.95	16.34	29.83	1.5862	-0.0161	33.2	38 592 16 484	Rm	%
33	565	6	435	42.08	29.14	7.99	30.22	1.6926	-0.21	15.3	45 627 17 488		%
33	566	10	450	41.54	35.13	-5.29	35.53	1.8457	-0.5274	351.4	-1 498c 19 498		%
33	568	12	460	40.71	37.54	-11.81	39.35	1.9221	-0.6901	342.5	-1 507c 21 507		%
33	569	13	465	39.85	38.45	-14.78	41.19	1.9647	-0.771	338.9	-1 514c 22 514		%
34	571	14	470	38.47	38.94	-17.51	42.7	2.0122	-0.8553	335.7	-1 522c 24 522		%
35	575	14	475	35.46	39.14	-18.72	43.38	2.1036	-0.9278	334.4	-1 525c 25 525	Mm	%
36	581	16	480	31.78	38.3	-23.26	44.81	2.205	-1.1319	328.7	-1 538c 27 538		%
39	595	17	485	23.29	34.16	-27.66	43.96	2.4665	-1.5876	320.9	-1 549c 29 549		%
-1	490c	18	490	5.45	11.19	-35.56	37.28	3.0513	-6.9152	287.4	11 459 33 568	min	%
-1	495c	19	495	6.81	9.88	-35.6	36.94	2.4491	-5.6211	285.5	12 461 33 568		%
-1	499c	19	500	6.81	9.88	-35.6	36.94	2.4491	-5.6211	285.5	12 461 33 568		%
-1	510c	22	510	13.25	3.57	-34.08	34.26	1.2699	-2.9707	275.9	13 469 34 571		%
-1	520c	24	520	19.85	-2.4	-31.74	31.83	0.879	-1.9985	265.6	14 473 34 574	Bm	%
-1	530c	26	530	27.88	-8.87	-28.69	30.03	0.6818	-1.4288	252.8	15 477 35 577		%
-1	540c	28	540	36.78	-15.04	-25.21	29.35	0.591	-1.0854	239.1	15 479 36 581		%
-1	545c	29	545	41.4	-17.8	-23.38	29.39	0.5699	-0.9647	232.7	16 480 36 583		%
-1	549c	29	550	41.4	-17.8	-23.38	29.39	0.5699	-0.9647	232.7	16 480 36 583		%
-1	554c	30	555	46.07	-20.26	-21.53	29.56	0.5601	-0.8673	226.7	16 482 37 585		%
-1	560c	32	560	55.35	-23.98	-17.83	29.88	0.5668	-0.7221	216.6	16 483 38 590		%
	380	770	100.0	0.0	0.0	0.0	0.01	1.0	-0.4	0.0			%