

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für E00, Y _w =100, Y _m =520...770, CIELAB-Daten																
l	λ ₁	λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	l _d	λ _d	l _c	λ _c	Code	%	
1	405	32	564	80.42	-71.93	-32.6	78.97	0.1811	-0.1001	204.3	16	484	38	592	Cm	%
6	435	33	565	80.69	-86.68	-17.31	88.4	0.1735	-0.0924	191.2	17	488	45	627		%
10	450	33	566	80.99	-110.3	13.71	111.15	0.1612	-0.0768	172.9	19	498	-1	498c		%
12	460	33	568	81.45	-119.36	34.48	124.25	0.1568	-0.0665	163.8	21	507	-1	507c		%
13	465	33	569	81.92	-121.61	45.97	130.01	0.1559	-0.0609	159.2	22	514	-1	514c		%
14	470	34	571	82.66	-120.77	57.74	133.86	0.1568	-0.0553	154.4	24	522	-1	522c		%
14	475	35	575	84.24	-115.44	60.46	130.32	0.1605	-0.0544	152.3	25	525	-1	525c	Gm	%
16	480	36	581	86.11	-105.73	83.03	134.43	0.1664	-0.0442	141.8	27	538	-1	538c		%
17	485	39	595	90.19	-81.64	98.55	127.97	0.18	-0.0386	129.6	29	549	-1	549c		%
18	490	-1	490c	97.85	-20.19	119.57	121.26	0.21	-0.0327	99.5	33	568	11	459	max	%
19	495	-1	495c	97.3	-17.91	125.92	127.19	0.211	-0.0297	98.0	33	568	12	461		%
19	500	-1	499c	97.3	-17.91	125.92	127.19	0.211	-0.0297	98.0	33	568	12	461		%
22	510	-1	510c	94.63	-6.64	140.85	141.01	0.216	-0.0218	92.7	34	571	13	469		%
24	520	-1	520c	91.75	4.59	146.03	146.1	0.2212	-0.0178	88.1	34	574	14	473	Ym	%
26	530	-1	530c	88.02	17.68	145.85	146.92	0.2277	-0.0145	83.0	35	577	15	477		%
28	540	-1	540c	83.56	31.64	141.2	144.7	0.2352	-0.0119	77.3	36	581	15	479		%
29	545	-1	545c	81.07	38.69	137.62	143.05	0.2393	-0.0109	74.3	36	583	16	480		%
29	550	-1	549c	81.07	38.69	137.62	143.05	0.2393	-0.0109	74.3	36	583	16	480		%
30	555	-1	554c	78.42	45.65	133.68	141.26	0.2436	-0.0102	71.1	37	585	16	482		%
32	560	-1	560c	72.66	58.88	124.34	137.58	0.2528	-0.0092	64.6	38	590	16	483		%
380	770	100.0	0.0	0.0	0.0	0.0	0.0	0.2191	-0.0837	0.0	0.0	0.0	0.0	0.0		%

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für E00, Y _w =100, Y _m =770...520, CIELAB komplementär%																
l	λ ₁	λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	l _d	λ _d	l _c	λ _c	Code	%	
33	564	1	405	71.27	62.52	98.78	116.91	0.2555	-0.0287	57.6	38	592	16	484	Rm	%
33	565	6	435	70.93	71.83	28.95	77.45	0.2611	-0.0675	21.9	45	627	17	488		%
33	566	10	450	70.56	84.55	-14.4	85.77	0.2687	-0.0918	350.3	-1	498	19	498		%
33	568	12	460	69.98	90.17	-29.54	94.89	0.2724	-0.1004	341.8	-1	507	21	507		%
33	569	13	465	69.37	92.89	-35.98	99.61	0.2744	-0.1042	338.8	-1	514	22	514		%
34	571	14	470	68.37	95.44	-41.93	104.24	0.2766	-0.1079	336.2	-1	522	24	522		%
35	575	14	475	66.11	99.55	-45.82	109.39	0.2807	-0.1108	335.2	-1	525	25	525	Mm	%
36	581	16	480	63.17	102.89	-56.56	117.41	0.2851	-0.1184	331.2	-1	538	27	538		%
39	595	17	485	55.38	108.0	-71.77	129.67	0.296	-0.1326	326.3	-1	549	29	549		%
-1	490c	18	490	28.02	85.37	-120.26	147.48	0.3177	-0.2165	305.3	11	459	33	568	min	%
-1	495c	19	495	31.41	71.03	-115.43	135.53	0.2953	-0.2021	301.6	12	461	33	568		%
-1	499c	19	500	31.41	71.03	-115.43	135.53	0.2953	-0.2021	301.6	12	461	33	568		%
-1	510c	22	510	43.16	21.12	-96.96	99.24	0.2372	-0.1634	282.2	13	469	34	571		%
-1	520c	24	520	51.68	-12.26	-82.78	83.68	0.2098	-0.1431	261.5	14	473	34	574	Bm	%
-1	530c	26	530	59.79	-39.13	-69.07	79.38	0.1928	-0.128	240.4	15	477	35	577		%
-1	540c	28	540	67.12	-57.58	-56.56	80.72	0.1838	-0.1168	224.4	15	479	36	581		%
-1	545c	29	545	70.46	-63.67	-50.83	81.48	0.1816	-0.1123	218.6	16	480	36	583		%
-1	549c	29	550	70.46	-63.67	-50.83	81.48	0.1816	-0.1123	218.6	16	480	36	583		%
-1	554c	30	555	73.6	-67.81	-45.45	81.64	0.1806	-0.1084	213.8	16	482	37	585		%
-1	560c	32	560	79.25	-70.77	-35.73	79.28	0.1813	-0.1019	206.7	16	483	38	590		%
380	770	100.0	0.0	0.0	0.0	0.0	0.0	0.2191	-0.0837	0.0	0.0	0.0	0.0	0.0		%

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für E00, Y _w =10-100, Y _m =520...770, CIELAB-Daten																
l	λ ₁	λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	l _d	λ _d	l _c	λ _c	Code	%	
1	405	31	559	79.43	-69.97	-33.95	77.77	0.1818	-0.101	205.8	15	477	37	589	Cm	%
7	435	32	561	79.66	-92.09	-9.07	92.53	0.1701	-0.0883	185.6	16	484	-1	484c		%
10	450	32	562	79.85	-108.58	17.48	109.98	0.1615	-0.0748	170.8	18	493	-1	493c		%
12	460	33	565	80.46	-114.73	39.56	121.36	0.1586	-0.0638	160.9	21	506	-1	506c		%
13	465	33	568	81.27	-113.49	52.13	124.89	0.1597	-0.0577	155.3	23	515	-1	515c		%
13	470	34	572	83.3	-106.48	55.62	120.14	0.1645	-0.0565	152.4	24	520	-1	520c		%
14	475	36	581	86.11	-93.97	71.54	118.1	0.1723	-0.0497	142.7	26	532	-1	532c	Gm	%
16	480	40	604	91.81	-55.72	101.41	115.71	0.1928	-0.038	118.7	30	551	-1	551c		%
17	485	-1	485c	96.74	-15.85	118.68	119.73	0.2119	-0.0326	97.6	32	564	11	456		%
18	490	-1	490c	96.74	-13.14	125.53	126.21	0.2131	-0.0293	95.9	32	564	11	456	max	%
19	495	-1	495c	95.33	-9.88	131.41	131.41	0.2145	-0.0263	94.3	33	565	12	460		%
20	500	-1	500c	94.43	-6.08	136.47	136.6	0.2162	-0.0236	92.5	33	566	12	462		%
22	510	-1	510c	92.16	3.03	143.93	143.96	0.2205	-0.019	88.7	33	569	13	466		%
23	520	-1	519c	90.77	8.29	146.41	146.64	0.223	-0.0169	86.7	34	570	13	468	Ym	%
25	530	-1	529c	87.45	19.7	146.61	147.93	0.2287	-0.013	82.3	34	573	14	470		%
27	540	-1	539c	83.46	31.82	142.58	146.09	0.2353	-0.0092	77.4	35	577	14	473		%
29	545	-1	545c	78.83	44.02	135.72	142.68	0.2426	-0.0052	72.0	36	582	15	475		%
29	550	-1	549c	78.83	44.02	135.72	142.68	0.2426	-0.0052	72.0	36	582	15	475		%
31	555	-1	555c	73.61	55.53	126.92	138.53	0.2505	0.0	66.3	37	587	15	476		%
32	560	3	415	70.87	63.43	69.32	93.97	0.2562	-0.0449	47.5	39	595	15	478		%
380	770	100.0	0.0	0.0	0.0	0.0	0.0	0.219	-0.0837	0.0	0.0	0.0	0.0	0.0		%

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für E00, Y _w =10-100, Y _m =770...520, CIELAB komplementär																
l	λ ₁	λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	l _d	λ _d	l _c	λ _c	Code	%	
31	559	1	405	72.45	58.84	95.98	112.58	0.2529	-0.0309	58.4	37	589	15	477	Rm	%
32	561	7	435	72.18	71.63	12.24	72.67	0.2603	-0.077	9.6	-1	484c	16	484	Bm	%
32	562	10	450	71.95	79.98	-16.73	81.72	0.2653	-0.093	348.1	-1	493c	18	493		%
33	565	12	460	71.21	84.68	-30.98	90.17	0.2684	-0.101	339.9	-1	506c	21	506		%
33	568	13	465	70.2	86.97	-37.58	94.74	0.2703	-0.1049	336.6	-1	515c	23	515		%
34	572	13	470	67.81	91.21	-42.27	100.53	0.2746	-0.1083	335.1	-1	520c	24	520		%
36	581	14	475	63.17	95.86	-53.49	109.78	0.2806	-0.1165	330.8	-1	532c	26	532	Mm	%
40	604	16	480	51.52	92.9	-78.43	121.58	0.289	-0.1402	319.8	-1	551c	30	551		%
-1	485c	17	485	34.38	59.2	-109.46	124.44	0.2788	-0.1893	298.4	11	456	32	564		%
-1	490c	18	490	37.42	46.35	-105.27	115.03	0.2632	-0.1795	293.7	11	458	32	564	min	%
-1	495c	19	495	40.57	32.86	-106.0	105.83	0.2486	-0.1701	288.0	12	460	33	566		%
-1	500c	20	500	43.84	19.01	-95.52	97.39	0.2352	-0.1613	281.2	12	462	33	566		%
-1	510c	22	510	50.61	-8											