

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520, 770, LINYAB-Daten																
λ ₁	λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	H _{AB}	λ _d	λ _c	λ _e	Code	%			
0	405	32	561	58.2	-22.74	-17.89	28.94	0.5596	-0.743	218.1	16	483	37	589	Cm	%
6	435	32	562	58.79	-26.78	-9.88	28.55	0.4948	-0.6036	200.2	17	486	42	610		
10	450	32	563	59.42	-33.54	4.93	23.59	0.3859	-0.3525	171.6	19	496	-1	496c		
12	460	33	565	60.32	-36.45	12.66	38.58	0.3461	-0.2256	160.8	21	505	-1	505c		
12	465	33	567	61.66	-36.65	13.24	39.77	0.356	-0.2207	160.1	21	506	-1	506c		
14	470	33	569	62.72	-38.14	19.32	42.76	0.3422	-0.1274	153.1	24	520	-1	520c		
15	475	34	573	65.29	-38.28	22.47	44.39	0.3164	-0.0913	149.5	25	528	-1	528c	Gm	%
16	480	36	580	69.95	-37.48	26.04	45.64	0.346	-0.0632	145.2	27	537	-1	537c		
17	485	39	595	78.75	-32.73	31.10	45.09	0.5347	-0.0418	136.5	29	548	-1	548c		
18	490	-1	490c	93.8	-12.06	38.4	40.25	0.8218	-0.0261	107.4	33	565	11	459	max	%
19	495	-1	495c	92.3	-10.68	38.39	39.85	0.8346	-0.0195	105.5	33	566	12	462		
20	500	-1	500c	90.42	-8.91	38.07	39.1	0.8518	-0.0144	103.1	33	567	12	464		
22	510	-1	510c	85.27	-4.15	36.48	36.72	0.9016	-0.0076	96.5	33	569	13	469		
23	520	-1	519c	81.98	-1.26	35.24	35.26	0.935	-0.0056	92.0	34	570	14	471	Ym	%
25	530	-1	529c	74.04	5.15	32.02	32.43	1.0201	-0.0031	80.8	34	573	15	475		
27	540	-1	539c	64.9	11.57	28.16	30.44	1.1288	-0.0016	67.6	35	577	15	478		
28	545	-1	544c	60.13	14.52	26.11	29.87	1.1917	-0.0012	60.9	35	579	15	479		
29	550	-1	549c	55.26	17.18	24.01	29.53	1.2613	-0.0009	54.4	36	582	16	480		
30	555	-1	554c	50.4	19.49	21.91	29.33	1.3372	-0.0007	48.3	36	584	16	481		
32	560	-1	560c	41.0	22.8	17.83	29.35	1.5064	-0.0005	38.0	37	589	16	483		
380	770	100.0	0.0	0.0	0.0	0.0	0.0	0.9504	-0.4355	0.0						

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =770, 520, LINYAB komplementäres																
λ ₁	λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	H _{AB}	λ _d	λ _c	λ _e	Code	%			
32	561	0	405	41.79	22.74	17.89	28.94	1.4946	-0.0072	38.1	37	589	16	483	Rm	%
32	562	6	435	41.2	26.78	9.88	28.55	1.6006	-0.1956	20.2	42	610	17	486		
33	563	10	450	40.57	33.54	-4.93	23.59	1.7771	-0.557	351.6	-1	496	19	496		
33	565	12	460	39.67	36.45	-12.66	38.58	1.8991	-0.7547	340.8	-1	505	21	505		
33	567	12	465	38.33	36.65	-13.24	39.77	1.9064	-0.781	340.1	-1	506	21	506		
33	569	14	470	37.27	38.14	-19.32	42.76	1.9738	-0.954	333.1	-1	520	24	520		
34	573	15	475	34.7	38.28	-22.47	44.39	2.0536	-1.083	329.5	-1	528	25	528	Mm	%
36	580	16	480	30.04	37.48	-26.04	45.64	2.1982	-1.3026	325.2	-1	537	27	537		
39	595	17	485	21.24	32.73	-31.10	45.09	2.4914	-1.8952	316.5	-1	548	29	548		
-1	490c	18	490	61.9	12.06	38.4	40.25	2.899	-6.6372	287.4	11	459	33	565	min	%
-1	495c	19	495	7.69	10.68	-38.39	39.85	2.3392	-5.4245	285.5	12	462	33	566		
-1	500c	20	500	9.57	8.91	-38.07	39.1	1.8814	-4.4105	283.1	12	464	33	567		
-1	510c	22	510	14.72	4.15	-36.48	36.72	1.2328	-2.9143	276.5	13	469	33	569		
-1	519c	23	520	18.01	1.26	-35.24	35.26	1.2024	-2.3925	272.0	14	471	34	570	Bm	%
-1	529c	25	530	25.95	-5.15	-32.02	32.43	0.7516	-1.6693	260.8	15	475	34	573		
-1	539c	27	540	35.09	-11.57	-28.16	30.44	0.2605	-1.238	247.6	15	478	35	577		
-1	544c	28	545	39.86	-14.5	-26.11	29.87	0.5865	-1.0906	240.9	15	479	35	579		
-1	549c	29	550	44.73	-17.18	-24.01	29.53	0.5663	-0.9725	234.4	16	480	36	582		
-1	554c	30	555	49.59	-19.49	-21.91	29.33	0.5572	-0.8774	228.3	16	481	36	584		
-1	560c	32	560	58.99	-22.8	-17.83	29.35	0.5638	-0.7379	218.0	16	483	37	589		
380	770	100.0	0.0	0.0	0.0	0.0	0.0	0.9504	-0.4355	0.0						

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520, 770, LINYAB-Daten																
λ ₁	λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	H _{AB}	λ _d	λ _c	λ _e	Code	%			
0	405	31	556	56.57	-21.89	-18.32	28.54	0.5611	-0.7532	219.9	15	476	37	585	Cm	%
6	435	31	557	57.41	-26.44	-8.79	27.86	0.4876	-0.5825	198.4	16	480	44	621		
10	450	31	559	57.53	-32.88	6.09	33.05	0.3834	-0.3234	169.3	18	491	-1	491c		
11	460	32	562	59.27	-33.9	10.52	35.5	0.3761	-0.2517	162.7	19	498	-1	498c		
12	465	33	565	60.91	-34.93	14.56	37.84	0.3747	-0.1903	157.3	21	506	-1	506c		
14	470	34	570	63.07	-35.18	20.67	40.8	0.3903	-0.1016	149.5	24	522	-1	522c		
15	475	35	579	68.64	-33.55	24.85	41.75	0.4593	-0.0672	143.4	26	533	-1	533c	Gm	%
16	480	41	606	81.94	-23.65	31.88	39.7	0.6594	-0.0401	126.5	30	550	-1	550c		
16	485	-1	484c	92.3	-10.45	36.33	37.3	0.8348	-0.0356	106.0	32	560	10	454		
18	490	-1	490c	89.06	-7.57	36.55	37.8	0.8635	-0.0188	101.7	32	562	11	459	max	%
19	495	-1	495c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32	563	12	461		
19	500	-1	499c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32	563	12	461		
22	510	-1	510c	79.1	1.43	33.55	33.58	0.9662	-0.0051	87.5	33	567	13	466		
23	520	-1	519c	75.81	4.11	32.27	32.53	1.0024	-0.0036	82.7	33	568	13	468	Ym	%
26	530	-1	530c	64.17	12.31	27.48	30.11	1.14	-0.001	65.8	34	573	14	472		
27	540	-1	539c	59.9	14.81	25.68	29.65	1.1955	-0.0005	60.3	35	576	14	473		
28	545	-1	544c	55.54	17.09	23.83	29.32	1.2559	-0.0002	54.3	35	578	14	474		
29	550	-1	549c	51.12	19.09	21.94	29.08	1.3215	-0.0001	48.9	36	580	15	475		
31	555	-1	555c	42.37	21.98	18.19	28.53	1.4668	0.0	39.6	37	586	15	476		
32	560	10	451	40.04	32.52	-6.18	33.11	1.7604	-0.5838	349.2	-1	492c	18	492		
380	770	100.0	0.0	0.0	0.0	0.0	0.0	0.9481	-0.4293	0.0						

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =770, 520, LINYAB komplementäres																
λ ₁	λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	H _{AB}	λ _d	λ _c	λ _e	Code	%			
31	556	0	405	43.42	21.89	18.32	28.54	1.4522	-0.0074	39.9	37	585	15	476	Rm	%
31	557	6	435	42.58	26.44	8.79	27.86	1.5691	-0.2226	18.4	44	621	16	480		
31	559	10	450	42.46	32.48	-6.09	33.05	1.713	-0.5727	349.3	-1	491c	18	491		
32	562	11	460	40.72	33.9	-10.52	35.5	1.7807	-0.6879	342.7	-1	498c	19	498		
33	565	12	465	39.08	34.93	-14.56	37.84	1.8419	-0.8019	337.3	-1	506c	21	506		
34	570	14	470	36.92	35.18	-20.67	40.8	1.901	-0.9891	329.5	-1	522c	24	522		
35	579	15	475	31.35	33.55	-24.85	41.75	2.2084	-1.2222	323.4	-1	533c	26	533	Mm	%
41	606	16	480	18.05	23.65	-31.88	39.7	2.2567	-2.1959	306.5	-1	550c	30	550		
-1	484c	16	485	7.69	10.45	-36.33	37.8	2.3808	-5.1484	286.0	10	454	32	560		
-1	490c	18	490	10.93	7.57	-36.55	37.3	1.6407	-3.7725	281.7	11	459	32	562	min	%
-1	495c	19	495	12.94	5.68	-36.18	36.62	1.3873	-3.2239	278.9	12	461	32	563		
-1	499c	19	500	12.94	5.68	-36.18	36.62	1.3873	-3.2239	278.9	12	461	32	563		
-1	510c	22	510	20.89	-1.43	-33.55	33.58	0.8795	-2.035	267.5	13	466	33	567		
-1	519c	23	520	24.18	-4.12	-32.27	32.53	0.7777	-1.7639	262.7	13	468	33	568	Bm	%
-1	530c	26	530	35.82	-12.31	-27.48	30.11									