

Ostwald optimal colours (o), maximum (m) C_{AB} for D50, $Y_N=3,6$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	X	Y	Z	x	y	z	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
1	405	32 564	26.33	48.45	66.13	0.1869	0.3438	0.4692	185.2	17 486	38 592	Cm
7	435	33 565	23.41	48.25	52.04	0.1892	0.39	0.4207	168.6	18 490	46 631	
10	450	33 566	20.93	48.75	35.69	0.1986	0.4625	0.3387	144.6	19 497	-1 497c	
12	460	33 567	19.83	49.37	24.66	0.2113	0.5259	0.2626	128.7	21 506	-1 506c	
13	465	33 568	19.81	50.0	19.91	0.2208	0.5572	0.2218	122.1	22 512	-1 512c	
14	470	34 570	19.94	50.5	15.93	0.2308	0.5846	0.1844	116.9	23 519	-1 519c	
15	475	34 573	21.53	52.24	12.71	0.2489	0.604	0.1469	111.4	25 527	-1 527c	Gm
15	480	35 578	24.67	55.34	12.71	0.266	0.5968	0.1371	108.4	26 532	-1 532c	
17	485	37 587	30.59	59.41	8.37	0.3109	0.6039	0.0851	98.0	28 544	-1 544c	
18	490	44 620	53.95	71.6	6.98	0.407	0.5402	0.0526	71.3	32 561	-1 561c	
19	495	-1 495c	67.75	76.06	5.88	0.4525	0.5081	0.0393	54.4	33 568	12 463	max
20	500	-1 500c	67.73	74.76	5.02	0.4591	0.5067	0.034	52.5	33 569	13 466	
22	510	-1 510c	67.65	71.15	3.88	0.4741	0.4986	0.0272	47.4	34 571	14 471	
23	520	-1 519c	67.48	68.78	3.54	0.4826	0.492	0.0253	44.2	34 572	14 473	Ym
25	530	-1 529c	66.65	62.96	3.11	0.5021	0.4743	0.0234	36.4	35 575	15 477	
27	540	-1 539c	64.95	56.11	2.88	0.524	0.4527	0.0232	27.8	35 579	16 480	
28	545	-1 544c	63.73	52.49	2.81	0.5353	0.4409	0.0236	23.4	36 581	16 481	
29	550	-1 549c	62.23	48.77	2.77	0.5469	0.4286	0.0244	19.1	36 583	16 483	
30	555	-1 554c	60.45	45.01	2.74	0.5586	0.4159	0.0254	15.0	37 585	16 484	
32	560	-1 560c	56.05	37.66	2.71	0.5812	0.3905	0.0281	7.7	38 590	17 486	
32	564	1 405	60.44	41.54	8.11	0.5489	0.3773	0.0736	5.2	38 592	17 486	Rm
33	565	7 435	63.36	41.74	22.19	0.4977	0.3279	0.1743	348.6	46 631	18 490	
33	566	10 450	65.84	41.24	38.54	0.452	0.2832	0.2646	324.7	-1 497c	19 497	
33	567	12 460	66.94	40.62	49.58	0.4259	0.2585	0.3155	308.7	-1 506c	21 506	
33	568	13 465	66.96	39.99	54.33	0.4151	0.2479	0.3368	302.1	-1 512c	22 512	
34	570	14 470	66.83	39.49	58.3	0.4059	0.2398	0.3541	296.9	-1 519c	23 519	
34	573	15 475	65.25	37.75	61.53	0.3965	0.2294	0.3739	291.5	-1 527c	25 527	Mm
35	578	15 480	62.1	34.65	61.52	0.3923	0.2189	0.3887	288.5	-1 532c	26 532	
37	587	17 485	56.18	30.58	65.87	0.368	0.2003	0.4315	278.0	-1 544c	28 544	
44	620	18 490	32.82	18.39	67.26	0.277	0.1552	0.5677	251.3	-1 561c	32 561	
-1 495c	19 495	19.02	13.93	68.36	0.1877	0.1375	0.6746	234.4	12 463	33 568	min	
-1 500c	20 500	19.04	15.23	69.22	0.1839	0.1471	0.6688	232.5	13 466	33 569		
-1 510c	22 510	19.13	18.84	70.36	0.1765	0.1739	0.6494	227.5	14 471	34 571		
-1 519c	23 520	19.29	21.21	70.7	0.1735	0.1907	0.6357	224.2	14 473	34 572	Bm	
-1 529c	25 530	20.12	27.03	71.13	0.1701	0.2285	0.6013	216.5	15 477	35 575		
-1 539c	27 540	21.82	33.88	71.36	0.1717	0.2666	0.5615	207.8	16 480	35 579		
-1 544c	28 545	23.04	37.5	71.42	0.1746	0.2841	0.5412	203.5	16 481	36 581		
-1 549c	29 550	24.54	41.22	71.47	0.1788	0.3004	0.5207	199.2	16 483	36 583		
-1 554c	30 555	26.32	44.98	71.49	0.1843	0.315	0.5006	195.0	16 484	37 585		
-1 560c	32 560	30.72	52.33	71.52	0.1987	0.3385	0.4627	187.7	17 486	38 590		
W0	380	770	86.78	90.0	74.24	0.3457	0.3585	0.2957	0.0			
N0	380	770	3.47	3.6	2.96	0.3457	0.3585	0.2957	0.0			