

<http://farbe.li.tu-berlin.de/eeh5/eeh501n.txt> / .ps; only vector graphic VG;
 see separate images of this page: <http://farbe.li.tu-berlin.de/eeh5/eeh5.htm>

Oswald optimal colours (o), maximum (m) C_{AB} for D50, $Y_N=3.6$, $Y_W=90$, $Y_m=520.770$

i_1	λ_1	i_2	λ_2	Y	A ₁	B ₁	C _{AB1}	a ₁	b ₁	b_{xy2}	i_d	λ_d	i_c	λ_c	Code
1	405	32	564	48.45	-52.52	-26.15	58.67	0.2236	-0.5457	206.4	17	486	38	592	Cm
7	435	33	565	48.25	-54.77	-12.23	56.12	0.2032	-0.4313	192.5	18	490	46	631	
10	450	33	566	48.75	-56.74	4.51	56.92	0.1916	-0.2928	175.4	19	497	-1	497c	
12	460	33	567	49.37	-57.34	16.06	59.55	0.1926	-0.1997	164.3	21	506	-1	506c	
13	465	33	568	50.0	-57.3	21.33	61.15	0.1988	-0.1592	159.5	22	512	-1	512c	
14	470	34	570	50.5	-56.89	25.72	62.43	0.2066	-0.1261	155.6	23	519	-1	519c	
15	475	34	573	52.24	-55.8	30.37	63.53	0.2299	-0.0973	151.4	25	527	-1	527c	Gm
15	485	35	578	55.34	-54.77	32.93	63.91	0.2613	-0.0919	148.9	26	532	-1	532c	
17	485	37	587	59.41	-48.2	40.63	63.04	0.3327	-0.0563	139.8	28	544	-1	544c	
18	490	44	620	71.6	-19.22	52.07	55.51	0.5498	-0.0389	110.2	32	561	-1	561c	
19	495	-1	495c	76.06	3.2	56.84	56.93	0.674	-0.0309	86.7	33	568	12	463	max
20	500	-1	500c	74.76	5.9	56.63	56.94	0.6888	-0.0268	84.0	33	569	13	466	
22	510	-1	510c	71.15	12.94	54.8	56.31	0.73	-0.0218	76.7	34	571	14	471	
23	520	-1	519c	68.78	17.2	53.19	55.9	0.7572	-0.0205	72.0	34	572	14	473	Ym
25	530	-1	529c	62.96	26.65	48.81	55.62	0.8265	-0.0197	61.3	35	575	15	477	
27	540	-1	539c	56.11	36.05	43.4	56.42	0.9142	-0.0205	50.2	35	579	16	480	
28	545	-1	544c	52.49	40.31	40.47	57.12	0.9643	-0.0214	45.1	36	581	16	481	
29	550	-1	549c	48.77	44.13	37.44	57.88	1.0192	-0.0227	40.3	36	583	16	483	
30	555	-1	554c	45.01	47.39	34.47	58.54	1.0783	-0.0244	35.9	37	585	16	484	
32	560	-1	560c	37.66	51.7	28.34	58.96	1.2062	-0.0288	28.7	38	590	17	486	
32	564	1	405	41.54	52.52	26.15	58.67	1.1629	-0.078	26.4	38	592	17	486	Rm
33	565	7	435	41.74	54.76	12.23	56.11	1.182	-0.2126	12.5	46	631	18	490	
33	566	10	450	41.24	56.73	-4.51	56.91	1.2074	-0.3736	355.4	-1	497c	19	497	
33	567	12	460	40.62	57.33	-16.06	59.54	1.2217	-0.488	344.3	-1	506c	21	506	
33	568	13	465	39.99	57.29	-21.33	61.13	1.2302	-0.5432	339.5	-1	512c	22	512	
34	570	14	470	39.49	56.88	-25.71	62.42	1.2333	-0.5903	335.6	-1	519c	23	519	
34	573	15	475	37.75	55.79	-30.36	63.52	1.2483	-0.6516	331.4	-1	527c	25	527	Mm
35	578	15	480	34.65	54.75	-32.92	63.89	1.2893	-0.7099	328.9	-1	532c	26	532	
37	587	17	485	30.58	48.18	-40.61	63.02	1.2874	-0.861	319.8	-1	544c	28	544	
44	620	18	490	18.39	19.21	-52.05	55.48	1.0751	-1.4618	290.2	-1	561c	32	561	
-1	495c	19	495	13.93	-3.2	-56.81	56.9	0.5652	-1.9609	266.7	12	463	33	568	min
-1	500c	20	500	15.23	-5.89	-56.61	56.91	0.5023	-1.8165	264.0	13	466	33	569	
-1	510c	22	510	18.84	-12.94	-54.78	56.28	0.3825	-1.4926	256.7	14	471	34	571	
-1	519c	23	520	21.21	-17.2	-53.17	55.88	0.3328	-1.3327	252.0	14	473	34	572	Bm
-1	529c	25	530	27.03	-26.65	-48.8	55.6	0.2629	-1.0518	241.3	15	477	35	575	
-1	539c	27	540	33.88	-36.05	-43.39	56.41	0.2316	-0.8422	230.2	16	480	35	579	
-1	544c	28	545	37.5	-40.3	-40.47	57.12	0.2273	-0.7615	225.1	16	481	36	581	
-1	549c	29	550	41.22	-44.13	-37.44	57.87	0.229	-0.6931	220.3	16	483	36	583	
-1	554c	30	555	44.98	-47.38	-34.37	58.54	0.2358	-0.6355	215.9	16	484	37	585	
-1	560c	32	560	52.33	-51.69	-28.34	58.96	0.262	-0.5465	208.7	17	486	38	590	
W0	380	770	90.0	0.0	0.0	0.0	0.0	0.6572	-0.3298	0.0	B _c =1,000				
N0	380	770	3.6	0.0	0.0	0.0	0.0	0.6572	-0.3298	0.0	x _c =0,110				

TUB-test chart eeh5; Oswald optimal colours, $Y_N=3.6$, $Y_W=90$, illuminant D50, CIE-02-degree
 Table data: $YA_1B_1C_{AB,1}h_{AB,1}$ and $YA_2B_2C_{AB,2}h_{AB,2}$ with different wavelength ranges

Oswald optimal colours (o), maximum (m) C_{AB} for D50, $Y_N=3.6$, $Y_W=90$, $Y_m=520.770$

i_1	λ_1	i_2	λ_2	Y	A ₂	B ₂	C _{AB2}	a ₂	b ₂	b_{xy2}	i_d	λ_d	i_c	λ_c	Code
1	405	32	564	48.45	-52.52	-26.15	58.67	0.2236	-0.5457	206.4	17	486	38	592	Cm
7	435	33	565	48.25	-54.77	-12.23	56.12	0.2032	-0.4313	192.5	18	490	46	631	
10	450	33	566	48.75	-56.74	4.51	56.92	0.1916	-0.2928	175.4	19	497	-1	497c	
12	460	33	567	49.37	-57.34	16.06	59.55	0.1926	-0.1997	164.3	21	506	-1	506c	
13	465	33	568	50.0	-57.3	21.33	61.15	0.1988	-0.1592	159.5	22	512	-1	512c	
14	470	34	570	50.5	-56.89	25.72	62.43	0.2066	-0.1261	155.6	23	519	-1	519c	
15	475	34	573	52.24	-55.8	30.37	63.53	0.2299	-0.0973	151.4	25	527	-1	527c	Gm
15	485	35	578	55.34	-54.77	32.93	63.91	0.2613	-0.0919	148.9	26	532	-1	532c	
17	485	37	587	59.41	-48.2	40.63	63.04	0.3327	-0.0563	139.8	28	544	-1	544c	
18	490	44	620	71.6	-19.22	52.07	55.51	0.5498	-0.0389	110.2	32	561	-1	561c	
19	495	-1	495c	76.06	3.2	56.84	56.93	0.674	-0.0309	86.7	33	568	12	463	max
20	500	-1	500c	74.76	5.9	56.63	56.94	0.6888	-0.0268	84.0	33	569	13	466	
22	510	-1	510c	71.15	12.94	54.8	56.31	0.73	-0.0218	76.7	34	571	14	471	
23	520	-1	519c	68.78	17.2	53.19	55.9	0.7572	-0.0205	72.0	34	572	14	473	Ym
25	530	-1	529c	62.96	26.65	48.81	55.62	0.8265	-0.0197	61.3	35	575	15	477	
27	540	-1	539c	56.11	36.05	43.4	56.42	0.9142	-0.0205	50.2	35	579	16	480	
28	545	-1	544c	52.49	40.31	40.47	57.12	0.9643	-0.0214	45.1	36	581	16	481	
29	550	-1	549c	48.77	44.13	37.44	57.88	1.0192	-0.0227	40.3	36	583	16	483	
30	555	-1	554c	45.01	47.39	34.47	58.54	1.0783	-0.0244	35.9	37	585	16	484	
32	560	-1	560c	37.66	51.7	28.34	58.96	1.2062	-0.0288	28.7	38	590	17	486	
32	564	1	405	41.54	52.52	26.15	58.67	1.1629	-0.078	26.4	38	592	17	486	Rm
33	565	7	435	41.74	54.76	12.23	56.11	1.182	-0.2126	12.5	46	631	18	490	
33	566	10	450	41.24	56.73	-4.51	56.91	1.2074	-0.3736	355.4	-1	497c	19	497	
33	567	12	460	40.62	57.33	-16.06	59.54	1.2217	-0.488	344.3	-1	506c	21	506	
33	568	13	465	39.99	57.29	-21.33	61.13	1.2302	-0.5432	339.5	-1	512c	22	512	
34	570	14	470	39.49	56.88	-25.71	62.42	1.2333	-0.5903	335.6	-1	519c	23	519	
34	573	15	475	37.75	55.79	-30.36	63.52	1.2483	-0.6516	331.4	-1	527c	25	527	Mm
35	578	15	480	34.65	54.75	-32.92	63.89	1.2893	-0.7099	328.9	-1	532c	26	532	
37	587	17	485	30.58	48.18	-40.61	63.02	1.2874	-0.861	319.8	-1	544c	28	544	
44	620	18	490	18.39	19.21	-52.05	55.48	1.0751	-1.4618	290.2	-1	561c	32	561	
-1	495c	19	495	13.93	-3.2	-56.81	56.9	0.5652	-1.9609	266.7	12	463	33	568	min
-1	500c	20	500	15.23	-5.89	-56.61	56.91	0.5023	-1.8165	264.0	13	466	33	569	
-1	510c	22	510	18.84	-12.94	-54.78	56.28	0.3825	-1.4926	256.7	14	471	34	571	
-1	519c	23	520	21.21	-17.2	-53.17	55.88	0.3328	-1.3327	252.0	14	473	34	572	Bm
-1	529c	25	530	27.03	-26.65	-48.8	55.6	0.2629	-1.0518	241.3	15	477	35	575	
-1	539c	27	540	33.88	-36.05	-43.39	56.41	0.2316	-0.8422	230.2	16	480	35	579	
-1	544c	28	545	37.5	-40.3	-40.47	57.12	0.2273	-0.7615	225.1	16	481	36	581	
-1	549c	29	550	41.22	-44.13	-37.44	57.87	0.229	-0.6931	220.3	16	483	36	583	
-1	554c	30	555	44.98	-47.38	-34.37	58.54	0.2358	-0.6355	215.9	16	484	37	585	
-1	560c	32	560	52.33	-51.69	-28.34	58.96	0.262	-0.5465	208.7	17	486	38	590	