

V scaling factor

$$L^* = V (L_s/s)^n [(1-s+s L/L_s)^n - 1] \quad [1]$$

$$n = -0,25 \quad [2]$$

$$V = 1/(0,036 n L_u^{-0,30}) \quad [3]$$

$$L_s = 0,025 L_u^{0,705} \quad [4]$$

$$s = 1/[1+(n V L_s^n)^{1/(1-n)}] \quad [5]$$

$$L_u = 0,1; 1; 10; 100; 1000 \text{ cd/m}^2 \quad [6]$$

$$dL = [1/n V] [(L_s/s)^{1-n} [1-s+s L/L_s]^{1-n}] \quad [7]$$

V scaling factor

surround-field luminance

L_w [cd/m²] →

$$L^* = V (L_s/s)^n [(1-s(L-L_s)/L_s)^n - 1] \quad [8]$$

$$dL = [1/n V] [(L_s/s)^{1-n} [(1-s(L-L_s)/L_s)^{1-n}]] \quad [9]$$

central-field luminance L [cd/m²]

0,001 0,01 0,1 1 10 100 1000 10000

-3

-2

-1

0

1

2

3

4

→ log L [cd/m²]

882.59

1000

442.34

100

221.7

10

111.11

1

55.69

0,1

1000

800

600

400

200

0