

# 9stufige Grauskalierung zwischen $L^*_{0aN}=22.3$ und $L^*_{0aW}=96.0$ , $Y_{0ref}=1.8$ , Normierung: Weiß W

$L^*_{0aN}=22.3$ ,  $L^*_{0aU}=59.1$ ,  $L^*_{0aW}=96.0$ ,  $Y_{0aN}=3.6$ ,  $Y_{0aU}=27.2$ ,  $Y_{0aW}=90.0$ ,  $C_{0aY}=Y_{0aW}:Y_{0aN}=25.0$

$L^*_{tN}=27.6$ ,  $L^*_{taU}=60.3$ ,  $L^*_{taW}=96.0$ ,  $Y_{taN}=5.3$ ,  $Y_{taU}=28.4$ ,  $Y_{taW}=90.0$ ,  $C_{taY}=Y_{taW}:Y_{taN}=17.0$

## Regularitätsindex nach ISO/IEC 15775:2022, Anhang G für 5 und 9 Stufen

$$g^* = 100 [\Delta L^*_{min}] / [\Delta L^*_{max}]$$

$g^*_5=99$ ,  $g^*_9=99$

angestrebte Ausgabe

$g^*_5=86$ ,  $g^*_9=82$

reale Ausgabe

$g^*_5=98$ ,  $g^*_9=98$

linearisierte Ausgabe

$L^*$	n0. i	$g^*_5=99, g^*_9=99$ angestrebte Ausgabe				$g^*_5=86, g^*_9=82$ reale Ausgabe				$g^*_5=98, g^*_9=98$ linearisierte Ausgabe		
		$L^*_{0a}$	$L^*_{0r}$	$Y_{0a}$	$Y_{0r}$	$L^*_{ta}$	$\Delta L^*_{ta}$	$L^*_{tr}$	$Y_{ta}$	$(L^*_{tr})^{1/1.07}$	$L^*_{la}$	$\Delta L^*_{la}$
100	9	96.0	1.0	90.0	1.0	96.0		1.0	90.0	1.0	96.0	8.5
	8	86.8	0.875	69.6	0.763	87.0	9.0	0.868	70.0	0.876	87.5	8.5
	7	77.6	0.75	52.5	0.566	78.0	9.0	0.737	53.2	0.752	79.0	8.5
75	6	68.4	0.625	38.5	0.403	69.1	8.9	0.607	39.5	0.627	70.5	8.6
	5	59.1	0.5	27.2	0.273	60.3	8.8	0.478	28.4	0.502	61.9	8.6
	4	49.9	0.375	18.4	0.171	51.6	8.7	0.351	19.8	0.376	53.3	8.6
50	3	40.7	0.25	11.7	0.094	43.1	8.5	0.227	13.2	0.25	44.7	8.5
	2	31.5	0.125	6.9	0.038	35.0	8.1	0.109	8.5	0.126	36.2	8.6
	1	22.3	0.0	3.6	0.0	27.6	7.4	0.0	5.3	0.0	27.6	

$\Delta L^*_{ta}=9.2$  (i=1,2,...,9)

Normierung:  $Y_{taiW}=Y_{0aW} \frac{Y_{0ai}+Y_{0ref}}{Y_{0aW}+Y_{0ref}}$