

Optimal-Optimalfarben (o), maximales (m) C_{AB} für D65, $Y_N=3,6$, $Y_W=90$, $Y_m=520_770$												
i_1, λ_1	i_2, λ_2	X	Y	Z	x	y	z	h_{xy}	i_d, λ_d	i_c, λ_c	Code	
0	405	32 561	28.34	48.4	87.6	0.1724	0.2945	0.533	193.8	16 483 37 589	Cm	
6	435	32 562	25.69	48.95	72.52	0.1746	0.3326	0.4927	178.5	17 486 42 610		
10	450	32 563	21.01	49.59	44.25	0.1829	0.4317	0.3852	141.6	19 496 -1 496c		
12	460	33 565	19.15	49.94	29.98	0.1933	0.504	0.3026	124.2	21 505 -1 505c		
12	465	33 567	20.12	51.15	29.99	0.1987	0.5051	0.2961	122.8	21 506 -1 506c		
14	470	33 569	19.94	52.23	19.06	0.2186	0.5724	0.2089	111.1	24 520 -1 520c		
15	475	34 573	21.65	54.1	15.12	0.2382	0.5953	0.1664	105.6	25 528 -1 528c	Gm	
16	480	36 580	25.4	57.45	12.12	0.2674	0.6048	0.1276	99.2	27 537 -1 537c		
17	485	39 595	35.62	64.35	9.93	0.3241	0.5855	0.0903	87.4	29 548 -1 548c		
18	490	-1 490c	63.02	76.18	8.3	0.4272	0.5164	0.0562	58.5	33 565 11 459	max	
19	495	-1 495c	62.98	75.01	7.04	0.4342	0.5171	0.0485	57.1	33 566 12 462		
20	500	-1 500c	62.97	73.55	6.07	0.4416	0.5158	0.0425	55.3	33 567 12 464		
22	510	-1 510c	62.87	69.55	4.8	0.4581	0.5068	0.035	50.6	33 569 13 469		
23	520	-1 519c	62.69	66.99	4.43	0.4674	0.4995	0.033	47.7	34 570 14 471	Ym	
25	530	-1 529c	61.81	60.81	3.97	0.4882	0.4803	0.0314	40.7	34 573 15 475		
27	540	-1 539c	60.05	53.7	3.73	0.511	0.4571	0.0318	32.8	35 577 15 478		
28	545	-1 544c	58.8	49.99	3.67	0.5228	0.4445	0.0326	28.7	35 579 15 479		
29	550	-1 549c	57.28	46.21	3.62	0.5347	0.4313	0.0338	24.7	36 582 16 480		
30	555	-1 554c	55.49	42.43	3.6	0.5465	0.4179	0.0354	20.8	36 584 16 481		
32	560	-1 560c	51.12	35.12	3.57	0.5691	0.391	0.0397	13.6	37 589 16 483		
32	561	0 405	57.19	41.59	10.39	0.5238	0.3809	0.0951	13.8	37 589 16 483	Rm	
32	562	6 435	59.84	41.04	25.47	0.4735	0.3248	0.2016	358.5	42 610 17 486		
32	563	10 450	64.52	40.4	53.74	0.4066	0.2546	0.3387	321.6	-1 496c 19 496		
33	565	12 460	66.38	40.05	68.01	0.3805	0.2295	0.3898	304.3	-1 505c 21 505		
33	567	12 465	65.41	38.84	68.01	0.3797	0.2254	0.3947	302.9	-1 506c 21 506		
33	569	14 470	65.59	37.76	78.93	0.3598	0.2071	0.433	291.1	-1 520c 24 520		
34	573	15 475	63.88	35.89	82.87	0.3497	0.1964	0.4537	285.6	-1 528c 25 528	Mm	
36	580	16 480	60.13	32.54	85.87	0.3367	0.1822	0.4809	279.3	-1 537c 27 537		
39	595	17 485	49.91	25.64	88.06	0.305	0.1567	0.5382	267.4	-1 548c 29 548		
-1	490c	18 490	22.51	13.81	89.7	0.1786	0.1096	0.7117	238.5	11 459 33 565	min	
-1	495c	19 495	22.55	14.98	90.95	0.1755	0.1166	0.7078	237.1	12 462 33 566		
-1	500c	20 500	22.56	16.44	91.92	0.1723	0.1256	0.702	235.4	12 464 33 567		
-1	510c	22 510	22.66	20.44	93.19	0.1662	0.1499	0.6837	230.7	13 469 33 569		
-1	519c	23 520	22.84	23.0	93.56	0.1638	0.165	0.6711	227.7	14 471 34 570	Bm	
-1	529c	25 530	23.72	29.18	94.02	0.1614	0.1986	0.6399	220.7	15 475 34 573		
-1	539c	27 540	25.48	36.29	94.26	0.1633	0.2325	0.604	212.8	15 478 35 577		
-1	544c	28 545	26.73	40.0	94.33	0.1659	0.2483	0.5856	208.8	15 479 35 579		
-1	549c	29 550	28.25	43.78	94.37	0.1697	0.2631	0.567	204.7	16 480 36 582		
-1	554c	30 555	30.04	47.56	94.4	0.1746	0.2765	0.5488	200.8	16 481 36 584		
-1	560c	32 560	34.41	54.87	94.43	0.1873	0.2986	0.5139	193.6	16 483 37 589		
W0	380	770	85.53	90.0	98.0	0.3127	0.329	0.3582	0.0			
N0	380	770	3.42	3.6	3.92	0.3127	0.329	0.3582	0.0			