

# 9stufige Grauskalierung zwischen $L^*_{0aN}=18.2$ und $L^*_{0aW}=109.2$ , $Y_{0ref}=1.8$ , Normierung Grau U

$L^*_{0aN}=18.2$ ,  $L^*_{0aU}=63.8$ ,  $L^*_{0aW}=109.3$ ,  $Y_{0aN}=2.6$ ,  $Y_{0aU}=32.5$ ,  $Y_{0aW}=126.0$ ,  $C_{0aY}=Y_{0aW}:Y_{0aN}=49.0$   
 $L^*_{taN}=24.1$ ,  $L^*_{taU}=63.8$ ,  $L^*_{taW}=107.6$ ,  $Y_{taN}=4.1$ ,  $Y_{taU}=32.5$ ,  $Y_{taW}=121.1$ ,  $C_{taY}=Y_{taW}:Y_{taN}=29.2$

## Regularitätsindex nach ISO/IEC 15775:2022, Anhang G für 5 und 9 Stufen

$g^* = 100 [\Delta L^*_{min}] / [\Delta L^*_{max}]$ ,  $L^*_{CIE LAB} = 116 [Y/Y_n]^{1/3} - 16$  mit  $Y \geq 0,882$ ,  $Y_n=100$

$g^*_5=99$ ,  $g^*_9=99$

$g^*_5=84$ ,  $g^*_9=78$

$g^*_5=97$ ,  $g^*_9=97$

$L^*_{CIE LAB}$	n0. i	angestrebte Ausgabe				reale Ausgabe				linearisierte Ausgabe		
		$L^*_{0a}$	$L^*_{0r}$	$Y_{0a}$	$Y_{0r}$	$L^*_{ta}$	$\Delta L^*_{ta}$	$L^*_{tr}$	$Y_{ta}$	$(L^*_{tr})^{1/1.08}$	$L^*_{la}$	$\Delta L^*_{la}$
	9	109.3	1.0	126.0	1.0	107.6		1.0	121.1	1.0	107.6	
100	8	97.9	0.875	94.7	0.746	96.6	11.0	0.867	91.4	0.876	97.3	10.3
	7	86.5	0.75	69.0	0.538	85.6	11.0	0.736	67.1	0.752	86.9	10.4
75	6	75.1	0.625	48.5	0.372	74.6	10.9	0.604	47.7	0.627	76.5	10.4
	5	63.8	0.5	32.5	0.242	63.8	10.8	0.474	32.5	0.501	66.0	10.5
50	4	52.4	0.375	20.5	0.145	53.1	10.7	0.346	21.1	0.374	55.4	10.6
	3	41.0	0.25	11.9	0.075	42.7	10.4	0.222	12.9	0.248	44.8	10.6
25	2	29.6	0.125	6.1	0.028	32.8	9.8	0.104	7.5	0.123	34.4	10.4
	1	18.2	0.0	2.6	0.0	24.1	8.7	0.0	4.1	0.0	24.1	10.3

$\Delta L^*_{0a}=11.4$  (i=1,2,...,8)

Normierung:  $Y_{taiU}=Y_{0aU} \frac{Y_{0ai}+Y_{0ref}}{Y_{0aU}+Y_{0ref}}$