

Optimalwald-Optimalfarben (o), maximales (m) C_{AB} für P50, $Y_N=3,6$, $Y_W=90$, $Y_m=520_770$													
i_1, λ_1	i_2, λ_2	X	Y	Z	x	y	z	h_{xy}	i_d, λ_d	i_c, λ_c	Code		
1	405	32 564	27.73	48.18	76.61	0.1818	0.3158	0.5022	189.4	16 484	38 591	Cm	
6	435	32 564	25.16	48.65	62.16	0.185	0.3577	0.4571	173.4	17 488	44 620		
9	450	33 565	21.96	48.79	44.16	0.1911	0.4246	0.3842	149.2	18 494	-1 494c		
11	460	33 567	20.71	49.67	31.95	0.2023	0.4853	0.3122	131.8	20 502	-1 502c		
13	465	33 568	19.81	50.22	21.2	0.2171	0.5504	0.2323	118.7	22 513	-1 513c		
14	470	34 570	20.12	50.95	16.99	0.2285	0.5785	0.1929	113.5	24 520	-1 520c		
15	475	34 574	22.08	53.09	13.63	0.2486	0.5978	0.1535	107.9	25 529	-1 529c	Gm	
16	480	36 580	25.24	55.87	11.03	0.2739	0.6063	0.1197	102.3	27 536	-1 536c		
17	485	38 592	34.13	62.09	9.06	0.3241	0.5897	0.086	91.8	29 547	-1 547c		
17	490	-1 489c	66.71	77.64	9.07	0.4348	0.506	0.0591	58.1	33 566	11 456		
19	495	-1 495c	66.59	75.71	6.41	0.4477	0.5091	0.0431	55.4	33 567	12 462		
19	500	-1 499c	66.59	75.71	6.41	0.4477	0.5091	0.0431	55.4	33 567	12 462	max	
21	510	-1 509c	66.55	72.67	4.83	0.4619	0.5044	0.0335	51.5	33 569	13 467		
24	520	-1 520c	65.99	65.37	3.72	0.4884	0.4839	0.0275	42.4	34 573	14 474	Ym	
26	530	-1 530c	64.75	58.99	3.4	0.5092	0.4639	0.0268	34.8	35 576	15 477		
27	540	-1 539c	63.79	55.52	3.31	0.5201	0.4527	0.027	30.7	35 578	15 479		
28	545	-1 544c	62.59	51.94	3.25	0.5313	0.4409	0.0276	26.6	36 580	16 480		
30	550	-1 550c	59.37	44.6	3.18	0.554	0.4161	0.0297	18.7	37 585	16 482		
30	555	-1 554c	59.37	44.6	3.18	0.554	0.4161	0.0297	18.7	37 585	16 482		
32	560	-1 560c	54.99	37.29	3.15	0.5761	0.3907	0.033	11.5	38 590	16 484		
32	564	1 405	59.97	41.81	9.77	0.5375	0.3748	0.0875	9.3	38 591	16 484	Rm	
32	564	6 435	62.54	41.34	24.21	0.4882	0.3227	0.189	353.4	44 620	17 488		
33	565	9 450	65.74	41.2	42.22	0.4407	0.2762	0.283	329.2	-1 494c	18 494		
33	567	11 460	66.99	40.32	54.43	0.4142	0.2492	0.3365	311.9	-1 502c	20 502		
33	568	13 465	67.9	39.77	65.18	0.3928	0.2301	0.377	298.7	-1 513c	22 513		
34	570	14 470	67.58	39.04	69.38	0.3839	0.2218	0.3942	293.5	-1 520c	24 520		
34	574	15 475	65.62	36.9	72.75	0.3743	0.2105	0.415	288.0	-1 529c	25 529	Mm	
36	580	16 480	62.46	34.12	75.35	0.3632	0.1984	0.4382	282.3	-1 536c	27 536		
38	592	17 485	53.57	27.9	77.32	0.3373	0.1757	0.4869	271.8	-1 547c	29 547		
-1	489c	17 490	20.99	12.35	77.31	0.1897	0.1116	0.6986	238.1	11 456	33 566		
-1	495c	19 495	21.12	14.28	79.97	0.183	0.1238	0.6931	235.5	12 462	33 567		
-1	499c	19 500	21.12	14.28	79.97	0.183	0.1238	0.6931	235.5	12 462	33 567	min	
-1	509c	21 510	21.15	17.32	81.55	0.1762	0.1443	0.6794	231.5	13 467	33 569		
-1	520c	24 520	21.71	24.62	82.65	0.1683	0.1908	0.6407	222.4	14 474	34 573	Bm	
-1	530c	26 530	22.95	31.0	82.97	0.1676	0.2264	0.6059	214.8	15 477	35 576		
-1	539c	27 540	23.91	34.47	83.06	0.169	0.2436	0.5872	210.7	15 479	35 578		
-1	544c	28 545	25.12	38.05	83.13	0.1716	0.2601	0.5681	206.7	16 480	36 580		
-1	550c	30 550	28.33	45.39	83.2	0.1805	0.2892	0.5301	198.7	16 482	37 585		
-1	554c	30 555	28.33	45.39	83.2	0.1805	0.2892	0.5301	198.7	16 482	37 585		
-1	560c	32 560	32.71	52.7	83.23	0.1939	0.3125	0.4935	191.5	16 484	38 590		
W0	380	770	87.71	90.0	86.38	0.3321	0.3407	0.327	0.0				
N0	380	770	3.5	3.6	3.45	0.3321	0.3407	0.327	0.0				