

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P30, Y_N=3,6, Y_W=90, Y_m=520 770

l ₁	l ₂	λ ₂	X	Y	Z	x	y	z	h _{xy}	l _d	l _e	l _c	λ _c	Code
1	405	34 570	24.86	46.52	42.04	0.2192	0.4101	0.3706	173.99	18 490	39	596	Cm	
7	435	34 570	23.28	46.73	32.98	0.2226	0.4537	0.3202	160.5	18 494	47	638		
9	450	34 571	22.54	47.13	26.98	0.2337	0.4886	0.2776	150.1	19 498	-1	498c		
12	460	34 572	21.38	47.45	16.89	0.2493	0.5535	0.197	133.5	21 507	-1	507c		
12	465	34 572	21.91	48.03	16.89	0.2523	0.5531	0.1945	133.1	21 508	-1	508c		
14	470	34 573	21.88	48.52	11.32	0.2677	0.5936	0.1385	123.9	23 519	-1	519c		
14	475	35 575	22.7	49.38	11.32	0.2721	0.592	0.1358	123.3	24 520	-1	520c	Gm	
15	480	35 578	24.82	51.36	9.2	0.2907	0.6015	0.1077	118.3	26 530	-1	530c		
17	485	36 583	28.38	53.85	6.17	0.321	0.6091	0.0698	110.9	28 542	-1	542c		
18	490	38 593	37.21	59.63	5.13	0.3648	0.5847	0.0503	101.5	30 552	-1	552c	max	
19	495	52 661	75.53	76.84	4.32	0.482	0.4903	0.0275	52.2	34 572	14	460		
20	500	-1 500c	77.56	76.58	3.66	0.4914	0.4853	0.0231	47.5	34 573	13	468		
22	510	-1 510c	77.48	73.68	2.74	0.5034	0.4787	0.0178	41.7	34 574	14	473		
23	520	-1 519c	77.35	71.71	2.46	0.5104	0.4732	0.0162	38.0	35 576	15	475	Ym	
26	530	-1 530c	76.01	63.9	1.98	0.5356	0.4503	0.0139	24.5	35 579	16	481		
27	540	-1 539c	75.15	60.8	1.9	0.5451	0.441	0.0137	19.8	36 581	16	483		
29	545	-1 545c	72.66	54.07	1.8	0.5652	0.4206	0.014	10.6	37 585	17	486		
29	550	-1 549c	72.66	54.07	1.8	0.5652	0.4206	0.014	10.6	37 585	17	486		
31	555	-1 555c	68.96	46.89	1.76	0.5863	0.3986	0.0149	2.5	37 589	17	488		
32	560	-1 560c	66.59	43.22	1.75	0.5968	0.3874	0.0156	359.0	38 591	17	489		
34	570	1 405	68.43	43.47	1.4	0.5846	0.3714	0.0149	353.9	39 596	18	490	Rm	
34	570	7 435	70.01	43.26	14.2	0.5491	0.3933	0.0134	340.5	47 638	18	494		
34	571	9 450	70.75	42.86	20.4	0.5279	0.3198	0.1522	330.1	-1 498c	19	498		
34	572	12 460	71.92	42.54	30.29	0.4968	0.2938	0.2093	313.6	-1 507c	21	507		
34	572	12 465	71.38	41.96	30.29	0.4969	0.2921	0.2109	313.1	-1 508c	21	508		
34	573	14 470	71.41	41.47	35.86	0.48	0.2788	0.241	304.0	-1 519c	23	519		
35	575	14 475	70.59	40.61	35.86	0.4799	0.2761	0.2438	303.3	-1 520c	24	520	Mm	
35	578	15 480	68.47	38.63	37.98	0.4719	0.2662	0.2617	298.4	-1 530c	26	530		
36	583	17 485	64.91	36.14	41.01	0.4569	0.2543	0.2886	290.9	-1 542c	28	542		
38	593	18 490	56.08	30.36	42.05	0.4364	0.2362	0.3272	281.6	-1 552c	30	552	min	
52	661	19 495	17.76	13.15	42.86	0.2407	0.1782	0.5809	232.3	12 460	34	572		
-1 500c	20 500	15.73	13.41	43.52	0.2165	0.1845	0.5989	227.5	13 468	34	573			
-1 510c	22 510	15.81	16.31	44.44	0.2065	0.213	0.5804	221.8	14 473	34	574			
-1 519c	23 520	15.95	18.28	44.72	0.202	0.2315	0.5664	218.0	15 475	35	576	Bm		
-1 530c	26 530	17.28	26.09	45.2	0.1951	0.2945	0.5103	204.5	16 481	35	579			
-1 539c	27 540	18.14	29.19	45.28	0.1958	0.3151	0.4889	199.8	16 483	36	581			
-1 545c	29 545	20.63	35.92	43.38	0.2024	0.3524	0.4451	190.6	17 486	37	585			
-1 549c	29 550	20.63	35.92	43.38	0.2024	0.3524	0.4451	190.6	17 486	37	585			
-1 555c	31 555	24.33	43.1	45.42	0.2156	0.3819	0.4024	182.5	17 488	37	589			
-1 560c	32 560	26.7	46.77	45.43	0.2245	0.3933	0.3821	179.0	17 489	38	591			
W0	380	770	93.3	89.99	47.19	0.4047	0.3904	0.2047	0.0					
N0	380	770	3.73	3.59	1.88	0.4047	0.3904	0.2047	0.0					

Siehe ähnliche Dateien der ganzen Serie: <http://farbe.li-berlin.de/egu9/vg9.htm>
 Technische Information: <http://farbe.li-berlin.de/egu9/vg9.htm>

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P30, Y_N=3,6, Y_W=90, Y_m=520 770

l ₁	l ₂	λ ₂	Y	A ₂	B ₂	C _{AB,2}	a ₂	b ₂	h _{xy,2}	l _d	l _e	λ _c	Code
1	405	34 570	46.52	-56.81	-80.69	98.69	0.2662	-0.9035	234.8	18 490	39	596	Cm
7	435	34 570	46.73	-58.29	-57.93	82.19	0.2557	-0.7056	224.8	18 494	47	638	
9	450	34 571	47.13	-59.1	-42.12	72.65	0.2531	-0.5681	215.5	19 498	-1	498c	
12	460	34 572	47.45	-59.68	-17.34	62.14	0.2517	-0.3558	196.2	21 507	-1	507c	
12	465	34 572	48.03	-59.74	-17.03	62.13	0.2572	-0.3515	195.9	21 508	-1	508c	
14	470	34 573	48.52	-59.33	-2.87	59.4	0.2656	-0.2333	182.7	23 519	-1	519c	
14	475	35 575	49.38	-59.36	-2.43	59.41	0.2739	-0.2293	182.3	24 520	-1	520c	Gm
15	480	35 578	51.36	-58.34	3.92	58.47	0.3003	-0.1791	176.1	26 530	-1	530c	
17	485	36 583	53.85	-54.98	12.8	56.45	0.3463	-0.1145	166.8	28 542	-1	542c	
18	490	38 593	59.63	-47.54	18.42	50.99	0.4358	-0.0861	158.8	30 552	-1	552c	max
19	495	52 661	76.84	0.71	29.48	29.98	0.7584	-0.0662	88.6	34 572	12	460	
20	500	-1 500c	76.58	5.96	30.99	31.56	0.7859	-0.0477	79.1	34 573	13	468	
22	510	-1 510c	73.68	12.32	31.75	34.06	0.8216	-0.0372	68.7	34 574	14	473	
23	520	-1 519c	71.71	16.35	31.42	35.43	0.8459	-0.0343	62.5	35 576	15	475	Ym
26	530	-1 530c	63.9	30.38	28.53	41.68	0.9449	-0.031	43.2	35 579	16	481	
27	540	-1 539c	60.8	35.2	27.12	44.44	0.9864	-0.031	37.6	36 581	16	483	
29	545	-1 545c	54.07	44.24	23.83	50.25	1.082	-0.0333	28.3	37 585	17	486	
29	550	-1 549c	54.07	44.24	23.83	50.25	1.082	-0.0333	28.3	37 585	17	486	
31	555	-1 555c	46.89	51.55	20.17	55.35	1.1945	-0.0375	21.3	37 589	17	488	
32	560	-1 560c	43.22	54.21	18.28	57.21	1.2564	-0.0404	18.6	38 591	17	489	
34	570	1 405	43.47	56.81	9.92	57.67	1.2775	-0.1183	9.9	39 596	18	490	Rm
34	570	7 435	43.26	58.29	-12.82	59.68	1.2936	-0.3282	34.75	47 638	18	494	
34	571	9 450	42.86	59.1	-23.52	65.62	1.3063	-0.4758	33.42	-1 498c	19	498	
34	572	12 460	42.54	59.67	-53.42	80.09	1.3158	-0.7119	31.81	-1 507c	21	507	
34	572	12 465	41.96	59.73	-53.72	80.34	1.3242	-0.7218	31.80	-1 508c	21	508	
34	573	14 470	41.47	59.32	-67.88	90.15	1.3269	-0.8644	31.11	-1 519c	23	519	
35	575	14 475	40.61	59.35	-68.32	90.5	1.3392	-0.8825	310.9	-1 520c	23	520	Mm
35	578	15 480	38.63	58.33	-74.67	94.76	1.3587	-0.9828	307.9	-1 530c	26	530	
36	583	17 485	36.14	54.97	-83.55	100.01	1.3631	-1.1343	303.3	-1 542c	28	542	
38	593	18 490	30.36	47.53	-89.17	101.05	1.3809	-1.3843	298.0	-1 552c	30	552	min
52	661	19 495	13.15	-0.71	-100.21	100.21	0.733	-3.2566	269.5	12 460	34	572	
-1 500c	20 500	13.41	-5.95	-101.73	101.9	0.577	-3.2435	266.6	13 468	34	573		
-1 510c	22 510	16.31	-12.31	-102.49	103.23	0.4527	-2.7227	263.1	14 473	34	574		
-1 519c	23 520	18.28	-16.35	-102.17	103.47	0.3971	-2.4446	260.9	15 475	35	576	Bm	
-1 530c	26 530	26.09	-30.38	-99.29	103.84	0.289	-1.7319	252.9	16 481	35	579		
-1 539c	27 540	29.19	-35.2	-97.88	104.01	0.2724	-1.5506	250.2	16 483	36	581		
-1 545c	29 545	35.92	-44.24	-94.59	104.03	0.2621	-1.2628	244.9	17 486	37	585		
-1 549c	29 550	35.92	-44.24	-94.59	104.03	0.2621	-1.2628	244.9	17 486	37	585		
-1 555c	31 555	43.1	-51.55	-90.94	104.53	0.2764	-1.0535	240.4	17 488	37	589		
-1 560c	32 560	46.77	-54.21	-89.05	104.25	0.2911	-0.9712	238.6	17 489	38	591		
W0	380	770	89.99	0.0	0.0	0.0	0.7547	-0.5242	0.0	B _c =2,500			
N0	380	770	3.59	0.0	0.0	0.0	0.7547	-0.5242	0.0	x _c =0,110			

TUB-Registrierung: 2023/0701-egu9/egu9l0n1.txt / ps
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe
 TUB-Material: Code=mat4ta