



Siehe ähnliche Dateien: <http://www.ps.bam.de/LG19/LG19.HTM>
 Information, Bestellung: <http://www.ps.bam.de> Version 2.0, io=0,3; i:TLS; o:TLS, CIELAB

BAM-Registrierung: 20030101-LG19/10L/L19G03FP.PS/.PDF BAM-Material: Code=tha4ta
 Anwendung für Messung von Monitor- (Yr=2.5) und Drucker Ausgabe

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
01	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
02	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
03	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
04	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
05	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
06	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
07	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
08	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
09	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
10	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
11	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
12	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
13	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
14	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]

Benutzte Koordinate
 Umfeld Infeld
C LAB*_{TLS00} 011*
 LAB*_{TLS00} 01v*
M LAB*_{TLS00} 111*
 LAB*_{TLS00} 00v*
Y LAB*_{TLS00} 11v*
 LAB*_{TLS00} 010*
O LAB*_{TLS00} 11v*
 LAB*_{TLS00} 000*
L LAB*_{TLS00} 01v*
 LAB*_{TLS00} 010*
V LAB*_{TLS00} 011*
 LAB*_{TLS00} 00v*
N/W LAB*_{TLS00} 01v*
 LAB*_{TLS00} w*



16 gleichabständige CIELAB-Stufen: C-W, C-N, M-W, M-N, Y-W, Y-N, O-W, O-N, L-W, L-N, V-W, V-N, N-W, W-N und 14 CIE-Testfarben (links)

Prüfvorlage LG19: CIELAB-Stufen ISO/IEC 15775
 Bunt-Weiß, Bunt-Schwarz, Schwarz-Weiß

Eingabe ,TLS00,TLS00: LAB* setcolor (2x)
 Ausgabe ,TLS00: olv* / www* setrgbcolor

