

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE^*	Intended output S2	
1	18.0	0.0	0.0	0.0	18.0	0.0	0.0	0.0	0.0	0.01	Specification according to ISO/IEC 15775:1999 Annex G and DIN 33866-1:2000 Annex G	
2	23.16	0.0	0.0	0.07	23.2	0.0	0.0	0.04	0.0	0.04		
3	28.32	0.0	0.0	0.13	28.3	0.0	0.0	-0.01	0.0	0.02		
4	33.48	0.0	0.0	0.2	33.5	0.0	0.0	0.02	0.0	0.02		
5	38.64	0.0	0.0	0.27	38.6	0.0	0.0	-0.03	0.0	0.04		
6	43.8	0.0	0.0	0.33	43.8	0.0	0.0	0.0	0.0	0.01		
7	48.96	0.0	0.0	0.4	49.0	0.0	0.0	0.04	0.0	0.04		
8	54.12	0.0	0.0	0.47	54.1	0.0	0.0	-0.01	0.0	0.02		
9	59.28	0.0	0.0	0.53	59.3	0.0	0.0	0.02	0.0	0.02		
10	64.44	0.0	0.0	0.6	64.4	0.0	0.0	-0.03	0.0	0.04		
11	69.6	0.0	0.0	0.67	69.6	0.0	0.0	0.0	0.0	0.01		
12	74.76	0.0	0.0	0.73	74.8	0.0	0.0	0.04	0.0	0.04		
13	79.92	0.0	0.0	0.8	79.9	0.0	0.0	-0.01	0.0	0.02		
14	85.08	0.0	0.0	0.87	85.1	0.0	0.0	0.02	0.0	0.02		
15	90.24	0.0	0.0	0.93	90.2	0.0	0.0	-0.03	0.0	0.04		Mean lightness difference (16 steps)
16	95.4	0.0	0.0	1.0	95.4	0.0	0.0	0.0	0.0	0.01		$\Delta E^*_{\text{CIELAB}} = 0.0$
17	18.0	0.0	0.0	0.0	18.0	0.0	0.0	0.0	0.0	0.01		
18	37.35	0.0	0.0	0.25	37.32	0.0	0.0	-0.02	0.0	0.03		
19	56.7	0.0	0.0	0.5	56.7	0.0	0.0	0.0	0.0	0.01		
20	76.05	0.0	0.0	0.75	76.08	0.0	0.0	0.03	0.0	0.03		Mean lightness difference (5 steps)
21	95.4	0.0	0.0	1.0	95.4	0.0	0.0	0.0	0.0	0.01		$\Delta L^*_{\text{CIELAB}} = 0.0$
Mean colour reproduction index:										$R^*_{\text{ab,m}} = 100$		