









Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _N =0, Y _W =100, Y _m =520, 770													
λ ₁	λ ₂	λ ₃	λ ₁₀₀	Y ₂₅	Z ₁₀₀	x	y	z	h _{xy}	lg ₁₀ a	lg ₁₀ c	Code	
0.405	32.561	30.34	52.05	95.82	0.1698	0.2938	0.5362	193.8	16.483	37.589	37.589	Cm	
6.435	32.562	27.42	53.11	79.11	0.1717	0.3326	0.4955	178.5	17.486	42.610	42.610	G	
10.450	32.563	22.23	53.83	48.81	0.1794	0.4345	0.3589	141.5	19.496	51.496	51.496	M ₁	
12.460	33.565	20.17	54.2	32.01	0.1895	0.5094	0.3009	124.2	21.505	-1.505c	505c	C	
12.465	33.567	21.24	55.55	32.01	0.1952	0.5105	0.2942	122.8	21.506	-1.506c	506c	C	
14.470	33.569	21.05	56.75	19.92	0.2154	0.5806	0.2038	111.1	24.520	-1.520c	520c	G	
15.475	34.573	22.93	58.82	15.56	0.2356	0.6603	0.1599	105.6	25.528	-1.528c	528c	Gm	
16.480	36.580	27.09	62.51	12.24	0.2659	0.6138	0.1202	99.2	27.537	-1.537c	537c	G	
17.485	39.595	38.4	70.16	9.81	0.3243	0.5927	0.0828	87.4	29.548	-1.548c	548c	G	
18.490	-1.490c	68.75	83.26	8.0	0.4296	0.5203	0.05	58.5	33.565	11.459	max		
19.495	-1.495c	68.7	81.97	6.61	0.4368	0.5211	0.042	57.1	33.566	12.462	max		
20.500	-1.500c	68.89	80.35	5.53	0.4443	0.5197	0.0358	55.3	33.567	12.464	max		
22.510	-1.510c	68.58	75.92	4.14	0.4614	0.5107	0.0278	50.6	33.569	13.469	max		
23.520	-1.519c	68.38	73.09	3.72	0.4709	0.5033	0.0256	47.7	34.570	14.471	Ym		
25.530	-1.529c	67.41	66.25	3.21	0.4924	0.484	0.0235	40.7	34.573	15.475	575		
27.540	-1.539c	65.45	58.38	2.95	0.5162	0.4604	0.0232	32.8	35.577	15.478	577		
28.545	-1.544c	64.07	54.27	2.88	0.5285	0.4476	0.0237	28.7	35.579	15.479	579		
29.550	-1.549c	62.39	50.08	2.83	0.541	0.4343	0.0245	24.7	36.582	16.480	582		
30.555	-1.554c	60.41	45.89	2.8	0.5536	0.4206	0.0257	20.8	36.584	16.481	584		
32.560	-1.560c	55.56	37.8	2.77	0.5779	0.3932	0.0288	13.6	37.589	16.483	589		
32.561	0.405	64.69	47.49	13.07	0.5164	0.3791	0.1043	13.8	37.589	16.483	Rm		
32.562	6.435	67.62	46.88	29.77	0.4687	0.3249	0.2063	35.8	42.610	17.486	8		
32.563	10.450	72.8	46.16	61.07	0.4043	0.2564	0.3392	321.6	-1.496c	19.496	505		
33.565	12.460	74.87	45.79	76.87	0.379	0.2318	0.3891	304.3	-1.505c	21.506	506		
33.567	12.465	73.79	44.44	76.87	0.3782	0.2278	0.3939	302.9	-1.506c	21.506	506		
33.569	14.470	73.98	43.24	88.96	0.3588	0.2097	0.4314	291.1	-1.520c	24.520	520		
34.573	15.475	72.1	41.17	93.32	0.3489	0.1992	0.4517	285.6	-1.528c	25.528	528	Mm	
36.580	16.480	67.95	37.48	96.64	0.3362	0.1854	0.4782	279.3	-1.537c	27.537	537	G	
39.595	17.485	56.63	29.83	99.07	0.3052	0.1607	0.5339	267.4	-1.548c	29.548	548	G	
-1.490c	18.490	26.29	16.73	100.88	0.1826	0.1162	0.701	238.5	11.459	33.565	min		
-1.495c	19.495	26.33	18.02	102.27	0.1795	0.1229	0.6974	237.1	12.462	33.566			
-1.500c	20.500	26.35	19.64	103.35	0.1764	0.1315	0.692	235.4	12.464	33.567			
-1.510c	22.510	26.46	24.07	104.75	0.1703	0.155	0.6745	230.7	13.469	33.569			
-1.519c	23.520	26.65	26.9	105.16	0.1679	0.1695	0.6625	227.7	14.471	34.570	Bm		
-1.529c	25.530	27.63	33.74	105.67	0.1654	0.202	0.6325	220.5	15.475	34.573	575		
-1.539c	27.540	29.58	41.61	105.93	0.167	0.2349	0.598	212.8	15.478	35.577	577		
-1.544c	28.545	30.96	45.72	106.01	0.1694	0.2502	0.5802	208.8	15.479	35.579	579		
-1.549c	29.550	32.65	49.91	106.05	0.173	0.2646	0.5622	204.7	16.480	36.582			
-1.554c	30.555	34.63	54.1	106.08	0.1777	0.2777	0.5445	200.8	16.481	36.584			
-1.560c	32.560	39.47	62.19	106.12	0.1899	0.2993	0.5107	193.6	16.483	37.589			
W1	380	770	95.04	100.0	0.1889	0.3127	0.329	358.2	0.0				
N1	380	770	2.7	2.84	3.09	0.3127	0.329	358.2	0.0				

Siehe ähnliche Dateien: http://farbe.li.tu-berlin.de/AGS8/AGS8L01.TXT /PS
 Technische Information: http://farbe.li.tu-berlin.de/AGS8/AGS8L01.TXT /PS



TUB-Registrierung: 20201101-AGS8/AGS8L01.TXT /PS
 Anwendung für Breustellung und Messung von Display- oder Druck-Ausgabe
 TUB-Material: Code=mat4ta