



Name	Range	$X_{d,10}$	$Y_{d,10}$	$Z_{d,10}$	$x_{d,10}$	$y_{d,10}$	$\lambda_d$	$\lambda_c$
R <sub>d</sub>	578_775	89.16	52.06	2.63	0.6197	0.3619	605	495
Y <sub>d</sub>	500_775	113.02	95.19	3.75	0.5332	0.449	580	473
G <sub>d</sub>	500_578	35.63	53.22	3.75	0.3847	0.5747	547	547c
C <sub>d</sub>	380_578	39.16	58.04	26.14	0.3175	0.4705	495	605
B <sub>d</sub>	380_500	15.3	14.91	25.03	0.2769	0.2699	473	580
M <sub>d</sub>	578_500	92.69	56.88	25.03	0.5308	0.3257	547c	547
W <sub>d</sub>	380_775	116.54	99.99	26.13	0.4802	0.412	100%	
N <sub>d</sub>	380_775	11.65	9.99	2.61	0.4802	0.412	10%	
Z <sub>d</sub>	380_775	20.97	17.99	4.7	0.4802	0.412	18%	

**Parameter:**  
 $Y_{10}$  & Name  
 Illuminant P25  
 $Y_{W,10}=100, Y_{N,10}=10$

**CIE 1964**