

Ostwald-Optimalfarben (o) von maximalem (m) $C_{AB,10}$ für D65, $Y_w,10=100$ , $Y_m=520\_770$												
$i_1, \lambda_1$	$i_2, \lambda_2$	$X_{10}$	$Y_{10}$	$Z_{10}$	$x_{10}$	$y_{10}$	$z_{10}$	$h_{xy,10}$	$i_d, \lambda_d$	$i_c, \lambda_c$	Code	
0	405	31 556	31.74	56.57	106.53	0.1629	0.2903	0.5467	195.0	15 476 37 585	Cm	
6	435	31 557	28.0	57.42	83.63	0.1656	0.3396	0.4947	176.6	16 480 44 621		
10	450	31 559	22.06	57.53	46.52	0.1749	0.4561	0.3689	137.9	18 491 -1 491c		
11	460	32 562	22.29	59.27	37.3	0.1875	0.4986	0.3137	126.9	19 498 -1 498c		
12	465	33 565	22.82	60.92	28.98	0.2025	0.5403	0.2571	117.9	21 506 -1 506c		
14	470	34 570	24.62	63.07	16.02	0.2373	0.6081	0.1544	105.3	24 522 -1 522c		
15	475	35 579	31.53	68.64	11.53	0.2822	0.6144	0.1032	96.3	26 533 -1 533c	Gm	
16	480	41 606	54.03	81.94	8.23	0.3746	0.5682	0.0571	75.5	30 550 -1 550c		
16	485	-1 484c	77.05	92.3	8.23	0.4339	0.5197	0.0463	57.5	32 560 10 454		
18	490	-1 490c	76.87	89.06	4.2	0.4518	0.5234	0.0247	54.3	32 562 11 459	max	
19	495	-1 495c	76.85	87.05	2.97	0.4605	0.5216	0.0178	52.4	32 563 12 461		
19	500	-1 499c	76.85	87.05	2.97	0.4605	0.5216	0.0178	52.4	32 563 12 461		
22	510	-1 510c	76.43	79.1	1.01	0.4882	0.5052	0.0064	44.9	33 566 13 466		
23	520	-1 519c	76.0	75.81	0.68	0.4983	0.4971	0.0045	41.9	33 568 13 468	Ym	
26	530	-1 530c	73.15	64.17	0.16	0.532	0.4667	0.0012	31.8	34 573 14 472		
27	540	-1 539c	71.61	59.9	0.08	0.5441	0.4551	0.0006	28.3	35 576 14 473		
28	545	-1 544c	69.75	55.54	0.04	0.5565	0.4431	0.0003	24.7	35 578 14 474		
29	550	-1 549c	67.56	51.12	0.01	0.5691	0.4306	0.0001	21.3	36 580 15 475		
31	555	-1 555c	62.15	42.37	0.0	0.5946	0.4053	0.0	14.8	37 586 15 476		
32	560	10 451	70.49	40.04	58.45	0.4171	0.2369	0.3458	317.7	-1 492c 18 492		
31	556	0 405	63.06	43.42	0.8	0.5877	0.4047	0.0074	15.0	37 585 15 476	Rm	
31	557	6 435	66.81	42.57	23.7	0.5019	0.3199	0.178	356.6	44 621 16 480		
31	559	10 450	72.75	42.46	60.8	0.4132	0.2412	0.3454	317.9	-1 491c 18 491		
32	562	11 460	72.51	40.72	70.03	0.3956	0.2222	0.3821	307.0	-1 498c 19 498		
33	565	12 465	71.98	39.07	78.34	0.38	0.2063	0.4136	298.0	-1 506c 21 506		
34	570	14 470	70.19	36.92	91.31	0.3537	0.186	0.4601	285.4	-1 522c 24 522		
35	579	15 475	63.28	31.35	95.79	0.3323	0.1646	0.503	276.3	-1 533c 26 533	Mm	
41	606	16 480	40.77	18.05	99.09	0.2581	0.1143	0.6275	255.6	-1 550c 30 550		
-1	484c	16 485	17.75	7.69	99.09	0.1425	0.0618	0.7956	237.5	10 454 32 560		
-1	490c	18 490	17.94	10.93	103.13	0.1359	0.0828	0.7812	234.3	11 459 32 562	min	
-1	495c	19 495	17.96	12.94	104.35	0.1327	0.0957	0.7714	232.4	12 461 32 563		
-1	499c	19 500	17.96	12.94	104.35	0.1327	0.0957	0.7714	232.4	12 461 32 563		
-1	510c	22 510	18.38	20.89	106.32	0.1262	0.1435	0.7302	224.9	13 466 33 566		
-1	519c	23 520	18.8	24.18	106.64	0.1256	0.1616	0.7126	222.0	13 468 33 568	Bm	
-1	530c	26 530	21.65	35.82	107.16	0.1315	0.2175	0.6508	211.8	14 472 34 573		
-1	539c	27 540	23.19	40.09	107.24	0.136	0.2351	0.6288	208.3	14 473 35 576		
-1	544c	28 545	25.05	44.45	107.29	0.1417	0.2514	0.6068	204.8	14 474 35 578		
-1	549c	29 550	27.25	48.87	107.32	0.1485	0.2664	0.585	201.3	15 475 36 580		
-1	555c	31 555	32.65	57.62	107.33	0.1652	0.2916	0.5431	194.8	15 476 37 586		
10	451	32 560	24.31	59.95	48.88	0.1826	0.4502	0.367	137.6	18 492 -1 492c		
380	770	94.81	100.0	107.33	0.3137	0.3309	0.3552	0.0				