

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für D65, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
0 405 32 561	31.49	53.78	97.34	0.1724	0.2945	0.533	193.8	16 483	37 589	Cm	
6 435 32 562	28.55	54.39	80.58	0.1746	0.3326	0.4927	178.5	17 486	42 610		
10 450 32 563	23.35	55.1	49.17	0.1829	0.4317	0.3852	141.6	19 496	-1 496c		
12 460 33 565	21.28	55.49	33.31	0.1933	0.504	0.3026	124.2	21 505	-1 505c		
12 465 33 567	22.36	56.83	33.32	0.1987	0.5051	0.2961	122.8	21 506	-1 506c		
14 470 33 569	22.16	58.03	21.18	0.2186	0.5724	0.2089	111.1	24 520	-1 520c	Gm	
15 475 34 573	24.05	60.12	16.8	0.2382	0.5953	0.1664	105.6	25 528	-1 528c		
16 480 36 580	28.23	63.83	13.47	0.2674	0.6048	0.1276	99.2	27 537	-1 537c		
17 485 39 595	39.58	71.51	11.03	0.3241	0.5855	0.0903	87.4	29 548	-1 548c		
18 490 -1 490c	70.02	84.64	9.22	0.4272	0.5164	0.0562	58.5	33 565	11 459	max	
19 495 -1 495c	69.98	83.35	7.82	0.4342	0.5171	0.0485	57.1	33 566	12 462		
20 500 -1 500c	69.96	81.72	6.74	0.4416	0.5158	0.0425	55.3	33 567	12 464		
22 510 -1 510c	69.85	77.28	5.33	0.4581	0.5068	0.035	50.6	33 569	13 469		
23 520 -1 519c	69.66	74.43	4.92	0.4674	0.4995	0.033	47.7	34 570	14 471	Ym	
25 530 -1 529c	68.68	67.57	4.41	0.4882	0.4803	0.0314	40.7	34 573	15 475		
27 540 -1 539c	66.72	59.67	4.15	0.511	0.4571	0.0318	32.8	35 577	15 478		
28 545 -1 544c	65.33	55.55	4.08	0.5228	0.4445	0.0326	28.7	35 579	15 479		
29 550 -1 549c	63.64	51.35	4.03	0.5347	0.4313	0.0338	24.7	36 582	16 480		
30 555 -1 554c	61.66	47.14	4.0	0.5465	0.4179	0.0354	20.8	36 584	16 481		
32 560 -1 560c	56.8	39.03	3.96	0.5691	0.391	0.0397	13.6	37 589	16 483		
32 561 0 405	63.55	46.21	11.54	0.5238	0.3809	0.0951	13.8	37 589	16 483	Rm	
32 562 6 435	66.48	45.6	28.3	0.4735	0.3248	0.2016	358.5	42 610	17 486		
32 563 10 450	71.69	44.89	59.71	0.4066	0.2546	0.3387	321.6	-1 496c	19 496		
33 565 12 460	73.75	44.5	75.57	0.3805	0.2295	0.3898	304.3	-1 505c	21 505		
33 567 12 465	72.68	43.16	75.56	0.3797	0.2254	0.3947	302.9	-1 506c	21 506		
33 569 14 470	72.87	41.96	87.7	0.3598	0.2071	0.433	291.1	-1 520c	24 520	Mm	
34 573 15 475	70.98	39.87	92.08	0.3497	0.1964	0.4537	285.6	-1 528c	25 528		
36 580 16 480	66.81	36.16	95.41	0.3367	0.1822	0.4809	279.3	-1 537c	27 537		
39 595 17 485	55.46	28.48	97.85	0.305	0.1567	0.5382	267.4	-1 548c	29 548		
-1 490c 18 490	25.01	15.35	99.66	0.1786	0.1096	0.7117	238.5	11 459	33 565	min	
-1 495c 19 495	25.05	16.64	101.06	0.1755	0.1166	0.7078	237.1	12 462	33 566		
-1 500c 20 500	25.07	18.27	102.14	0.1723	0.1256	0.702	235.4	12 464	33 567		
-1 510c 22 510	25.18	22.71	103.55	0.1662	0.1499	0.6837	230.7	13 469	33 569		
-1 519c 23 520	25.38	25.56	103.96	0.1638	0.165	0.6711	227.7	14 471	34 570	Bm	
-1 529c 25 530	26.35	32.42	104.47	0.1614	0.1986	0.6399	220.7	15 475	34 573		
-1 539c 27 540	28.32	40.32	104.73	0.1633	0.2325	0.604	212.8	15 478	35 577		
-1 544c 28 545	29.7	44.44	104.81	0.1659	0.2483	0.5856	208.8	15 479	35 579		
-1 549c 29 550	31.39	48.64	104.85	0.1697	0.2631	0.567	204.7	16 480	36 582		
-1 554c 30 555	33.38	52.85	104.88	0.1746	0.2765	0.5488	200.8	16 481	36 584		
-1 560c 32 560	38.24	60.96	104.92	0.1873	0.2986	0.5139	193.6	16 483	37 589		
W0 380 770	95.04	100.0	108.89	0.3127	0.329	0.3582	0.0				
N0 380 770	3.8	4.0	4.35	0.3127	0.329	0.3582	0.0				

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für D65, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code
0 405 32 561	53.78	-49.05	-38.76	62.52	0.5853	-0.7237	218.3	16 483	37 589	Cm	
6 435 32 562	54.39	-57.84	-21.34	61.65	0.5247	-0.5924	200.2	17 486	42 610		
10 450 32 563	55.1	-72.53	10.82	73.34	0.4236	-0.3568	171.5	19 496	-1 496c		
12 460 33 565	55.49	-78.62	27.09	83.16	0.3834	-0.2401	160.9	21 505	-1 505c		
12 465 33 567	56.83	-79.12	28.55	84.12	0.3933	-0.2344	160.1	21 506	-1 506c		
14 470 33 569	58.03	-82.45	41.99	92.53	0.3818	-0.146	153.0	24 520	-1 520c	Gm	
15 475 34 573	60.12	-82.67	48.63	95.92	0.4	-0.1118	149.5	25 528	-1 528c		
16 480 36 580	63.83	-81.06	56.01	98.53	0.4421	-0.0844	145.3	27 537	-1 537c		
17 485 39 595	71.51	-70.92	66.8	97.43	0.5534	-0.0617	136.7	29 548	-1 548c		
18 490 -1 490c	84.64	-26.03	82.92	86.91	0.8271	-0.0435	107.4	33 565	11 459	max	
19 495 -1 495c	83.35	-23.06	82.9	86.05	0.8394	-0.0375	105.5	33 566	12 462		
20 500 -1 500c	81.72	-19.23	82.21	84.43	0.8559	-0.033	103.1	33 567	12 464		
22 510 -1 510c	77.28	-8.95	78.79	79.29	0.9037	-0.0276	96.4	33 569	13 469		
23 520 -1 519c	74.43	-2.7	76.1	76.15	0.9356	-0.0264	92.0	34 570	14 471	Ym	
25 530 -1 529c	67.57	11.15	69.14	70.04	1.0161	-0.0261	80.8	34 573	15 475		
27 540 -1 539c	59.67	25.01	60.81	65.75	1.1178	-0.0278	67.6	35 577	15 478		
28 545 -1 544c	55.55	31.34	56.39	64.52	1.1758	-0.0293	60.9	35 579	15 479		
29 550 -1 549c	51.35	37.11	51.86	63.77	1.2392	-0.0314	54.4	36 582	16 480		
30 555 -1 554c	47.14	42.11	47.32	63.35	1.3074	-0.0339	48.3	36 584	16 481		
32 560 -1 560c	39.03	49.24	38.52	62.52	1.4548	-0.0406	38.0	37 589	16 483		
32 561 0 405	46.21	49.05	38.76	62.52	1.3747	-0.0999	38.3	37 589	16 483	Rm	
32 562 6 435	45.6	57.84	21.34	61.65	1.4575	-0.2481	20.2	42 610	17 486		
32 563 10 450	44.89	72.52	-10.82	73.32	1.5963	-0.5318	351.5	-1 496c	19 496		
33 565 12 460	44.5	78.6	-27.09	83.14	1.6566	-0.6789	340.9	-1 505c	21 505		
33 567 12 465	43.16	79.1	-28.55	84.09	1.6832	-0.7	340.1	-1 506c	21 506		
33 569 14 470	41.96	82.43	-41.98	92.5	1.7359	-0.8356	333.0	-1 520c	24 520	Mm	
34 573 15 475	39.87	82.64	-48.62	95.89	1.7791	-0.9231	329.5	-1 528c	25 528		
36 580 16 480	36.16	81.03	-55.99	98.49	1.8464	-1.0547	325.3	-1 537c	27 537		
39 595 17 485	28.48	70.88	-66.77	97.38	1.9454	-1.373	316.7	-1 548c	29 548		
-1 490c 18 490	15.35	26.01	-82.86	86.85	1.6281	-2.5947	287.4	11 459	33 565	min	
-1 495c 19 495	16.64	23.04	-82.85	85.99	1.5038	-2.4259	285.5	12 462	33 566		
-1 500c 20 500	18.27	19.22	-82.16	84.38	1.3709	-2.2338	283.1	12 464	33 567		
-1 510c 22 510	22.71	8.95	-78.75	79.26	1.1078	-1.822	276.4	13 469	33 569		
-1 519c 23 520	25.56	2.7	-76.07	76.12	0.9924	-1.6259	272.0	14 471	34 570	Bm	
-1 529c 25 530	32.42	-11.15	-69.12	70.01	0.8125	-1.2882	260.8	15 475	34 573		
-1 539c 27 540	40.32	-25.0	-60.8	65.74	0.702	-1.0385	247.6	15 478	35 577		
-1 544c 28 545	44.44	-31.33	-56.38	64.5	0.6681	-0.9428	240.9	15 479	35 579		
-1 549c 29 550	48.64	-37.1	-51.85	63.76	0.645	-0.8618	234.4	16 480	36 582		
-1 554c 30 555	52.85	-42.1	-47.31	63.34	0.6314	-0.7935	228.3	16 481	36 584		
-1 560c 32 560	60.96	-49.24	-38.51	62.51	0.627	-0.6881	218.0	16 483	37 589		
W0 380 770	100.0	0.0	0.0	0.0	0.9501	-0.4354	0.0	B _c =1,000			
N0 380 770	4.0	0.0	0.0	0.0	0.9501	-0.4354	0.0	x _c =0,000			

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/CGX1/CGX1L0NP.PDF> / .PS
 Technische Information: <http://farbe.li.tu-berlin.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20201101-CGX1/CGX1L0NP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für D50, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405	32	564	29.26	53.83	73.48	0.1869	0.3438	0.4692	185.2	17 486 38 592 Cm
7	435	33	565	26.01	53.61	57.83	0.1892	0.39	0.4207	168.6	18 490 46 631
10	450	33	566	23.26	54.16	39.66	0.1986	0.4625	0.3387	144.6	19 497 -1 497c
12	460	33	567	22.04	54.86	27.4	0.2113	0.5259	0.2626	128.7	21 506 -1 506c
13	465	33	568	22.01	55.56	22.12	0.2208	0.5572	0.2218	122.1	22 512 -1 512c
14	470	34	570	22.15	56.11	17.7	0.2308	0.5846	0.1844	116.9	23 519 -1 519c Gm
15	475	34	573	23.92	58.04	14.12	0.2489	0.604	0.1469	111.4	25 527 -1 527c
15	480	35	578	27.41	61.49	14.13	0.266	0.5968	0.1371	108.4	26 532 -1 532c
17	485	37	587	33.99	66.01	9.3	0.3109	0.6039	0.0851	98.0	28 544 -1 544c
18	490	44	620	59.95	79.56	7.75	0.407	0.5402	0.0526	71.3	32 561 -1 561c
19	495	-1 495c	75.28	84.51	6.54	0.4525	0.5081	0.0393	54.4	33 568 12 463 max	
20	500	-1 500c	75.26	83.07	5.58	0.4591	0.5067	0.034	52.5	33 569 13 466	
22	510	-1 510c	75.16	79.06	4.31	0.4741	0.4986	0.0272	47.4	34 571 14 471	
23	520	-1 519c	74.98	76.43	3.93	0.4826	0.492	0.0253	44.2	34 572 14 473 Ym	
25	530	-1 529c	74.05	69.95	3.45	0.5021	0.4743	0.0234	36.4	35 575 15 477	
27	540	-1 539c	72.16	62.35	3.2	0.524	0.4527	0.0232	27.8	35 579 16 480	
28	545	-1 544c	70.81	58.33	3.13	0.5353	0.4409	0.0236	23.4	36 581 16 481	
29	550	-1 549c	69.15	54.19	3.08	0.5469	0.4286	0.0244	19.1	36 583 16 483	
30	555	-1 554c	67.17	50.01	3.05	0.5586	0.4159	0.0254	15.0	37 585 16 484	
32	560	-1 560c	62.28	41.85	3.02	0.5812	0.3905	0.0281	7.7	38 590 17 486	
32	564	1 405	67.15	46.16	9.01	0.5489	0.3773	0.0736	5.2	38 592 17 486 Rm	
33	565	7 435	70.4	46.38	24.66	0.4977	0.3279	0.1743	348.6	46 631 18 490	
33	566	10 450	73.15	45.83	42.83	0.452	0.2832	0.2646	324.7	-1 497c 19 497	
33	567	12 460	74.37	45.13	55.09	0.4259	0.2585	0.3155	308.7	-1 506c 21 506	
33	568	13 465	74.4	44.43	60.37	0.4151	0.2479	0.3368	302.1	-1 512c 22 512	
34	570	14 470	74.26	43.88	64.78	0.4059	0.2398	0.3541	296.9	-1 519c 23 519 Mm	
34	573	15 475	72.5	41.95	68.37	0.3965	0.2294	0.3739	291.5	-1 527c 25 527	
35	578	15 480	69.0	38.5	68.36	0.3923	0.2189	0.3887	288.5	-1 532c 26 532	
37	587	17 485	62.42	33.98	73.19	0.368	0.2003	0.4315	278.0	-1 544c 28 544	
44	620	18 490	36.46	20.43	74.74	0.277	0.1552	0.5677	251.3	-1 561c 32 561	
-1 495c	19 495	21.14	15.48	75.95	0.1877	0.1375	0.6746	234.4	12 463 33 568 min		
-1 500c	20 500	21.15	16.92	76.91	0.1839	0.1471	0.6688	232.5	13 466 33 569		
-1 510c	22 510	21.25	20.93	78.18	0.1765	0.1739	0.6494	227.5	14 471 34 571		
-1 519c	23 520	21.44	23.56	78.56	0.1735	0.1907	0.6357	224.2	14 473 34 572 Bm		
-1 529c	25 530	22.36	30.04	79.04	0.1701	0.2285	0.6013	216.5	15 477 35 575		
-1 539c	27 540	24.25	37.64	79.29	0.1717	0.2666	0.5615	207.8	16 480 35 579		
-1 544c	28 545	25.6	41.66	79.36	0.1746	0.2841	0.5412	203.5	16 481 36 581		
-1 549c	29 550	27.26	45.8	79.41	0.1788	0.3004	0.5207	199.2	16 483 36 583		
-1 554c	30 555	29.24	49.98	79.44	0.1843	0.315	0.5006	195.0	16 484 37 585		
-1 560c	32 560	34.13	58.14	79.47	0.1987	0.3385	0.4627	187.7	17 486 38 590		
W0	380	770	96.42	100.0	82.49	0.3457	0.3585	0.2957	0.0		
N0	380	770	3.85	4.0	3.29	0.3457	0.3585	0.2957	0.0		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für D50, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405	32	564	53.83	-56.59	-29.05	63.62	0.5434	-0.5457	207.1	17 486 38 592 Cm
7	435	33	565	53.61	-64.17	-13.59	65.6	0.4851	-0.4313	191.9	18 490 46 631
10	450	33	566	54.16	-72.38	5.01	72.56	0.4294	-0.2928	176.0	19 497 -1 497c
12	460	33	567	54.86	-77.11	17.85	79.14	0.4017	-0.1997	166.9	21 506 -1 506c
13	465	33	568	55.56	-78.87	23.7	82.35	0.3961	-0.1592	163.2	22 512 -1 512c
14	470	34	570	56.11	-79.85	28.57	84.81	0.3947	-0.1261	160.3	23 519 -1 519c Gm
15	475	34	573	58.04	-80.09	33.75	86.91	0.412	-0.0973	157.1	25 527 -1 527c
15	480	35	578	61.49	-79.68	36.59	87.68	0.4456	-0.0919	155.3	26 532 -1 532c
17	485	37	587	66.01	-74.12	45.14	86.79	0.5148	-0.0563	148.6	28 544 -1 544c
18	490	44	620	79.56	-41.87	57.86	71.42	0.7534	-0.0389	125.8	32 561 -1 561c
19	495	-1 495c	84.51	-15.51	63.16	65.04	0.8905	-0.0309	103.7	33 568 12 463 max	
20	500	-1 500c	83.07	-12.07	62.93	64.08	0.9058	-0.0268	100.8	33 569 13 466	
22	510	-1 510c	79.06	-2.65	60.89	60.94	0.9505	-0.0218	92.4	34 571 14 471	
23	520	-1 519c	76.43	3.22	59.1	59.18	0.9808	-0.0205	86.8	34 572 14 473 Ym	
25	530	-1 529c	69.95	16.52	54.23	56.7	1.0584	-0.0197	73.0	35 575 15 477	
27	540	-1 539c	62.35	30.11	48.22	56.85	1.1571	-0.0205	58.0	35 579 16 480	
28	545	-1 544c	58.33	36.43	44.97	57.87	1.2137	-0.0214	50.9	36 581 16 481	
29	550	-1 549c	54.19	42.24	41.6	59.29	1.2758	-0.0227	44.5	36 583 16 483	
30	555	-1 554c	50.01	47.36	38.19	60.84	1.3427	-0.0244	38.8	37 585 16 484	
32	560	-1 560c	41.85	54.81	31.49	63.21	1.4878	-0.0288	29.8	38 590 17 486	
32	564	1 405	46.16	56.59	29.05	63.62	1.4543	-0.078	27.1	38 592 17 486 Rm	
33	565	7 435	46.38	64.17	13.59	65.59	1.5173	-0.2126	11.9	46 631 18 490	
33	566	10 450	45.83	72.37	-5.01	72.55	1.5956	-0.3736	356.0	-1 497c 19 497	
33	567	12 460	45.13	77.09	-17.84	79.13	1.6471	-0.488	346.9	-1 506c 21 506	
33	568	13 465	44.43	78.85	-23.7	82.33	1.6737	-0.5432	343.2	-1 512c 22 512	
34	570	14 470	43.88	79.83	-28.57	84.79	1.6917	-0.5903	340.3	-1 519c 23 519 Mm	
34	573	15 475	41.95	80.07	-33.74	86.89	1.7274	-0.6516	337.1	-1 527c 25 527	
35	578	15 480	38.5	79.66	-36.57	87.65	1.7916	-0.7099	335.3	-1 532c 26 532	
37	587	17 485	33.98	74.1	-45.12	86.76	1.8361	-0.861	328.6	-1 544c 28 544	
44	620	18 490	20.43	41.86	-57.83	71.39	1.7832	-1.4618	305.8	-1 561c 32 561	
-1 495c	19 495	15.48	15.5	-63.13	65.0	1.3645	-1.9609	283.7	12 463 33 568 min		
-1 500c	20 500	16.92	12.07	-62.9	64.04	1.2492	-1.8165	280.8	13 466 33 569		
-1 510c	22 510	20.93	2.64	-60.86	60.92	1.0145	-1.4926	272.4	14 471 34 571		
-1 519c	23 520	23.56	-3.22	-59.08	59.17	0.9092	-1.3327	266.8	14 473 34 572 Bm		
-1 529c	25 530	30.04	-16.51	-54.22	56.68	0.744	-1.0518	253.0	15 477 35 575		
-1 539c	27 540	37.64	-30.11	-48.21	56.84	0.644	-0.8422	238.0	16 480 35 579		
-1 544c	28 545	41.66	-36.42	-44.97	57.87	0.6142	-0.7615	230.9	16 481 36 581		
-1 549c	29 550	45.8	-42.24	-41.6	59.29	0.595	-0.6931	224.5	16 483 36 583		
-1 554c	30 555	49.98	-47.36	-38.19	60.84	0.5849	-0.6355	218.8	16 484 37 585		
-1 560c	32 560	58.14	-54.81	-31.49	63.21	0.5869	-0.5465	209.8	17 486 38 590		
W0	380	770	100.0	0.0	0.0	0.0	0.9639	-0.3298	0.0	B _c =1,000	
N0	380	770	4.0	0.0	0.0	0.0	0.9639	-0.3298	0.0	x _c =0,000	

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/CGX1/CGX1L0NP.PDF> / .PS
 Technische Information: <http://farbe.li.tu-berlin.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20201101-CGX1/CGX1L0NP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P40, Y_N=0, Y_W=100, Y_m=520 770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
0 405 33 568 28.56 52.58 57.84 0.2054 0.3783 0.4161 179.3 17 488 38 594 Cm											
7 435 33 568 26.11 52.87 44.22 0.2119 0.4291 0.3589 162.5 18 493 -1 493c											
10 450 33 569 24.13 53.33 30.9 0.2226 0.4921 0.2851 143.6 19 499 -1 499c											
12 460 34 570 22.8 53.28 21.91 0.2326 0.5437 0.2236 131.3 21 507 -1 507c											
13 465 34 571 22.89 53.83 17.91 0.2418 0.5688 0.1892 125.6 22 512 -1 512c											
14 470 34 572 23.51 54.75 14.51 0.2534 0.5901 0.1564 120.6 23 519 -1 519c Gm											
14 475 34 574 25.3 56.7 14.51 0.2622 0.5874 0.1503 119.1 24 522 -1 522c											
15 480 35 578 27.64 58.85 11.73 0.2814 0.5991 0.1194 113.8 26 531 -1 531c											
17 485 37 585 32.27 62.11 7.83 0.3157 0.6076 0.0766 105.5 28 543 -1 543c											
17 490 40 600 46.83 71.73 7.84 0.3704 0.5674 0.062 92.8 30 554 -1 554c											
19 495 -1 495c 81.89 85.57 5.49 0.4734 0.4947 0.0317 51.6 34 571 12 464 max											
20 500 -1 500c 81.88 84.33 4.67 0.4791 0.4934 0.0273 49.6 34 571 13 467											
21 510 -1 509c 81.86 82.76 4.03 0.4853 0.4906 0.0239 47.2 34 572 13 469											
24 520 -1 520c 81.3 75.67 2.97 0.5083 0.473 0.0185 36.9 35 575 15 476 Ym											
26 530 -1 530c 80.05 69.21 2.65 0.5269 0.4556 0.0174 28.2 35 578 16 480											
27 540 -1 539c 79.05 65.61 2.55 0.5369 0.4456 0.0173 23.7 36 580 16 481											
29 545 -1 545c 76.21 57.91 2.44 0.558 0.424 0.0179 14.9 36 584 16 484											
29 550 -1 549c 76.21 57.91 2.44 0.558 0.424 0.0179 14.9 36 584 16 484											
31 555 -1 555c 72.04 49.83 2.39 0.5797 0.4009 0.0192 6.9 37 588 17 486											
32 560 -1 560c 69.41 45.75 2.38 0.5905 0.3892 0.0202 3.4 38 591 17 487											
33 568 0 405 72.36 47.41 6.83 0.5715 0.3744 0.054 359.3 38 594 17 488 Rm											
33 568 7 435 74.82 47.12 20.46 0.5254 0.3308 0.1437 342.6 -1 493c 18 493											
33 569 10 450 76.8 46.66 33.78 0.4884 0.2967 0.2148 323.6 -1 499c 19 499											
34 570 12 460 78.12 46.71 42.77 0.4661 0.2786 0.2551 311.4 -1 507c 21 507											
34 571 13 465 78.03 46.16 46.77 0.4564 0.2699 0.2735 305.7 -1 512c 22 512											
34 572 14 470 77.41 45.24 50.17 0.4478 0.2617 0.2903 300.6 -1 519c 23 519 Mm											
34 574 14 475 75.62 43.29 50.17 0.4472 0.256 0.2967 299.2 -1 522c 24 522											
35 578 15 480 73.28 41.14 52.95 0.4378 0.2458 0.3163 293.9 -1 531c 26 531											
37 585 17 485 68.65 37.88 56.85 0.4201 0.2318 0.3479 285.5 -1 543c 28 543											
40 600 17 490 54.09 28.26 56.84 0.3886 0.203 0.4083 272.8 -1 554c 30 554											
-1 495c 19 495 19.03 14.42 59.19 0.2054 0.1556 0.6388 231.6 12 464 34 571 min											
-1 500c 20 500 19.04 15.66 60.01 0.2011 0.1653 0.6335 229.7 13 467 34 571											
-1 509c 21 510 19.06 17.23 60.65 0.1966 0.1777 0.6255 227.3 13 469 34 572											
-1 520c 24 520 19.62 24.32 61.71 0.1857 0.2302 0.584 216.9 15 476 35 575 Bm											
-1 530c 26 530 20.87 30.78 62.03 0.1836 0.2707 0.5456 208.3 16 480 35 578											
-1 539c 27 540 21.87 34.38 62.13 0.1847 0.2904 0.5248 203.7 16 481 36 580											
-1 545c 29 545 24.72 42.08 62.24 0.1915 0.3261 0.4823 194.9 16 484 36 584											
-1 549c 29 550 24.72 42.08 62.24 0.1915 0.3261 0.4823 194.9 16 484 36 584											
-1 555c 31 555 28.88 50.16 62.29 0.2043 0.3549 0.4407 186.9 17 486 37 588											
-1 560c 32 560 31.51 54.24 62.3 0.2128 0.3663 0.4208 183.4 17 487 38 591											
W0 380 770 100.93 100.0 64.68 0.3799 0.3764 0.2435 0.0											
N0 380 770 4.03 4.0 2.58 0.3799 0.3764 0.2435 0.0											

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P40, Y_N=0, Y_W=100, Y_m=520 770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code
0 405 33 568 52.58 -61.26 -23.82 65.73 0.543 -0.4399 201.2 17 488 38 594 Cm											
7 435 33 568 52.87 -68.13 -10.01 68.86 0.4936 -0.3344 188.3 18 493 -1 493c											
10 450 33 569 53.33 -74.23 3.59 74.32 0.4523 -0.2317 177.2 19 499 -1 499c											
12 460 34 570 53.28 -77.42 12.55 78.43 0.4278 -0.1644 170.7 21 507 -1 507c											
13 465 34 571 53.83 -78.58 16.9 80.38 0.4251 -0.133 167.8 22 512 -1 512c											
14 470 34 572 54.75 -79.33 20.89 82.04 0.4294 -0.106 165.2 23 519 -1 519c Gm											
14 475 34 574 56.7 -79.77 22.15 82.78 0.4463 -0.1023 164.4 24 522 -1 522c											
15 480 35 578 58.85 -79.36 26.33 83.62 0.4696 -0.0797 161.6 26 531 -1 531c											
17 485 37 585 62.11 -76.01 32.33 82.61 0.5194 -0.0504 156.9 28 543 -1 543c											
17 490 40 600 71.73 -63.89 38.54 74.62 0.6527 -0.0437 148.8 30 554 -1 554c											
19 495 -1 495c 85.57 -11.18 49.84 51.08 0.9567 -0.0256 102.6 34 571 12 464 max											
20 500 -1 500c 84.33 -8.08 49.86 50.51 0.9706 -0.0221 99.2 34 571 13 467											
21 510 -1 509c 82.76 -4.16 49.48 49.66 0.9889 -0.0195 94.8 34 572 13 469											
24 520 -1 520c 75.67 12.33 45.96 47.59 1.0742 -0.0157 74.9 35 575 15 476 Ym											
26 530 -1 530c 69.21 25.48 42.11 49.22 1.1562 -0.0153 58.8 35 578 16 480											
27 540 -1 539c 65.61 32.07 39.88 51.17 1.2045 -0.0155 51.1 36 580 16 481											
29 545 -1 545c 57.91 44.38 35.0 56.53 1.3156 -0.0168 38.2 36 584 16 484											
29 550 -1 549c 57.91 44.38 35.0 56.53 1.3156 -0.0168 38.2 36 584 16 484											
31 555 -1 555c 49.83 54.37 29.82 62.01 1.4455 -0.0192 28.7 37 588 17 486											
32 560 -1 560c 45.75 58.08 27.2 64.13 1.5168 -0.0208 25.0 38 591 17 487											
33 568 0 405 47.41 61.26 23.82 65.73 1.5259 -0.0576 21.2 38 594 17 488 Rm											
33 568 7 435 47.12 68.13 10.01 68.86 1.5873 -0.1736 8.3 -1 493c 18 493											
33 569 10 450 46.66 74.22 -3.59 74.31 1.6453 -0.2894 357.2 -1 499c 19 499											
34 570 12 460 46.71 77.4 -12.54 78.41 1.6719 -0.3661 350.7 -1 507c 21 507											
34 571 13 465 46.16 78.57 -16.9 80.37 1.6899 -0.4051 347.8 -1 512c 22 512											
34 572 14 470 45.24 79.32 -20.89 82.02 1.7102 -0.4434 345.2 -1 519c 23 519 Mm											
34 574 14 475 43.29 79.75 -22.15 82.77 1.7458 -0.4633 344.4 -1 522c 24 522											
35 578 15 480 41.14 79.34 -26.32 83.6 1.7805 -0.5146 341.6 -1 531c 26 531											
37 585 17 485 37.88 75.99 -32.32 82.58 1.8114 -0.5999 336.9 -1 543c 28 543											
40 600 17 490 28.26 63.87 -38.53 74.59 1.913 -0.804 328.8 -1 554c 30 554											
-1 495c 19 495 14.42 11.17 -49.82 51.06 1.3189 -1.6404 282.6 12 464 34 571 min											
-1 500c 20 500 15.66 8.08 -49.84 50.49 1.2155 -1.5316 279.2 13 467 34 571											
-1 509c 21 510 17.23 4.16 -49.46 49.64 1.1056 -1.4065 274.8 13 469 34 572											
-1 520c 24 520 24.32 -12.33 -45.95 47.58 0.8062 -1.0143 254.9 15 476 35 575 Bm											
-1 530c 26 530 30.78 -25.47 -42.1 49.21 0.6779 -0.8058 238.8 16 480 35 578											
-1 539c 27 540 34.38 -32.07 -39.87 51.17 0.6359 -0.7225 231.1 16 481 36 580											
-1 545c 29 545 42.08 -44.38 -35.0 56.52 0.5871 -0.5913 218.2 16 484 36 584											
-1 549c 29 550 42.08 -44.38 -35.0 56.52 0.5871 -0.5913 218.2 16 484 36 584											
-1 555c 31 555 50.16 -54.37 -29.82 62.01 0.5755 -0.4965 208.7 17 486 37 588											
-1 560c 32 560 54.24 -58.08 -27.2 64.13 0.5807 -0.4593 205.0 17 487 38 591											
W0 380 770 100.0 0.0 0.0 0.0 1.009 -0.2586 0.0 B _c =1,000											
N0 380 770 4.0 0.0 0.0 0.0 1.009 -0.2586 0.0 x _c =0,000											

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/CGX1/CGX1L0NP.PDF> / .PS
 Technische Information: <http://farbe.li.tu-berlin.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20201101-CGX1/CGX1L0NP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für A00, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1 405 34 574	27.98	51.03	31.76	0.2525	0.4606	0.2867	164.7	18 494	39 599	Cm	
6 435 34 574	27.34	51.22	27.68	0.2573	0.482	0.2605	158.5	19 496	42 612		
9 450 34 574	26.46	51.5	21.43	0.2662	0.5181	0.2156	148.5	20 501	-1 501c		
12 460 35 575	24.99	51.11	14.02	0.2773	0.567	0.1555	136.8	21 508	-1 508c		
13 465 35 575	25.08	51.41	11.68	0.2844	0.583	0.1325	132.8	22 512	-1 512c		
13 470 35 576	25.78	52.07	11.68	0.2879	0.5815	0.1305	132.5	22 513	-1 513c	Gm	
14 475 35 577	26.59	52.94	9.63	0.2982	0.5937	0.108	128.7	23 519	-1 519c		
16 480 35 579	28.02	54.11	6.49	0.3162	0.6105	0.0732	122.8	26 533	-1 533c		
17 485 36 582	30.53	55.92	5.36	0.3325	0.609	0.0584	119.6	28 540	-1 540c		
18 490 37 588	36.19	59.84	4.46	0.3601	0.5954	0.0444	114.9	29 548	-1 548c		
19 495 40 601	49.98	67.85	3.74	0.411	0.558	0.0308	103.5	31 559	-1 559c		
20 500 -1 500c	94.21	86.26	3.16	0.513	0.4697	0.0172	43.5	35 576	13 469	max	
21 510 -1 509c	94.19	85.08	2.68	0.5176	0.4675	0.0147	40.5	35 576	14 472		
24 520 -1 520c	93.75	79.47	1.85	0.5355	0.4539	0.0105	27.8	35 579	16 480	Ym	
26 530 -1 530c	92.69	74.02	1.58	0.5507	0.4398	0.0094	17.4	36 582	16 484		
28 540 -1 540c	90.67	67.47	1.44	0.5681	0.4227	0.009	7.2	37 585	17 487		
28 545 -1 544c	90.67	67.47	1.44	0.5681	0.4227	0.009	7.2	37 585	17 487		
29 550 -1 549c	89.22	63.86	1.4	0.5775	0.4134	0.009	2.6	37 586	17 489		
31 555 -1 555c	85.25	56.16	1.35	0.5971	0.3933	0.0094	354.6	38 590	18 491		
32 560 -1 560c	82.65	52.14	1.34	0.6071	0.383	0.0098	351.3	38 593	18 492		
34 574 1 405	81.86	48.96	3.81	0.6079	0.3636	0.0283	344.7	39 599	18 494	Rm	
34 574 6 435	82.5	48.77	7.9	0.5927	0.3504	0.0567	338.5	42 612	19 496		
34 574 9 450	83.38	48.49	14.15	0.5709	0.332	0.0969	328.6	-1 501c	20 501		
35 575 12 460	84.85	48.88	21.55	0.5463	0.3147	0.1388	316.8	-1 508c	21 508		
35 575 13 465	84.76	48.58	23.89	0.539	0.3089	0.1519	312.9	-1 512c	22 512		
35 576 13 470	84.06	47.92	23.89	0.5392	0.3074	0.1532	312.5	-1 513c	22 513	Mm	
35 577 14 475	83.25	47.05	25.94	0.5328	0.3011	0.166	308.7	-1 519c	23 519		
35 579 16 480	81.82	45.88	29.09	0.5218	0.2926	0.1855	302.9	-1 533c	26 533		
36 582 17 485	79.31	44.07	30.21	0.5163	0.2869	0.1967	299.7	-1 540c	28 540		
37 588 18 490	73.65	40.15	31.11	0.5081	0.277	0.2147	294.9	-1 548c	29 548		
40 601 19 495	59.86	32.14	31.83	0.4833	0.2595	0.257	283.6	-1 559c	31 559		
-1 500c	20 500	15.63	13.73	0.253	0.2222	0.5246	223.5	13 469	35 576	min	
-1 509c	21 510	15.64	14.91	0.289	0.2466	0.235	0.5183	220.6	14 472	35 576	
-1 520c	24 520	16.09	20.52	0.3372	0.2287	0.2918	0.4794	207.8	16 480	35 579	Bm
-1 530c	26 530	17.15	25.97	0.3399	0.2224	0.3367	0.4407	197.4	16 484	36 582	
-1 540c	28 540	19.17	32.52	0.2233	0.3789	0.3977	187.2	17 487	37 585		
-1 544c	28 545	19.17	32.52	0.2233	0.3789	0.3977	187.2	17 487	37 585		
-1 549c	29 550	20.62	36.13	0.2267	0.3973	0.3758	182.6	17 489	37 586		
-1 555c	31 555	24.59	43.83	0.2395	0.4269	0.3334	174.6	18 491	38 590		
-1 560c	32 560	27.19	47.85	0.2488	0.4378	0.3133	171.2	18 492	38 593		
W0	380	770	109.84	99.99	35.58	0.4475	0.4074	0.1449	0.0		
N0	380	770	4.39	3.99	1.42	0.4475	0.4074	0.1449	0.0		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für A00, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1 405 34 574	51.03	-70.17	-13.6	71.48	0.5481	-0.2489	190.9	18 494	39 599	Cm	
6 435 34 574	51.22	-72.28	-9.45	72.89	0.5337	-0.2161	187.4	19 496	42 612		
9 450 34 574	51.5	-75.25	-3.1	75.31	0.5137	-0.1664	182.3	20 501	-1 501c		
12 460 35 575	51.11	-77.85	4.16	77.96	0.4889	-0.1097	176.9	21 508	-1 508c		
13 465 35 575	51.41	-78.45	6.6	78.73	0.4878	-0.0909	175.1	22 512	-1 512c		
13 470 35 576	52.07	-78.52	6.83	78.82	0.4949	-0.0897	175.0	22 513	-1 513c	Gm	
14 475 35 577	52.94	-78.89	9.19	79.42	0.5021	-0.0727	173.3	23 519	-1 519c		
16 480 35 579	54.11	-78.52	12.76	79.55	0.5178	-0.0479	170.7	26 533	-1 533c		
17 485 36 582	55.92	-77.21	14.53	78.56	0.5459	-0.0383	169.3	28 540	-1 540c		
18 490 37 588	59.84	-73.81	16.82	75.7	0.6048	-0.0298	167.1	29 548	-1 548c		
19 495 40 601	67.85	-61.36	20.38	64.65	0.7364	-0.022	161.6	31 559	-1 559c		
20 500 -1 500c	86.26	-1.35	27.52	27.55	1.0919	-0.0146	92.8	35 576	13 469	max	
21 510 -1 509c	85.08	1.83	27.58	27.64	1.1068	-0.0126	86.1	35 576	14 472		
24 520 -1 520c	79.47	16.14	26.41	30.96	1.1795	-0.0093	58.5	35 579	16 480	Ym	
26 530 -1 530c	74.02	28.44	24.74	37.7	1.2519	-0.0085	41.0	36 582	16 484		
28 540 -1 540c	67.47	41.38	22.56	47.13	1.3435	-0.0085	28.6	37 585	17 487		
28 545 -1 544c	67.47	41.38	22.56	47.13	1.3435	-0.0085	28.6	37 585	17 487		
29 550 -1 549c	63.86	47.65	21.32	52.2	1.3966	-0.0087	24.1	37 586	17 489		
31 555 -1 555c	56.16	58.87	18.62	61.74	1.5174	-0.0096	17.5	38 590	18 491		
32 560 -1 560c	52.14	63.42	17.2	65.71	1.5847	-0.0102	15.1	38 593	18 492		
34 574 1 405	48.96	70.17	13.6	71.47	1.6714	-0.0311	10.9	39 599	18 494	Rm	
34 574 6 435	48.77	72.27	9.45	72.89	1.6909	-0.0647	7.4	42 612	19 496		
34 574 9 450	48.49	75.24	3.1	75.3	1.7188	-0.1166	2.3	-1 501c	20 501		
35 575 12 460	48.88	77.84	-4.16	77.95	1.7352	-0.1763	356.9	-1 508c	21 508		
35 575 13 465	48.58	78.44	-6.6	78.71	1.7439	-0.1966	355.1	-1 512c	22 512		
35 576 13 470	47.92	78.51	-6.83	78.81	1.7535	-0.1993	355.0	-1 513c	22 513	Mm	
35 577 14 475	47.05	78.88	-9.19	79.41	1.7687	-0.2204	353.3	-1 519c	23 519		
35 579 16 480	45.88	78.51	-12.76	79.54	1.7827	-0.2535	350.7	-1 533c	26 533		
36 582 17 485	44.07	77.19	-14.52	78.55	1.7988	-0.2741	349.3	-1 540c	28 540		
37 588 18 490	40.15	73.8	-16.81	75.69	1.8333	-0.3098	347.1	-1 548c	29 548		
40 601 19 495	32.14	61.34	-20.38	64.64	1.8615	-0.3959	341.6	-1 559c	31 559		
-1 500c	20 500	13.73	1.35	-27.51	27.55	1.1377	-0.9436	272.8	13 469	35 576	min
-1 509c	21 510	14.91	-1.83	-27.57	27.63	1.0489	-0.8819	266.1	14 472	35 576	
-1 520c	24 520	20.52	-16.14	-26.41	30.95	0.7836	-0.6569	238.5	16 480	35 579	Bm
-1 530c	26 530	25.97	-28.43	-24.74	37.69	0.6602	-0.5233	221.0	16 484	36 582	
-1 540c	28 540	32.52	-41.38	-22.56	47.13	0.5893	-0.4197	208.6	17 487	37 585	
-1 544c	28 545	32.52	-41.38	-22.56	47.13	0.5893	-0.4197	208.6	17 487	37 585	
-1 549c	29 550	36.13	-47.65	-21.32	52.2	0.5706	-0.3783	204.1	17 489	37 586	
-1 555c	31 555	43.83	-58.87	-18.62	61.74	0.5609	-0.3122	197.5	18 491	38 590	
-1 560c	32 560	47.85	-63.42	-17.2	65.71	0.5681	-0.2861	195.1	18 492	38 593	
W0	380	770	99.99	0.0	0.0	0.0	1.0982	-0.1422	0.0	B _c =1,000	
N0	380	770	3.99	0.0	0.0	0.0	1.0982	-0.1422	0.0	x _c =0,000	

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/CGX1/CGX1L0NP.PDF> / .PS
 Technische Information: <http://farbe.li.tu-berlin.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20201101-CGX1/CGX1L0NP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für E00, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405 32 564	31.84	53.49	88.52	0.1831	0.3077	0.5091	189.6	16 484	38 592	Cm
6	435 33 565	28.26	53.39	70.9	0.1852	0.3499	0.4647	173.5	17 488	45 625	
10	450 33 566	23.66	54.0	42.66	0.1966	0.4487	0.3545	139.7	19 498	-1 498c	
12	460 33 568	22.46	54.91	29.3	0.2105	0.5147	0.2747	124.0	21 507	-1 507c	
13	465 33 569	22.55	55.83	23.62	0.2211	0.5473	0.2315	117.6	22 514	-1 514c	
14	470 34 571	23.04	56.68	18.91	0.2335	0.5746	0.1917	112.4	24 522	-1 522c	Gm
14	475 35 575	25.29	59.12	18.91	0.2447	0.5721	0.183	110.3	25 525	-1 525c	
16	480 36 581	29.33	62.44	12.28	0.2818	0.6	0.118	100.8	27 538	-1 538c	
17	485 39 595	40.01	69.67	10.11	0.334	0.5815	0.0844	89.8	29 549	-1 549c	
18	490 -1 490c	75.61	85.28	8.47	0.4464	0.5035	0.05	56.3	33 568	11 459	max
19	495 -1 495c	75.57	84.1	7.2	0.4528	0.5039	0.0431	54.9	33 568	12 461	
19	500 -1 499c	75.57	84.1	7.2	0.4528	0.5039	0.0431	54.9	33 568	12 461	
22	510 -1 510c	75.45	78.54	4.93	0.4747	0.4942	0.031	48.6	34 571	13 469	
24	520 -1 520c	74.91	72.84	4.27	0.4927	0.4791	0.0281	42.4	34 574	14 473	Ym
26	530 -1 530c	73.57	65.9	3.92	0.513	0.4595	0.0273	35.0	35 577	15 477	
28	540 -1 540c	71.21	58.21	3.75	0.5346	0.437	0.0282	27.2	36 581	15 479	
29	545 -1 545c	69.61	54.22	3.71	0.5457	0.4251	0.0291	23.3	36 583	16 480	
29	550 -1 549c	69.61	54.22	3.71	0.5457	0.4251	0.0291	23.3	36 583	16 480	
30	555 -1 554c	67.7	50.19	3.68	0.5568	0.4128	0.0303	19.5	37 585	16 482	
32	560 -1 560c	62.89	42.16	3.65	0.5785	0.3879	0.0335	12.5	38 590	16 483	
32	564 1 405	68.15	46.5	11.48	0.5403	0.3686	0.091	9.6	38 592	16 484	Rm
33	565 6 435	71.73	46.6	29.09	0.4865	0.316	0.1973	353.5	45 625	17 488	
33	566 10 450	76.33	45.99	57.33	0.4248	0.2559	0.3191	319.8	-1 498c	19 498	
33	568 12 460	77.54	45.08	70.69	0.4011	0.2332	0.3656	304.1	-1 507c	21 507	
33	569 13 465	77.44	44.16	76.38	0.3911	0.223	0.3857	297.7	-1 514c	22 514	
34	571 14 470	76.96	43.31	81.08	0.3821	0.2151	0.4026	292.4	-1 522c	24 522	Mm
35	575 14 475	74.7	40.87	81.08	0.3798	0.2078	0.4122	290.3	-1 525c	25 525	
36	581 16 480	70.66	37.55	87.71	0.3606	0.1916	0.4476	280.9	-1 538c	27 538	
39	595 17 485	59.98	30.32	89.88	0.3328	0.1683	0.4988	269.8	-1 549c	29 549	
-1 490c	18 490	24.39	14.71	91.53	0.1867	0.1126	0.7006	236.4	11 459	33 568	min
-1 495c	19 495	24.42	15.89	92.79	0.1835	0.1193	0.697	235.0	12 461	33 568	
-1 499c	19 500	24.42	15.89	92.79	0.1835	0.1193	0.697	235.0	12 461	33 568	
-1 510c	22 510	24.54	21.45	95.06	0.1739	0.152	0.6739	228.6	13 469	34 571	
-1 520c	24 520	25.08	27.15	95.72	0.1695	0.1835	0.6469	222.4	14 473	34 574	Bm
-1 530c	26 530	26.42	34.09	96.07	0.1687	0.2177	0.6135	215.1	15 477	35 577	
-1 540c	28 540	28.78	41.78	96.24	0.1725	0.2504	0.5769	207.2	15 479	36 581	
-1 545c	29 545	30.38	45.77	96.28	0.1762	0.2654	0.5583	203.3	16 480	36 583	
-1 549c	29 550	30.38	45.77	96.28	0.1762	0.2654	0.5583	203.3	16 480	36 583	
-1 554c	30 555	32.3	49.8	96.31	0.181	0.2791	0.5398	199.5	16 482	37 585	
-1 560c	32 560	37.11	57.83	96.34	0.194	0.3023	0.5036	192.5	16 483	38 590	
W0	380 770	100.0	100.0	100.0	0.3333	0.3333	0.3333	0.0			
N0	380 770	4.0	4.0	4.0	0.3333	0.3333	0.3333	0.0			

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für E00, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405 32 564	53.49	-54.11	-35.0	64.45	0.5951	-0.6616	212.8	16 484	38 592	Cm
6	435 33 565	53.39	-62.81	-17.5	65.21	0.5291	-0.531	195.5	17 488	45 625	
10	450 33 566	54.0	-75.82	11.33	76.66	0.4381	-0.3159	171.4	19 498	-1 498c	
12	460 33 568	54.91	-81.11	25.6	85.06	0.4088	-0.2134	162.4	21 507	-1 507c	
13	465 33 569	55.83	-83.15	32.19	89.17	0.4039	-0.1691	158.8	22 514	-1 514c	
14	470 34 571	56.68	-84.07	37.75	92.16	0.4064	-0.1334	155.8	24 522	-1 522c	Gm
14	475 35 575	59.12	-84.54	40.19	93.61	0.4277	-0.1279	154.5	25 525	-1 525c	
16	480 36 581	62.44	-82.74	50.14	96.75	0.4697	-0.0786	148.7	27 538	-1 538c	
17	485 39 595	69.67	-74.1	59.54	95.05	0.5742	-0.058	141.2	29 549	-1 549c	
18	490 -1 490c	85.28	-24.15	76.79	80.5	0.8863	-0.0397	107.4	33 568	11 459	max
19	495 -1 495c	84.1	-21.31	76.87	79.78	0.8983	-0.0342	105.4	33 568	12 461	
19	500 -1 499c	84.1	-21.31	76.87	79.78	0.8983	-0.0342	105.4	33 568	12 461	
22	510 -1 510c	78.54	-7.7	73.59	73.99	0.9604	-0.0251	95.9	34 571	13 469	
24	520 -1 520c	72.84	5.2	68.54	68.74	1.0282	-0.0234	85.6	34 574	14 473	Ym
26	530 -1 530c	65.9	19.17	61.95	64.85	1.116	-0.0238	72.8	35 577	15 477	
28	540 -1 540c	58.21	32.49	54.44	63.4	1.2229	-0.0258	59.1	36 581	15 479	
29	545 -1 545c	54.22	38.46	50.49	63.47	1.2834	-0.0273	52.7	36 583	16 480	
29	550 -1 549c	54.22	38.46	50.49	63.47	1.2834	-0.0273	52.7	36 583	16 480	
30	555 -1 554c	50.19	43.76	46.49	63.85	1.3485	-0.0293	46.7	37 585	16 482	
32	560 -1 560c	42.16	51.79	38.5	64.53	1.4909	-0.0346	36.6	38 590	16 483	
32	564 1 405	46.5	54.11	35.0	64.45	1.4652	-0.0987	32.8	38 592	16 484	Rm
33	565 6 435	46.6	62.81	17.5	65.2	1.5388	-0.2496	15.5	45 625	17 488	
33	566 10 450	45.99	75.81	-11.33	76.65	1.659	-0.4984	351.4	-1 498c	19 498	
33	568 12 460	45.08	81.09	-25.59	85.04	1.7192	-0.6269	342.4	-1 507c	21 507	
33	569 13 465	44.16	83.13	-32.18	89.15	1.7525	-0.6913	338.8	-1 514c	22 514	
34	571 14 470	43.31	84.05	-37.74	92.13	1.7758	-0.7484	335.8	-1 522c	24 522	Mm
35	575 14 475	40.87	84.52	-40.17	93.58	1.8267	-0.793	334.5	-1 525c	25 525	
36	581 16 480	37.55	82.71	-50.12	96.71	1.8807	-0.9338	328.7	-1 538c	27 538	
39	595 17 485	30.32	74.06	-59.51	95.01	1.9766	-1.1848	321.2	-1 549c	29 549	
-1 490c	18 490	14.71	24.14	-76.73	80.44	1.6559	-2.4857	287.4	11 459	33 568	min
-1 495c	19 495	15.89	21.3	-76.83	79.73	1.5359	-2.3337	285.4	12 461	33 568	
-1 499c	19 500	15.89	21.3	-76.83	79.73	1.5359	-2.3337	285.4	12 461	33 568	
-1 510c	22 510	21.45	7.7	-73.55	73.96	1.1433	-1.7713	275.9	13 469	34 571	
-1 520c	24 520	27.15	-5.2	-68.52	68.72	0.923	-1.4091	265.6	14 473	34 574	Bm
-1 530c	26 530	34.09	-19.17	-61.94	64.84	0.7748	-1.1266	252.8	15 477	35 577	
-1 540c	28 540	41.78	-32.48	-54.43	63.39	0.6886	-0.9209	239.1	15 479	36 581	
-1 545c	29 545	45.77	-38.46	-50.48	63.46	0.6636	-0.841	232.7	16 480	36 583	
-1 549c	29 550	45.77	-38.46	-50.48	63.46	0.6636	-0.841	232.7	16 480	36 583	
-1 554c	30 555	49.8	-43.76	-46.48	63.84	0.6482	-0.7732	226.7	16 482	37 585	
-1 560c	32 560	57.83	-51.78	-38.5	64.53	0.6415	-0.6662	216.6	16 483	38 590	
W0	380 770	100.0	0.0	0.0	0.0	0.9997	-0.3998	0.0	B _c =1,000		
N0	380 770	4.0	0.0	0.0	0.0	0.9997	-0.3998	0.0	x _c =0,000		

Siehe ähnliche Dateien: http://farbe.li.tu-berlin.de/CGX1/CGX1L0NP.PDF /.PS
 Technische Information: http://farbe.li.tu-berlin.de oder http://130.149.60.45/~farbmetrik

TUB-Registrierung: 20201101-CGX1/CGX1L0NP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für C00, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405	32	562	33.31	53.39	105.37	0.1734	0.2779	0.5485	195.6	16 482 37 589 Cm
6	435	32	563	30.01	54.08	86.45	0.1759	0.3171	0.5069	179.5	17 486 42 612
10	450	32	564	24.28	54.92	51.75	0.1854	0.4194	0.3951	140.3	19 496 -1 496c
11	460	33	566	23.64	55.77	43.21	0.1927	0.4548	0.3523	130.1	20 501 -1 501c
13	465	33	568	22.4	56.56	28.17	0.2091	0.5279	0.2629	115.4	22 513 -1 513c
14	470	34	570	22.98	57.79	22.31	0.2229	0.5605	0.2164	109.5	24 522 -1 522c Gm
15	475	35	575	25.24	60.29	17.65	0.2446	0.5842	0.171	103.6	26 530 -1 530c
16	480	36	582	30.95	65.05	14.08	0.2811	0.5908	0.1279	95.9	28 540 -1 540c
16	485	40	602	45.67	74.9	14.1	0.3391	0.5561	0.1047	83.0	30 551 -1 551c
18	490	-1	490c	71.26	84.24	9.45	0.432	0.5106	0.0573	57.8	33 566 11 459 max
19	495	-1	495c	71.22	82.89	7.99	0.4393	0.5113	0.0493	56.4	33 567 12 462
19	500	-1	499c	71.22	82.89	7.99	0.4393	0.5113	0.0493	56.4	33 567 12 462
21	510	-1	509c	71.17	79.34	6.12	0.4543	0.5065	0.0391	52.8	33 568 13 466
24	520	-1	520c	70.57	71.51	4.93	0.48	0.4864	0.0335	45.0	34 572 14 472 Ym
26	530	-1	530c	69.24	64.67	4.59	0.4999	0.4669	0.0331	38.4	35 575 15 475
28	540	-1	540c	66.82	56.8	4.41	0.5219	0.4435	0.0345	31.0	35 579 15 478
28	545	-1	544c	66.82	56.8	4.41	0.5219	0.4435	0.0345	31.0	35 579 15 478
29	550	-1	549c	65.14	52.6	4.37	0.5334	0.4307	0.0358	27.1	36 581 15 479
31	555	-1	555c	60.75	44.07	4.32	0.5566	0.4037	0.0395	19.5	37 586 16 481
31	560	-1	559c	60.75	44.07	4.32	0.5566	0.4037	0.0395	19.5	37 586 16 481
32	562	1	405	64.75	46.6	12.85	0.5213	0.3752	0.1034	15.6	37 589 16 482 Rm
32	563	6	435	68.06	45.91	31.76	0.467	0.315	0.2179	359.5	42 612 17 486
32	564	10	450	73.78	45.07	66.47	0.3981	0.2431	0.3586	320.3	-1 496c 19 496
33	566	11	460	74.42	44.22	75.0	0.3843	0.2283	0.3873	310.2	-1 501c 20 501
33	568	13	465	75.66	43.43	90.05	0.3617	0.2076	0.4305	295.5	-1 513c 22 513
34	570	14	470	75.08	42.2	95.9	0.3521	0.1979	0.4498	289.6	-1 522c 24 522 Mm
35	575	15	475	72.82	39.7	100.56	0.3417	0.1863	0.4719	283.7	-1 530c 26 530
36	582	16	480	67.12	34.94	104.13	0.3255	0.1694	0.505	276.0	-1 540c 28 540
40	602	16	485	52.39	25.09	104.12	0.2885	0.1381	0.5733	263.1	-1 551c 30 551
-1	490c	18	490	26.8	15.75	108.77	0.1771	0.1041	0.7187	237.9	11 459 33 566 min
-1	495c	19	495	26.85	17.1	110.22	0.1741	0.1109	0.7148	236.5	12 462 33 567
-1	499c	19	500	26.85	17.1	110.22	0.1741	0.1109	0.7148	236.5	12 462 33 567
-1	509c	21	510	26.89	20.65	112.09	0.1684	0.1293	0.7021	232.8	13 466 33 568
-1	520c	24	520	27.49	28.48	113.29	0.1624	0.1682	0.6693	225.0	14 472 34 572 Bm
-1	530c	26	530	28.82	35.32	113.63	0.1621	0.1986	0.6391	218.4	15 475 35 575
-1	540c	28	540	31.24	43.19	113.8	0.1659	0.2294	0.6045	211.0	15 478 35 579
-1	544c	28	545	31.24	43.19	113.8	0.1659	0.2294	0.6045	211.0	15 478 35 579
-1	549c	29	550	32.92	47.39	113.85	0.1695	0.244	0.5863	207.1	15 479 36 581
-1	555c	31	555	37.31	55.92	113.9	0.1801	0.2699	0.5498	199.5	16 481 37 586
-1	559c	31	560	37.31	55.92	113.9	0.1801	0.2699	0.5498	199.5	16 481 37 586
W0	380	770	98.07	100.0	118.22	0.31	0.3161	0.3737	0.0		
N0	380	770	3.92	4.0	4.72	0.31	0.3161	0.3737	0.0		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für C00, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405	32	562	53.39	-47.61	-42.22	63.64	0.6237	-0.7891	221.5	16 482 37 589 Cm
6	435	32	563	54.08	-57.56	-22.5	61.81	0.5546	-0.6391	201.3	17 486 42 612
10	450	32	564	54.92	-73.93	13.17	75.1	0.4419	-0.3768	169.8	19 496 -1 496c
11	460	33	566	55.77	-77.61	22.71	80.86	0.4238	-0.3098	163.6	20 501 -1 501c
13	465	33	568	56.56	-82.65	38.69	91.26	0.3959	-0.1991	154.9	22 513 -1 513c
14	470	34	570	57.79	-84.19	45.99	95.93	0.3976	-0.1544	151.3	24 522 -1 522c Gm
15	475	35	575	60.29	-84.68	53.6	100.22	0.4186	-0.1171	147.6	26 530 -1 530c
16	480	36	582	65.05	-82.08	62.79	103.34	0.4756	-0.0866	142.5	28 540 -1 540c
16	485	40	602	74.9	-69.42	74.42	101.78	0.6096	-0.0752	133.0	30 551 -1 551c
18	490	-1	490c	84.24	-28.34	90.11	94.46	0.8458	-0.0448	107.4	33 566 11 459 max
19	495	-1	495c	82.89	-25.15	89.97	93.42	0.859	-0.0385	105.6	33 567 12 462
19	500	-1	499c	82.89	-25.15	89.97	93.42	0.859	-0.0385	105.6	33 567 12 462
21	510	-1	509c	79.34	-16.56	87.65	89.2	0.8968	-0.0308	100.7	33 568 13 466
24	520	-1	520c	71.51	1.12	79.59	79.59	0.9867	-0.0275	89.1	34 572 14 472 Ym
26	530	-1	530c	64.67	14.56	71.84	73.3	1.0704	-0.0283	78.5	35 575 15 475
28	540	-1	540c	56.8	27.81	62.71	68.6	1.1762	-0.0311	66.0	35 579 15 478
28	545	-1	544c	56.8	27.81	62.71	68.6	1.1762	-0.0311	66.0	35 579 15 478
29	550	-1	549c	52.6	33.87	57.8	67.0	1.2379	-0.0332	59.6	36 581 15 479
31	555	-1	555c	44.07	43.82	47.76	64.82	1.3781	-0.0392	47.4	37 586 16 481
31	560	-1	559c	44.07	43.82	47.76	64.82	1.3781	-0.0392	47.4	37 586 16 481
32	562	1	405	46.6	47.61	42.23	63.64	1.389	-0.1102	41.5	37 589 16 482 Rm
32	563	6	435	45.91	57.56	22.5	61.81	1.4819	-0.2766	21.3	42 612 17 486
32	564	10	450	45.07	73.92	-13.17	75.08	1.6364	-0.5896	349.8	-1 496c 19 496
33	566	11	460	44.22	77.59	-22.71	80.85	1.6822	-0.6781	343.6	-1 501c 20 501
33	568	13	465	43.43	82.63	-38.68	91.23	1.7414	-0.829	334.9	-1 513c 22 513
34	570	14	470	42.2	84.16	-45.97	95.9	1.778	-0.9084	331.3	-1 522c 24 522 Mm
35	575	15	475	39.7	84.65	-53.59	100.19	1.8332	-1.0126	327.6	-1 530c 26 530
36	582	16	480	34.94	82.04	-62.77	103.3	1.9194	-1.1912	322.5	-1 540c 28 540
40	602	16	485	25.09	69.39	-74.38	101.72	2.0864	-1.6584	313.0	-1 551c 30 551
-1	490c	18	490	15.75	28.32	-90.04	94.39	1.6993	-2.7581	287.4	11 459 33 566 min
-1	495c	19	495	17.1	25.13	-89.91	93.35	1.5681	-2.575	285.6	12 462 33 567
-1	499c	19	500	17.1	25.13	-89.91	93.35	1.5681	-2.575	285.6	12 462 33 567
-1	509c	21	510	20.65	16.55	-87.59	89.15	1.301	-2.1692	280.7	13 466 33 568
-1	520c	24	520	28.48	-1.12	-79.55	79.56	0.9645	-1.5899	269.1	14 472 34 572 Bm
-1	530c	26	530	35.32	-14.56	-71.82	73.28	0.8155	-1.286	258.5	15 475 35 575
-1	540c	28	540	43.19	-27.81	-62.7	68.59	0.7229	-1.0533	246.0	15 478 35 579
-1	544c	28	545	43.19	-27.81	-62.7	68.59	0.7229	-1.0533	246.0	15 478 35 579
-1	549c	29	550	47.39	-33.87	-57.79	66.99	0.6945	-0.9605	239.6	15 479 36 581
-1	555c	31	555	55.92	-43.82	-47.76	64.82	0.6669	-0.8143	227.4	16 481 37 586
-1	559c	31	560	55.92	-43.82	-47.76	64.82	0.6669	-0.8143	227.4	16 481 37 586
W0	380	770	100.0	0.0	0.0	0.0	0.9804	-0.4727	0.0	B _c =1,000	
N0	380	770	4.0	0.0	0.0	0.0	0.9804	-0.4727	0.0	x _c =0,000	

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/CGX1/CGX1L0NP.PDF> / .PS
 Technische Information: <http://farbe.li.tu-berlin.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20201101-CGX1/CGX1L0NP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P00, Y_N=0, Y_W=100, Y_m=520 770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405 33 567	30.23	52.67	71.87	0.1953	0.3402	0.4643	184.4	17 486	38 594	Cm
7	435 33 567	26.81	53.01	53.14	0.2016	0.3986	0.3996	164.0	18 491	-1 491c	
10	450 33 568	24.24	53.57	36.03	0.2129	0.4705	0.3164	141.4	19 499	-1 499c	
12	460 34 570	22.73	53.69	25.06	0.2239	0.529	0.2469	127.8	21 507	-1 507c	
13	465 34 571	22.87	54.38	20.32	0.2344	0.5573	0.2082	121.6	22 513	-1 513c	
13	470 34 572	24.26	55.89	20.32	0.2414	0.5562	0.2022	120.3	23 515	-1 515c	Gm
15	475 35 575	25.01	56.94	13.16	0.2629	0.5986	0.1383	111.6	25 529	-1 529c	
16	480 36 580	28.39	59.85	10.68	0.2869	0.605	0.1079	106.2	27 537	-1 537c	
17	485 37 589	36.65	65.78	8.79	0.3295	0.5914	0.079	97.3	29 547	-1 547c	
18	490 45 625	65.84	80.35	7.35	0.4288	0.5232	0.0478	68.0	32 564	-1 564c	
18	495 -1 494c	80.37	85.99	7.35	0.4626	0.495	0.0423	54.2	34 570	12 460	max
20	500 -1 500c	80.32	83.62	5.35	0.4744	0.4939	0.0316	50.9	34 571	13 465	
22	510 -1 510c	80.23	79.9	4.17	0.4882	0.4862	0.0254	46.1	34 573	14 470	
24	520 -1 520c	79.73	74.6	3.56	0.5049	0.4724	0.0225	39.5	35 575	14 474	Ym
25	530 -1 529c	79.2	71.45	3.37	0.5141	0.4638	0.0219	35.7	35 577	15 476	
28	540 -1 540c	76.18	60.63	3.07	0.5445	0.4334	0.022	23.5	36 582	16 481	
28	545 -1 544c	76.18	60.63	3.07	0.5445	0.4334	0.022	23.5	36 582	16 481	
30	550 -1 550c	72.72	52.75	3.0	0.566	0.4105	0.0233	15.5	37 586	16 483	
30	555 -1 554c	72.72	52.75	3.0	0.566	0.4105	0.0233	15.5	37 586	16 483	
32	560 -1 560c	67.91	44.73	2.97	0.5874	0.3868	0.0257	8.4	38 591	17 485	
33	567 1 405	71.83	47.32	9.18	0.5596	0.3687	0.0715	4.4	38 594	17 486	Rm
33	567 7 435	75.24	46.98	27.91	0.5011	0.3129	0.1859	344.0	-1 491c	18 491	
33	568 10 450	77.81	46.42	45.02	0.4597	0.2742	0.266	321.5	-1 499c	19 499	
34	570 12 460	79.33	46.3	55.99	0.4367	0.2549	0.3082	307.8	-1 507c	21 507	
34	571 13 465	79.19	45.61	60.74	0.4268	0.2458	0.3273	301.7	-1 513c	22 513	
34	572 13 470	77.8	44.1	60.73	0.4259	0.2414	0.3325	300.4	-1 515c	23 515	Mm
35	575 15 475	77.05	43.05	67.89	0.4098	0.2289	0.3611	291.7	-1 529c	25 529	
36	580 16 480	73.67	40.14	70.37	0.3999	0.2179	0.382	286.3	-1 537c	27 537	
37	589 17 485	65.4	34.21	72.26	0.3805	0.199	0.4204	277.4	-1 547c	29 547	
45	625 18 490	36.21	19.64	73.7	0.2795	0.1516	0.5688	248.1	-1 564c	32 564	
-1 494c	18 495	21.69	14.0	73.7	0.1982	0.1279	0.6737	234.2	12 460	34 570	min
-1 500c	20 500	21.74	16.37	75.7	0.191	0.1438	0.6651	231.0	13 465	34 571	
-1 510c	22 510	21.83	20.09	76.88	0.1837	0.1691	0.6471	226.1	14 470	34 573	
-1 520c	24 520	22.33	25.39	77.49	0.1783	0.2027	0.6188	219.5	14 474	35 575	Bm
-1 529c	25 530	22.85	28.54	77.68	0.177	0.2211	0.6018	215.7	15 476	35 577	
-1 540c	28 540	25.88	39.36	77.98	0.1807	0.2748	0.5444	203.5	16 481	36 582	
-1 544c	28 545	25.88	39.36	77.98	0.1807	0.2748	0.5444	203.5	16 481	36 582	
-1 550c	30 550	29.33	47.24	78.05	0.1897	0.3055	0.5047	195.6	16 483	37 586	
-1 554c	30 555	29.33	47.24	78.05	0.1897	0.3055	0.5047	195.6	16 483	37 586	
-1 560c	32 560	34.14	55.26	78.08	0.2038	0.3299	0.4661	188.4	17 485	38 591	
W0	380 770	102.06	100.0	81.06	0.3604	0.3531	0.2863	0.0			
N0	380 770	4.08	4.0	3.24	0.3604	0.3531	0.2863	0.0			

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P00, Y_N=0, Y_W=100, Y_m=520 770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405 33 567	52.67	-58.79	-29.17	65.63	0.5738	-0.5457	206.3	17 486	38 594	Cm
7	435 33 567	53.01	-68.21	-10.17	68.97	0.5057	-0.4008	188.4	18 491	-1 491c	
10	450 33 568	53.57	-76.06	7.39	76.42	0.4524	-0.2689	174.4	19 499	-1 499c	
12	460 34 570	53.69	-80.15	18.44	82.24	0.4232	-0.1867	167.0	21 507	-1 507c	
13	465 34 571	54.38	-81.56	23.75	84.95	0.4205	-0.1494	163.7	22 513	-1 513c	
13	470 34 572	55.89	-81.94	24.97	85.66	0.4339	-0.1454	163.0	23 515	-1 515c	Gm
15	475 35 575	56.94	-82.75	32.98	89.08	0.4391	-0.0924	158.2	25 529	-1 529c	
16	480 36 580	59.85	-81.71	37.82	90.04	0.4742	-0.0713	155.1	27 537	-1 537c	
17	485 37 589	65.78	-76.19	44.52	88.24	0.5571	-0.0534	149.7	29 547	-1 547c	
18	490 45 625	80.35	-40.38	57.76	70.48	0.8193	-0.0365	124.9	32 564	-1 564c	
18	495 -1 494c	85.99	-18.48	62.33	65.02	0.9343	-0.0341	106.5	34 570	12 460	max
20	500 -1 500c	83.62	-12.56	62.41	63.66	0.9602	-0.0256	101.3	34 571	13 465	
22	510 -1 510c	79.9	-3.29	60.57	60.66	1.0038	-0.0209	93.1	34 573	14 470	
24	520 -1 520c	74.6	8.96	56.89	57.59	1.0684	-0.0191	81.0	35 575	14 474	Ym
25	530 -1 529c	71.45	15.69	54.52	56.74	1.1082	-0.0189	73.9	35 577	15 476	
28	540 -1 540c	60.63	35.74	46.05	58.3	1.2562	-0.0202	52.1	36 582	16 481	
28	545 -1 544c	60.63	35.74	46.05	58.3	1.2562	-0.0202	52.1	36 582	16 481	
30	550 -1 550c	52.75	47.21	39.74	61.71	1.3783	-0.0227	40.0	37 586	16 483	
30	555 -1 554c	52.75	47.21	39.74	61.71	1.3783	-0.0227	40.0	37 586	16 483	
32	560 -1 560c	44.73	55.64	33.27	64.83	1.5179	-0.0265	30.8	38 591	17 485	
33	567 1 405	47.32	58.79	29.17	65.63	1.5173	-0.0775	26.3	38 594	17 486	Rm
33	567 7 435	46.98	68.21	10.17	68.96	1.6011	-0.2375	8.4	-1 491c	18 491	
33	568 10 450	46.42	76.05	-7.39	76.41	1.6756	-0.3878	354.4	-1 499c	19 499	
34	570 12 460	46.3	80.13	-18.44	82.22	1.7125	-0.4834	347.0	-1 507c	21 507	
34	571 13 465	45.61	81.54	-23.75	84.93	1.7355	-0.5324	343.7	-1 513c	22 513	
34	572 13 470	44.1	81.92	-24.97	85.64	1.7633	-0.5506	343.0	-1 515c	23 515	Mm
35	575 15 475	43.05	82.73	-32.98	89.06	1.789	-0.6305	338.2	-1 529c	25 529	
36	580 16 480	40.14	81.69	-37.81	90.02	1.8344	-0.7009	335.1	-1 537c	27 537	
37	589 17 485	34.21	76.16	-44.5	88.21	1.9108	-0.8445	329.7	-1 547c	29 547	
45	625 18 490	19.64	40.36	-57.73	70.44	1.8422	-1.4996	304.9	-1 564c	32 564	
-1 494c	18 495	14.0	18.47	-62.3	64.98	1.5482	-2.1041	286.5	12 460	34 570	min
-1 500c	20 500	16.37	12.55	-62.38	63.63	1.3271	-1.8485	281.3	13 465	34 571	
-1 510c	22 510	20.09	3.29	-60.55	60.64	1.0859	-1.5295	273.1	14 470	34 573	
-1 520c	24 520	25.39	-8.96	-56.87	57.58	0.8791	-1.2201	261.0	14 474	35 575	Bm
-1 529c	25 530	28.54	-15.69	-54.51	56.73	0.8004	-1.0881	253.9	15 476	35 577	
-1 540c	28 540	39.36	-35.74	-46.05	58.29	0.6572	-0.792	232.1	16 481	36 582	
-1 544c	28 545	39.36	-35.74	-46.05	58.29	0.6572	-0.792	232.1	16 481	36 582	
-1 550c	30 550	47.24	-47.21	-39.74	61.7	0.6207	-0.6605	220.0	16 483	37 586	
-1 554c	30 555	47.24	-47.21	-39.74	61.7	0.6207	-0.6605	220.0	16 483	37 586	
-1 560c	32 560	55.26	-55.63	-33.27	64.83	0.6176	-0.5649	210.8	17 485	38 591	
W0	380 770	100.0	0.0	0.0	0.0	1.0203	-0.3241	0.0	B _c =1,000		
N0	380 770	4.0	0.0	0.0	0.0	1.0203	-0.3241	0.0	x _c =0,000		

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/CGX1/CGX1L0NP.PDF> / .PS
 Technische Information: <http://farbe.li.tu-berlin.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20201101-CGX1/CGX1L0NP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für Q00, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405	32	562	33.12	53.55	105.16	0.1726	0.2791	0.5481	194.9	16 482 38 590 Cm
7	435	32	562	27.52	54.09	75.04	0.1756	0.3452	0.479	167.4	17 488 -1 488c
10	450	32	564	23.54	54.98	49.3	0.1841	0.4301	0.3857	137.4	19 497 -1 497c
11	460	33	566	22.93	55.81	41.14	0.1912	0.4655	0.3431	128.1	20 502 -1 502c
12	465	33	568	22.83	56.97	33.55	0.2014	0.5025	0.2959	119.8	21 508 -1 508c
14	470	34	570	22.37	57.8	21.47	0.2201	0.5686	0.2112	109.3	24 522 -1 522c Gm
15	475	35	575	24.6	60.27	17.17	0.2411	0.5906	0.1682	103.8	26 530 -1 530c
16	480	36	582	30.32	65.07	13.89	0.2774	0.5954	0.1271	96.4	27 539 -1 539c
17	485	40	602	45.41	74.39	11.43	0.346	0.5668	0.0871	81.6	30 552 -1 552c
17	490	-1	489c	70.95	85.62	11.44	0.4222	0.5096	0.0681	59.7	33 565 11 455 max
18	495	-1	494c	70.84	84.56	9.58	0.4293	0.5125	0.0581	58.5	33 565 11 458
20	500	-1	500c	70.78	81.63	7.1	0.4437	0.5117	0.0445	55.5	33 567 12 463
21	510	-1	509c	70.75	79.62	6.28	0.4516	0.5082	0.04	53.4	33 568 13 465
23	520	-1	519c	70.47	74.31	5.27	0.4696	0.4952	0.0351	48.1	34 571 14 470 Ym
26	530	-1	530c	68.68	63.76	4.61	0.501	0.4652	0.0336	37.9	35 576 15 475
27	540	-1	539c	67.59	59.83	4.51	0.5123	0.4534	0.0341	34.1	35 578 15 477
28	545	-1	544c	66.24	55.8	4.44	0.5237	0.4411	0.0351	30.3	36 580 15 478
29	550	-1	549c	64.6	51.71	4.39	0.5351	0.4284	0.0364	26.5	36 582 15 479
30	555	-1	554c	62.66	47.63	4.36	0.5465	0.4153	0.038	22.7	36 584 16 480
31	560	-1	559c	60.42	43.57	4.34	0.5576	0.4022	0.0401	19.2	37 587 16 481
32	562	1	405	64.8	46.44	13.78	0.5183	0.3714	0.1102	14.9	38 590 16 482 Rm
32	562	7	435	70.4	45.9	43.9	0.4394	0.2864	0.274	347.4	-1 488c 17 488
32	564	10	450	74.38	45.01	69.64	0.3934	0.2381	0.3683	317.5	-1 497c 19 497
33	566	11	460	74.99	44.18	77.8	0.3807	0.2243	0.3949	308.1	-1 502c 20 502
33	568	12	465	75.09	43.02	85.39	0.369	0.2113	0.4196	299.9	-1 508c 21 508
34	570	14	470	75.55	42.19	97.47	0.351	0.196	0.4528	289.4	-1 522c 24 522 Mm
35	575	15	475	73.32	39.72	101.77	0.3413	0.1849	0.4737	283.9	-1 530c 26 530
36	582	16	480	67.6	34.92	105.05	0.3256	0.1682	0.5061	276.4	-1 539c 27 539
40	602	17	485	52.51	25.6	107.51	0.2829	0.1379	0.5791	261.6	-1 552c 30 552
-1	489c	17	490	26.98	14.37	107.51	0.1812	0.0965	0.7221	239.7	11 455 33 565 min
-1	494c	18	495	27.08	15.43	109.36	0.1783	0.1015	0.72	238.6	11 458 33 565
-1	500c	20	500	27.14	18.36	111.85	0.1725	0.1167	0.7107	235.5	12 463 33 567
-1	509c	21	510	27.17	20.37	112.67	0.1696	0.1271	0.7032	233.5	13 465 33 568
-1	519c	23	520	27.45	25.68	113.68	0.1646	0.1539	0.6814	228.2	14 470 34 571 Bm
-1	530c	26	530	29.24	36.23	114.33	0.1626	0.2014	0.6358	217.9	15 475 35 576
-1	539c	27	540	30.33	40.16	114.44	0.164	0.2171	0.6188	214.1	15 477 35 578
-1	544c	28	545	31.68	44.19	114.51	0.1664	0.2321	0.6014	210.3	15 478 36 580
-1	549c	29	550	33.32	48.28	114.56	0.1698	0.2461	0.5839	206.5	15 479 36 582
-1	554c	30	555	35.26	52.36	114.58	0.1743	0.2589	0.5666	202.8	16 480 36 584
-1	559c	31	560	37.51	56.42	114.6	0.1798	0.2705	0.5495	199.2	16 481 37 587
W0	380	770	97.93	100.0	118.95	0.309	0.3155	0.3753	0.0		
N0	380	770	3.91	4.0	4.75	0.309	0.3155	0.3753	0.0		

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für Q00, Y_N=0, Y_W=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code
1	405	32	562	53.55	-48.3	-41.43	63.64	0.6182	-0.7851	220.6	16 482 38 590 Cm
7	435	32	562	54.09	-63.61	-10.69	64.5	0.5086	-0.5547	189.5	17 488 -1 488c
10	450	32	564	54.98	-75.73	16.08	77.42	0.428	-0.3586	168.0	19 497 -1 497c
11	460	33	566	55.81	-79.28	25.23	83.2	0.4108	-0.2948	162.3	20 502 -1 502c
12	465	33	568	56.97	-82.38	34.2	89.2	0.4006	-0.2355	157.4	21 508 -1 508c
14	470	34	570	57.8	-85.53	47.26	97.72	0.387	-0.1485	151.0	24 522 -1 522c Gm
15	475	35	575	60.27	-86.02	54.5	101.84	0.4081	-0.1139	147.6	26 530 -1 530c
16	480	36	582	65.07	-83.47	63.49	104.88	0.4659	-0.0853	142.7	27 539 -1 539c
17	485	40	602	74.39	-68.57	77.03	103.13	0.6103	-0.0614	131.6	30 552 -1 552c
17	490	-1	489c	85.62	-32.23	90.38	95.95	0.8284	-0.0534	109.6	33 565 11 455 max
18	495	-1	494c	84.56	-29.9	90.98	95.77	0.8375	-0.0453	108.1	33 565 11 458
20	500	-1	500c	81.63	-22.87	89.97	92.84	0.8669	-0.0347	104.2	33 567 12 463
21	510	-1	509c	79.62	-18.01	88.4	90.22	0.8885	-0.0315	101.5	33 568 13 465
23	520	-1	519c	74.31	-5.75	83.1	83.3	0.948	-0.0283	93.9	34 571 14 470 Ym
26	530	-1	530c	63.76	15.6	71.21	72.9	1.0768	-0.0289	77.6	35 576 15 475
27	540	-1	539c	59.83	22.5	66.64	70.34	1.1294	-0.0301	71.3	35 578 15 477
28	545	-1	544c	55.8	28.99	61.91	68.37	1.1868	-0.0318	64.9	36 580 15 478
29	550	-1	549c	51.71	34.88	57.1	66.92	1.2488	-0.0339	58.5	36 582 15 479
30	555	-1	554c	47.63	40.05	52.27	65.85	1.3153	-0.0366	52.5	36 584 16 480
31	560	-1	559c	43.57	44.35	47.47	64.97	1.3861	-0.0398	46.9	37 587 16 481
32	562	1	405	46.44	48.31	41.44	63.65	1.3951	-0.1187	40.6	38 590 16 482 Rm
32	562	7	435	45.9	63.61	10.69	64.5	1.5333	-0.3824	9.5	-1 488c 17 488
32	564	10	450	45.01	75.71	-16.08	77.4	1.6518	-0.6186	348.0	-1 497c 19 497
33	566	11	460	44.18	79.26	-25.22	83.18	1.6965	-0.704	342.3	-1 502c 20 502
33	568	12	465	43.02	82.36	-34.19	89.17	1.7447	-0.7936	337.4	-1 508c 21 508
34	570	14	470	42.19	85.5	-47.24	97.69	1.7895	-0.9235	331.0	-1 522c 24 522 Mm
35	575	15	475	39.72	85.99	-54.48	101.8	1.8449	-1.0243	327.6	-1 530c 26 530
36	582	16	480	34.92	83.44	-63.47	104.83	1.9347	-1.2026	322.7	-1 539c 27 539
40	602	17	485	25.6	68.53	-76.99	103.08	2.0499	-1.6786	311.6	-1 552c 30 552
-1	489c	17	490	14.37	32.2	-90.3	95.87	1.8751	-2.9886	289.6	11 455 33 565 min
-1	494c	18	495	15.43	29.88	-90.9	95.69	1.7537	-2.8321	288.1	11 458 33 565
-1	500c	20	500	18.36	22.86	-89.91	92.77	1.4769	-2.434	284.2	12 463 33 567
-1	509c	21	510	20.37	18.0	-88.35	90.16	1.3324	-2.2099	281.5	13 465 33 568
-1	519c	23	520	25.68	5.74	-83.06	83.26	1.0685	-1.7694	273.9	14 470 34 571 Bm
-1	530c	26	530	36.23	-15.59	-71.19	72.88	0.8068	-1.2616	257.6	15 475 35 576
-1	539c	27	540	40.16	-22.5	-66.62	70.32	0.7549	-1.1392	251.3	15 477 35 578
-1	544c	28	545	44.19	-28.98	-61.9	68.35	0.7166	-1.0359	244.9	15 478 36 580
-1	549c	29	550	48.28	-34.88	-57.09	66.91	0.69	-0.9487	238.5	15 479 36 582
-1	554c	30	555	52.36	-40.04	-52.27	65.84	0.6731	-0.8749	232.5	16 480 36 584
-1	559c	31	560	56.42	-44.34	-47.47	64.96	0.6646	-0.8122	226.9	16 481 37 587
W0	380	770	100.0	0.0	0.0	0.0	0.979	-0.4756	0.0	B _c =1,000	
N0	380	770	4.0	0.0	0.0	0.0	0.979	-0.4756	0.0	x _c =0,000	

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/CGX1/CGX1L0NP.PDF> / .PS
 Technische Information: <http://farbe.li.tu-berlin.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20201101-CGX1/CGX1L0NP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe