

Interpretation *rgb* \rightarrow *olv**- und CIELAB-Daten

sRGB-Display mit der Leuchtdichte-Reflexion $L_r=0\%$

Buntonkreis mit 6 Geräte-Bunttönen *OYLCVM*:

$h_{ab,a} = 40.0, 102.8, 136.0, 196.3, 306.2, 328.2$

Elementar-Bunttöne *RJGB*: $h_{ab,a} = 25.4, 92.3, 162.2, 271.7$

<i>Code</i>	L^*	a^*_a	b^*_a	C^*_{ab}	$h_{ab,a}$	<i>rgb</i> \rightarrow <i>olv*</i>
<i>m00o=M</i>	57.2	94.3	-58.4	110.9	328.2	1.00 0.00 1.00
<i>m12o</i>	55.6	90.3	-43.9	100.4	334.0	1.00 0.00 0.87
<i>m25o</i>	54.2	86.7	-28.6	91.3	341.6	1.00 0.00 0.75
<i>m37o</i>	53.0	83.6	-12.6	84.6	351.4	1.00 0.00 0.62
<i>m50o</i>	52.0	81.1	4.1	81.2	2.9	1.00 0.00 0.50
<i>m62o</i>	51.3	79.2	21.6	82.1	15.2	1.00 0.00 0.37
<i>m75o</i>	50.8	77.9	39.2	87.2	26.7	1.00 0.00 0.25
<i>m87o</i>	50.6	77.2	54.9	94.8	35.4	1.00 0.00 0.12

R