

Interpretation *rgb* \rightarrow *olv**- und CIELAB-Daten

sRGB-Display mit der Leuchtdichte-Reflexion $L_r=2,5\%$

Buntonkreis mit 6 Geräte-Bunttönen *OYLCVM*:

$h_{ab,a} = 34.8, 103.2, 136.9, 196.4, 304.3, 328.0$

Elementar-Bunttöne *RJGB*: $h_{ab,a} = 25.4, 92.3, 162.2, 271.7$

<i>Code</i>	L^*	a^*_a	b^*_a	C^*_{ab}	$h_{ab,a}$	<i>rgb</i> \rightarrow <i>olv*</i>
<i>m00o=M</i>	59.0	89.3	-55.7	105.2	328.0	1.00 0.00 1.00
<i>m12o</i>	57.4	85.2	-41.5	94.8	333.9	1.00 0.00 0.87
<i>m25o</i>	56.1	81.5	-26.9	85.9	341.7	1.00 0.00 0.75
<i>m37o</i>	55.0	78.4	-11.7	79.3	351.5	1.00 0.00 0.62
<i>m50o</i>	54.1	75.9	3.8	76.0	2.8	1.00 0.00 0.50
<i>m62o</i>	53.5	74.0	19.1	76.4	14.5	1.00 0.00 0.37
<i>m75o</i>	53.0	72.6	33.4	80.0	24.6	1.00 0.00 0.25
<i>m87o</i>	52.8	71.9	44.4	84.5	31.6	1.00 0.00 0.12

R