

Optimal colours for CIE Standard Illuminant A

<i>X</i>	<i>Y</i>	<i>Z</i>	<i>x</i>	<i>y</i>	<i>A</i>	<i>B</i>	<i>C_r</i>	<i>OYLCVM_ONW_1</i>	
83.5	46.7	0.0	0.64	0.358	32.1	6.6	32.8	%O=JR	00 575_770
104.3	92.5	1.2	0.526	0.467	2.7	12.6	12.9	%Y=J=JG+JR	01 515_770
20.8	45.8	1.1	0.307	0.675	-29.4	6.0	30.0	%L=JG	02 515_575
22.5	48.0	11.4	0.274	0.585	-30.2	2.2	30.3	%G	03 0,70*L+0,30*C
26.3	53.2	35.5	0.228	0.462	-32.1	-6.6	32.8	%C=L+V	04 380_575
5.4	7.4	34.3	0.115	0.157	-2.7	-12.6	12.9	%V=B=BR+BG	05 380_515
88.9	54.1	34.4	0.501	0.305	29.4	-6.0	30.0	%M=V+O	06 380_515+575_770
84.4	48.0	6.2	0.608	0.346	31.6	4.3	31.9	%R	07 0,18*M+0,82*O
83.5	46.7	0.0	0.64	0.358	32.1	6.6	32.8	%O=JR	08 575_770
0.1	0.0	0.0	0.445	0.405	0.0	0.0	0.0	%N0 ($\beta=0,001$)	09 380_770
109.8	99.9	35.5	0.447	0.407	0.0	0.0	0.0	%W1 ($\beta=1,000$)	10 380_770