

Contrast step C_{Y1} (i=1 to 8), CIE tristimulus value Y_N , grey steps according to ISO 9241-306 ¹⁾							
Contrast step C_{Y1} and Y-ratio (i=1 .. 8)	CIE tristimulus value Y_N and CIE lightness L^*_{N} of black	total viewing display illuminance $E_{P,R}$ [lux] ²⁾	measured projector (P) display illuminance E_P [lux] ³⁾	room light (R) display illuminance E_R [lux] ³⁾	grey steps without output linearisation delta $L^*_{\Delta=1}$ amount $a_{\Delta}^2)$	grey steps with output linearisation delta $L^*_{\Delta=1}$ amount $a_{\Delta}^2)$	
C_{Y8} 288:1	0,31 / 1	80000+64000	143500	500	47 (max)	94 (max)	
C_{Y7} 144:1	0,62 / 6	40000+32000	61500	500	44	88	
C_{Y6} 72:1	1,25 / 11	20000+16000	35500	500	42	84	
C_{Y5} 36:1	2,5 / 18	10000+8000	17500	500	38	77	
C_{Y4} 18:1	5,0 / 27	5000+4000	8500	500	34	68	
C_{Y3} 9:1	10 / 38	2500+2000	4000	500	28	57	
C_{Y2} 4,5:1	20 / 52	1250+1000	1750	500	21	43	
C_{Y1} 2,25:1	40 / 70	625+500	625	500	12	25	

- 1) The example is intended for data projectors (P). The standard contrast step (bold) C_{Y5} = 36:1 is hard to reach.
 2) For the amount of discriminable colour steps use the equations: $c_{\Delta} = a_{\Delta}^2$ or $c_{\Delta} = a_{\Delta}^3$, for example $c_{\Delta} = 4096$ for $a_{\Delta} = 16$.
 3) For the contrast C_{Yi} < 2:1 the viewing luminances of both the black in the projection and the white standard offset paper are equal (1). Visual fatigue caused by the adaptation luminance ratio 36:1 of the black at the screen and the black at the paper shall be reduced. If for example a grey screen with the CIE tristimulus value $Y_{\Delta} = 22,2$ (<0,25*88,9) is used the contrast step C_{Yi} remains constant. Then the luminance ratio of all colours at the screen and the paper has reduced to 9:1. This reduces visual fatigue.

PS040-3N

Contrast step C_{Y1} (i=1 to 8), CIE tristimulus value Y_N , grey steps according to ISO 9241-306 ¹⁾							
Contrast step C_{Y1} and Y-ratio (i=1 .. 8)	CIE tristimulus value Y_N and CIE lightness L^*_{N} of black	total viewing display illuminance $E_{P,R}$ [lux] ²⁾	measured projector (P) display illuminance E_P [lux] ³⁾	room light (R) display illuminance E_R [lux] ³⁾	grey steps without output linearisation delta $L^*_{\Delta=1}$ amount $a_{\Delta}^3)$	grey steps with output linearisation delta $L^*_{\Delta=1}$ amount $a_{\Delta}^3)$	
C_{Y3} 9:1	10 / 38	2500+2000	4000	500	28	57	
C_{Y2} 4,5:1	20 / 52	1250+1000	1750	500	21	43	
C_{Y1} 2,25:1	40 / 70	625+500	625	500	12	25	

The following example assumes that a projector produces the contrast step C_{Y3} for the illuminances measured for 5 times the horizontal A4 direction (149 cm):

C_{Y3} 9:1	10 / 38	2500+2000	4000	500	28	57
C_{Y2} 4,5:1	20 / 52	1250+1000	1750	500	21	43
C_{Y1} 2,25:1	40 / 70	625+500	625	500	12	25

The illuminances E_{Δ} are by the factor 4 less for 10 times the A4-direction (298 cm):

C_{Y3} 3:1 ⁴⁾	30 / 61	1000+500	1000	500	17	34
C_{Y2} 1,9:1 ⁵⁾	45 / 74	438+500	438	500	10	21

- 1) The example is intended for data projectors (P). The standard contrast step (bold) C_{Y3} = 36:1 is not reached.
 2) 500 lux corresponds to the viewing luminance $L_{\Delta}=142$ cd/m² for a standard white paper with the tristimulus value $Y_{\Delta}=88,9$.
 3) For the amount of discriminable colour steps use the equations: $c_{\Delta} = a_{\Delta}^3$ or $c_{\Delta} = a_{\Delta}^4$, for example $c_{\Delta} = 4096$ for $a_{\Delta} = 16$.
 4) The viewing contrast C_{Y31} = 1500:500 = 3:1 is larger compared to the contrast C_{Y1} = 2,25:1.
 5) The viewing contrast C_{Y21} = 938:500 = 1,9:1 is smaller compared to the contrast C_{Y1} = 2,25:1. A contrast step is not defined.

PS040-7N

gráfico PS04; Contrast steps of data projectors
 Eight contrast steps, and illuminances of displays for 500 lux salida: ningún cambio

Contrast step C_{Y1} (i=1 to 8), CIE tristimulus value Y_N , grey steps according to ISO 9241-306 ¹⁾							
Contrast step C_{Y1} and Y-ratio (i=1 .. 8)	CIE tristimulus value Y_N and CIE lightness L^*_{N} of black	total viewing display illuminance $E_{P,R}$ [lux] ²⁾	measured projector (P) display illuminance E_P [lux] ²⁾	room light (R) display illuminance E_R [lux] ²⁾	grey steps without output linearisation delta $L^*_{\Delta=1}$ amount $a_{\Delta}^2)$	grey steps with output linearisation delta $L^*_{\Delta=1}$ amount $a_{\Delta}^2)$	
C_{Y8} 288:1	0,31 / 1	19200+16000	35075	125	47 (max)	94 (max)	
C_{Y7} 144:1	0,62 / 6	9600+8000	17475	125	44	88	
C_{Y6} 72:1	1,25 / 11	4800+4000	8675	125	42	84	
C_{Y5} 36:1	2,5 / 18	2400+2000	4275	125	38	77	
C_{Y4} 18:1	5,0 / 27	1200+1000	2075	125	34	68	
C_{Y3} 9:1	10 / 38	600+500	975	125	28	57	
C_{Y2} 4,5:1	20 / 52	300+250	425	125	21	43	
C_{Y1} 2,25:1	40 / 70	150+125	150	125	12	25	

- 1) The example is intended for data projectors (P). The standard contrast step (bold) C_{Y5} = 36:1 is hard to reach.
 2) For the amount of discriminable colour steps use the equations: $c_{\Delta} = a_{\Delta}^2$ or $c_{\Delta} = a_{\Delta}^3$, for example $c_{\Delta} = 4096$ for $a_{\Delta} = 16$.
 3) For the contrast C_{Yi} < 2:1 the viewing luminances of both the black in the projection and the white standard offset paper are equal (1). Visual fatigue caused by the adaptation luminance ratio 36:1 of the black at the screen and the black at the paper shall be reduced. If for example a grey screen with the CIE tristimulus value $Y_{\Delta} = 22,2$ (<0,25*88,9) is used the contrast step C_{Yi} remains constant. Then the luminance ratio of all colours at the screen and the paper has reduced to 9:1. This reduces visual fatigue.

PS041-3N

Contrast step C_{Y1} (i=1 to 8), CIE tristimulus value Y_N , grey steps according to ISO 9241-306 ¹⁾							
Contrast step C_{Y1} and Y-ratio (i=1 .. 8)	CIE tristimulus value Y_N and CIE lightness L^*_{N} of black	total viewing display illuminance $E_{P,R}$ [lux] ²⁾	measured projector (P) display illuminance E_P [lux] ²⁾	room light (R) display illuminance E_R [lux] ²⁾	grey steps without output linearisation delta $L^*_{\Delta=1}$ amount $a_{\Delta}^3)$	grey steps with output linearisation delta $L^*_{\Delta=1}$ amount $a_{\Delta}^3)$	
C_{Y4} 36:1	10 / 38	2400+2000	4275	125	38	77	
C_{Y3} 9:1	20 / 52	1200+1000	2075	125	34	68	
C_{Y2} 4,5:1	40 / 70	600+500	975	125	28	57	

The following example assumes that a projector produces the contrast step C_{Y3} for the illuminances measured for 5 times the horizontal A4 direction (149 cm):

C_{Y4} 36:1	10 / 38	2400+2000	4275	125	38	77
C_{Y3} 9:1	20 / 52	1200+1000	2075	125	34	68
C_{Y2} 4,5:1	40 / 70	600+500	975	125	28	57

The illuminances E_{Δ} are by the factor 4 less for 10 times the A4-direction (298 cm):

C_{Y3} 4:1 ⁴⁾	30 / 61	1069+125	1069	125	17	34
C_{Y2} 2:1 ⁵⁾	45 / 74	518+125	518	125	10	21

- 1) The example is intended for data projectors (P). The standard contrast step (bold) C_{Y3} = 36:1 is not reached.
 2) 125 lux corresponds to the viewing luminance $L_{\Delta}=35$ cd/m² for a standard white paper with the tristimulus value $Y_{\Delta}=88,9$.
 3) For the amount of discriminable colour steps use the equations: $c_{\Delta} = a_{\Delta}^3$ or $c_{\Delta} = a_{\Delta}^4$, for example $c_{\Delta} = 4096$ for $a_{\Delta} = 16$.
 4) The viewing contrast C_{Y31} = 1194:125 = 8,5:1 is larger compared to the contrast C_{Y1} = 4,5:1. The contrast step is C_{Y2} = 4,5:1.
 5) The viewing contrast C_{Y21} = 643:125 = 5,1:1 is larger compared to the contrast C_{Y1} = 4,5:1. The contrast step is C_{Y2} = 4,5:1.

PS041-7N

entrada: w/rgb/cmyk -> rgb-
 salida: ningún cambio