

CIE data for all optimal colours of maximum (m) C_{AB}, P40 and Y_w=88,6, Y_m=495_770

Table with columns: i1, λ1, i2, λ2, Y88.6, A88.6, B88.6, CAB, a, b, hAB, id, λd, ic, λc, Code. Rows include color codes like Cm, Gm, Ym, Rm, Mm, Bm.

CIE data for all optimal colours of maximum (m) C_{AB}, P40 and Y_w=88,6, Y_m=495_770

Table with columns: i1, λ1, i2, λ2, L*88.6, a*88.6, b*88.6, C*ab, a', b', hab, id, λd, ic, λc, Code. Rows include color codes like Cm, Gm, Ym, Rm, Mm, Bm.

voir des fichiers similaires: http://130.149.60.45/~farbmetrik/SF91/SF91.HTM informations techniques: http://www.ps.bam.de ou http://130.149.60.45/~farbmetrik

TUB enregistrement: 20130201-SF91/SF91L0NA.TXT /.PS application pour la mesure de sortie sur écran TUB matériel: code=rh4ta

CIE data for all optimal colours of maximum (m) C_{AB} , A00 and $Y_w=88.6, Y_m=495.770$





Table with columns for color indices (i1, lambda1, i2, lambda2), Y88.6, A88.6, B88.6, CAB, a, b, hAB, id, lambda_d, ic, lambda_c, Code. Contains 50 rows of color data.

CIE data for all optimal colours of maximum (m) C_{AB} , A00 and $Y_w=88.6, Y_m=495.770$

Table with columns for color indices (i1, lambda1, i2, lambda2), L*88.6, a*88.6, b*88.6, C*ab, a', b', hab, id, lambda_d, ic, lambda_c, Code. Contains 50 rows of color data.

voir des fichiers similaires: http://130.149.60.45/~farbmetrik/SF91/SF91.L0NA.TXT /PS
informations techniques: http://www.ps.bam.de ou http://130.149.60.45/~farbmetrik

TUB enregistrement: 20130201-SF91/SF91L0NA.TXT /.PS
application pour la mesure de sortie sur écran
TUB matériel: code=rh4ta



3-000330-L0

SF910-7N_4

3-000330-L0

SF911-7N_4

CIE data for all optimal colours of maximum (m) CAB, C00 and Yw=88.6, Ym=495.770. Table with 13 columns: i1, lambda1, i2, lambda2, Y88.6, A88.6, B88.6, CAB, a, b, hAB, id, lambda_d, ic, lambda_c, Code. Rows include CMYK patches (1-31) and color bars (32-38).

CIE data for all optimal colours of maximum (m) CAB, C00 and Yw=88.6, Ym=495.770. Table with 13 columns: i1, lambda1, i2, lambda2, L*88.6, a*88.6, b*88.6, C*ab, a', b', hab, id, lambda_d, ic, lambda_c, Code. Rows include CMYK patches (1-31) and color bars (32-38).

voir des fichiers similaires: http://130.149.60.45/~farbmetrik/SF91/SF91.HTM informations techniques: http://www.ps.bam.de ou http://130.149.60.45/~farbmetrik

TUB enregistrement: 20130201-SF91/SF91L0NA.TXT /.PS TUB matériel: code=rh4ta application pour la mesure de sortie sur écran

CIE data for all optimal colours of maximum (m) C_{AB}, D50 and Y_{w,10}=88,6, Y_m=495_770

i ₁ , λ ₁	i ₂ , λ ₂	Y _{88.6}	A _{88.6}	B _{88.6}	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code
1 405 31 555 43.51 -20.36 -14.54 25.03 0.5817 -0.6643 215.5 16 483 37 586 Cm											
7 435 32 563 49.66 -26.1 -6.1 26.8 0.5243 -0.4529 193.1 17 489 45 627											
10 450 32 564 50.37 -29.9 1.57 29.94 0.4562 -0.2987 176.9 19 497 -1 497c											
12 460 33 566 51.38 -31.95 6.93 32.69 0.428 -0.1949 167.7 21 505 -1 505c											
13 465 33 567 52.13 -32.61 9.34 33.92 0.4241 -0.1506 164.0 22 511 -1 511c											
14 470 33 569 53.58 -33.07 11.63 35.06 0.4326 -0.1127 160.6 23 518 -1 518c											
15 475 34 573 55.82 -33.0 13.84 35.78 0.4586 -0.0819 157.2 25 527 -1 527c Gm											
16 480 35 579 59.25 -32.27 16.11 36.07 0.5051 -0.058 153.4 27 535 -1 535c											
17 485 37 589 65.2 -29.5 18.91 35.04 0.5973 -0.0398 147.3 29 545 -1 545c											
18 490 -1 490c 84.13 -8.1 25.79 27.04 0.9535 -0.0233 107.4 33 566 11 459											
19 495 -1 495c 82.96 -6.9 25.91 26.81 0.9666 -0.0176 104.9 33 566 12 462 Ym											
19 500 -1 499c 82.96 -6.9 25.91 26.81 0.9666 -0.0176 104.9 33 566 12 462											
22 510 -1 510c 77.37 -1.39 24.98 25.01 1.0318 -0.0071 93.1 33 569 13 469											
24 520 -1 520c 71.55 3.71 23.32 23.62 1.1017 -0.0039 80.9 34 572 14 473											
25 530 -1 529c 68.03 6.54 22.25 23.19 1.1459 -0.0029 73.6 34 574 15 475											
27 540 -1 539c 60.24 12.11 19.78 23.19 1.2509 -0.0015 58.5 35 577 15 479											
28 545 -1 544c 56.11 14.67 18.45 23.57 1.3114 -0.0011 51.4 35 579 16 480											
29 550 -1 549c 51.87 17.02 17.07 24.1 1.378 -0.0009 45.0 36 581 16 481											
30 555 -1 554c 47.59 19.06 15.67 24.67 1.4503 -0.0007 39.4 36 584 16 483											
32 560 3 416 39.23 22.73 11.98 25.7 1.6293 -0.0245 27.7 38 591 17 485											
31 555 1 405 56.48 20.36 14.54 25.03 1.4104 -0.0724 35.5 37 586 16 483 Rm											
32 563 7 435 50.33 26.1 6.1 26.8 1.5684 -0.2085 13.1 45 627 17 489											
32 564 10 450 49.62 29.9 -1.57 29.94 1.6524 -0.3617 356.9 -1 497c 19 497											
33 566 12 460 48.61 31.95 -6.93 32.69 1.707 -0.4727 347.7 -1 505c 21 505											
33 567 13 465 47.86 32.61 -9.34 33.92 1.7312 -0.5252 344.0 -1 511c 22 511											
33 569 14 470 46.41 33.07 -11.63 35.06 1.7624 -0.5807 340.6 -1 518c 23 518											
34 573 15 475 44.17 33.0 -13.84 35.78 1.7968 -0.6433 337.2 -1 527c 25 527 Mm											
35 579 16 480 40.74 32.27 -16.11 36.07 1.8418 -0.7253 333.4 -1 535c 27 535											
37 589 17 485 34.79 29.5 -18.91 35.04 1.8977 -0.8736 327.3 -1 545c 29 545											
-1 490c 18 490 15.86 8.1 -25.79 27.04 1.5605 -1.9558 287.4 11 459 33 566											
-1 495c 19 495 17.03 6.9 -25.91 26.81 1.4549 -1.8515 284.9 12 462 33 566 Bm											
-1 499c 19 500 17.03 6.9 -25.91 26.81 1.4549 -1.8515 284.9 12 462 33 566											
-1 510c 22 510 22.62 1.39 -24.98 25.01 1.1115 -1.434 273.1 13 469 33 569											
-1 520c 24 520 28.44 -3.71 -23.32 23.62 0.9191 -1.1502 260.9 14 473 34 572											
-1 529c 25 530 31.96 -6.54 -22.25 23.19 0.8451 -1.0261 253.6 15 475 34 574											
-1 539c 27 540 39.75 -12.11 -19.78 23.19 0.7451 -0.8276 238.5 15 479 35 577											
-1 544c 28 545 43.88 -14.67 -18.45 23.57 0.7153 -0.7504 231.4 16 480 35 579											
-1 549c 29 550 48.12 -17.02 -17.07 24.1 0.696 -0.6846 225.0 16 481 36 581											
-1 554c 30 555 52.4 -19.06 -15.67 24.67 0.6861 -0.6289 219.4 16 483 36 584											
3 416 32 560 60.76 -22.73 -11.98 25.7 0.6756 -0.5271 207.7 17 485 38 591											
380 770 88.59 0.0 0.0 0.01 1.0498 -0.3299 0.0											

CIE data for all optimal colours of maximum (m) C_{AB}, D50 and Y_{w,10}=88,6, Y_m=495_770

i ₁ , λ ₁	i ₂ , λ ₂	L* _{88.6}	a* _{88.6}	b* _{88.6}	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405 31 555 71.9 -67.66 -39.81 78.5 0.1829 -0.0991 210.4 16 483 37 586 Cm											
7 435 32 563 75.87 -81.79 -17.64 83.67 0.1766 -0.0873 192.1 17 489 45 627											
10 450 32 564 76.3 -96.48 5.19 96.62 0.1686 -0.0759 176.9 19 497 -1 497c											
12 460 33 566 76.91 -103.48 25.76 106.64 0.1651 -0.0659 166.0 21 505 -1 505c											
13 465 33 567 77.36 -104.89 37.01 111.23 0.1646 -0.0604 160.5 22 511 -1 511c											
14 470 33 569 78.22 -103.87 48.85 114.78 0.1657 -0.0549 154.8 23 518 -1 518c											
15 475 34 573 79.51 -99.29 61.14 116.61 0.1689 -0.0493 148.3 25 527 -1 527c Gm											
16 480 35 579 81.43 -90.86 73.82 117.07 0.1744 -0.044 140.9 27 535 -1 535c											
17 485 37 589 84.59 -74.28 87.68 114.91 0.1845 -0.0388 130.2 29 545 -1 545c											
18 490 -1 490c 93.51 -14.89 110.68 111.68 0.2156 -0.0324 97.6 33 566 11 459											
19 495 -1 495c 93.0 -12.74 117.07 117.76 0.2166 -0.0295 96.2 33 566 12 462 Ym											
19 500 -1 499c 93.0 -12.74 117.07 117.76 0.2166 -0.0295 96.2 33 566 12 462											
22 510 -1 510c 90.49 -2.64 132.38 132.4 0.2213 -0.0218 91.1 33 569 13 469											
24 520 -1 520c 87.76 7.25 140.25 140.44 0.2262 -0.0179 87.0 34 572 14 473											
25 530 -1 529c 86.03 13.03 140.55 141.15 0.2292 -0.0162 84.7 34 574 15 475											
27 540 -1 539c 81.97 25.4 137.63 139.96 0.236 -0.0132 79.5 35 577 15 479											
28 545 -1 544c 79.68 31.74 134.8 138.49 0.2398 -0.012 76.7 35 579 16 480											
29 550 -1 549c 77.21 38.12 131.28 136.7 0.2438 -0.011 73.8 36 581 16 481											
30 555 -1 554c 74.57 44.39 127.21 134.74 0.248 -0.0102 70.7 36 584 16 483											
32 560 3 416 68.92 57.74 84.73 102.54 0.2578 -0.033 55.7 38 591 17 485											
31 555 1 405 79.89 42.74 65.59 78.29 0.2457 -0.0473 56.9 37 586 16 483 Rm											
32 563 7 435 76.27 56.94 22.55 61.24 0.2545 -0.0674 21.6 45 627 17 489											
32 564 10 450 75.84 64.61 -4.92 64.8 0.259 -0.0809 355.6 -1 497c 19 497											
33 566 12 460 75.21 69.15 -20.01 71.99 0.2618 -0.0885 343.8 -1 505c 21 505											
33 567 13 465 74.74 70.95 -26.21 75.64 0.263 -0.0917 339.7 -1 511c 22 511											
33 569 14 470 73.81 72.96 -32.1 79.71 0.2646 -0.0948 336.2 -1 518c 23 518											
34 573 15 475 72.35 74.7 -37.96 83.79 0.2663 -0.0981 333.0 -1 527c 25 527 Mm											
35 579 16 480 70.0 76.38 -44.51 88.4 0.2685 -0.1021 329.7 -1 535c 27 535											
37 589 17 485 65.59 76.71 -53.92 93.77 0.2712 -0.1086 324.8 -1 545c 29 545											
-1 490c 18 490 46.81 38.22 -87.65 95.62 0.2541 -0.1421 293.5 11 459 33 566											
-1 495c 19 495 48.31 31.84 -86.12 91.81 0.2482 -0.1395 290.2 12 462 33 566 Bm											
-1 499c 19 500 48.31 31.84 -86.12 91.81 0.2482 -0.1395 290.2 12 462 33 566											
-1 510c 22 510 54.69 5.85 -76.99 77.22 0.2269 -0.1281 274.3 13 469 33 569											
-1 520c 24 520 60.29 -14.25 -67.89 69.37 0.213 -0.1191 258.1 14 473 34 572											
-1 529c 25 530 63.31 -23.83 -62.84 67.21 0.2071 -0.1146 249.2 15 475 34 574											
-1 539c 27 540 69.3 -39.69 -52.73 66.01 0.1986 -0.1067 233.0 15 479 35 577											
-1 544c 28 545 72.15 -45.6 -47.87 66.12 0.1959 -0.1033 226.3 16 480 35 579											
-1 549c 29 550 74.91 -50.15 -43.16 66.17 0.1941 -0.1001 220.7 16 481 36 581											
-1 554c 30 555 77.52 -53.27 -38.67 65.83 0.1932 -0.0974 215.9 16 483 36 584											
3 416 32 560 82.25 -57.85 -28.62 64.54 0.1922 -0.0918 206.3 17 485 38 591											
380 770 95.41 0.0 0.0 0.0 0.2226 -0.0785 0.0											

voir des fichiers similaires: <http://130.149.60.45/~farbmetrik/SF91/SF91.HTM>
 informations techniques: <http://www.ps.bam.de> ou <http://130.149.60.45/~farbmetrik>

TUB enregistrement: 20130201-SF91/SF91L0NA.TXT /.PS TUB matériel: code=rh4ta
 application pour la mesure de sortie sur écran

CIE data for all optimal colours of maximum (m) C_{AB}, C₀₀ and Y_{w,10}=88,6, Y_m=495_770

i ₁ , λ ₁	i ₂ , λ ₂	Y _{88.6}	A _{88.6}	B _{88.6}	C _{AB}	a	b	<i>h</i> _{AB}	i _d , λ _d	i _c , λ _c	Code
1 405	29 548	39.56	-14.39	-22.73	26.91	0.7095	-1.0476	237.6	15 478	36 581	Cm
6 435	32 560	49.73	-23.52	-10.19	25.63	0.6005	-0.6778	203.4	16 484	42 610	
9 450	32 562	50.95	-29.26	0.99	29.28	0.499	-0.4533	178.0	18 492	-1 492c	
12 460	33 565	52.36	-33.84	12.06	35.93	0.4271	-0.2425	160.3	21 505	-1 505c	
13 465	33 567	53.54	-34.78	15.51	38.08	0.4237	-0.1831	155.9	22 512	-1 512c	
14 470	34 570	55.82	-35.41	18.99	40.18	0.4389	-0.1327	151.8	24 521	-1 521c	
14 475	35 576	59.82	-35.45	20.88	41.14	0.4808	-0.1238	149.5	25 527	-1 527c	Gm
16 480	36 584	64.26	-33.75	26.35	42.82	0.5481	-0.0627	142.0	28 540	-1 540c	
17 485	42 611	75.87	-24.3	32.93	40.93	0.7531	-0.0387	126.4	31 555	3 416	
18 490	-1 490c	82.68	-12.75	36.96	39.1	0.9191	-0.0257	109.0	32 564	11 457	
18 495	-1 494c	82.68	-12.75	36.96	39.1	0.9191	-0.0257	109.0	32 564	11 457	Ym
20 500	-1 500c	79.64	-9.55	36.57	37.79	0.9534	-0.0137	104.6	33 566	12 462	
22 510	-1 510c	75.34	-5.28	35.08	35.48	1.0033	-0.0071	98.5	33 568	13 466	
24 520	-1 520c	69.63	-0.12	32.65	32.65	1.0716	-0.0039	90.2	34 571	14 470	
26 530	-1 530c	62.62	5.45	29.47	29.97	1.1606	-0.0021	79.5	34 574	14 473	
28 540	-1 540c	54.54	10.91	25.72	27.94	1.2736	-0.0012	67.0	35 578	15 476	
29 545	-1 545c	50.25	13.39	23.71	27.23	1.34	-0.0009	60.5	36 580	15 478	
29 550	1 408	50.25	13.78	23.26	27.04	1.3478	-0.01	59.3	36 581	15 478	
31 555	3 415	41.51	18.39	18.47	26.07	1.5166	-0.0278	45.1	37 587	16 480	
31 560	4 424	41.55	20.19	15.85	25.67	1.5593	-0.0914	38.1	38 591	16 482	
29 548	1 405	60.43	14.39	22.73	26.91	1.3117	-0.0966	57.6	36 581	15 478	Rm
32 560	6 435	50.26	23.52	10.19	25.63	1.5414	-0.2701	23.4	42 610	16 484	
32 562	9 450	49.04	29.26	-0.99	29.28	1.6702	-0.4931	358.0	-1 492c	18 492	
33 565	12 460	47.63	33.84	-12.06	35.93	1.7839	-0.726	340.3	-1 505c	21 505	
33 567	13 465	46.45	34.78	-15.51	38.08	1.8222	-0.8067	335.9	-1 512c	22 512	
34 570	14 470	44.17	35.41	-18.99	40.18	1.8752	-0.9027	331.8	-1 521c	24 521	
35 576	14 475	40.17	35.45	-20.88	41.14	1.956	-0.9926	329.5	-1 527c	25 527	Mm
36 584	16 480	35.73	33.75	-26.35	42.82	2.0179	-1.2103	322.0	-1 540c	28 540	
42 611	17 485	24.12	24.29	-32.93	40.93	2.0805	-1.8379	306.4	3 416	31 555	
-1 490c	18 490	17.31	12.75	-36.96	39.1	1.8102	-2.6079	289.0	11 457	32 564	
-1 494c	18 495	17.31	12.75	-36.96	39.1	1.8102	-2.6079	289.0	11 457	32 564	Bm
-1 500c	20 500	20.35	9.55	-36.57	37.79	1.5429	-2.2694	284.6	12 462	33 566	
-1 510c	22 510	24.65	5.28	-35.08	35.48	1.2878	-1.8961	278.5	13 466	33 568	
-1 520c	24 520	30.36	0.12	-32.65	32.65	1.0775	-1.5483	270.2	14 470	34 571	
-1 530c	26 530	37.37	-5.45	-29.47	29.97	0.9274	-1.2615	259.5	14 473	34 574	
-1 540c	28 540	45.45	-10.91	-25.72	27.94	0.8332	-1.0389	247.0	15 476	35 578	
-1 545c	29 545	49.74	-13.39	-23.71	27.23	0.8042	-0.9496	240.5	15 478	36 580	
1 408	29 550	49.74	-13.78	-23.26	27.04	0.7962	-0.9405	239.3	15 478	36 581	
3 415	31 555	58.48	-18.39	-18.47	26.07	0.7588	-0.7887	225.1	16 480	37 587	
4 424	31 560	58.44	-20.19	-15.85	25.67	0.7279	-0.7441	218.1	16 482	38 591	
380	770	88.59	0.0	0.0	0.01	1.0734	-0.4729	0.0			

CIE data for all optimal colours of maximum (m) C_{AB}, C₀₀ and Y_{w,10}=88,6, Y_m=495_770

i ₁ , λ ₁	i ₂ , λ ₂	L* _{88.6}	a** _{88.6}	b** _{88.6}	C*_ab	a'	b'	<i>h</i> _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	29 548	69.16	-47.3	-44.57	64.99	0.1954	-0.1154	223.2	15 478	36 581	Cm
6 435	32 560	75.91	-69.71	-20.19	72.58	0.1848	-0.0998	196.1	16 484	42 610	
9 450	32 562	76.65	-89.96	2.22	89.99	0.1737	-0.0873	178.5	18 492	-1 492c	
12 460	33 565	77.5	-106.57	32.15	111.32	0.165	-0.0708	163.2	21 505	-1 505c	
13 465	33 567	78.19	-108.15	44.0	116.76	0.1645	-0.0645	157.8	22 512	-1 512c	
14 470	34 570	79.51	-106.09	56.84	120.36	0.1665	-0.0579	151.8	24 521	-1 521c	
14 475	35 576	81.74	-98.93	60.68	116.05	0.1716	-0.0566	148.4	25 527	-1 527c	Gm
16 480	36 584	84.1	-86.58	84.52	121.0	0.1793	-0.0451	135.6	28 540	-1 540c	
17 485	42 611	89.8	-50.79	103.13	114.96	0.1993	-0.0384	116.2	31 555	3 416	
18 490	-1 490c	92.88	-23.65	116.49	118.87	0.213	-0.0335	101.4	32 564	11 457	
18 495	-1 494c	92.88	-23.65	116.49	118.87	0.213	-0.0335	101.4	32 564	11 457	Ym
20 500	-1 500c	91.52	-17.95	128.36	129.61	0.2156	-0.0272	97.9	33 566	12 462	
22 510	-1 510c	89.55	-10.13	136.78	137.16	0.2193	-0.0219	94.2	33 568	13 466	
24 520	-1 520c	86.82	-0.24	138.89	138.89	0.2242	-0.018	90.1	34 571	14 470	
26 530	-1 530c	83.24	11.27	138.16	138.62	0.2302	-0.0147	85.3	34 574	14 473	
28 540	-1 540c	78.78	23.95	133.23	135.37	0.2374	-0.0121	79.8	35 578	15 476	
29 545	-1 545c	76.22	30.49	129.57	133.11	0.2415	-0.0111	76.7	36 580	15 478	
29 550	1 408	76.23	31.33	114.78	118.98	0.242	-0.0245	74.7	36 581	15 478	
31 555	3 415	70.54	45.53	91.05	101.8	0.2517	-0.0344	63.4	37 587	16 480	
31 560	4 424	70.57	49.44	62.91	80.01	0.254	-0.0512	51.8	38 591	16 482	
29 548	1 405	82.08	29.2	69.47	75.36	0.2398	-0.0521	67.1	36 581	15 478	Rm
32 560	6 435	76.23	50.95	27.07	57.69	0.253	-0.0734	27.9	42 610	16 484	
32 562	9 450	75.48	62.59	-2.22	62.63	0.2599	-0.0898	357.9	-1 492c	18 492	
33 565	12 460	74.6	72.03	-23.99	75.92	0.2657	-0.1021	341.5	-1 505c	21 505	
33 567	13 465	73.84	74.69	-30.18	80.56	0.2676	-0.1058	337.9	-1 512c	22 512	
34 570	14 470	72.35	77.8	-36.63	86.0	0.2701	-0.1098	334.7	-1 521c	24 521	
35 576	14 475	69.59	81.67	-41.37	91.55	0.274	-0.1134	333.1	-1 527c	25 527	Mm
36 584	16 480	66.32	83.07	-52.2	98.11	0.2768	-0.1211	327.8	-1 540c	28 540	
42 611	17 485	56.22	76.8	-71.24	104.75	0.2797	-0.1392	317.1	3 416	31 555	
-1 490c	18 490	48.66	53.01	-85.45	100.56	0.267	-0.1564	301.8	11 457	32 564	
-1 494c	18 495	48.66	53.01	-85.45	100.56	0.267	-0.1564	301.8	11 457	32 564	Bm
-1 500c	20 500	52.24	37.79	-80.78	89.18	0.2531	-0.1493	295.0	12 462	33 566	
-1 510c	22 510	56.74	19.6	-73.81	76.37	0.2383	-0.1407	284.8	13 466	33 568	
-1 520c	24 520	61.97	0.42	-65.17	65.17	0.2246	-0.1315	270.3	14 470	34 571	
-1 530c	26 530	67.56	-17.13	-55.73	58.3	0.2136	-0.1228	252.9	14 473	34 574	
-1 540c	28 540	73.19	-31.11	-46.12	55.64	0.2061	-0.1151	235.9	15 476	35 578	
-1 545c	29 545	75.92	-36.34	-41.45	55.13	0.2037	-0.1117	228.7	15 478	36 580	
1 408	29 550	75.91	-37.54	-40.81	55.45	0.203	-0.1113	227.3	15 478	36 581	
3 415	31 555	81.01	-45.64	-31.09	55.23	0.1998	-0.105	214.2	16 480	37 587	
4 424	31 560	80.98	-50.76	-27.27	57.62	0.197	-0.103	208.2	16 482	38 591	
380	770	95.41	0.0	0.0	0.0	0.2243	-0.0885	0.0			

voir des fichiers similaires: <http://130.149.60.45/~farbmetrik/SF91/SF91.L0NA.TXT> / .PS
 informations techniques: <http://www.ps.bam.de> ou <http://130.149.60.45/~farbmetrik>

TUB enregistrement: 20130201-SF91/SF91L0NA.TXT /.PS
 application pour la mesure de sortie sur écran
 TUB matériel: code=rh4ta

CIE data for all optimal colours of maximum (m) C_{AB} , P00 and $Y_{w,10}=88.6$, $Y_m=495_770$

i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code
1	405	31	558	43.17	-21.3	-14.27	25.64	0.6134	-0.6548	213.8	16 483 37 588 Cm
7	435	33	565	48.86	-27.71	-4.75	28.11	0.5398	-0.4215	189.7	18 490 -1 490c
10	450	33	567	49.57	-31.23	2.49	31.33	0.4769	-0.2739	175.4	19 498 -1 498c
11	460	33	568	50.86	-32.39	5.22	32.81	0.47	-0.2216	170.8	20 502 -1 502c
13	465	34	570	51.4	-33.73	9.53	35.05	0.4507	-0.1388	164.2	22 513 -1 513c
14	470	34	572	52.85	-34.03	11.62	35.96	0.463	-0.1042	161.1	24 521 -1 521c
15	475	35	575	55.03	-34.0	13.64	36.64	0.4889	-0.0763	158.1	25 529 -1 529c Gm
16	480	36	581	58.37	-33.26	15.74	36.79	0.5372	-0.0545	154.6	27 538 -1 538c
17	485	38	591	64.88	-30.19	18.62	35.48	0.6415	-0.0371	148.3	29 548 -1 548c
18	490	-1 490c	84.48	-8.44	25.57	26.93	1.007	-0.0215	108.2	33 568 11 457 Ym	
18	495	-1 494c	84.48	-8.44	25.57	26.93	1.007	-0.0215	108.2	33 568 11 457 Ym	
20	500	-1 500c	82.05	-5.81	25.6	26.25	1.0361	-0.0121	102.7	33 569 12 463	
22	510	-1 510c	78.23	-1.88	24.85	24.92	1.0828	-0.0066	94.3	34 571 13 468	
24	520	-1 520c	72.8	3.19	23.34	23.55	1.1509	-0.0036	82.1	34 574 14 473	
26	530	-1 530c	66.07	8.78	21.29	23.03	1.2399	-0.002	67.5	35 577 15 476	
28	540	-1 540c	58.47	14.17	18.89	23.62	1.3494	-0.0011	53.1	36 581 15 479	
28	545	-1 544c	58.47	14.17	18.89	23.62	1.3494	-0.0011	53.1	36 581 15 479	
29	550	-1 549c	54.47	16.62	17.61	24.21	1.412	-0.0008	46.6	36 582 16 481	
31	555	-1 555c	46.28	20.62	14.97	25.48	1.5525	-0.0005	35.9	37 587 16 483	
32	560	2	410	42.18	22.56	13.04	26.06	1.642	-0.0149	30.0	38 591 16 484
31	558	1	405	56.82	21.3	14.27	25.64	1.4819	-0.073	33.8	37 588 16 483 Rm
33	565	7	435	51.13	27.71	4.75	28.11	1.6489	-0.2312	9.7	-1 490c 18 490
33	567	10	450	50.42	31.23	-2.49	31.33	1.7264	-0.3737	35.4	-1 498c 19 498
33	568	11	460	49.13	32.39	-5.22	32.81	1.7662	-0.4304	35.0	-1 502c 20 502
34	570	13	465	48.59	33.73	-9.53	35.05	1.8011	-0.5204	34.2	-1 513c 22 513
34	572	14	470	47.14	34.03	-11.62	35.96	1.8288	-0.5708	34.1	-1 521c 24 521
35	575	15	475	44.96	34.0	-13.64	36.64	1.8632	-0.6276	33.8	-1 529c 25 529 Mm
36	581	16	480	41.62	33.26	-15.74	36.79	1.9061	-0.7025	33.4	-1 538c 27 538
38	591	17	485	35.11	30.19	-18.62	35.48	1.9668	-0.8546	32.8	-1 548c 29 548
-1 490c	18	490	15.51	8.44	-25.57	26.93	1.6515	-1.9729	288.2	11 457 33 568	
-1 494c	18	495	15.51	8.44	-25.57	26.93	1.6515	-1.9729	288.2	11 457 33 568 Bm	
-1 500c	20	500	17.94	5.81	-25.6	26.25	1.4308	-1.7514	282.7	12 463 33 569	
-1 510c	22	510	21.76	1.88	-24.85	24.92	1.1938	-1.4663	274.3	13 468 34 571	
-1 520c	24	520	27.19	-3.19	-23.34	23.55	0.9893	-1.1826	262.1	14 473 34 574	
-1 530c	26	530	33.92	-8.78	-21.29	23.03	0.848	-0.9518	247.5	15 476 35 577	
-1 540c	28	540	41.52	-14.17	-18.89	23.62	0.7655	-0.7792	233.1	15 479 36 581	
-1 544c	28	545	41.52	-14.17	-18.89	23.62	0.7655	-0.7792	233.1	15 479 36 581	
-1 549c	29	550	45.52	-16.62	-17.61	24.21	0.7419	-0.7111	226.6	16 481 36 582	
-1 555c	31	555	53.71	-20.62	-14.97	25.48	0.7231	-0.603	215.9	16 483 37 587	
2	410	32	560	57.81	-22.56	-13.04	26.06	0.7166	-0.5498	210.0	16 484 38 591
380	770	88.59	0.0	0.0	0.01	1.1069	-0.3242	0.0			

3-001630-L0

SF910-7N_7

CIE data for all optimal colours of maximum (m) C_{AB} , P00 and $Y_{w,10}=88.6$, $Y_m=495_770$

i_1, λ_1	i_2, λ_2	$L^*_{88.6}$	$a^*_{88.6}$	$b^*_{88.6}$	C^*_{ab}	a'	b'	h_{ab}	i_d, λ_d	i_c, λ_c	Code
1	405	31	558	71.68	-67.48	-39.9	78.39	0.1861	-0.0987	210.6	16 483 37 588 Cm
7	435	33	565	75.37	-83.81	-14.4	85.04	0.1784	-0.0852	189.7	18 490 -1 490c
10	450	33	567	75.81	-96.82	8.65	97.21	0.1711	-0.0738	174.8	19 498 -1 498c
11	460	33	568	76.6	-99.11	19.01	100.92	0.1703	-0.0687	169.1	20 502 -1 502c
13	465	34	570	76.93	-103.63	39.45	110.88	0.1679	-0.0588	159.1	22 513 -1 513c
14	470	34	572	77.79	-101.9	50.91	113.91	0.1695	-0.0535	153.4	24 521 -1 521c
15	475	35	575	79.06	-97.66	62.66	116.04	0.1726	-0.0482	147.3	25 529 -1 529c Gm
16	480	36	581	80.95	-89.47	74.84	116.65	0.1781	-0.0431	140.0	27 538 -1 538c
17	485	38	591	84.42	-71.95	89.02	114.46	0.1889	-0.0379	128.9	29 548 -1 548c
18	490	-1 490c	93.66	-14.68	112.46	113.42	0.2196	-0.0316	97.4	33 568 11 457 Ym	
18	495	-1 494c	93.66	-14.68	112.46	113.42	0.2196	-0.0316	97.4	33 568 11 457 Ym	
20	500	-1 500c	92.6	-10.2	124.47	124.89	0.2217	-0.0261	94.6	33 569 12 463	
22	510	-1 510c	90.89	-3.37	133.86	133.91	0.2249	-0.0213	91.4	34 571 13 468	
24	520	-1 520c	88.36	5.87	141.96	142.09	0.2296	-0.0175	87.6	34 574 14 473	
26	530	-1 530c	85.04	16.77	141.47	142.46	0.2353	-0.0143	83.2	35 577 15 476	
28	540	-1 540c	81.0	28.53	137.12	140.06	0.2421	-0.0117	78.2	36 581 15 479	
28	545	-1 544c	81.0	28.53	137.12	140.06	0.2421	-0.0117	78.2	36 581 15 479	
29	550	-1 549c	78.74	34.51	133.91	138.29	0.2458	-0.0108	75.5	36 582 16 481	
31	555	-1 555c	73.73	46.15	126.05	134.23	0.2537	-0.0095	69.8	37 587 16 483	
32	560	2	410	71.0	52.66	96.07	109.55	0.2584	-0.028	61.2	38 591 16 484
31	558	1	405	80.08	42.29	64.85	77.42	0.2497	-0.0475	56.8	37 588 16 483 Rm
33	565	7	435	76.76	56.79	17.04	59.29	0.2588	-0.0697	16.7	-1 490c 18 490
33	567	10	450	76.33	63.54	-7.71	64.0	0.2628	-0.0818	35.0	-1 498c 19 498
33	568	11	460	75.54	66.48	-15.63	68.29	0.2648	-0.0858	34.7	-1 502c 20 502
34	570	13	465	75.2	69.24	-26.85	74.27	0.2665	-0.0914	33.8	-1 513c 22 513
34	572	14	470	74.29	70.88	-32.29	77.89	0.2679	-0.0943	33.5	-1 521c 24 521
35	575	15	475	72.87	72.59	-37.72	81.81	0.2696	-0.0973	33.5	-1 529c 25 529 Mm
36	581	16	480	70.61	74.12	-43.89	86.14	0.2716	-0.101	32.9	-1 538c 27 538
38	591	17	485	65.84	74.48	-53.8	91.89	0.2745	-0.1078	32.4	-1 548c 29 548
-1 490c	18	490	46.34	38.31	-88.7	96.62	0.2589	-0.1425	293.3	11 457 33 568	
-1 494c	18	495	46.34	38.31	-88.7	96.62	0.2589	-0.1425	293.3	11 457 33 568 Bm	
-1 500c	20	500	49.43	25.17	-85.1	88.75	0.2468	-0.137	286.4	12 463 33 569	
-1 510c	22	510	53.78	7.66	-78.62	78.99	0.2324	-0.1291	275.5	13 468 34 571	
-1 520c	24	520	59.16	-11.9	-69.87	70.87	0.2183	-0.1202	260.3	14 473 34 574	
-1 530c	26	530	64.91	-29.63	-60.23	67.12	0.2073	-0.1118	243.8	15 476 35 577	
-1 540c	28	540	70.54	-43.14	-50.65	66.53	0.2004	-0.1046	229.5	15 479 36 581	
-1 544c	28	545	70.54	-43.14	-50.65	66.53	0.2004	-0.1046	229.5	15 479 36 581	
-1 549c	29	550	73.24	-48.02	-46.04	66.52	0.1983	-0.1014	223.7	16 481 36 582	
-1 555c	31	555	78.3	-53.77	-37.35	65.47	0.1966	-0.096	214.7	16 483 37 587	
2	410	32	560	80.64	-56.19	-32.07	64.7	0.196	-0.0931	209.7	16 484 38 591
380	770	95.41	0.0	0.0	0.0	0.2266	-0.078	0.0			

3-001630-L0

SF911-7N_7

voir des fichiers similaires: <http://130.149.60.45/~farbmetrik/SF91/SF91.HTM>
informations techniques: <http://www.ps.bam.de> ou <http://130.149.60.45/~farbmetrik>

TUB enregistrement: 20130201-SF91/SF91L0NA.TXT /.PS
application pour la mesure de sortie sur écran
TUB matériel: code=rh4ta

