



Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/SG75/SG75LONI.TXT> /PS
 Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>



Optimalfarben (o) RYGBCM von maximalem (m) C_{AB} für D65, Y_n=88,6

Code	Y _{88,6}	X _{88,6}	Y _{88,6}	Z _{88,6}	x	y	z	h _{xy}	l _t , λ _d	i _c , λ _c
R _m 565_770	54.73	36.33	0.05	0.0007	0.3987	0.0005	13.6	37	589	16 483
Y _m 495_770	68.29	83.1	5.43	0.0354	0.5298	0.0346	58.5	33	565	11 459
G _o 495_565	13.56	46.77	5.38	0.2063	0.7116	0.0819	105.5	25	529	-1 529c
C _m 380_565	29.46	52.25	96.41	0.1654	0.2933	0.5412	193.6	16	483	37 589
B _m 380_495	15.9	5.48	91.02	0.1414	0.0487	0.8097	238.5	11	459	33 565
M _o 575_475	70.63	41.81	91.07	0.347	0.2054	0.4474	285.5	-1	529c	25 529
N _o 380_770	0.08	0.08	0.09	0.3127	0.329	0.3582	0.0	18	490	-1 490c
W _o 380_770	84.19	88.59	96.46	0.3127	0.329	0.3582	0.0	23	516	-1 516c





Optimalfarben (o) RYGBCM von maximalem (m) C_{AB} für D65, Y_n=88,6

Code	Y _{88,6}	A _{88,6}	B _{88,6}	C _{AB}	a	b	h _{AB}	l _t , λ _d	i _c , λ _c	
R _m 565_770	36.33	20.2	15.8	25.64	1.5064	-0.0005	38.0	37	589	16 483
Y _m 495_770	83.1	-10.68	34.02	35.66	0.8218	-0.0261	107.4	33	565	13 429
G _o 495_565	46.77	-30.89	18.21	35.86	0.2899	-0.046	149.4	25	529	-1 529c
C _m 380_565	52.25	-20.2	-15.8	25.64	0.5638	-0.7379	218.0	16	483	37 589
B _m 380_495	5.48	10.68	-34.02	35.66	2.899	-6.6373	287.4	11	459	32 562
M _o 575_475	41.81	30.89	-18.21	35.86	1.6891	-0.8712	329.4	-1	516	22 513
N _o 380_770	0.08	0.0	0.0	0.01	0.9493	-0.435	83.2	38	590	16 483
W _o 380_770	88.59	0.0	0.0	0.01	0.9504	-0.4355	3.5	38	591	16 484





Optimalfarben (o) RYGBCM von maximalem (m) C_{AB} für D65, Y_n=88,6

Code	L [*] _{88,6}	a [*] _{88,6}	b [*] _{88,6}	C [*] _{ab}	a'	b'	h _{ab}	l _t , λ _d	i _c , λ _c	
R _m 565_770	66.77	59.19	114.35	128.76	0.2511	-0.0093	62.6	38	591	15 476
Y _m 495_770	93.06	-22.24	114.34	116.48	0.2052	-0.0337	101.0	32	563	14 470
G _o 495_565	74.05	-126.79	81.78	150.88	0.145	-0.0407	147.1	25	525	-1 525c
C _m 380_565	77.44	-64.31	-30.95	71.37	0.1809	-0.1027	205.6	16	481	-1 481c
B _m 380_495	28.1	85.48	-112.37	141.18	0.3122	-0.2134	307.2	12	460	28 543
M _o 575_475	70.75	78.99	-38.87	88.04	0.2608	-0.1085	333.7	-1	519c	23 519
N _o 380_770	0.8	0.0	-0.12	0.12	0.2153	-0.0861	270.0	14	474	34 571
W _o 380_770	95.41	0.0	0.0	0.0	0.2153	-0.0861	0.0	-1	571c	-1 472c



Optimalfarben (o) RYGBCM von maximalem (m) C_{AB} für D65, Y_n=88,6

CodeD65	L [*] _{88,6}	a [*] _{88,6}	b [*] _{88,6}	C [*] _{ab}	a'	b'	h _{ab}	l _t , λ _d	i _c , λ _c	
R _m 565_770	66.77	59.2	127.26	140.36	0.2511	-0.0093	65.0	37	589	15 475
Y _m 495_770	93.06	-22.24	114.38	116.52	0.2052	-0.0337	101.0	32	563	14 470
G _o 495_565	74.05	-126.83	81.82	150.93	0.145	-0.0407	147.1	25	525	-1 525c
C _m 380_565	77.44	-64.32	-30.95	71.38	0.181	-0.1027	205.6	16	481	-1 481c
B _m 380_495	28.1	85.54	-112.41	141.25	0.3122	-0.2135	307.2	12	460	28 543
M _o 575_475	70.75	79.0	-38.88	88.05	0.2609	-0.1085	333.7	-1	519c	23 519
N _o 380_770	0.8	-0.01	0.0	0.01	0.2154	-0.0861	158.2	23	515	-1 515c
W _o 380_770	95.41	0.0	0.0	0.0	0.2154	-0.0861	180.0	18	492	-1 492c



TUB-Registrierung: 20130201-SG75/SG75LONI.TXT /PS
 Anwendung für Messung von Display-Ausgabe

TUB-Material: Code=thdata