

Gerätefarben $RYGCBM_d$ von maximalem (m) C_{AB} für D65, $Y_w=100$

Code	X	Y	Z	x	y	z	h_{xy}	l^*_{dm}	λ^*_d	i_c	λ_c
R _d RECS	30.96	17.2	4.58	0.5869	0.3261	0.2068	359.4	41.607	17.486		
Y _d RECS	68.17	76.74	10.96	0.4373	0.4923	0.0703	52.6	33.568	13.467		
G _d RECS	11.05	23.64	9.47	0.2501	0.5325	0.2145	106.8	25.527	-1.527c		
C _d RECS	22.6	31.61	75.13	0.1747	0.2444	0.5808	211.5	15.478	35.578		
B _d RECS	7.38	5.26	24.41	0.1992	0.1419	0.6587	238.7	11.459	33.565		
M _d RECS	34.22	18.04	23.89	0.4493	0.2369	0.3137	326.0	-1.494c	18.494		
R _d RECS	31.41	17.44	6.62	0.5662	0.3143	0.1193	356.7	43.615	17.487		
Y _d RECS	63.12	68.2	10.32	0.4456	0.4815	0.0728	48.9	34.570	14.470		
G _d RECS	12.32	24.86	15.72	0.2338	0.4699	0.2971	119.4	22.510	-1.510c		
B _d RECS	11.61	12.05	39.53	0.1838	0.1906	0.6254	227.0	14.472	34.570		

Gerätefarben $RYGCBM_d$ von maximalem (m) C_{AB} für D65, $Y_w=100$









Code	Y	A	B	C_{AB}	h_{AB}	l^*_{dm}	λ^*_d	i_c	λ_c
R _d RECS	17.2	14.61	5.66	15.66	1.7994	-0.1064	21.1	41.607	17.486
Y _d RECS	76.74	-4.76	29.04	29.43	0.8883	-0.0571	99.3	33.568	14.472
G _d RECS	23.64	-11.42	6.5	19.14	0.4674	-0.1603	150.3	25.527	-1.531c
C _d RECS	5.26	2.38	-7.47	7.84	1.715	-0.9506	245.4	15.478	35.576
B _d RECS	18.04	17.07	-1.69	17.15	1.8965	-0.5296	354.3	-1.492c	18.492
R _d RECS	17.44	14.83	4.94	15.63	1.8009	-0.1518	18.4	42.614	17.486
Y _d RECS	68.2	-1.7	25.58	25.63	0.9254	-0.0605	93.8	34.570	14.474
G _d RECS	24.86	-11.31	4.54	12.18	0.4955	-0.2529	158.3	23.516	-1.516c
B _d RECS	12.05	0.16	-10.56	10.56	0.9642	-1.3122	270.9	14.471	33.567

Gerätefarben $RYGCBM_d$ von maximalem (m) C_{AB} für D65, $Y_w=100$

Code	L^*	a^*	b^*	C^*_{ab}	h_{ab}	l^*_{dm}	λ^*_d	i_c	λ_c
R _d RECS	48.53	65.92	41.65	77.97	0.2664	-0.0538	32.2	-1.480c	16.480
Y _d RECS	90.2	-10.19	90.05	90.62	0.2106	-0.0437	96.4	33.566	14.471
G _d RECS	55.74	-65.11	35.02	73.93	0.17	-0.0617	151.7	24.521	-1.521c
C _d RECS	63.03	-30.81	-40.47	50.86	0.1959	-0.1117	232.7	15.477	40.604
B _d RECS	27.49	26.0	-46.53	53.3	0.2452	-0.1396	299.2	13.465	30.550
M _d RECS	49.56	73.14	-7.61	73.54	0.2711	-0.0919	354.0	-1.499c	19.499
R _d RECS	48.82	66.31	33.06	74.1	0.2665	-0.0606	26.5	-1.481c	16.481
Y _d RECS	86.11	-3.88	84.83	84.92	0.2135	-0.0446	92.6	33.569	14.471
G _d RECS	56.95	-61.32	20.83	64.77	0.1733	-0.0718	161.2	22.512	-1.512c
B _d RECS	41.31	1.19	-43.87	43.89	0.2164	-0.1244	271.5	14.472	34.570

Gerätefarben $RYGCBM_d$ von maximalem (m) C_{AB} für D65, $Y_w=100$

CodeD65	L^*	a^*	b^*	C^*_{ab}	h_{ab}	l^*_{dm}	λ^*_d	i_c	λ_c
R _d RECS	48.53	65.93	41.68	78.01	0.2665	-0.0538	32.2	-1.480c	16.480
Y _d RECS	90.2	-10.19	90.07	90.65	0.2106	-0.0437	96.4	33.566	14.471
G _d RECS	55.74	-65.14	35.04	73.97	0.17	-0.0617	151.7	24.521	-1.521c
C _d RECS	63.03	-30.81	-40.48	50.87	0.1959	-0.1117	232.7	15.477	40.604
B _d RECS	27.49	26.02	-46.56	53.34	0.2453	-0.1396	299.2	13.465	30.550
M _d RECS	49.56	73.16	-7.61	73.56	0.2711	-0.0919	354.0	-1.499c	19.499
R _d RECS	48.82	66.33	33.08	74.12	0.2665	-0.0606	26.5	-1.481c	16.481
Y _d RECS	86.11	-3.88	84.86	84.95	0.2135	-0.0446	92.6	33.569	14.472
G _d RECS	56.95	-61.35	20.84	64.79	0.1733	-0.0718	161.2	22.512	-1.512c
B _d RECS	41.31	1.19	-43.88	43.9	0.2164	-0.1244	271.5	14.472	34.570



Stiche ähnliche Dateien: <http://130.149.60.45/~farbmetrik/SG82/SG82LONI.TXT> /PS; Start-Ausgabe
 Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20130201_SG82_SG82LONI.TXT /PS
 Anwendung für Messung von Display-Ausgabe
 TUB-Material: Code=thdtda