

CIE data for all optimal colours of maximum (m) C_{AB}, A00 and Y_w=100, Y_m=520_770







Table with 13 columns: i1, λ1; i2, λ2; Y100; A100; B100; CAB; a; b; hAB; id, λd; ic, λc; Code. Rows include various color codes like Cm, Gm, Ym, Rm, Mm, Bm.

CIE data for all optimal colours of maximum (m) C_{AB}, A00 and Y_w=100, Y_m=520_770

Table with 13 columns: i1, λ1; i2, λ2; L*100; a*100; b*100; C*ab; a'; b'; hab; id, λd; ic, λc; Code. Rows include various color codes like Cm, Gm, Ym, Rm, Mm, Bm.

TUB iscrizione: 20130201-SI66/SI66LONA.TXT /.PS la domanda per la misura di stampa di display

TUB materiale: code=rh4ta



CIE data for all optimal colours of maximum (m) C_{AB}, Q00 and Y_w=100, Y_m=520_770

Table with 13 columns: i1, λ1; i2, λ2; Y100; A100; B100; CAB; a; b; hAB; id, λd; ic, λc; Code. Rows include color patches like 1 405 32 562 57.89 -22.38 -19.16 29.46 0.5925 -0.8068 220.5 16 482 38 590 Cm.

CIE data for all optimal colours of maximum (m) C_{AB}, Q00 and Y_w=100, Y_m=520_770

Table with 13 columns: i1, λ1; i2, λ2; L*100; a*100; b*100; C*ab; a'; b'; hab; id, λd; ic, λc; Code. Rows include color patches like 1 405 32 562 80.68 -64.24 -32.07 71.8 0.184 -0.1058 206.5 16 482 38 590 Cm.

vedere dei file simili: http://130.149.60.45/~farbmetrik/SI66/SI66.HTM
informazioni tecniche: http://www.ps.bam.de o http://130.149.60.45/~farbmetrik

TUB iscrizione: 20130201-SI66/SI66LONA.TXT /.PS
la domanda per la misura di stampa di display

TUB materiale: code=rh4ta

CIE data for all optimal colours of maximum (m) C_{AB}, A00 and Y_{w,10}=100, Y_m=520_770

Table with columns: i1, λ1; i2, λ2; Y100; A100; B100; CAB; a; b; hAB; id, λd; ic, λc; Code. Rows include various color codes like Cm, Gm, Ym, Rm, Mm, Bm.



grafico TUB-SI66; maximum C_{AB}, Y_m=520_770

YABCABh & LabCa'b'h data for illuminant A00, Yw,10=100

CIE data for all optimal colours of maximum (m) C_{AB}, A00 and Y_{w,10}=100, Y_m=520_770

Table with columns: i1, λ1; i2, λ2; L*100; a*100; b*100; C*ab; a'; b'; hab; id, λd; ic, λc; Code. Rows include various color codes like Cm, Gm, Ym, Rm, Mm, Bm.



immettere: w/rgb/cmyk -> w/rgb/cmyk-

uscita: nessun cambiamento

TUB iscrizione: 20130201-SI66/SI66LONA.TXT /.PS

TUB materiale: code=rh4ta

vedere dei file simili: http://130.149.60.45/~farbmetrik/SI66/SI66.HTM

informazioni tecniche: http://www.ps.bam.de o http://130.149.60.45/~farbmetrik

vedere dei file simili: http://130.149.60.45/~farbmetrik/SI66/SI66.HTM
 informazioni tecniche: http://www.ps.bam.de o http://130.149.60.45/~farbmetrik

CIE data for all optimal colours of maximum (m) C_{AB}, P00 and Y_{w,10}=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code
1 405 31 558 48.73	-24.05 -16.11	28.95	0.6134	-0.6548	213.8	16 483 37 588	Cm				
7 435 33 565 55.15	-31.28 -5.36	31.73	0.5398	-0.4215	189.7	18 490 -1 490c					
10 450 33 567 55.96	-35.25 2.81	35.37	0.4769	-0.2739	175.4	19 498 -1 498c					
11 460 33 568 57.41	-36.56 5.89	37.04	0.47	-0.2216	170.8	20 502 -1 502c					
13 465 34 570 58.02	-38.07 10.75	39.56	0.4507	-0.1388	164.2	22 513 -1 513c					
14 470 34 572 59.65	-38.41 13.12	40.59	0.463	-0.1042	161.1	24 521 -1 521c					
15 475 35 575 62.11	-38.38 15.39	41.36	0.4889	-0.0763	158.1	25 529 -1 529c	Gm				
16 480 36 581 65.89	-37.54 17.77	41.53	0.5372	-0.0545	154.6	27 538 -1 538c					
17 485 38 591 73.23	-34.08 21.02	40.05	0.6415	-0.0371	148.3	29 548 -1 548c					
18 490 -1 490c 95.36	-9.53 28.86	30.4	1.007	-0.0215	108.2	33 568 11 457					
18 495 -1 494c 95.36	-9.53 28.86	30.4	1.007	-0.0215	108.2	33 568 11 457					
20 500 -1 500c 92.62	-6.55 28.9	29.64	1.0361	-0.0121	102.7	33 569 12 463					
22 510 -1 510c 88.31	-2.13 28.05	28.13	1.0828	-0.0066	94.3	34 571 13 468					
24 520 -1 520c 82.18	3.6 26.34	26.59	1.1509	-0.0036	82.1	34 574 14 473	Ym				
26 530 -1 530c 74.58	9.91 24.03	26.0	1.2399	-0.002	67.5	35 577 15 476					
28 540 -1 540c 66.0	16.0 21.32	26.66	1.3494	-0.0011	53.1	36 581 15 479					
28 545 -1 544c 66.0	16.0 21.32	26.66	1.3494	-0.0011	53.1	36 581 15 479					
29 550 -1 549c 61.49	18.76 19.88	27.33	1.412	-0.0008	46.6	36 582 16 481					
31 555 -1 555c 52.24	23.27 16.9	28.76	1.5525	-0.0005	35.9	37 587 16 483					
32 560 2 410 47.61	25.47 14.72	29.42	1.642	-0.0149	30.0	38 591 16 484					
31 558 1 405 51.26	24.05 16.11	28.95	1.5762	-0.0098	33.8	37 588 16 483	Rm				
33 565 7 435 44.84	31.28 5.36	31.73	1.8045	-0.2045	9.7	-1 490c 18 490					
33 567 10 450 44.03	35.25 -2.81	35.37	1.9076	-0.3881	355.4	-1 498c 19 498					
33 568 11 460 42.58	36.56 -5.89	37.04	1.9656	-0.4626	350.8	-1 502c 20 502					
34 570 13 465 41.97	38.07 -10.75	39.56	2.0142	-0.5806	344.2	-1 513c 22 513					
34 572 14 470 40.34	38.41 -13.12	40.59	2.0592	-0.6495	341.1	-1 521c 24 521					
35 575 15 475 37.88	38.38 -15.39	41.36	2.1204	-0.7307	338.1	-1 529c 25 529	Mm				
36 581 16 480 34.1	37.54 -17.77	41.53	2.2079	-0.8453	334.6	-1 538c 27 538					
38 591 17 485 26.76	34.08 -21.02	40.05	2.3807	-1.11	328.3	-1 548c 29 548					
-1 490c 18 490 4.63	9.53 -28.86	30.4	3.1661	-6.5585	288.2	11 457 33 568					
-1 494c 18 495 4.63	9.53 -28.86	30.4	3.1661	-6.5585	288.2	11 457 33 568					
-1 500c 20 500 7.37	6.55 -28.9	29.64	1.9964	-4.2445	282.7	12 463 33 569					
-1 510c 22 510 11.68	2.13 -28.05	28.13	1.2895	-2.7253	274.3	13 468 34 571					
-1 520c 24 520 17.81	-3.61 -26.34	26.59	0.9043	-1.8032	262.1	14 473 34 574	Bm				
-1 530c 26 530 25.41	-9.91 -24.03	26.0	0.7167	-1.2699	247.5	15 476 35 577					
-1 540c 28 540 33.99	-16.0 -21.32	26.66	0.6361	-0.9517	233.1	15 479 36 581					
-1 544c 28 545 33.99	-16.0 -21.32	26.66	0.6361	-0.9517	233.1	15 479 36 581					
-1 549c 29 550 38.5	-18.76 -19.88	27.33	0.6198	-0.8406	226.6	16 481 36 582					
-1 555c 31 555 47.75	-23.27 -16.9	28.76	0.6195	-0.6782	215.9	16 483 37 587					
2 410 32 560 52.38	-25.47 -14.72	29.42	0.6206	-0.6053	210.0	16 484 38 591					
380 770 100.0	0.0 0.0	0.01	1.1069	-0.3242	0.0						

4-001630-L0 SI660-7N_7

CIE data for all optimal colours of maximum (m) C_{AB}, P00 and Y_{w,10}=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405 31 558 75.29	-70.26 -41.55	81.63	0.1861	-0.0987	210.6	16 483 37 588	Cm				
7 435 33 565 79.13	-87.27 -14.99	88.55	0.1784	-0.0852	189.7	18 490 -1 490c					
10 450 33 567 79.59	-100.82 9.0	101.22	0.1711	-0.0738	174.8	19 498 -1 498c					
11 460 33 568 80.41	-103.2 19.8	105.08	0.1703	-0.0687	169.1	20 502 -1 502c					
13 465 34 570 80.76	-107.9 41.08	115.45	0.1679	-0.0588	159.1	22 513 -1 513c					
14 470 34 572 81.65	-106.11 53.01	118.61	0.1695	-0.0535	153.4	24 521 -1 521c					
15 475 35 575 82.98	-101.69 65.25	120.82	0.1726	-0.0482	147.3	25 529 -1 529c	Gm				
16 480 36 581 84.94	-93.15 77.93	121.46	0.1781	-0.0431	140.0	27 538 -1 538c					
17 485 38 591 88.56	-74.91 92.69	119.18	0.1889	-0.0379	128.9	29 548 -1 548c					
18 490 -1 490c 98.18	-15.28 117.1	118.1	0.2196	-0.0316	97.4	33 568 11 457					
18 495 -1 494c 98.18	-15.28 117.1	118.1	0.2196	-0.0316	97.4	33 568 11 457					
20 500 -1 500c 97.08	-10.62 129.61	130.05	0.2217	-0.0261	94.6	33 569 12 463					
22 510 -1 510c 95.29	-3.51 139.39	139.44	0.2249	-0.0213	91.4	34 571 13 468					
24 520 -1 520c 92.66	6.11 145.17	145.29	0.2296	-0.0175	87.5	34 574 14 473	Ym				
26 530 -1 530c 89.2	17.47 147.98	149.01	0.2353	-0.0143	83.2	35 577 15 476					
28 540 -1 540c 85.0	29.71 143.68	146.72	0.2421	-0.0117	78.3	36 581 15 479					
28 545 -1 544c 85.0	29.71 143.68	146.72	0.2421	-0.0117	78.3	36 581 15 479					
29 550 -1 549c 82.64	35.93 140.4	144.93	0.2458	-0.0108	75.6	36 582 16 481					
31 555 -1 555c 77.43	48.05 132.28	140.74	0.2537	-0.0095	70.0	37 587 16 483					
32 560 2 410 74.58	54.83 100.03	114.08	0.2584	-0.028	61.2	38 591 16 484					
31 558 1 405 76.84	50.01 109.94	120.79	0.2549	-0.0244	65.5	37 588 16 483	Rm				
33 565 7 435 72.79	67.69 21.79	71.11	0.2667	-0.0669	17.8	-1 490c 18 490					
33 567 10 450 72.26	75.65 -9.4	76.23	0.2717	-0.0829	352.9	-1 498c 19 498					
33 568 11 460 71.28	79.33 -18.92	81.56	0.2744	-0.0879	346.5	-1 502c 20 502					
34 570 13 465 70.85	82.65 -32.09	88.67	0.2767	-0.0948	338.7	-1 513c 22 513					
34 572 14 470 69.71	84.91 -38.5	93.23	0.2787	-0.0984	335.6	-1 521c 24 521					
35 575 15 475 67.93	87.5 -45.01	98.4	0.2814	-0.1023	332.7	-1 529c 25 529	Mm				
36 581 16 480 65.05	90.38 -52.57	104.56	0.2853	-0.1074	329.8	-1 538c 27 538					
38 591 17 485 58.76	93.68 -65.35	114.22	0.2925	-0.1177	325.1	-1 548c 29 548					
-1 490c 18 490 25.68	75.25 -123.82	144.89	0.3217	-0.2127	301.2	11 457 33 568					
-1 494c 18 495 25.68	75.25 -123.82	144.89	0.3217	-0.2127	301.2	11 457 33 568					
-1 500c 20 500 32.66	45.51 -113.75	122.52	0.2758	-0.184	291.8	12 463 33 569					
-1 510c 22 510 40.72	12.75 -101.0	101.8	0.2384	-0.1587	277.1	13 468 34 571					
-1 520c 24 520 49.28	-18.32 -86.83	88.74	0.2118	-0.1383	258.0	14 473 34 574	Bm				
-1 530c 26 530 57.48	-42.7 -72.99	84.57	0.196	-0.1231	239.6	15 476 35 577					
-1 540c 28 540 64.96	-58.82 -60.26	84.21	0.1884	-0.1118	225.6	15 479 36 581					
-1 544c 28 545 64.96	-58.82 -60.26	84.21	0.1884	-0.1118	225.6	15 479 36 581					
-1 549c 29 550 68.4	-63.93 -54.37	83.92	0.1868	-0.1072	220.3	16 481 36 582					
-1 555c 31 555 74.67	-68.72 -43.6	81.39	0.1867	-0.0998	212.3	16 483 37 587					
2 410 32 560 77.51	-70.69 -37.29	79.92	0.1868	-0.0961	207.8	16 484 38 591					
380 770 100.0	0.0 0.0	0.0	0.2266	-0.078	0.0						

4-001630-L0 SI661-7N_7

TUB iscrizione: 20130201-SI66/SI66LONA.TXT /.PS
 la domanda per la misura di stampa di display
 TUB materiale: code=rh4ta

