

CIE data for all optimal colours of maximum (m) C_{AB} , $D65$ and $Y_w=88,6$, $Y_m=495_770$												
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	
0	405	32 561	51.56	-20.15	-15.85	25.64	0.5596	-0.743	218.1	16 483	37 589	Cm
6	435	32 562	52.08	-23.73	-8.75	25.29	0.4948	-0.6036	200.2	17 486	42 610	
10	450	32 563	52.64	-29.71	4.36	30.03	0.3859	-0.3525	171.6	19 496	-1 496c	
12	460	33 565	53.43	-32.29	11.21	34.18	0.3461	-0.2256	160.8	21 505	-1 505c	
12	465	33 567	54.62	-32.47	11.73	34.52	0.356	-0.2207	160.1	21 506	-1 506c	
14	470	33 569	55.56	-33.79	17.12	37.88	0.3422	-0.1274	153.1	24 520	-1 520c	
15	475	34 573	57.84	-33.91	19.9	39.33	0.364	-0.0913	149.5	25 528	-1 528c	Gm
16	480	36 580	61.97	-33.2	23.07	40.43	0.4146	-0.0632	145.2	27 537	-1 537c	
17	485	39 595	69.76	-29.0	27.46	39.94	0.5347	-0.0418	136.5	29 548	-1 548c	
18	490	-1 490c	83.1	-10.68	34.02	35.66	0.8218	-0.0261	107.4	33 565	11 459	
19	495	-1 495c	81.77	-9.46	34.01	35.3	0.8346	-0.0195	105.5	33 566	12 462	Ym
20	500	-1 500c	80.1	-7.9	33.73	34.64	0.8518	-0.0144	103.1	33 567	12 464	
22	510	-1 510c	75.54	-3.68	32.32	32.53	0.9016	-0.0076	96.5	33 569	13 469	
23	520	-1 519c	72.63	-1.11	31.22	31.24	0.935	-0.0056	92.0	34 570	14 471	
25	530	-1 529c	65.59	4.57	28.36	28.73	1.0201	-0.0031	80.8	34 573	15 475	
27	540	-1 539c	57.49	10.25	24.94	26.97	1.1288	-0.0016	67.6	35 577	15 478	
28	545	-1 544c	53.27	12.85	23.13	26.46	1.1917	-0.0012	60.9	35 579	15 479	
29	550	-1 549c	48.96	15.22	21.27	26.16	1.2613	-0.0009	54.4	36 582	16 480	
30	555	-1 554c	44.65	17.27	19.41	25.98	1.3372	-0.0007	48.3	36 584	16 481	
32	560	-1 560c	36.33	20.2	15.8	25.64	1.5064	-0.0005	38.0	37 589	16 483	
32	561	0 405	48.43	20.15	15.85	25.64	1.3665	-0.1081	38.1	37 589	16 483	Rm
32	562	6 435	47.91	23.73	8.75	25.29	1.4458	-0.2528	20.2	42 610	17 486	
32	563	10 450	47.35	29.71	-4.36	30.03	1.5779	-0.5277	351.6	-1 496c	19 496	
33	565	12 460	46.56	32.29	-11.21	34.18	1.6439	-0.6765	340.8	-1 505c	21 505	
33	567	12 465	45.37	32.47	-11.73	34.52	1.666	-0.6942	340.1	-1 506c	21 506	
33	569	14 470	44.43	33.79	-17.12	37.88	1.711	-0.8209	333.1	-1 520c	24 520	
34	573	15 475	42.15	33.91	-19.9	39.33	1.755	-0.9078	329.5	-1 528c	25 528	Mm
36	580	16 480	38.02	33.2	-23.07	40.43	1.8237	-1.0424	325.2	-1 537c	27 537	
39	595	17 485	30.23	29.0	-27.46	39.94	1.9097	-1.3442	316.5	-1 548c	29 548	
-1	490c	18 490	16.89	10.68	-34.02	35.66	1.5831	-2.4491	287.4	11 459	33 565	
-1	495c	19 495	18.22	9.46	-34.01	35.3	1.4699	-2.3016	285.5	12 462	33 566	Bm
-1	500c	20 500	19.89	7.9	-33.73	34.64	1.3475	-2.1309	283.1	12 464	33 567	
-1	510c	22 510	24.45	3.68	-32.32	32.53	1.101	-1.7576	276.5	13 469	33 569	
-1	519c	23 520	27.36	1.11	-31.22	31.24	0.9912	-1.5765	272.0	14 471	34 570	
-1	529c	25 530	34.4	-4.57	-28.36	28.73	0.8175	-1.2601	260.8	15 475	34 573	
-1	539c	27 540	42.5	-10.25	-24.94	26.97	0.7091	-1.0225	247.6	15 478	35 577	
-1	544c	28 545	46.72	-12.85	-23.13	26.46	0.6753	-0.9306	240.9	15 479	35 579	
-1	549c	29 550	51.03	-15.22	-21.27	26.16	0.6522	-0.8524	234.4	16 480	36 582	
-1	554c	30 555	55.34	-17.27	-19.41	25.98	0.6383	-0.7863	228.3	16 481	36 584	
-1	560c	32 560	63.66	-20.2	-15.8	25.64	0.6331	-0.6837	218.0	16 483	37 589	
380	770	88.59	0.0	0.0	0.01	0.9504	-0.4355	0.0				

CIE data for all optimal colours of maximum (m) C_{AB} , $D50$ and $Y_w=88,6$, $Y_m=495_770$												
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	
1	405	32 564	51.21	-23.13	-12.01	26.07	0.5124	-0.5646	207.4	17 486	38 592	Cm
7	435	33 565	51.54	-26.37	-5.49	26.93	0.4526	-0.4365	191.7	18 490	46 634	
10	450	33 566	51.98	-29.72	2.1	29.79	0.3925	-0.2895	175.9	19 497	-1 497c	
12	460	33 567	52.53	-31.63	7.31	32.46	0.3621	-0.1907	166.9	21 506	-1 506c	
13	465	33 568	53.11	-32.33	9.67	33.74	0.3555	-0.1478	163.3	22 511	-1 511c	
14	470	34 570	54.07	-32.77	11.8	34.83	0.3581	-0.1117	160.1	23 519	-1 519c	
15	475	34 573	55.72	-32.85	13.81	35.64	0.3745	-0.0821	157.2	25 527	-1 527c	Gm
15	480	35 578	59.28	-32.7	14.98	35.97	0.4125	-0.0772	155.3	26 531	-1 531c	
17	485	37 587	64.0	-30.41	18.52	35.6	0.489	-0.0405	148.6	28 544	-1 544c	
18	490	44 620	77.97	-17.06	23.76	29.25	0.7454	-0.0251	125.6	32 561	-1 561c	
19	495	-1 495c	82.96	-6.37	25.91	26.68	0.8874	-0.0176	103.8	33 568	12 463	Ym
20	500	-1 500c	81.49	-4.96	25.81	26.29	0.9033	-0.0131	100.8	33 569	13 466	
22	510	-1 510c	77.37	-1.09	24.98	25.0	0.95	-0.0071	92.5	34 571	14 471	
23	520	-1 519c	74.67	1.31	24.24	24.28	0.9818	-0.0053	86.8	34 572	14 473	
25	530	-1 529c	68.03	6.77	22.25	23.26	1.0637	-0.0029	73.0	35 575	15 477	
27	540	-1 539c	60.24	12.35	19.78	23.32	1.1692	-0.0015	58.0	35 579	16 480	
28	545	-1 544c	56.11	14.94	18.45	23.74	1.2304	-0.0011	50.9	36 581	16 481	
29	550	-1 549c	51.87	17.32	17.07	24.32	1.2983	-0.0009	44.5	36 583	16 483	
30	555	-1 554c	47.59	19.42	15.67	24.96	1.3724	-0.0007	38.8	37 585	16 484	
32	560	-1 560c	39.22	22.48	12.92	25.93	1.5375	-0.0005	29.8	38 590	17 486	
32	564	1 405	48.78	23.13	12.01	26.07	1.4385	-0.0836	27.4	38 592	17 486	Rm
33	565	7 435	48.45	26.37	5.49	26.93	1.5084	-0.2166	11.7	46 634	18 490	
33	566	10 450	48.01	29.72	-2.1	29.79	1.5832	-0.3738	355.9	-1 497c	19 497	
33	567	12 460	47.46	31.63	-7.31	32.46	1.6306	-0.4841	346.9	-1 506c	21 506	
33	568	13 465	46.88	32.33	-9.67	33.74	1.6538	-0.5362	343.3	-1 511c	22 511	
34	570	14 470	45.92	32.77	-11.8	34.83	1.6779	-0.5869	340.1	-1 519c	23 519	
34	573	15 475	44.27	32.85	-13.81	35.64	1.7062	-0.6419	337.2	-1 527c	25 527	Mm
35	578	15 480	40.71	32.7	-14.98	35.97	1.7673	-0.6979	335.3	-1 531c	26 531	
37	587	17 485	35.99	30.41	-18.52	35.6	1.809	-0.8444	328.6	-1 544c	28 544	
44	620	18 490	22.02	17.06	-23.76	29.25	1.739	-1.4092	305.6	-1 561c	32 561	
-1	495c	19 495	17.03	6.37	-25.91	26.68	1.3382	-1.8515	283.8	12 463	33 568	Bm
-1	500c	20 500	18.5	4.96	-25.81	26.29	1.2322	-1.7248	280.8	13 466	33 569	
-1	510c	22 510	22.62	1.09	-24.98	25.0	1.0125	-1.434	272.5	14 471	34 571	
-1	519c	23 520	25.32	-1.31	-24.24	24.28	0.9122	-1.2875	266.8	14 473	34 572	
-1	529c	25 530	31.96	-6.77	-22.25	23.26	0.7523	-1.0261	253.0	15 477	35 575	
-1	539c	27 540	39.75	-12.35	-19.78	23.32	0.6535	-0.8276	238.0	16 480	35 579	
-1	544c	28 545	43.88	-14.94	-18.45	23.74	0.6237	-0.7504	230.9	16 481	36 581	
-1	549c	29 550	48.12	-17.32	-17.07	24.32	0.6041	-0.6846	224.5	16 483	36 583	
-1	554c	30 555	52.4	-19.42	-15.67	24.96	0.5934	-0.6289	218.8	16 484	37 585	
-1	560c	32 560	60.77	-22.48	-12.92	25.93	0.5942	-0.5425	209.8	17 486	38 590	
	380	770	88.59	0.0	0.0	0.01	0.9642	-0.3299	0.0			

CIE data for all optimal colours of maximum (m) C_{AB} , P40 and $Y_w=88,6$, $Y_m=495_770$															
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code				
0	405	33	568	50.12	-25.11	-9.79	26.95	0.5083	-0.4542	201.3	17	488	38	594	Cm
7	435	33	568	50.37	-27.92	-4.14	28.22	0.455	-0.3411	188.4	18	493	54	674	
10	450	33	569	50.74	-30.4	1.4	30.43	0.4101	-0.2309	177.3	19	499	-1	499c	
12	460	34	570	51.2	-31.78	5.21	32.21	0.3884	-0.1569	170.6	21	507	-1	507c	
13	465	34	571	51.65	-32.25	6.97	33.0	0.3848	-0.1237	167.7	22	512	-1	512c	
14	470	34	572	52.42	-32.54	8.56	33.65	0.3884	-0.0953	165.2	23	519	-1	519c	
14	475	34	574	54.15	-32.7	9.01	33.92	0.4054	-0.0923	164.5	24	522	-1	522c	Gm
15	480	35	578	56.54	-32.56	10.77	34.3	0.4332	-0.0682	161.6	26	531	-1	531c	
17	485	37	585	60.26	-31.09	13.33	33.83	0.4932	-0.0374	156.7	28	543	-1	543c	
17	490	40	600	70.01	-26.08	15.85	30.52	0.6366	-0.0323	148.7	30	554	-1	554c	
19	495	-1	495c	84.05	-4.59	20.45	20.95	0.9546	-0.0154	102.6	34	571	12	464	Ym
20	500	-1	500c	82.78	-3.32	20.45	20.72	0.9691	-0.0116	99.2	34	571	13	467	
21	510	-1	509c	81.16	-1.71	20.3	20.37	0.9882	-0.0086	94.8	34	572	13	469	
24	520	-1	520c	73.89	5.05	18.85	19.52	1.0777	-0.0035	74.9	35	575	15	476	
26	530	-1	530c	67.28	10.44	17.27	20.19	1.1646	-0.0019	58.8	35	578	16	480	
27	540	-1	539c	63.58	13.15	16.36	20.99	1.2161	-0.0014	51.1	36	580	16	481	
29	545	-1	545c	55.69	18.2	14.36	23.19	1.3362	-0.0008	38.2	36	584	16	484	
29	550	-1	549c	55.69	18.2	14.36	23.19	1.3362	-0.0008	38.2	36	584	16	484	
31	555	-1	555c	47.4	22.3	12.23	25.44	1.4798	-0.0005	28.7	37	588	17	486	
32	560	-1	560c	43.22	23.82	11.16	26.31	1.5605	-0.0005	25.1	38	591	17	487	
33	568	0	405	49.87	25.11	9.8	26.95	1.5129	-0.0622	21.3	38	594	17	488	Rm
33	568	7	435	49.62	27.92	4.14	28.22	1.5719	-0.1751	8.4	54	674	18	493	
33	569	10	450	49.25	30.4	-1.4	30.43	1.6265	-0.2873	357.3	-1	499c	19	499	
34	570	12	460	48.79	31.78	-5.21	32.21	1.6606	-0.3656	350.6	-1	507c	21	507	
34	571	13	465	48.34	32.25	-6.97	33.0	1.6765	-0.403	347.7	-1	512c	22	512	
34	572	14	470	47.57	32.54	-8.56	33.65	1.6934	-0.4388	345.2	-1	519c	23	519	
34	574	14	475	45.84	32.7	-9.01	33.92	1.7225	-0.4553	344.5	-1	522c	24	522	Mm
35	578	15	480	43.45	32.56	-10.77	34.3	1.7587	-0.5066	341.6	-1	531c	26	531	
37	585	17	485	39.73	31.09	-13.33	33.83	1.7918	-0.5943	336.7	-1	543c	28	543	
40	600	17	490	29.98	26.08	-15.85	30.52	1.8794	-0.7875	328.7	-1	554c	30	554	
-1	495c	19	495	15.94	4.59	-20.44	20.95	1.2972	-1.5411	282.6	12	464	34	571	Bm
-1	500c	20	500	17.21	3.32	-20.45	20.72	1.2023	-1.447	279.2	13	467	34	571	
-1	509c	21	510	18.83	1.71	-20.3	20.37	1.1002	-1.3368	274.8	13	469	34	572	
-1	520c	24	520	26.1	-5.05	-18.85	19.52	0.8155	-0.9812	254.9	15	476	35	575	
-1	530c	26	530	32.71	-10.44	-17.27	20.19	0.6899	-0.7867	238.8	16	480	35	578	
-1	539c	27	540	36.41	-13.15	-16.36	20.99	0.648	-0.7081	231.1	16	481	36	580	
-1	545c	29	545	44.3	-18.2	-14.36	23.19	0.5983	-0.5828	218.2	16	484	36	584	
-1	549c	29	550	44.3	-18.2	-14.36	23.19	0.5983	-0.5828	218.2	16	484	36	584	
-1	555c	31	555	52.59	-22.3	-12.23	25.44	0.5852	-0.4914	208.7	17	486	37	588	
-1	560c	32	560	56.77	-23.82	-11.16	26.31	0.5896	-0.4553	205.1	17	487	38	591	
	380	770	88.59	0.0	0.0	0.01	1.0093	-0.2587	0.0						

CIE data for all optimal colours of maximum (m) C _{AB} , A00 and Y _w =88,6, Y _m =495_770															
i ₁ , λ ₁	i ₂ , λ ₂	Y _{88.6}	A _{88.6}	B _{88.6}	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code				
1	405	34	574	48.43	-28.75	-5.6	29.29	0.5048	-0.2581	191.0	18	494	39	599	Cm
6	435	34	574	48.59	-29.61	-3.91	29.87	0.4891	-0.2227	187.5	19	496	42	611	
9	450	34	574	48.83	-30.82	-1.31	30.85	0.4673	-0.1692	182.4	20	501	-1	501c	
12	460	35	575	49.01	-31.95	1.74	32.0	0.4465	-0.1066	176.8	21	508	-1	508c	
13	465	35	575	49.25	-32.19	2.74	32.31	0.4448	-0.0866	175.1	22	512	-1	512c	
13	470	35	576	49.84	-32.22	2.82	32.34	0.452	-0.0856	174.9	22	513	-1	513c	
14	475	35	577	50.59	-32.36	3.77	32.58	0.4587	-0.0677	173.3	23	519	-1	519c	Gm
16	480	35	579	51.55	-32.2	5.2	32.62	0.4738	-0.0414	170.8	26	532	-1	532c	
17	485	36	582	53.64	-31.67	5.96	32.23	0.5079	-0.0312	169.3	28	540	-1	540c	
18	490	37	588	57.57	-30.3	6.88	31.08	0.572	-0.0226	167.1	29	548	-1	548c	
19	495	40	601	65.98	-25.09	8.37	26.46	0.718	-0.0153	161.5	31	559	-1	559c	Ym
20	500	-1	500c	84.75	-0.56	11.29	11.3	1.0918	-0.0091	92.8	35	576	13	469	
21	510	-1	509c	83.55	0.75	11.31	11.34	1.1074	-0.0069	86.2	35	576	14	472	
24	520	-1	520c	77.79	6.62	10.83	12.7	1.1836	-0.003	58.5	35	579	16	480	
26	530	-1	530c	72.2	11.66	10.15	15.46	1.26	-0.0017	41.0	36	582	16	484	
28	540	-1	540c	65.49	16.97	9.25	19.33	1.3576	-0.001	28.6	37	585	17	487	
28	545	-1	544c	65.49	16.97	9.25	19.33	1.3576	-0.001	28.6	37	585	17	487	
29	550	-1	549c	61.79	19.54	8.74	21.41	1.4148	-0.0007	24.1	37	586	17	489	
31	555	-1	555c	53.89	24.15	7.64	25.33	1.5466	-0.0005	17.5	38	590	18	491	
32	560	-1	560c	49.77	26.01	7.05	26.95	1.6212	-0.0004	15.1	38	593	18	492	
34	574	1	405	51.56	28.75	5.6	29.29	1.6561	-0.0335	11.0	39	599	18	494	Rm
34	574	6	435	51.4	29.61	3.91	29.87	1.6745	-0.0662	7.5	42	611	19	496	
34	574	9	450	51.16	30.82	1.31	30.85	1.7009	-0.1166	2.4	-1	501c	20	501	
35	575	12	460	50.98	31.95	-1.74	32.0	1.7252	-0.1766	356.8	-1	508c	21	508	
35	575	13	465	50.74	32.19	-2.74	32.31	1.733	-0.1963	355.1	-1	512c	22	512	
35	576	13	470	50.15	32.22	-2.82	32.34	1.7409	-0.1986	354.9	-1	513c	22	513	
35	577	14	475	49.4	32.36	-3.77	32.58	1.7536	-0.2187	353.3	-1	519c	23	519	Mm
35	579	16	480	48.44	32.2	-5.2	32.62	1.7633	-0.2497	350.8	-1	532c	26	532	
36	582	17	485	46.35	31.67	-5.96	32.23	1.7819	-0.2709	349.3	-1	540c	28	540	
37	588	18	490	42.42	30.3	-6.88	31.08	1.8128	-0.3046	347.1	-1	548c	29	548	
40	601	19	495	34.01	25.09	-8.37	26.46	1.8363	-0.3886	341.5	-1	559c	31	559	Bm
-1	500c	20	500	15.24	0.56	-11.29	11.3	1.1352	-0.8832	272.8	13	469	35	576	
-1	509c	21	510	16.44	-0.75	-11.31	11.34	1.0528	-0.8302	266.2	14	472	35	576	
-1	520c	24	520	22.2	-6.62	-10.83	12.7	0.8002	-0.6303	238.5	16	480	35	579	
-1	530c	26	530	27.79	-11.66	-10.15	15.46	0.6787	-0.5076	221.0	16	484	36	582	
-1	540c	28	540	34.5	-16.97	-9.25	19.33	0.6065	-0.4105	208.6	17	487	37	585	
-1	544c	28	545	34.5	-16.97	-9.25	19.33	0.6065	-0.4105	208.6	17	487	37	585	
-1	549c	29	550	38.2	-19.54	-8.74	21.41	0.5867	-0.3712	204.1	17	489	37	586	
-1	555c	31	555	46.1	-24.15	-7.64	25.33	0.5745	-0.308	197.5	18	491	38	590	
-1	560c	32	560	50.22	-26.01	-7.05	26.95	0.5804	-0.2828	195.1	18	492	38	593	
	380	770	88.58	0.0	0.0	0.01	1.0984	-0.1423	0.0						

CIE data for all optimal colours of maximum (m) C_{AB} , E_{00} and $Y_w=88.6$, $Y_m=495_770$													
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code		
1	405	32 564	50.87	-22.11	-14.47	26.43	0.5653	-0.6846	213.2	16 484	38 592	16 484	Cm
6	435	33 565	51.3	-25.82	-7.08	26.77	0.4967	-0.538	195.3	17 488	45 627	17 488	
10	450	33 566	51.78	-31.12	4.68	31.48	0.3988	-0.3094	171.4	19 498	-1 498c	19 498	
12	460	33 568	52.51	-33.26	10.46	34.86	0.3666	-0.2007	162.5	21 507	-1 507c	21 507	
13	465	33 569	53.28	-34.06	13.1	36.49	0.3606	-0.1541	158.9	22 514	-1 514c	22 514	
14	470	34 571	54.5	-34.5	15.52	37.83	0.367	-0.1152	155.7	24 522	-1 522c	24 522	
14	475	35 575	57.16	-34.67	16.58	38.43	0.3934	-0.1099	154.4	25 525	-1 525c	25 525	Gm
16	480	36 581	60.43	-33.93	20.61	39.7	0.4385	-0.0589	148.7	27 538	-1 538c	27 538	
17	485	39 595	67.95	-30.26	24.5	38.94	0.5546	-0.0393	140.9	29 549	-1 549c	29 549	
18	490	-1 490c	83.75	-9.91	31.5	33.02	0.8815	-0.0238	107.4	33 568	11 459	33 568	
19	495	-1 495c	82.54	-8.75	31.54	32.73	0.8939	-0.0179	105.5	33 568	12 461	33 568	Ym
19	500	-1 499c	82.54	-8.75	31.54	32.73	0.8939	-0.0179	105.5	33 568	12 461	33 568	
22	510	-1 510c	76.84	-3.16	30.19	30.35	0.9587	-0.0071	95.9	34 571	13 469	34 571	
24	520	-1 520c	70.99	2.12	28.12	28.2	1.0299	-0.0038	85.6	34 574	14 473	34 574	
26	530	-1 530c	63.88	7.86	25.41	26.6	1.123	-0.0021	72.8	35 577	15 477	35 577	
28	540	-1 540c	56.0	13.32	22.33	26.0	1.2379	-0.0011	59.1	36 581	15 479	36 581	
29	545	-1 545c	51.9	15.77	20.71	26.03	1.3039	-0.0009	52.7	36 583	16 480	36 583	
29	550	-1 549c	51.9	15.77	20.71	26.03	1.3039	-0.0009	52.7	36 583	16 480	36 583	
30	555	-1 554c	47.77	17.95	19.07	26.19	1.3757	-0.0007	46.7	37 585	16 482	37 585	
32	560	-1 560c	39.54	21.24	15.79	26.47	1.5372	-0.0005	36.6	38 590	16 483	38 590	
32	564	1 405	49.12	22.11	14.47	26.42	1.45	-0.1052	33.2	38 592	16 484	38 592	Rm
33	565	6 435	48.69	25.82	7.08	26.77	1.5303	-0.2545	15.3	45 627	17 488	45 627	
33	566	10 450	48.21	31.12	-4.68	31.48	1.6455	-0.4972	351.4	-1 498c	19 498	19 498	
33	568	12 460	47.48	33.26	-10.46	34.86	1.7005	-0.6203	342.5	-1 507c	21 507	21 507	
33	569	13 465	46.71	34.06	-13.1	36.49	1.7291	-0.6804	338.9	-1 514c	22 514	22 514	
34	571	14 470	45.49	34.5	-15.52	37.83	1.7583	-0.7411	335.7	-1 522c	24 522	24 522	
35	575	14 475	42.83	34.67	-16.58	38.43	1.8096	-0.7872	334.4	-1 525c	25 525	25 525	Mm
36	581	16 480	39.56	33.93	-20.61	39.7	1.8575	-0.9209	328.7	-1 538c	27 538	27 538	
39	595	17 485	32.04	30.26	-24.5	38.94	1.9444	-1.1648	320.9	-1 549c	29 549	29 549	
-1	490c	18 490	16.24	9.91	-31.5	33.02	1.6105	-2.3392	287.4	11 459	33 568	33 568	
-1	495c	19 495	17.45	8.75	-31.54	32.73	1.5016	-2.2074	285.5	12 461	33 568	33 568	Bm
-1	499c	19 500	17.45	8.75	-31.54	32.73	1.5016	-2.2074	285.5	12 461	33 568	33 568	
-1	510c	22 510	23.15	3.16	-30.19	30.35	1.1369	-1.7039	275.9	13 469	34 571	34 571	
-1	520c	24 520	29.0	-2.12	-28.12	28.2	0.9266	-1.3696	265.6	14 473	34 574	34 574	
-1	530c	26 530	36.11	-7.86	-25.41	26.6	0.7823	-1.1038	252.8	15 477	35 577	35 577	
-1	540c	28 540	43.99	-13.32	-22.33	26.0	0.6971	-0.9076	239.1	15 479	36 581	36 581	
-1	545c	29 545	48.09	-15.77	-20.71	26.03	0.6719	-0.8307	232.7	16 480	36 583	36 583	
-1	549c	29 550	48.09	-15.77	-20.71	26.03	0.6719	-0.8307	232.7	16 480	36 583	36 583	
-1	554c	30 555	52.22	-17.95	-19.07	26.19	0.6562	-0.7652	226.7	16 482	37 585	37 585	
-1	560c	32 560	60.45	-21.24	-15.79	26.47	0.6485	-0.6613	216.6	16 483	38 590	38 590	
	380	770	88.59	0.0	0.0	0.01	1.0	-0.4	0.0				

CIE data for all optimal colours of maximum (m) C_{AB} , C_{00} and $Y_w=88.6$, $Y_m=495_770$												
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	
1	405	32	562	51.1	-19.54	-17.3	26.1	0.5982	-0.8115	221.5	16 482 37 589	Cm
6	435	32	563	51.69	-23.59	-9.26	25.35	0.5242	-0.6521	201.4	17 486 42 612	
10	450	32	564	52.35	-30.25	5.27	30.71	0.4027	-0.3721	170.1	19 496 -1 496c	
11	460	33	566	53.63	-31.86	9.38	33.22	0.3865	-0.2979	163.5	20 501 -1 501c	
13	465	33	568	54.22	-33.89	15.83	37.41	0.3556	-0.1808	154.9	22 513 -1 513c	
14	470	34	570	55.77	-34.55	18.96	39.42	0.3611	-0.1328	151.2	24 522 -1 522c	
15	475	35	575	58.4	-34.72	22.12	41.17	0.3861	-0.0941	147.4	26 530 -1 530c	Gm
16	480	36	582	62.97	-33.68	25.74	42.4	0.4457	-0.064	142.6	28 540 -1 540c	
16	485	40	602	73.14	-28.46	30.55	41.75	0.5915	-0.0552	132.9	30 551 -1 551c	
18	490	-1	490c	82.68	-11.63	36.96	38.75	0.8399	-0.0257	107.4	33 566 11 459	
19	495	-1	495c	81.3	-10.32	36.91	38.33	0.8536	-0.0188	105.6	33 567 12 462	Ym
19	500	-1	499c	81.3	-10.32	36.91	38.33	0.8536	-0.0188	105.6	33 567 12 462	
21	510	-1	509c	77.66	-6.8	35.96	36.59	0.893	-0.0098	100.7	33 568 13 466	
24	520	-1	520c	69.63	0.45	32.65	32.65	0.9872	-0.0039	89.2	34 572 14 472	
26	530	-1	530c	62.62	5.96	29.47	30.07	1.076	-0.0021	78.5	35 575 15 475	
28	540	-1	540c	54.54	11.4	25.72	28.14	1.1898	-0.0012	66.0	35 579 15 478	
28	545	-1	544c	54.54	11.4	25.72	28.14	1.1898	-0.0012	66.0	35 579 15 478	
29	550	-1	549c	50.25	13.89	23.71	27.48	1.2572	-0.0009	59.6	36 581 15 479	
31	555	-1	555c	41.49	17.97	19.59	26.59	1.4138	-0.0006	47.4	37 586 16 481	
31	560	-1	559c	41.49	17.97	19.59	26.59	1.4138	-0.0006	47.4	37 586 16 481	
32	562	1	405	48.89	19.54	17.3	26.1	1.3804	-0.1189	41.5	37 589 16 482	Rm
32	563	6	435	48.3	23.59	9.26	25.35	1.4692	-0.281	21.4	42 612 17 486	
32	564	10	450	47.64	30.25	-5.27	30.71	1.6157	-0.5836	350.1	-1 496c 19 496	
33	566	11	460	46.36	31.86	-9.38	33.22	1.668	-0.6752	343.5	-1 501c 20 501	
33	568	13	465	45.77	33.89	-15.83	37.41	1.7213	-0.8189	334.9	-1 513c 22 513	
34	570	14	470	44.22	34.55	-18.96	39.42	1.7621	-0.9018	331.2	-1 522c 24 522	
35	575	15	475	41.59	34.72	-22.12	41.17	1.8156	-1.0048	327.4	-1 530c 26 530	Mm
36	582	16	480	37.02	33.68	-25.74	42.4	1.8905	-1.1682	322.6	-1 540c 28 540	
40	602	16	485	26.85	28.46	-30.55	41.75	2.0405	-1.6104	312.9	-1 551c 30 551	
-1	490c	18	490	17.31	11.63	-36.96	38.75	1.6528	-2.6079	287.4	11 459 33 566	
-1	495c	19	495	18.69	10.32	-36.91	38.33	1.5331	-2.4471	285.6	12 462 33 567	Bm
-1	499c	19	500	18.69	10.32	-36.91	38.33	1.5331	-2.4471	285.6	12 462 33 567	
-1	509c	21	510	22.33	6.8	-35.96	36.59	1.2854	-2.083	280.7	13 466 33 568	
-1	520c	24	520	30.36	-0.45	-32.65	32.65	0.9657	-1.5483	269.2	14 472 34 572	
-1	530c	26	530	37.37	-5.96	-29.47	30.07	0.821	-1.2615	258.5	15 475 35 575	
-1	540c	28	540	45.45	-11.4	-25.72	28.14	0.7297	-1.0389	246.0	15 478 35 579	
-1	544c	28	545	45.45	-11.4	-25.72	28.14	0.7297	-1.0389	246.0	15 478 35 579	
-1	549c	29	550	49.74	-13.89	-23.71	27.48	0.7014	-0.9496	239.6	15 479 36 581	
-1	555c	31	555	58.5	-17.97	-19.59	26.59	0.6734	-0.8079	227.4	16 481 37 586	
-1	559c	31	560	58.5	-17.97	-19.59	26.59	0.6734	-0.8079	227.4	16 481 37 586	
380	770	88.59	0.0	0.0	0.01	0.9807	-0.4729	0.0				

CIE data for all optimal colours of maximum (m) C_{AB} , P00 and $Y_w=88,6$, $Y_m=495_770$												
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	
1	405	33 567	50.33	-24.12	-11.96	26.92	0.5413	-0.5619	206.3	17 486	38 594	Cm
7	435	33 567	50.61	-27.97	-4.18	28.28	0.4679	-0.407	188.5	18 491	-1 491c	
10	450	33 568	51.06	-31.16	2.97	31.31	0.4103	-0.2659	174.5	19 499	-1 499c	
12	460	34 570	51.65	-32.91	7.66	33.79	0.3834	-0.1758	166.8	21 507	-1 507c	
13	465	34 571	52.22	-33.48	9.79	34.88	0.3796	-0.1366	163.6	22 513	-1 513c	
13	470	34 572	53.56	-33.61	10.22	35.13	0.3931	-0.1332	163.0	23 515	-1 515c	
15	475	35 575	54.9	-33.94	13.6	36.57	0.4024	-0.0765	158.1	25 529	-1 529c	Gm
16	480	36 580	57.9	-33.49	15.58	36.94	0.4422	-0.055	155.0	27 537	-1 537c	
17	485	37 589	63.52	-31.34	18.18	36.23	0.5273	-0.0379	149.8	29 547	-1 547c	
18	490	45 625	78.78	-16.44	23.72	28.87	0.8119	-0.023	124.7	32 564	-1 564c	
18	495	-1 494c	84.48	-7.59	25.57	26.67	0.9308	-0.0215	106.5	34 570	12 460	Ym
20	500	-1 500c	82.05	-5.16	25.6	26.12	0.9577	-0.0121	101.3	34 571	13 465	
22	510	-1 510c	78.23	-1.35	24.85	24.88	1.0033	-0.0066	93.1	34 573	14 470	
24	520	-1 520c	72.8	3.67	23.34	23.62	1.0711	-0.0036	81.0	35 575	14 474	
25	530	-1 529c	69.57	6.43	22.37	23.27	1.1131	-0.0027	73.9	35 577	15 476	
28	540	-1 540c	58.47	14.66	18.89	23.91	1.2713	-0.0011	52.1	36 582	16 481	
28	545	-1 544c	58.47	14.66	18.89	23.91	1.2713	-0.0011	52.1	36 582	16 481	
30	550	-1 550c	50.39	19.36	16.3	25.31	1.4049	-0.0007	40.0	37 586	16 483	
30	555	-1 554c	50.39	19.36	16.3	25.31	1.4049	-0.0007	40.0	37 586	16 483	
32	560	-1 560c	42.17	22.82	13.65	26.59	1.5618	-0.0005	30.8	38 591	17 485	
33	567	1 405	49.66	24.12	11.96	26.92	1.5064	-0.0833	26.3	38 594	17 486	Rm
33	567	7 435	49.38	27.97	4.18	28.28	1.5871	-0.2394	8.5	-1 491c	18 491	
33	568	10 450	48.93	31.16	-2.97	31.31	1.6576	-0.385	354.5	-1 499c	19 499	
34	570	12 460	48.34	32.91	-7.66	33.79	1.7014	-0.4827	346.8	-1 507c	21 507	
34	571	13 465	47.77	33.48	-9.79	34.88	1.7215	-0.5293	343.6	-1 513c	22 513	
34	572	13 470	46.43	33.61	-10.22	35.13	1.7445	-0.5445	343.0	-1 515c	23 515	
35	575	15 475	45.09	33.94	-13.6	36.57	1.7735	-0.6258	338.1	-1 529c	25 529	Mm
36	580	16 480	42.09	33.49	-15.58	36.94	1.8161	-0.6945	335.0	-1 537c	27 537	
37	589	17 485	36.47	31.34	-18.18	36.23	1.8799	-0.8229	329.8	-1 547c	29 547	
45	625	18 490	21.21	16.44	-23.72	28.87	1.796	-1.4429	304.7	-1 564c	32 564	
-1	494c	18 495	15.51	7.59	-25.57	26.67	1.5099	-1.9729	286.5	12 460	34 570	Bm
-1	500c	20 500	17.94	5.16	-25.6	26.12	1.3082	-1.7514	281.3	13 465	34 571	
-1	510c	22 510	21.76	1.35	-24.85	24.88	1.083	-1.4663	273.1	14 470	34 573	
-1	520c	24 520	27.19	-3.67	-23.34	23.62	0.8855	-1.1826	261.0	14 474	35 575	
-1	529c	25 530	30.42	-6.43	-22.37	23.27	0.8091	-1.0595	253.9	15 476	35 577	
-1	540c	28 540	41.52	-14.66	-18.89	23.91	0.6675	-0.7792	232.1	16 481	36 582	
-1	544c	28 545	41.52	-14.66	-18.89	23.91	0.6675	-0.7792	232.1	16 481	36 582	
-1	550c	30 550	49.6	-19.36	-16.3	25.31	0.6302	-0.6529	220.0	16 483	37 586	
-1	554c	30 555	49.6	-19.36	-16.3	25.31	0.6302	-0.6529	220.0	16 483	37 586	
-1	560c	32 560	57.82	-22.82	-13.65	26.59	0.6259	-0.5603	210.8	17 485	38 591	
380	770	88.59	0.0	0.0	0.01	1.0206	-0.3242	0.0				

CIE data for all optimal colours of maximum (m) C_{AB} , $Q00$ and $Y_w=88,6$, $Y_m=495_770$												
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	
1	405	32 562	51.28	-19.83	-16.97	26.1	0.5925	-0.8068	220.5	16 482 38 590	Cm	
7	435	32 562	51.72	-26.08	-4.41	26.45	0.475	-0.5611	189.5	17 488 -1 488c		
10	450	32 564	52.44	-31.0	6.48	31.67	0.3881	-0.3521	168.1	19 497 -1 497c		
11	460	33 566	53.67	-32.55	10.42	34.18	0.3728	-0.2816	162.2	20 502 -1 502c		
12	465	33 568	54.66	-33.78	14.0	36.57	0.3611	-0.2196	157.4	21 508 -1 508c		
14	470	34 570	55.78	-35.1	19.49	40.15	0.3499	-0.1264	150.9	24 522 -1 522c		
15	475	35 575	58.38	-35.27	22.49	41.83	0.3751	-0.0905	147.4	26 530 -1 530c	Gm	
16	480	36 582	62.99	-34.26	26.03	43.02	0.4354	-0.0625	142.7	27 539 -1 539c		
17	485	40 602	72.6	-28.13	31.61	42.31	0.5918	-0.0404	131.6	30 552 -1 552c		
17	490	-1 489c	84.1	-13.23	37.08	39.37	0.8219	-0.0349	109.6	33 565 11 455		
18	495	-1 494c	83.02	-12.27	37.32	39.29	0.8314	-0.0262	108.2	33 565 11 458	Ym	
20	500	-1 500c	80.01	-9.39	36.91	38.09	0.8619	-0.0144	104.2	33 567 12 463		
21	510	-1 509c	77.94	-7.4	36.26	37.01	0.8843	-0.0105	101.5	33 568 13 465		
23	520	-1 519c	72.51	-2.36	34.09	34.17	0.9466	-0.0056	93.9	34 571 14 470		
26	530	-1 530c	61.69	6.39	29.21	29.9	1.0829	-0.0022	77.6	35 576 15 475		
27	540	-1 539c	57.66	9.22	27.34	28.85	1.1393	-0.0016	71.3	35 578 15 477		
28	545	-1 544c	53.52	11.88	25.4	28.04	1.2014	-0.0012	64.9	36 580 15 478		
29	550	-1 549c	49.33	14.3	23.43	27.45	1.2693	-0.0009	58.5	36 582 15 479		
30	555	-1 554c	45.14	16.42	21.44	27.01	1.3431	-0.0007	52.5	36 584 16 480		
31	560	-1 559c	40.99	18.19	19.47	26.65	1.4231	-0.0006	46.9	37 587 16 481		
32	562	1 405	48.71	19.83	16.97	26.1	1.3864	-0.1273	40.5	38 590 16 482	Rm	
32	562	7 435	48.27	26.08	4.41	26.45	1.5196	-0.3844	9.5	-1 488c 17 488		
32	564	10 450	47.55	31.0	-6.48	31.67	1.6311	-0.6121	348.1	-1 497c 19 497		
33	566	11 460	46.32	32.55	-10.42	34.18	1.682	-0.7007	342.2	-1 502c 20 502		
33	568	12 465	45.33	33.78	-14.0	36.57	1.7246	-0.7846	337.4	-1 508c 21 508		
34	570	14 470	44.21	35.1	-19.49	40.15	1.7734	-0.9166	330.9	-1 522c 24 522		
35	575	15 475	41.61	35.27	-22.49	41.83	1.827	-1.0163	327.4	-1 530c 26 530	Mm	
36	582	16 480	37.0	34.26	-26.03	43.02	1.9052	-1.1793	322.7	-1 539c 27 539		
40	602	17 485	27.39	28.13	-31.61	42.31	2.0061	-1.6296	311.6	-1 552c 30 552		
-1	489c	17 490	15.89	13.23	-37.08	39.37	1.8117	-2.8086	289.6	11 455 33 565		
-1	494c	18 495	16.97	12.27	-37.32	39.29	1.7025	-2.6742	288.2	11 458 33 565	Bm	
-1	500c	20 500	19.98	9.39	-36.91	38.09	1.4493	-2.3227	284.2	12 463 33 567		
-1	509c	21 510	22.05	7.4	-36.26	37.01	1.3149	-2.1206	281.5	13 465 33 568		
-1	519c	23 520	27.48	2.36	-34.09	34.17	1.0654	-1.7161	273.9	14 470 34 571		
-1	530c	26 530	38.3	-6.39	-29.21	29.9	0.8124	-1.2384	257.6	15 475 35 576		
-1	539c	27 540	42.33	-9.22	-27.34	28.85	0.7613	-1.1216	251.3	15 477 35 578		
-1	544c	28 545	46.47	-11.88	-25.4	28.04	0.7235	-1.0224	244.9	15 478 36 580		
-1	549c	29 550	50.66	-14.3	-23.43	27.45	0.6969	-0.9383	238.5	15 479 36 582		
-1	554c	30 555	54.85	-16.42	-21.44	27.01	0.6798	-0.8668	232.5	16 480 36 584		
-1	559c	31 560	59.0	-18.19	-19.47	26.65	0.671	-0.8059	226.9	16 481 37 587		
	380	770	88.59	0.0	0.0	0.01	0.9793	-0.4758	0.0			

CIE data for all optimal colours of maximum (m) C_{AB} , D65 and $Y_{w,10}=88.6$, $Y_m=495_770$												
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	
-1 549c	29 549	41.2	-15.57	-20.59	25.82	0.6646	-0.9354	232.9	15 479	36 581	Cm	
7 435	32 560	50.19	-25.24	-6.73	26.13	0.5396	-0.5698	194.9	17 487	-1 487c		
10 450	32 562	51.12	-30.36	3.7	30.59	0.4486	-0.363	173.0	19 495	-1 495c		
11 460	32 564	52.82	-32.13	7.81	33.07	0.4343	-0.2876	166.3	20 500	-1 500c		
12 465	33 566	53.89	-33.37	11.41	35.27	0.4233	-0.2237	161.1	21 506	-1 506c		
13 470	33 569	55.95	-34.34	15.04	37.49	0.4288	-0.1667	156.3	22 514	-1 514c		
15 475	34 574	58.52	-34.57	20.2	40.04	0.4518	-0.0903	149.6	25 529	-1 529c	Gm	
16 480	36 582	63.08	-33.3	23.55	40.79	0.5146	-0.0621	144.7	27 538	-1 538c		
16 485	40 601	73.27	-27.78	27.99	39.43	0.6635	-0.0535	134.7	0 400	1 407		
18 490	-1 490c	83.1	-11.75	34.02	35.99	0.9011	-0.0261	109.0	32 563	11 457		
18 495	-1 494c	83.1	-11.75	34.02	35.99	0.9011	-0.0261	109.0	32 563	11 457	Ym	
20 500	-1 500c	80.1	-8.69	33.73	34.83	0.934	-0.0144	104.4	33 565	12 462		
22 510	-1 510c	75.54	-4.3	32.32	32.61	0.9855	-0.0076	97.5	33 567	13 467		
24 520	-1 520c	69.3	1.13	29.89	29.91	1.059	-0.0042	87.8	34 570	14 471		
26 530	-1 530c	61.61	7.02	26.69	27.6	1.1566	-0.0022	75.2	34 574	15 475		
27 540	-1 539c	57.49	9.81	24.94	26.81	1.2134	-0.0016	68.5	35 576	15 476		
28 545	-1 544c	53.27	12.41	23.13	26.25	1.2757	-0.0012	61.7	35 578	15 478		
0 400	1 407	0.0	0.25	-0.25	0.36	67.5944	-66.9128	15.0	1 406	0 401		
30 555	3 415	44.67	17.93	18.14	25.51	1.4441	-0.0294	45.3	36 584	16 481		
31 560	5 428	40.52	22.1	12.27	25.28	1.5879	-0.1326	29.0	39 596	16 484		
29 549	-1 549c	58.79	15.57	20.59	25.82	1.3074	-0.0852	52.9	36 581	15 479	Rm	
32 560	7 435	49.8	25.24	6.73	26.13	1.5495	-0.3002	14.9	-1 487c	17 487		
32 562	10 450	48.87	30.36	-3.7	30.59	1.6639	-0.5114	353.0	-1 495c	19 495		
32 564	11 460	47.17	32.13	-7.81	33.07	1.7238	-0.6012	346.3	-1 500c	20 500		
33 566	12 465	46.1	33.37	-11.41	35.27	1.7666	-0.6832	341.1	-1 506c	21 506		
33 569	13 470	44.04	34.34	-15.04	37.49	1.8224	-0.777	336.3	-1 514c	22 514		
34 574	15 475	41.47	34.57	-20.2	40.04	1.876	-0.9226	329.6	-1 529c	25 529	Mm	
36 582	16 480	36.91	33.3	-23.55	40.79	1.9446	-1.0736	324.7	-1 538c	27 538		
40 601	16 485	26.72	27.78	-27.99	39.43	2.0823	-1.4831	314.7	1 407	0 400		
-1 490c	18 490	16.89	11.75	-34.02	35.99	1.7386	-2.4491	289.0	11 457	32 563		
-1 494c	18 495	16.89	11.75	-34.02	35.99	1.7386	-2.4491	289.0	11 457	32 563	Bm	
-1 500c	20 500	19.89	8.69	-33.73	34.83	1.4797	-2.1309	284.4	12 462	33 565		
-1 510c	22 510	24.45	4.3	-32.32	32.61	1.2189	-1.7576	277.5	13 467	33 567		
-1 520c	24 520	30.69	-1.13	-29.89	29.91	1.0056	-1.4096	267.8	14 471	34 570		
-1 530c	26 530	38.38	-7.02	-26.69	27.6	0.8596	-1.1312	255.2	15 475	34 574		
-1 539c	27 540	42.5	-9.81	-24.94	26.81	0.8115	-1.0225	248.5	15 476	35 576		
-1 544c	28 545	46.72	-12.41	-23.13	26.25	0.7769	-0.9306	241.7	15 478	35 578		
1 407	0 400	99.99	-0.26	0.26	0.37	1.04	-0.4329	135.0	0 401	1 406		
3 415	30 555	55.32	-17.93	-18.14	25.51	0.7184	-0.7634	225.3	16 481	36 584		
5 428	31 560	59.47	-22.1	-12.27	25.28	0.671	-0.6419	209.0	16 484	39 596		
380	770	88.59	0.0	0.0	0.01	1.0426	-0.4355	0.0				

CIE data for all optimal colours of maximum (m) C_{AB} , D50 and $Y_{w,10}=88,6$, $Y_m=495_770$													
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code		
1	405	31 555	43.51	-20.36	-14.54	25.03	0.5817	-0.6643	215.5	16 483	37 586	Cm	
7	435	32 563	49.66	-26.1	-6.1	26.8	0.5243	-0.4529	193.1	17 489	45 627		
10	450	32 564	50.37	-29.9	1.57	29.94	0.4562	-0.2987	176.9	19 497	-1 497c		
12	460	33 566	51.38	-31.95	6.93	32.69	0.428	-0.1949	167.7	21 505	-1 505c		
13	465	33 567	52.13	-32.61	9.34	33.92	0.4241	-0.1506	164.0	22 511	-1 511c		
14	470	33 569	53.58	-33.07	11.63	35.06	0.4326	-0.1127	160.6	23 518	-1 518c		
15	475	34 573	55.82	-33.0	13.84	35.78	0.4586	-0.0819	157.2	25 527	-1 527c	Gm	
16	480	35 579	59.25	-32.27	16.11	36.07	0.5051	-0.058	153.4	27 535	-1 535c		
17	485	37 589	65.2	-29.5	18.91	35.04	0.5973	-0.0398	147.3	29 545	-1 545c		
18	490	-1 490c	84.13	-8.1	25.79	27.04	0.9535	-0.0233	107.4	33 566	11 459		
19	495	-1 495c	82.96	-6.9	25.91	26.81	0.9666	-0.0176	104.9	33 566	12 462	Ym	
19	500	-1 499c	82.96	-6.9	25.91	26.81	0.9666	-0.0176	104.9	33 566	12 462		
22	510	-1 510c	77.37	-1.39	24.98	25.01	1.0318	-0.0071	93.1	33 569	13 469		
24	520	-1 520c	71.55	3.71	23.32	23.62	1.1017	-0.0039	80.9	34 572	14 473		
25	530	-1 529c	68.03	6.54	22.25	23.19	1.1459	-0.0029	73.6	34 574	15 475		
27	540	-1 539c	60.24	12.11	19.78	23.19	1.2509	-0.0015	58.5	35 577	15 479		
28	545	-1 544c	56.11	14.67	18.45	23.57	1.3114	-0.0011	51.4	35 579	16 480		
29	550	-1 549c	51.87	17.02	17.07	24.1	1.378	-0.0009	45.0	36 581	16 481		
30	555	-1 554c	47.59	19.06	15.67	24.67	1.4503	-0.0007	39.4	36 584	16 483		
32	560	3 416	39.23	22.73	11.98	25.7	1.6293	-0.0245	27.7	38 591	17 485		
31	555	1 405	56.48	20.36	14.54	25.03	1.4104	-0.0724	35.5	37 586	16 483	Rm	
32	563	7 435	50.33	26.1	6.1	26.8	1.5684	-0.2085	13.1	45 627	17 489		
32	564	10 450	49.62	29.9	-1.57	29.94	1.6524	-0.3617	356.9	-1 497c	19 497		
33	566	12 460	48.61	31.95	-6.93	32.69	1.707	-0.4727	347.7	-1 505c	21 505		
33	567	13 465	47.86	32.61	-9.34	33.92	1.7312	-0.5252	344.0	-1 511c	22 511		
33	569	14 470	46.41	33.07	-11.63	35.06	1.7624	-0.5807	340.6	-1 518c	23 518		
34	573	15 475	44.17	33.0	-13.84	35.78	1.7968	-0.6433	337.2	-1 527c	25 527	Mm	
35	579	16 480	40.74	32.27	-16.11	36.07	1.8418	-0.7253	333.4	-1 535c	27 535		
37	589	17 485	34.79	29.5	-18.91	35.04	1.8977	-0.8736	327.3	-1 545c	29 545		
-1	490c	18 490	15.86	8.1	-25.79	27.04	1.5605	-1.9558	287.4	11 459	33 566		
-1	495c	19 495	17.03	6.9	-25.91	26.81	1.4549	-1.8515	284.9	12 462	33 566	Bm	
-1	499c	19 500	17.03	6.9	-25.91	26.81	1.4549	-1.8515	284.9	12 462	33 566		
-1	510c	22 510	22.62	1.39	-24.98	25.01	1.1115	-1.434	273.1	13 469	33 569		
-1	520c	24 520	28.44	-3.71	-23.32	23.62	0.9191	-1.1502	260.9	14 473	34 572		
-1	529c	25 530	31.96	-6.54	-22.25	23.19	0.8451	-1.0261	253.6	15 475	34 574		
-1	539c	27 540	39.75	-12.11	-19.78	23.19	0.7451	-0.8276	238.5	15 479	35 577		
-1	544c	28 545	43.88	-14.67	-18.45	23.57	0.7153	-0.7504	231.4	16 480	35 579		
-1	549c	29 550	48.12	-17.02	-17.07	24.1	0.696	-0.6846	225.0	16 481	36 581		
-1	554c	30 555	52.4	-19.06	-15.67	24.67	0.6861	-0.6289	219.4	16 483	36 584		
3	416	32 560	60.76	-22.73	-11.98	25.7	0.6756	-0.5271	207.7	17 485	38 591		
	380	770	88.59	0.0	0.0	0.01	1.0498	-0.3299	0.0				

CIE data for all optimal colours of maximum (m) C_{AB} , P40 and $Y_{w,10}=88,6$, $Y_m=495_770$															
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code				
1	405	32	560	44.07	-23.04	-11.24	25.64	0.5691	-0.5138	205.9	17	486	37	589	Cm
7	435	33	566	48.6	-27.47	-4.6	27.85	0.5268	-0.3534	189.5	18	492	-1	492c	
10	450	33	567	49.19	-30.21	1.01	30.22	0.478	-0.2382	178.0	19	499	-1	499c	
12	460	33	569	50.04	-31.71	4.91	32.09	0.4583	-0.1605	171.1	21	506	-1	506c	
12	465	34	570	50.9	-31.85	5.13	32.26	0.4664	-0.1578	170.8	21	507	-1	507c	
13	470	34	571	52.11	-32.31	7.09	33.08	0.4719	-0.1226	167.6	22	513	-1	513c	
14	475	34	574	53.96	-32.59	8.96	33.8	0.4882	-0.0926	164.6	24	522	-1	522c	Gm
16	480	35	578	56.22	-31.95	11.59	33.99	0.5236	-0.0525	160.0	27	535	-1	535c	
16	485	37	585	61.42	-30.85	12.93	33.45	0.5898	-0.0481	157.2	28	541	-1	541c	
18	490	41	605	71.65	-22.38	16.81	27.99	0.7797	-0.024	143.0	31	557	-1	557c	
19	495	-1	495c	84.05	-5.01	20.45	21.05	1.0323	-0.0154	103.7	33	569	12	462	Ym
20	500	-1	500c	82.78	-3.66	20.45	20.78	1.0478	-0.0116	100.1	34	570	13	465	
22	510	-1	510c	79.15	0.0	19.97	19.97	1.0921	-0.0063	89.9	34	572	14	470	
24	520	-1	520c	73.89	4.84	18.85	19.47	1.1577	-0.0035	75.5	34	574	15	475	
26	530	-1	530c	67.28	10.24	17.27	20.08	1.2443	-0.0019	59.3	35	577	15	478	
28	540	-1	540c	59.71	15.5	15.38	21.83	1.3517	-0.0011	44.7	36	581	16	482	
29	545	-1	545c	55.69	17.89	14.36	22.94	1.4133	-0.0008	38.7	36	583	16	483	
29	550	-1	549c	55.69	17.89	14.36	22.94	1.4133	-0.0008	38.7	36	583	16	483	
30	555	-1	554c	51.57	20.02	13.3	24.04	1.4803	-0.0007	33.6	37	585	16	484	
32	560	-1	560c	43.22	23.2	11.16	25.74	1.6288	-0.0005	25.6	37	589	17	486	
32	560	1	405	55.92	23.04	11.24	25.64	1.5041	-0.0577	25.9	37	589	17	486	Rm
33	566	7	435	51.39	27.47	4.6	27.85	1.6266	-0.1691	9.5	-1	492c	18	492	
33	567	10	450	50.8	30.21	-1.01	30.22	1.6867	-0.2786	358.0	-1	499c	19	499	
33	569	12	460	49.95	31.71	-4.91	32.09	1.7269	-0.3571	351.1	-1	506c	21	506	
34	570	12	465	49.09	31.85	-5.13	32.26	1.7408	-0.3634	350.8	-1	507c	21	507	
34	571	13	470	47.88	32.31	-7.09	33.08	1.767	-0.4068	347.6	-1	513c	22	513	
34	574	14	475	46.03	32.58	-8.96	33.8	1.8	-0.4535	344.6	-1	522c	24	522	Mm
35	578	16	480	43.77	31.95	-11.59	33.99	1.8221	-0.5235	340.0	-1	535c	27	535	
37	585	16	485	38.57	30.85	-12.93	33.45	1.8918	-0.594	337.2	-1	541c	28	541	
41	605	18	490	28.34	22.38	-16.81	27.99	1.8817	-0.8521	323.0	-1	557c	31	557	
-1	495c	19	495	15.94	5.01	-20.44	21.05	1.4067	-1.5411	283.7	12	462	33	569	Bm
-1	500c	20	500	17.21	3.66	-20.45	20.78	1.305	-1.447	280.1	13	465	34	570	
-1	510c	22	510	20.84	0.0	-19.97	19.97	1.0918	-1.2171	269.9	14	470	34	572	
-1	520c	24	520	26.1	-4.84	-18.85	19.47	0.9063	-0.9812	255.5	15	475	34	574	
-1	530c	26	530	32.71	-10.24	-17.27	20.08	0.779	-0.7867	239.3	15	478	35	577	
-1	540c	28	540	40.28	-15.5	-15.38	21.83	0.7073	-0.6405	224.7	16	482	36	581	
-1	545c	29	545	44.3	-17.89	-14.36	22.94	0.6882	-0.5828	218.7	16	483	36	583	
-1	549c	29	550	44.3	-17.89	-14.36	22.94	0.6882	-0.5828	218.7	16	483	36	583	
-1	554c	30	555	48.42	-20.02	-13.3	24.04	0.6786	-0.5335	213.6	16	484	37	585	
-1	560c	32	560	56.77	-23.2	-11.16	25.74	0.6834	-0.4553	205.6	17	486	37	589	
	380	770	88.59	0.0	0.0	0.01	1.092	-0.2587	0.0						

CIE data for all optimal colours of maximum (m) C_{AB} , A_{00} and $Y_{w,10}=88,6$, $Y_m=495_770$															
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code				
1	405	33	569	44.75	-27.14	-6.12	27.82	0.5657	-0.2792	192.7	18	493	39	595	Cm
6	435	34	572	47.1	-28.54	-4.12	28.83	0.5662	-0.2298	188.2	19	495	42	610	
10	450	34	573	47.4	-30.3	-0.52	30.3	0.5328	-0.1534	180.9	20	502	-1	502c	
12	460	34	573	47.83	-31.09	1.58	31.13	0.5221	-0.1092	177.0	21	508	-1	508c	
13	465	34	574	48.14	-31.37	2.58	31.47	0.5206	-0.0886	175.2	22	512	-1	512c	
14	470	35	575	48.72	-31.52	3.5	31.72	0.5251	-0.0703	173.6	23	518	-1	518c	
15	475	35	576	49.56	-31.45	4.33	31.75	0.5376	-0.0547	172.1	25	525	-1	525c	Gm
16	480	35	578	50.92	-31.21	5.11	31.63	0.5592	-0.0419	170.6	26	532	-1	532c	
17	485	36	581	53.19	-30.58	5.89	31.15	0.5972	-0.0314	169.0	28	540	-1	540c	
18	490	37	588	57.48	-28.9	6.87	29.71	0.6693	-0.0227	166.6	29	548	-1	548c	
18	495	40	603	68.12	-23.04	8.38	24.52	0.8339	-0.0192	160.0	31	558	-1	558c	Ym
20	500	-1	500c	84.76	-0.61	11.29	11.3	1.165	-0.0091	93.0	34	574	13	468	
21	510	-1	509c	83.55	0.73	11.31	11.33	1.181	-0.0069	86.2	35	575	14	471	
24	520	-1	520c	77.79	6.61	10.83	12.69	1.2572	-0.003	58.6	35	578	15	479	
26	530	-1	530c	72.2	11.6	10.15	15.41	1.3329	-0.0017	41.1	36	580	16	483	
27	540	-1	539c	68.97	14.21	9.72	17.22	1.3782	-0.0013	34.3	36	581	17	485	
28	545	-1	544c	65.49	16.8	9.25	19.18	1.4287	-0.001	28.8	36	583	17	486	
30	550	-1	550c	57.92	21.61	8.2	23.11	1.5453	-0.0006	20.7	37	587	17	489	
30	555	-1	554c	57.92	21.61	8.2	23.11	1.5453	-0.0006	20.7	37	587	17	489	
32	560	-1	560c	49.77	25.35	7.05	26.32	1.6816	-0.0004	15.5	38	591	18	491	
33	569	1	405	55.24	27.14	6.12	27.82	1.6636	-0.0313	12.7	39	595	18	493	Rm
34	572	6	435	52.89	28.54	4.12	28.83	1.7118	-0.0644	8.2	42	610	19	495	
34	573	10	450	52.59	30.3	0.52	30.3	1.7483	-0.1322	0.9	-1	502c	20	502	
34	573	12	460	52.16	31.09	-1.58	31.13	1.7682	-0.1726	357.0	-1	508c	21	508	
34	574	13	465	51.85	31.37	-2.58	31.47	1.7772	-0.1921	355.2	-1	512c	22	512	
35	575	14	470	51.27	31.52	-3.5	31.72	1.787	-0.2107	353.6	-1	518c	23	518	
35	576	15	475	50.43	31.45	-4.33	31.75	1.7958	-0.2283	352.1	-1	525c	25	525	Mm
35	578	16	480	49.07	31.21	-5.11	31.63	1.8083	-0.2465	350.6	-1	532c	26	532	
36	581	17	485	46.8	30.58	-5.89	31.15	1.8257	-0.2683	349.0	-1	540c	28	540	
37	588	18	490	42.51	28.9	-6.87	29.71	1.8521	-0.304	346.6	-1	548c	29	548	
40	603	18	495	31.87	23.04	-8.38	24.52	1.8954	-0.4054	340.0	-1	558c	31	558	Bm
-1	500c	20	500	15.23	0.61	-11.29	11.3	1.2122	-0.8832	273.0	13	468	34	574	
-1	509c	21	510	16.44	-0.73	-11.31	11.33	1.1275	-0.8302	266.2	14	471	35	575	
-1	520c	24	520	22.2	-6.61	-10.83	12.69	0.8744	-0.6303	238.6	15	479	35	578	
-1	530c	26	530	27.79	-11.6	-10.15	15.41	0.7546	-0.5076	221.1	16	483	36	580	
-1	539c	27	540	31.02	-14.21	-9.72	17.22	0.714	-0.4558	214.3	17	485	36	581	
-1	544c	28	545	34.5	-16.8	-9.25	19.18	0.6852	-0.4105	208.8	17	486	36	583	
-1	550c	30	550	42.07	-21.61	-8.2	23.11	0.6586	-0.3373	200.7	17	489	37	587	
-1	554c	30	555	42.07	-21.61	-8.2	23.11	0.6586	-0.3373	200.7	17	489	37	587	
-1	560c	32	560	50.22	-25.35	-7.05	26.32	0.6673	-0.2828	195.5	18	491	38	591	
	380	770	88.58	0.0	0.0	0.01	1.1722	-0.1423	0.0						

CIE data for all optimal colours of maximum (m) C_{AB} , E00 and $Y_{w,10}=88,6$, $Y_m=495_770$															
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code				
1	405	30	553	42.02	-18.33	-18.0	25.7	0.6551	-0.8285	224.4	16	481	37	585	Cm
6	435	32	563	49.53	-25.67	-7.78	26.82	0.5733	-0.5572	196.8	17	487	44	622	
10	450	32	564	50.32	-31.66	4.1	31.92	0.4625	-0.3183	172.6	19	497	-1	497c	
12	460	33	567	51.62	-33.91	10.1	35.39	0.4346	-0.2042	163.4	21	506	-1	506c	
13	465	33	568	52.59	-34.69	12.82	36.99	0.4318	-0.1561	159.7	22	513	-1	513c	
14	470	34	571	54.41	-35.14	15.48	38.4	0.4458	-0.1154	156.2	24	521	-1	521c	
15	475	35	576	57.15	-35.08	18.11	39.48	0.4778	-0.083	152.6	26	530	-1	530c	Gm
15	480	36	583	62.0	-34.41	20.05	39.83	0.5365	-0.0765	149.7	27	536	-1	536c	
17	485	39	599	70.35	-28.5	25.47	38.22	0.6864	-0.0379	138.2	30	551	-1	551c	
18	490	-1	490c	83.75	-11.08	31.5	33.39	0.9592	-0.0238	109.3	33	566	11	456	
19	495	-1	495c	82.54	-9.79	31.54	33.02	0.973	-0.0179	107.2	33	566	11	459	Ym
19	500	-1	499c	82.54	-9.79	31.54	33.02	0.973	-0.0179	107.2	33	566	11	459	
22	510	-1	510c	76.84	-3.94	30.19	30.44	1.0403	-0.0071	97.4	34	570	13	467	
24	520	-1	520c	70.99	1.44	28.12	28.16	1.112	-0.0038	87.0	34	572	14	471	
26	530	-1	530c	63.88	7.24	25.41	26.43	1.205	-0.0021	74.0	35	576	15	475	
27	540	-1	539c	60.01	10.06	23.91	25.94	1.2592	-0.0015	67.1	35	578	15	476	
29	545	-1	545c	51.9	15.15	20.71	25.66	1.3836	-0.0009	53.8	36	582	15	479	
29	550	-1	549c	51.9	15.15	20.71	25.66	1.3836	-0.0009	53.8	36	582	15	479	
30	555	1	409	47.78	17.86	18.38	25.63	1.4655	-0.0151	45.8	37	585	16	481	
32	560	3	417	39.57	21.98	13.98	26.05	1.6472	-0.0465	32.4	38	592	16	483	
30	553	1	405	57.97	18.33	18.0	25.7	1.4079	-0.0894	44.4	37	585	16	481	Rm
32	563	6	435	50.46	25.67	7.78	26.82	1.6003	-0.2456	16.8	44	622	17	487	
32	564	10	450	49.67	31.66	-4.1	31.92	1.729	-0.4827	352.6	-1	497c	19	497	
33	567	12	460	48.37	33.91	-10.1	35.39	1.7927	-0.6089	343.4	-1	506c	21	506	
33	568	13	465	47.4	34.69	-12.82	36.99	1.8235	-0.6705	339.7	-1	513c	22	513	
34	571	14	470	45.58	35.14	-15.48	38.4	1.8625	-0.7397	336.2	-1	521c	24	521	
35	576	15	475	42.84	35.08	-18.11	39.48	1.9105	-0.8229	332.6	-1	530c	26	530	Mm
36	583	15	480	37.99	34.41	-20.05	39.83	1.9975	-0.9277	329.7	-1	536c	27	536	
39	599	17	485	29.64	28.5	-25.47	38.22	2.0534	-1.2593	318.2	-1	551c	30	551	
-1	490c	18	490	16.24	11.08	-31.5	33.39	1.7742	-2.3393	289.3	11	456	33	566	
-1	495c	19	495	17.45	9.79	-31.54	33.02	1.6527	-2.2074	287.2	11	459	33	566	Bm
-1	499c	19	500	17.45	9.79	-31.54	33.02	1.6527	-2.2074	287.2	11	459	33	566	
-1	510c	22	510	23.15	3.94	-30.19	30.44	1.2618	-1.7039	277.4	13	467	34	570	
-1	520c	24	520	29.0	-1.44	-28.12	28.16	1.0417	-1.3696	267.0	14	471	34	572	
-1	530c	26	530	36.11	-7.24	-25.41	26.43	0.891	-1.1038	254.0	15	475	35	576	
-1	539c	27	540	39.98	-10.06	-23.91	25.94	0.84	-0.9979	247.1	15	476	35	578	
-1	545c	29	545	48.09	-15.15	-20.71	25.66	0.7764	-0.8307	233.8	15	479	36	582	
-1	549c	29	550	48.09	-15.15	-20.71	25.66	0.7764	-0.8307	233.8	15	479	36	582	
1	409	30	555	52.21	-17.86	-18.38	25.63	0.7494	-0.7521	225.8	16	481	37	585	
3	417	32	560	60.42	-21.98	-13.98	26.05	0.7277	-0.6315	212.4	16	483	38	592	
	380	770	88.59	0.0	0.0	0.01	1.0916	-0.4	0.0						

CIE data for all optimal colours of maximum (m) C_{AB} , C_{00} and $Y_{w,10}=88.6$, $Y_m=495_770$															
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code				
1	405	29	548	39.56	-14.39	-22.73	26.91	0.7095	-1.0476	237.6	15	478	36	581	Cm
6	435	32	560	49.73	-23.52	-10.19	25.63	0.6005	-0.6778	203.4	16	484	42	610	
9	450	32	562	50.95	-29.26	0.99	29.28	0.499	-0.4533	178.0	18	492	-1	492c	
12	460	33	565	52.36	-33.84	12.06	35.93	0.4271	-0.2425	160.3	21	505	-1	505c	
13	465	33	567	53.54	-34.78	15.51	38.08	0.4237	-0.1831	155.9	22	512	-1	512c	
14	470	34	570	55.82	-35.41	18.99	40.18	0.4389	-0.1327	151.8	24	521	-1	521c	
14	475	35	576	59.82	-35.45	20.88	41.14	0.4808	-0.1238	149.5	25	527	-1	527c	Gm
16	480	36	584	64.26	-33.75	26.35	42.82	0.5481	-0.0627	142.0	28	540	-1	540c	
17	485	42	611	75.87	-24.3	32.93	40.93	0.7531	-0.0387	126.4	31	555	3	416	
18	490	-1	490c	82.68	-12.75	36.96	39.1	0.9191	-0.0257	109.0	32	564	11	457	
18	495	-1	494c	82.68	-12.75	36.96	39.1	0.9191	-0.0257	109.0	32	564	11	457	Ym
20	500	-1	500c	79.64	-9.55	36.57	37.79	0.9534	-0.0137	104.6	33	566	12	462	
22	510	-1	510c	75.34	-5.28	35.08	35.48	1.0033	-0.0071	98.5	33	568	13	466	
24	520	-1	520c	69.63	-0.12	32.65	32.65	1.0716	-0.0039	90.2	34	571	14	470	
26	530	-1	530c	62.62	5.45	29.47	29.97	1.1606	-0.0021	79.5	34	574	14	473	
28	540	-1	540c	54.54	10.91	25.72	27.94	1.2736	-0.0012	67.0	35	578	15	476	
29	545	-1	545c	50.25	13.39	23.71	27.23	1.34	-0.0009	60.5	36	580	15	478	
29	550	1	408	50.25	13.78	23.26	27.04	1.3478	-0.01	59.3	36	581	15	478	
31	555	3	415	41.51	18.39	18.47	26.07	1.5166	-0.0278	45.1	37	587	16	480	
31	560	4	424	41.55	20.19	15.85	25.67	1.5593	-0.0914	38.1	38	591	16	482	
29	548	1	405	60.43	14.39	22.73	26.91	1.3117	-0.0966	57.6	36	581	15	478	Rm
32	560	6	435	50.26	23.52	10.19	25.63	1.5414	-0.2701	23.4	42	610	16	484	
32	562	9	450	49.04	29.26	-0.99	29.28	1.6702	-0.4931	358.0	-1	492c	18	492	
33	565	12	460	47.63	33.84	-12.06	35.93	1.7839	-0.726	340.3	-1	505c	21	505	
33	567	13	465	46.45	34.78	-15.51	38.08	1.8222	-0.8067	335.9	-1	512c	22	512	
34	570	14	470	44.17	35.41	-18.99	40.18	1.8752	-0.9027	331.8	-1	521c	24	521	
35	576	14	475	40.17	35.45	-20.88	41.14	1.956	-0.9926	329.5	-1	527c	25	527	Mm
36	584	16	480	35.73	33.75	-26.35	42.82	2.0179	-1.2103	322.0	-1	540c	28	540	
42	611	17	485	24.12	24.29	-32.93	40.93	2.0805	-1.8379	306.4	3	416	31	555	
-1	490c	18	490	17.31	12.75	-36.96	39.1	1.8102	-2.6079	289.0	11	457	32	564	
-1	494c	18	495	17.31	12.75	-36.96	39.1	1.8102	-2.6079	289.0	11	457	32	564	Bm
-1	500c	20	500	20.35	9.55	-36.57	37.79	1.5429	-2.2694	284.6	12	462	33	566	
-1	510c	22	510	24.65	5.28	-35.08	35.48	1.2878	-1.8961	278.5	13	466	33	568	
-1	520c	24	520	30.36	0.12	-32.65	32.65	1.0775	-1.5483	270.2	14	470	34	571	
-1	530c	26	530	37.37	-5.45	-29.47	29.97	0.9274	-1.2615	259.5	14	473	34	574	
-1	540c	28	540	45.45	-10.91	-25.72	27.94	0.8332	-1.0389	247.0	15	476	35	578	
-1	545c	29	545	49.74	-13.39	-23.71	27.23	0.8042	-0.9496	240.5	15	478	36	580	
1	408	29	550	49.74	-13.78	-23.26	27.04	0.7962	-0.9405	239.3	15	478	36	581	
3	415	31	555	58.48	-18.39	-18.47	26.07	0.7588	-0.7887	225.1	16	480	37	587	
4	424	31	560	58.44	-20.19	-15.85	25.67	0.7279	-0.7441	218.1	16	482	38	591	
	380	770	88.59	0.0	0.0	0.01	1.0734	-0.4729	0.0						

CIE data for all optimal colours of maximum (m) C_{AB} , P00 and $Y_{w,10}=88,6$, $Y_m=495_770$															
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code				
1	405	31	558	43.17	-21.3	-14.27	25.64	0.6134	-0.6548	213.8	16	483	37	588	Cm
7	435	33	565	48.86	-27.71	-4.75	28.11	0.5398	-0.4215	189.7	18	490	-1	490c	
10	450	33	567	49.57	-31.23	2.49	31.33	0.4769	-0.2739	175.4	19	498	-1	498c	
11	460	33	568	50.86	-32.39	5.22	32.81	0.47	-0.2216	170.8	20	502	-1	502c	
13	465	34	570	51.4	-33.73	9.53	35.05	0.4507	-0.1388	164.2	22	513	-1	513c	
14	470	34	572	52.85	-34.03	11.62	35.96	0.463	-0.1042	161.1	24	521	-1	521c	
15	475	35	575	55.03	-34.0	13.64	36.64	0.4889	-0.0763	158.1	25	529	-1	529c	Gm
16	480	36	581	58.37	-33.26	15.74	36.79	0.5372	-0.0545	154.6	27	538	-1	538c	
17	485	38	591	64.88	-30.19	18.62	35.48	0.6415	-0.0371	148.3	29	548	-1	548c	
18	490	-1	490c	84.48	-8.44	25.57	26.93	1.007	-0.0215	108.2	33	568	11	457	
18	495	-1	494c	84.48	-8.44	25.57	26.93	1.007	-0.0215	108.2	33	568	11	457	Ym
20	500	-1	500c	82.05	-5.81	25.6	26.25	1.0361	-0.0121	102.7	33	569	12	463	
22	510	-1	510c	78.23	-1.88	24.85	24.92	1.0828	-0.0066	94.3	34	571	13	468	
24	520	-1	520c	72.8	3.19	23.34	23.55	1.1509	-0.0036	82.1	34	574	14	473	
26	530	-1	530c	66.07	8.78	21.29	23.03	1.2399	-0.002	67.5	35	577	15	476	
28	540	-1	540c	58.47	14.17	18.89	23.62	1.3494	-0.0011	53.1	36	581	15	479	
28	545	-1	544c	58.47	14.17	18.89	23.62	1.3494	-0.0011	53.1	36	581	15	479	
29	550	-1	549c	54.47	16.62	17.61	24.21	1.412	-0.0008	46.6	36	582	16	481	
31	555	-1	555c	46.28	20.62	14.97	25.48	1.5525	-0.0005	35.9	37	587	16	483	
32	560	2	410	42.18	22.56	13.04	26.06	1.642	-0.0149	30.0	38	591	16	484	
31	558	1	405	56.82	21.3	14.27	25.64	1.4819	-0.073	33.8	37	588	16	483	Rm
33	565	7	435	51.13	27.71	4.75	28.11	1.6489	-0.2312	9.7	-1	490c	18	490	
33	567	10	450	50.42	31.23	-2.49	31.33	1.7264	-0.3737	355.4	-1	498c	19	498	
33	568	11	460	49.13	32.39	-5.22	32.81	1.7662	-0.4304	350.8	-1	502c	20	502	
34	570	13	465	48.59	33.73	-9.53	35.05	1.8011	-0.5204	344.2	-1	513c	22	513	
34	572	14	470	47.14	34.03	-11.62	35.96	1.8288	-0.5708	341.1	-1	521c	24	521	
35	575	15	475	44.96	34.0	-13.64	36.64	1.8632	-0.6276	338.1	-1	529c	25	529	Mm
36	581	16	480	41.62	33.26	-15.74	36.79	1.9061	-0.7025	334.6	-1	538c	27	538	
38	591	17	485	35.11	30.19	-18.62	35.48	1.9668	-0.8546	328.3	-1	548c	29	548	
-1	490c	18	490	15.51	8.44	-25.57	26.93	1.6515	-1.9729	288.2	11	457	33	568	
-1	494c	18	495	15.51	8.44	-25.57	26.93	1.6515	-1.9729	288.2	11	457	33	568	Bm
-1	500c	20	500	17.94	5.81	-25.6	26.25	1.4308	-1.7514	282.7	12	463	33	569	
-1	510c	22	510	21.76	1.88	-24.85	24.92	1.1938	-1.4663	274.3	13	468	34	571	
-1	520c	24	520	27.19	-3.19	-23.34	23.55	0.9893	-1.1826	262.1	14	473	34	574	
-1	530c	26	530	33.92	-8.78	-21.29	23.03	0.848	-0.9518	247.5	15	476	35	577	
-1	540c	28	540	41.52	-14.17	-18.89	23.62	0.7655	-0.7792	233.1	15	479	36	581	
-1	544c	28	545	41.52	-14.17	-18.89	23.62	0.7655	-0.7792	233.1	15	479	36	581	
-1	549c	29	550	45.52	-16.62	-17.61	24.21	0.7419	-0.7111	226.6	16	481	36	582	
-1	555c	31	555	53.71	-20.62	-14.97	25.48	0.7231	-0.603	215.9	16	483	37	587	
2	410	32	560	57.81	-22.56	-13.04	26.06	0.7166	-0.5498	210.0	16	484	38	591	
	380	770	88.59	0.0	0.0	0.01	1.1069	-0.3242	0.0						

CIE data for all optimal colours of maximum (m) C_{AB} , $Q00$ and $Y_{w,10}=88,6$, $Y_m=495_770$												
i_1, λ_1	i_2, λ_2	$Y_{88.6}$	$A_{88.6}$	$B_{88.6}$	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code	
1	405	29 548	40.41	-14.85	-22.12	26.64	0.7088	-1.0231	236.1	15 478	36 582	Cm
6	435	32 560	50.11	-24.66	-8.58	26.11	0.584	-0.647	199.1	17 485	45 625	
10	450	32 562	51.05	-31.87	5.82	32.4	0.4518	-0.3617	169.6	19 496	-1 496c	
12	460	33 565	52.61	-34.71	13.02	37.07	0.4165	-0.2281	159.4	21 506	-1 506c	
12	465	33 567	54.15	-34.94	13.76	37.56	0.4309	-0.2216	158.5	21 508	-1 508c	
14	470	34 570	55.97	-36.2	19.58	41.15	0.4295	-0.1259	151.5	24 522	-1 522c	
15	475	35 576	59.28	-36.09	22.91	42.75	0.4674	-0.0892	147.5	26 531	-1 531c	Gm
16	480	37 585	64.42	-34.57	26.7	43.68	0.5396	-0.0612	142.3	28 540	-1 540c	
17	485	42 613	76.62	-24.63	33.52	41.6	0.7547	-0.0383	126.3	31 555	3 416	
18	490	-1 490c	83.02	-13.75	37.32	39.78	0.9105	-0.0262	110.2	32 564	11 455	
19	495	-1 495c	81.68	-12.33	37.26	39.25	0.9252	-0.0195	108.3	32 564	11 458	Ym
20	500	-1 500c	80.01	-10.58	36.91	38.4	0.944	-0.0144	105.9	33 565	12 461	
22	510	-1 510c	75.45	-6.03	35.32	35.83	0.9962	-0.0076	99.6	33 568	13 466	
24	520	-1 520c	69.18	-0.35	32.63	32.63	1.071	-0.0041	90.6	34 571	14 470	
25	530	-1 529c	65.55	2.65	30.99	31.1	1.1167	-0.003	85.1	34 573	14 472	
28	540	-1 540c	53.52	11.18	25.4	27.75	1.2852	-0.0012	66.2	35 579	15 476	
28	545	-1 544c	53.52	11.18	25.4	27.75	1.2852	-0.0012	66.2	35 579	15 476	
29	550	1 408	49.35	14.3	22.59	26.73	1.366	-0.018	57.6	36 581	15 478	
31	555	3 415	41.01	19.0	17.7	25.97	1.5396	-0.0442	42.9	37 588	16 481	
31	560	4 424	41.07	21.12	14.63	25.69	1.5906	-0.1195	34.7	38 594	16 482	
29	548	1 405	59.58	14.85	22.12	26.64	1.3255	-0.1044	56.1	36 582	15 478	Rm
32	560	6 435	49.88	24.66	8.58	26.11	1.5708	-0.3038	19.1	45 625	17 485	
32	562	10 450	48.94	31.87	-5.82	32.4	1.7274	-0.5948	349.6	-1 496c	19 496	
33	565	12 460	47.38	34.71	-13.02	37.07	1.8087	-0.7507	339.4	-1 506c	21 506	
33	567	12 465	45.84	34.94	-13.76	37.56	1.8386	-0.776	338.5	-1 508c	21 508	
34	570	14 470	44.02	36.2	-19.58	41.15	1.8986	-0.9206	331.5	-1 522c	24 522	
35	576	15 475	40.71	36.09	-22.91	42.75	1.9627	-1.0387	327.5	-1 531c	26 531	Mm
37	585	16 480	35.57	34.57	-26.7	43.68	2.0479	-1.2265	322.3	-1 540c	28 540	
42	613	17 485	23.37	24.63	-33.52	41.6	2.1303	-1.9099	306.3	3 416	31 555	
-1	490c	18 490	16.97	13.75	-37.32	39.78	1.8864	-2.6742	290.2	11 455	32 564	
-1	495c	19 495	18.31	12.33	-37.26	39.25	1.7495	-2.5101	288.3	11 458	32 564	Bm
-1	500c	20 500	19.98	10.58	-36.91	38.4	1.6057	-2.3227	285.9	12 461	33 565	
-1	510c	22 510	24.54	6.03	-35.32	35.83	1.3221	-1.9147	279.6	13 466	33 568	
-1	520c	24 520	30.81	0.35	-32.63	32.63	1.0879	-1.5348	270.6	14 470	34 571	
-1	529c	25 530	34.44	-2.65	-30.99	31.1	0.9993	-1.3756	265.1	14 472	34 573	
-1	540c	28 540	46.47	-11.18	-25.4	27.75	0.8356	-1.0224	246.2	15 476	35 579	
-1	544c	28 545	46.47	-11.18	-25.4	27.75	0.8356	-1.0224	246.2	15 476	35 579	
1	408	29 550	50.64	-14.3	-22.59	26.73	0.7939	-0.9218	237.6	15 478	36 581	
3	415	31 555	58.98	-19.0	-17.7	25.97	0.754	-0.7759	222.9	16 481	37 588	
4	424	31 560	58.92	-21.12	-14.63	25.69	0.7177	-0.724	214.7	16 482	38 594	
	380	770	88.59	0.0	0.0	0.01	1.0762	-0.4758	0.0			