

Performance (STRESS values) for small colour difference data (SCD)

iimp=418, WI=WITT colour difference pairs %

ia	d_rangeLAB	LABmin,max,mean	STRESS	CMCmin,max,mean	STRESS	C94min,max,mean	STRESS	C00min,max,mean	STRESS	C85min,max,mean	STRESS					
418 418	0.0 to <99	0.11	10.62 1.86 51.7	0.08	4.7	1.25 39.5	0.08	3.72	1.07 31.6	0.08	3.75	1.09 33.7	0.55	29.71	6.85	55.1
418 400	0.0 to <5.0	0.11	4.94 1.67 51.9	0.08	4.7	1.19 38.8	0.08	3.72	1.02 31.9	0.08	3.75	1.04 33.8	0.55	29.71	6.63	55.7
418 38	0.0 to <0.5	0.11	0.49 0.36 51.4	0.08	0.72	0.32 33.8	0.08	0.47	0.28 29.1	0.08	0.62	0.29 22.7	0.55	4.44	2.0	52.4
418 88	0.5 to <1.0	0.51	0.99 0.74 57.7	0.27	1.53	0.64 37.8	0.23	0.99	0.55 33.1	0.23	1.42	0.58 30.3	0.79	8.71	3.56	55.4
418 91	1.0 to <1.5	1.01	1.49 1.26 57.7	0.42	2.15	1.06 37.7	0.34	1.49	0.91 32.9	0.34	1.86	0.92 30.2	1.45	13.86	6.02	55.2
418 57	1.5 to <2.0	1.51	1.99 1.74 56.4	0.78	2.77	1.44 34.9	0.62	1.92	1.26 28.5	0.63	2.82	1.3 23.6	2.34	15.67	8.34	53.6
418 126	2.0 to <5.0	2.03	4.94 2.98 56.8	0.83	4.7	1.83 42.0	0.66	3.72	1.55 34.0	0.66	3.75	1.55 32.6	2.8	29.71	9.83	58.3
418 17	5.0 to <10	5.03	8.75 5.89 43.7	2.02	3.38	2.55 29.0	1.69	2.66	2.14 28.8	1.63	2.83	2.17 24.8	6.98	26.87	11.5	41.5
418 1	10 to <15	10.62	10.62 10.62 0.1	4.07	4.07	4.07 0.1	3.18	3.18	3.18 0.1	3.43	3.43	3.43 0.1	14.9	14.9	14.9	0.1
418 0	15 to <20	%														
418 0	20 to <25	%														
418 0	25 to <30	%														
418 0	30 to <99	%														

iimp=418, WI=WITT colour difference pairs %

ia	d_rangeC00	LABmin,max,mean	STRESS	CMCmin,max,mean	STRESS	C94min,max,mean	STRESS	C00min,max,mean	STRESS	C85min,max,mean	STRESS					
418 418	0.0 to <99	0.11	10.62 1.86 51.7	0.08	4.7	1.25 39.5	0.08	3.72	1.07 31.6	0.08	3.75	1.09 33.7	0.55	29.71	6.85	55.1
418 418	0.0 to <5.0	0.11	10.62 1.86 51.7	0.08	4.7	1.25 39.5	0.08	3.72	1.07 31.6	0.08	3.75	1.09 33.7	0.55	29.71	6.85	55.1
418 83	0.0 to <0.5	0.11	1.21 0.58 58.6	0.08	0.69	0.37 38.5	0.08	0.54	0.34 33.1	0.08	0.49	0.33 30.4	0.55	6.24	2.51	52.7
418 123	0.5 to <1.0	0.44	3.69 1.26 56.7	0.42	1.5	0.84 41.9	0.44	1.34	0.75 33.8	0.5	0.99	0.74 32.4	1.08	12.77	4.99	57.8
418 107	1.0 to <1.5	0.76	4.45 2.09 57.2	0.84	2.38	1.41 41.2	0.75	2.1	1.22 32.8	1.0	1.49	1.22 30.9	1.83	17.41	8.11	53.4
418 69	1.5 to <2.0	1.17	5.72 2.98 59.4	1.2	2.96	2.01 38.8	1.15	2.94	1.7 32.4	1.5	1.99	1.71 29.4	2.47	25.7	10.36	51.9
418 36	2.0 to <5.0	1.54	10.62 4.08 50.8	1.69	4.7	2.8 34.4	1.52	3.72	2.26 29.4	2.0	3.75	2.43 23.1	3.82	29.71	12.7	52.7
418 0	5.0 to <10	%														
418 0	10 to <15	%														
418 0	15 to <20	%														
418 0	20 to <25	%														
418 0	25 to <30	%														
418 0	30 to <99	%														

iimp=418, WI=WITT colour difference pairs %

ia	d_rangeC85	LABmin,max,mean	STRESS	CMCmin,max,mean	STRESS	C94min,max,mean	STRESS	C00min,max,mean	STRESS	C85min,max,mean	STRESS					
418 418	0.0 to <99	0.11	10.62 1.86 51.7	0.08	4.7	1.25 39.5	0.08	3.72	1.07 31.6	0.08	3.75	1.09 33.7	0.55	29.71	6.85	55.1
418 189	0.0 to <5.0	0.11	4.39 1.11 54.5	0.08	2.75	0.83 40.0	0.08	1.88	0.64 33.2	0.08	2.82	0.7 32.9	0.55	4.97	2.91	57.9
418 0	0.0 to <0.5	%														
418 8	0.5 to <1.0	0.11	0.56 0.31 12.6	0.08	0.3	0.2 12.3	0.08	0.24	0.17 12.3	0.08	0.27	0.19 11.0	0.55	0.88	0.76	11.1
418 18	1.0 to <1.5	0.23	1.03 0.61 45.8	0.13	0.82	0.42 30.1	0.13	0.52	0.33 29.9	0.13	0.78	0.37 25.6	1.08	1.49	1.34	43.6
418 20	1.5 to <2.0	0.24	1.12 0.72 49.3	0.2	1.43	0.62 30.4	0.19	0.92	0.45 30.3	0.17	1.35	0.55 25.5	1.5	1.99	1.72	46.9
418 143	2.0 to <5.0	0.21	4.39 1.27 56.7	0.19	2.75	0.95 42.1	0.19	1.88	0.73 34.6	0.17	2.82	0.79 33.9	2.0	4.97	3.39	59.5
418 132	5.0 to <10	0.59	6.68 2.3 57.1	0.43	4.51	1.54 42.4	0.49	2.51	1.24 34.6	0.45	3.75	1.27 33.7	5.01	9.74	7.03	59.5
418 71	10 to <15	1.08	10.62 2.54 59.8	0.78	4.7	1.58 39.3	0.95	3.31	1.54 33.2	0.81	3.43	1.47 30.5	10.0	14.94	12.38	51.8
418 16	15 to <20	1.84	7.51 3.27 41.4	1.22	3.2	1.92 27.3	1.39	2.52	1.93 27.1	1.36	2.61	1.8 23.2	15.0	19.58	16.71	39.2
418 6	20 to <25	2.12	4.25 2.95 14.2	1.69	2.23	1.87 13.9	1.86	2.94	2.28 13.9	1.56	2.28	2.02 12.9	20.36	23.8	21.7	13.2
418 4	25 to <30	2.64	5.67 3.92 12.3	2.14	2.96	2.45 12.1	2.34	3.72	2.85 12.1	1.96	2.73	2.46 11.5	25.7	29.71	27.26	11.4
418 0	30 to <99	%														

see similar files: http://130.149.60.45/~farbmetrik/VE92/VE92L0N1.TXT /PS
 technical information: http://www.psc.bamd.de or http://130.149.60.45/~farbmetrik

TUB registration: 20140801-VE92/VE92L0N1.TXT /PS
 application for measurement of display or printer output

TUB material: code=thata