


N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*ab	SUM	DV*v	DVvr	DVab	dVvr	dVab	CODE	VIM	ia	inr	%
%1000*(CIEXYZ & DV) for all colours (a) of experiment, iimp=114, colour difference pairs VA_LC114=VIK_ADJACENT, xchart3=0, xchart4=0 %																											
27	5	109	110	111	112	113	W	Wm	CW	Mw	M	22.34	23.73	22.19	22.5	21.0	90.77	22.34	0.246	0.231	0.753	0.768	W-Wm	0.231	58	51000027	%
21.59 90.77 23.73 0.26 0.23 0.73 0.76 Wm-MW 0.469 57 51000027 % 20.03 90.77 22.19 0.24 0.22 0.75 0.77 MW-Mw 0.69 1 51000027 % 28.14 90.77 22.5 0.24 0.31 0.75 0.69 Mw-M 0.0 59 51000027 % 28 5 119 120 121 122 123 W Wo CW Ow O 22.94 23.82 24.97 22.64 21.1 94.38 22.94 0.243 0.223 0.756 0.776 W-Wo 0.223 62 51000028 % 21.64 94.38 23.82 0.25 0.22 0.74 0.77 Wo-OW 0.452 61 51000028 % 21.3 94.38 24.97 0.26 0.22 0.73 0.77 OW-Ow 0.678 1 51000028 % 30.33 94.38 22.64 0.23 0.32 0.76 0.67 Ow-O 0.0 63 51000028 % 29 5 129 130 131 132 133 W Wy CW Yw Y 22.21 23.65 25.94 20.97 21.0 92.79 22.21 0.239 0.175 0.76 0.824 W-Wy 0.175 66 51000029 % 19.03 92.79 23.65 0.25 0.31 0.74 0.68 Wy-YW 0.488 65 51000029 % 22.6 92.79 25.94 0.27 0.24 0.72 0.75 YW-Yw 0.732 1 51000029 % 24.85 92.79 20.97 0.22 0.26 0.77 0.73 Yw-Y 0.0 67 51000029 % 30 5 139 140 141 142 143 W Wl CW Lw L 20.01 21.19 19.69 20.27 18.84 81.18 20.01 0.246 0.232 0.753 0.767 W-Wl 0.232 70 51000030 % 19.42 81.18 21.19 0.26 0.23 0.73 0.76 Wl-LW 0.471 69 51000030 % 18.43 81.18 19.69 0.24 0.22 0.75 0.77 LW-Lw 0.698 1 51000030 % 24.47 81.18 20.27 0.24 0.3 0.75 0.69 Lw-L 0.0 71 51000030 % 31 5 149 150 151 152 153 C Cn CN Nc N 16.6 17.03 16.27 17.07 17.99 66.98 16.6 0.247 0.268 0.752 0.731 C-Cn 0.268 74 51000031 % 15.69 66.98 17.03 0.25 0.23 0.74 0.76 Cn-CN 0.502 73 51000031 % 16.45 66.98 16.27 0.24 0.24 0.75 0.75 CN-Nc 0.748 1 51000031 % 16.84 66.98 17.07 0.25 0.25 0.74 0.74 Nc-N 0.0 75 51000031 % 32 5 159 160 161 162 163 V Vn VN Nv N 12.49 14.09 14.93 13.61 14.77 55.14 12.49 0.226 0.267 0.773 0.732 V-Vn 0.267 78 51000032 % 14.49 55.14 14.09 0.25 0.26 0.74 0.73 Vn-VN 0.53 77 51000032 % 14.65 55.14 14.93 0.27 0.26 0.72 0.73 VN-Nv 0.796 1 51000032 % 11.22 55.14 13.61 0.24 0.2 0.75 0.79 Nv-N 0.0 79 51000032 % 33 5 169 170 171 172 173 M Mn MN Nm N 20.1 20.51 18.8 20.26 21.4 79.69 20.1 0.252 0.268 0.747 0.731 M-Mn 0.268 82 51000033 % 18.5 79.69 20.51 0.25 0.23 0.74 0.76 Mn-MN 0.5 81 51000033 % 17.76 79.69 18.8 0.23 0.22 0.76 0.77 MN-Nm 0.723 1 51000033 % 22.02 79.69 20.26 0.25 0.27 0.74 0.72 Nm-N 0.0 83 51000033 % 34 5 179 180 181 182 183 O On ON No N 22.7 21.8 20.33 23.51 23.15 88.34 22.7 0.256 0.262 0.743 0.737 O-On 0.262 86 51000034 % 20.19 88.34 21.8 0.24 0.22 0.75 0.77 On-ON 0.49 85 51000034 % 20.19 88.34 20.33 0.23 0.22 0.76 0.77 ON-No 0.719 1 51000034 % 24.8 88.34 23.51 0.26 0.28 0.73 0.71 No-N 0.0 87 51000034 % 35 5 189 190 191 192 193 Y Yn YN Ny N 29.12 31.21 28.89 30.39 29.73 119.63 29.12 0.243 0.248 0.756 0.751 Y-Yn 0.248 90 51000035 % 29.13 119.63 31.21 0.26 0.24 0.73 0.75 Yn-YN 0.492 89 51000035 % 25.46 119.63 28.89 0.24 0.21 0.75 0.78 YN-Ny 0.705 1 51000035 % 35.29 119.63 30.39 0.25 0.29 0.74 0.7 Ny-N 0.0 91 51000035 % 36 5 199 200 201 202 203 L Ln LN Nl N 20.2 20.83 20.42 19.73 20.99 81.2 20.2 0.248 0.258 0.751 0.741 L-Ln 0.258 94 51000036 % 19.66 81.2 20.83 0.25 0.24 0.74 0.75 Ln-LN 0.5 93 51000036 % 17.98 81.2 20.42 0.25 0.22 0.74 0.77 LN-Nl 0.722 1 51000036 % 22.56 81.2 19.73 0.24 0.27 0.75 0.72 Nl-N 0.0 95 51000036 % 37 3 281 282 283 0 0 C CV V 0 0 35.03 35.26 0.0 0.0 32.48 70.3 35.03 0.498 0.462 0.501 0.537 CV-C 0.462 96 51000037 % 37.81 70.3 35.26 0.5 0.53 0.49 0.46 CV-V 0.0 97 51000037 % 38 3 283 284 285 0 0 V MV M 0 0 29.74 32.14 0.0 0.0 34.3 61.88 29.74 0.48 0.554 0.519 0.445 VM-V 0.554 98 51000038 % 27.58 61.88 32.14 0.51 0.44 0.48 0.55 M-M 0.0 99 51000038 % 39 3 291 292 293 0 0 M MO O 0 0 29.58 30.02 0.0 0.0 33.68 59.61 29.58 0.496 0.565 0.503 0.434 MO-M 0.565 100 51000039 % 25.93 59.61 30.02 0.5 0.43 0.49 0.56 MO-O 0.0 101 51000039 % 40 3 293 294 295 0 0 O YO Y 0 0 48.88 46.54 0.0 0.0 43.96 95.43 48.88 0.512 0.46 0.487 0.539 YO-O 0.46 102 51000040 % 51.46 95.43 46.54 0.48 0.53 0.51 0.46 YO-Y 0.0 103 51000040 % 41 3 301 302 303 0 0 Y YL L 0 0 47.1 41.44 0.0 0.0 38.83 88.54 47.1 0.531 0.438 0.468 0.561 YL-Y 0.438 104 51000041 % 49.71 88.54 41.44 0.46 0.56 0.53 0.43 YL-L 0.0 105 51000041 %																											

Technische Information: http://www.ps.bam.de oder http://130.149.60.45/~farbmetrik
 Siehe ähnliche Dateien: http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF / .PS
 http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF / .PS

TUB-Registrierung: 20140801-XG50/XG50LONP.PDF / .PS
 Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation
 TUB-Material: Code=rh4ta



N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*ab	SUM	DV*v	DVvr	DVab	dVvr	dVab	CODE	VIM	ia	inr	%			
%1000*(CIEXYZ & DV) for all colours (a) of experiment, iimp=114, colour difference pairs KS_LC114=KIT_SEPARATE, xchart3=0, xchart4=2 %																														
1	3	4	5	6	0	0	W	CW	C	0	0	34.3	33.07	0.0	0.0	33.29	67.38	34.3	0.509	0.494	0.49	0.505	CW_W	0.494	0	53000001	%			
...																														
26	5	104	105	106	107	108	W	Wv	CW	Vw	V	23.53	23.89	21.37	23.33	19.24	92.14	23.53	0.255	0.208	0.744	0.791	W-Wv	0.208	54	53000026	%			
...																														
55																										Vw-V	0.0	55	53000026	%

Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>
 Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
<http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS

TUB-Registrierung: 20140801-XG50/XG50LONP.PDF / .PS
 Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation
 TUB-Material: Code=rh4ta

N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*ab	SUM	DV*v	DVvr	DVab	dVvr	dVab	CODE	VIM	iia	inr	%
%1000*(CIEXYZ & DV) for all colours (a) of experiment, iimp=98, colour difference pairs MA_LC098=MEL_ADJACENT, xchart3=0, xchart4=3 %																											
27	4	109	110	111	0	0	W	Wm	CW	0	0	7.54	0.0	0.0	0.0	40.65	80.35	20.66	0.257	0.505	0.742	0.494	W-Wv	0.505	52	54000027	%
																39.69	80.35	59.68	0.74	0.49	0.25	0.5	Wv-VW	0.0	53	54000027	%
28	4	119	120	121	0	0	W	Wo	CW	0	0	6.9	0.0	0.0	0.0	43.55	82.95	22.46	0.27	0.525	0.729	0.474	VW-Vw	0.525	54	54000028	%
																39.4	82.95	60.48	0.72	0.47	0.27	0.52	Vw-V	0.0	55	54000028	%
29	4	129	130	131	0	0	W	Wy	CW	0	0	4.43	0.0	0.0	0.0	40.88	83.6	20.78	0.248	0.489	0.751	0.511	W-Wm	0.489	56	54000029	%
																42.72	83.6	62.81	0.75	0.51	0.24	0.48	Wm-MW	0.0	57	54000029	%
30	4	139	140	141	0	0	W	Wl	CW	0	0	6.33	0.0	0.0	0.0	33.82	69.31	18.36	0.264	0.488	0.735	0.511	MW-Mw	0.488	58	54000030	%
																35.48	69.31	50.94	0.73	0.51	0.26	0.48	Mw-M	0.0	59	54000030	%
31	4	91	92	93	0	0	CW	Cw	C	0	0	6.54	0.0	0.0	0.0	18.56	32.29	16.24	0.503	0.575	0.496	0.425	W-Wo	0.575	60	54000031	%
																13.72	32.29	16.04	0.49	0.42	0.5	0.57	Wo-OW	0.0	61	54000031	%
32	4	101	102	103	0	0	VW	Vw	V	0	0	9.86	0.0	0.0	0.0	10.3	22.12	10.71	0.484	0.466	0.515	0.534	OW-Ow	0.466	62	54000032	%
																11.81	22.12	11.4	0.51	0.53	0.48	0.46	Ow-O	0.0	63	54000032	%
33	4	111	112	113	0	0	MW	Mw	M	0	0	7.92	0.0	0.0	0.0	21.61	37.65	18.95	0.503	0.574	0.496	0.426	W-Wy	0.574	64	54000033	%
																16.04	37.65	18.69	0.49	0.42	0.5	0.57	Wy-YW	0.0	65	54000033	%
34	4	121	122	123	0	0	OW	Ow	O	0	0	8.95	0.0	0.0	0.0	24.05	42.27	22.05	0.521	0.569	0.478	0.431	YW-Yw	0.569	66	54000034	%
																18.21	42.27	20.21	0.47	0.43	0.52	0.56	Yw-Y	0.0	67	54000034	%
35	4	131	132	133	0	0	YW	Yw	Y	0	0	3.02	0.0	0.0	0.0	29.89	58.95	29.4	0.498	0.507	0.501	0.492	W-Wl	0.507	68	54000035	%
																29.06	58.95	29.55	0.5	0.49	0.49	0.5	Wl-LW	0.0	69	54000035	%
36	4	141	142	143	0	0	LW	Lw	L	0	0	6.98	0.0	0.0	0.0	18.33	34.14	17.83	0.522	0.537	0.477	0.463	LW-Lw	0.537	70	54000036	%
																15.8	34.14	16.3	0.47	0.46	0.52	0.53	Lw-L	0.0	71	54000036	%
37	4	149	150	151	0	0	C	Cn	CN	0	0	6.41	0.0	0.0	0.0	20.34	46.54	16.28	0.349	0.437	0.65	0.562	C-Cn	0.437	72	54000037	%
																26.2	46.54	30.26	0.65	0.56	0.34	0.43	Cn-CN	0.0	73	54000037	%
38	4	159	160	161	0	0	V	Vn	VN	0	0	2.6	0.0	0.0	0.0	17.11	41.84	18.9	0.451	0.409	0.548	0.59	CN-Nc	0.409	74	54000038	%
																24.73	41.84	22.93	0.54	0.59	0.45	0.4	Nc-N	0.0	75	54000038	%
39	4	169	170	171	0	0	M	Mn	MN	0	0	6.63	0.0	0.0	0.0	21.13	49.49	19.18	0.387	0.427	0.612	0.572	V-Vn	0.427	76	54000039	%
																28.36	49.49	30.31	0.61	0.57	0.38	0.42	Vn-VN	0.0	77	54000039	%
40	4	179	180	181	0	0	O	On	ON	0	0	7.46	0.0	0.0	0.0	24.02	55.74	21.25	0.381	0.431	0.618	0.569	VN-Nv	0.431	78	54000040	%
																31.71	55.74	34.48	0.61	0.56	0.38	0.43	Nv-N	0.0	79	54000040	%
41	4	189	190	191	0	0	Y	Yn	YN	0	0	7.3	0.0	0.0	0.0	37.45	70.66	23.38	0.33	0.53	0.669	0.469	M-Mn	0.53	80	54000041	%
																33.21	70.66	47.27	0.66	0.46	0.33	0.53	Mn-MN	0.0	81	54000041	%



Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF>
 Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

TUB-Registrierung: 20140801-XG50/XG50LONP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/XG50/XG50LONP.PDF> / .PS
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*00	SUM	DV*v	DVvr	DV00	dVvr	dV00	CODE	VIM	iaa	inr	%
27	5	114	115	116	117	118	W	Wm	CW	Mw	M	22.45	13.14	11.13	12.4	13.21	59.13	22.45	0.379	0.223	0.62	0.776	W-Wm	0.223	58	43000027	%
																							Wm-MW	0.473	57	43000027	%
																							MW-Mw	0.691	1	43000027	%
																							Mw-M	0.0	59	43000027	%
																							W-Wo	0.244	62	43000028	%
																							Wo-OW	0.47	61	43000028	%
																							OW-OW	0.688	1	43000028	%
																							OW-O	0.0	63	43000028	%
																							W-Wy	0.241	66	43000029	%
																							Wy-YW	0.508	65	43000029	%
																							YW-Yw	0.811	1	43000029	%
																							Yw-Y	0.0	67	43000029	%
																							W-Wl	0.217	70	43000030	%
																							Wl-LW	0.451	69	43000030	%
																							LW-Lw	0.697	1	43000030	%
																							Lw-L	0.0	71	43000030	%
																							C-Cn	0.276	74	43000031	%
																							Cn-CN	0.505	73	43000031	%
																							CN-Nc	0.758	1	43000031	%
																							Nc-N	0.0	75	43000031	%
																							V-Vn	0.17	78	43000032	%
																							Vn-VN	0.492	77	43000032	%
																							VN-Nv	0.833	1	43000032	%
																							Nv-N	0.0	79	43000032	%
																							M-Mn	0.282	82	43000033	%
																							Mn-MN	0.5	81	43000033	%
																							MN-Nm	0.732	1	43000033	%
																							Nm-N	0.0	83	43000033	%
																							O-On	0.282	86	43000034	%
																							On-ON	0.482	85	43000034	%
																							ON-No	0.71	1	43000034	%
																							No-N	0.0	87	43000034	%
																							Y-Yn	0.299	90	43000035	%
																							Yn-YN	0.5	89	43000035	%
																							YN-Ny	0.702	1	43000035	%
																							Ny-N	0.0	91	43000035	%
																							L-Ln	0.272	94	43000036	%
																							Ln-LN	0.451	93	43000036	%
																							LN-Nl	0.704	1	43000036	%
																							Nl-N	0.0	95	43000036	%
																							CV-C	0.511	96	43000037	%
																							CV-V	0.0	97	43000037	%
																							VM-V	0.541	98	43000038	%
																							VM-M	0.0	99	43000038	%
																							MO-M	0.594	100	43000039	%
																							MO-O	0.0	101	43000039	%
																							YO-O	0.47	102	43000040	%
																							YO-Y	0.0	103	43000040	%
																							YL-Y	0.528	104	43000041	%
																							YL-L	0.0	105	43000041	%



TUB-Registrierung: 20140801-XG50/XG50LONP.PDF / .PS
Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation
TUB-Material: Code=rh4ta



Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*00	SUM	DV*v	DVvr	DV00	dVvr	dV00	CODE	VIM	ia	inr	%
1	3	1	2	3	0	0	W	CW	C	0	0	25.14	15.74	0.0	0.0	20.68	40.88	25.14	0.615	0.505	0.384	0.494	CW_W	0.505	0	44000001	%
2	3	7	8	9	0	0	W	VW	V	0	0	33.65	29.18	0.0	0.0	20.19	40.88	15.74	0.38	0.49	0.61	0.5	CW-C	0.0	1	44000001	%
3	3	13	14	15	0	0	W	MW	M	0	0	29.72	29.18	0.0	0.0	33.11	62.83	33.65	0.535	0.527	0.464	0.473	VW-W	0.527	2	44000002	%
4	3	19	20	21	0	0	W	OW	O	0	0	25.04	21.27	0.0	0.0	29.72	62.83	29.18	0.46	0.47	0.53	0.52	VW-V	0.0	3	44000002	%
5	3	25	26	27	0	0	W	YW	Y	0	0	25.86	21.27	0.0	0.0	25.04	50.9	29.63	0.582	0.508	0.417	0.491	MW-W	0.508	4	44000003	%
6	3	31	32	33	0	0	W	LW	L	0	0	23.23	18.85	0.0	0.0	25.04	50.9	21.27	0.41	0.49	0.58	0.5	MW-M	0.0	5	44000003	%
7	3	37	38	39	0	0	C	CN	N	0	0	23.23	18.85	0.0	0.0	26.73	49.97	21.55	0.43	0.53	0.56	0.46	OW-O	0.0	7	44000004	%
8	3	43	44	45	0	0	V	VN	N	0	0	18.38	9.02	0.0	0.0	11.92	27.41	18.38	0.67	0.565	0.329	0.435	YW-W	0.565	8	44000005	%
9	3	49	50	51	0	0	M	MN	N	0	0	11.92	9.02	0.0	0.0	11.92	27.41	9.02	0.32	0.43	0.67	0.56	YW-Y	0.0	9	44000005	%
10	3	55	56	57	0	0	O	ON	N	0	0	22.75	18.85	0.0	0.0	21.3	41.61	22.75	0.546	0.512	0.453	0.487	LW-W	0.512	10	44000006	%
11	3	61	62	63	0	0	Y	YN	N	0	0	20.3	18.85	0.0	0.0	20.3	41.61	18.85	0.45	0.48	0.54	0.51	LW-L	0.0	11	44000006	%
12	3	67	68	69	0	0	L	LN	N	0	0	9.26	16.15	0.0	0.0	11.3	25.41	9.26	0.364	0.438	0.635	0.562	CN-C	0.438	12	44000007	%
13	3	209	210	211	0	0	W	C	N	0	0	14.28	16.15	0.0	0.0	14.28	25.41	16.15	0.63	0.56	0.36	0.43	CN-N	0.0	13	44000007	%
14	3	215	216	217	0	0	W	V	N	0	0	20.4	16.26	0.0	0.0	20.4	42.07	16.26	0.386	0.484	0.613	0.515	VN-V	0.484	14	44000008	%
15	3	221	222	223	0	0	W	M	N	0	0	21.67	25.81	0.0	0.0	21.67	42.07	25.81	0.61	0.51	0.38	0.48	VN-N	0.0	15	44000008	%
16	3	227	228	229	0	0	W	O	N	0	0	19.86	16.38	0.0	0.0	19.86	40.79	16.38	0.401	0.487	0.598	0.513	MN-M	0.487	16	44000009	%
17	3	233	234	235	0	0	W	Y	N	0	0	20.92	24.4	0.0	0.0	20.92	40.79	24.4	0.59	0.51	0.4	0.48	MN-N	0.0	17	44000009	%
18	3	239	240	241	0	0	W	L	N	0	0	19.57	16.38	0.0	0.0	19.57	40.79	16.38	0.401	0.48	0.598	0.52	ON-O	0.48	18	44000010	%
19	3	245	246	247	0	0	C	V	M	0	0	21.21	24.4	0.0	0.0	21.21	40.79	24.4	0.59	0.52	0.4	0.48	ON-N	0.0	19	44000010	%
20	3	251	252	253	0	0	M	O	Y	0	0	28.34	32.37	0.0	0.0	28.34	60.69	28.32	0.466	0.467	0.533	0.533	YN-Y	0.467	20	44000011	%
21	3	257	258	259	0	0	Y	L	C	0	0	32.35	32.37	0.0	0.0	32.35	60.69	32.37	0.53	0.53	0.46	0.46	YN-N	0.0	21	44000011	%
22	3	263	264	265	0	0	V	C	L	0	0	19.28	17.18	0.0	0.0	19.28	39.51	17.18	0.434	0.488	0.565	0.511	LN-L	0.488	22	44000012	%
23	3	269	270	271	0	0	L	Y	O	0	0	20.23	22.32	0.0	0.0	20.23	39.51	22.32	0.56	0.51	0.43	0.48	LN-N	0.0	23	44000012	%
24	3	275	276	277	0	0	O	M	V	0	0	35.69	38.07	0.0	0.0	35.69	79.5	38.07	0.478	0.448	0.521	0.551	C-W	0.448	24	44000013	%
25	4	89	90	91	0	0	W	Wc	CW	0	0	43.8	41.43	0.0	0.0	43.8	79.5	41.43	0.52	0.55	0.47	0.44	C-N	0.0	25	44000013	%
26	4	99	100	101	0	0	W	Wv	CW	0	0	51.66	23.97	0.0	0.0	51.66	87.42	63.45	0.725	0.591	0.274	0.408	V-W	0.591	26	44000014	%


TUB-Registrierung: 20140801-XG50/XG50L0NP.PDF /.PS Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation TUB-Material: Code=rha4ta



Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>
 Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/XG50/XG50.HTM>

N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*00	SUM	DV*v	DVvr	DV00	dVvr	dV00	CODE	VIM	ia	inr	%
%1000*(CIEXYZ & DV) for all colours (a) of experiment, iimp=98, colour difference pairs MA_LD098=MEL_ADJACENT, xchart3=1, xchart4=3 %																											
27	4	109	110	111	0	0	W	Wm	CW	0	0	7.54	0.0	0.0	0.0	27.95	55.24	21.75	0.393	0.505	0.606	0.494	W-Wv	0.505	52	44000027	%
27																27.29	55.24	33.49	0.6	0.49	0.39	0.5	Wv-VW	0.0	53	44000027	%
28	4	119	120	121	0	0	W	Wo	CW	0	0	6.9	0.0	0.0	0.0	27.1	51.62	19.43	0.376	0.525	0.623	0.474	VW-Vw	0.525	54	44000028	%
28																24.52	51.62	32.18	0.62	0.47	0.37	0.52	Vw-V	0.0	55	44000028	%
29	4	129	130	131	0	0	W	Wy	CW	0	0	4.43	0.0	0.0	0.0	14.01	28.66	11.17	0.389	0.489	0.61	0.511	W-Wm	0.489	56	44000029	%
29																14.64	28.66	17.48	0.61	0.51	0.38	0.48	Wm-MW	0.0	57	44000029	%
30	4	139	140	141	0	0	W	Wl	CW	0	0	6.33	0.0	0.0	0.0	21.41	43.88	13.83	0.315	0.488	0.684	0.511	MW-Mw	0.488	58	44000030	%
30																22.46	43.88	30.04	0.68	0.51	0.31	0.48	Mw-M	0.0	59	44000030	%
31	4	91	92	93	0	0	CW	Cw	C	0	0	6.54	0.0	0.0	0.0	11.36	19.76	10.33	0.522	0.575	0.477	0.425	W-Wo	0.575	60	44000031	%
31																8.39	19.76	9.42	0.47	0.42	0.52	0.57	Wo-OW	0.0	61	44000031	%
32	4	101	102	103	0	0	VW	Vw	V	0	0	9.86	0.0	0.0	0.0	3.93	8.44	3.55	0.42	0.466	0.579	0.534	OW-Ow	0.466	62	44000032	%
32																4.51	8.44	4.89	0.57	0.53	0.42	0.46	Ow-O	0.0	63	44000032	%
33	4	111	112	113	0	0	MW	Mw	M	0	0	7.92	0.0	0.0	0.0	9.27	16.16	8.29	0.513	0.574	0.486	0.426	W-Wy	0.574	64	44000033	%
33																6.88	16.16	7.87	0.48	0.42	0.51	0.57	Wy-YW	0.0	65	44000033	%
34	4	121	122	123	0	0	OW	Ow	O	0	0	8.95	0.0	0.0	0.0	9.51	16.72	8.45	0.505	0.569	0.494	0.431	YW-Yw	0.569	66	44000034	%
34																7.2	16.72	8.27	0.49	0.43	0.5	0.56	Yw-Y	0.0	67	44000034	%
35	4	131	132	133	0	0	YW	Yw	Y	0	0	3.02	0.0	0.0	0.0	14.61	28.82	12.58	0.436	0.507	0.563	0.492	W-Wl	0.507	68	44000035	%
35																14.2	28.82	16.23	0.56	0.49	0.43	0.5	Wl-LW	0.0	69	44000035	%
36	4	141	142	143	0	0	LW	Lw	L	0	0	6.98	0.0	0.0	0.0	9.03	16.82	8.56	0.509	0.537	0.49	0.463	LW-Lw	0.537	70	44000036	%
36																7.79	16.82	8.25	0.49	0.46	0.5	0.53	Lw-L	0.0	71	44000036	%
37	4	149	150	151	0	0	C	Cn	CN	0	0	6.41	0.0	0.0	0.0	15.98	36.57	8.29	0.226	0.437	0.773	0.562	C-Cn	0.437	72	44000037	%
37																20.59	36.57	28.28	0.77	0.56	0.22	0.43	Cn-CN	0.0	73	44000037	%
38	4	159	160	161	0	0	V	Vn	VN	0	0	2.6	0.0	0.0	0.0	12.93	31.63	15.42	0.487	0.409	0.512	0.59	CN-Nc	0.409	74	44000038	%
38																18.69	31.63	16.2	0.51	0.59	0.48	0.4	Nc-N	0.0	75	44000038	%
39	4	169	170	171	0	0	M	Mn	MN	0	0	6.63	0.0	0.0	0.0	14.46	33.88	10.49	0.309	0.427	0.69	0.572	V-Vn	0.427	76	44000039	%
39																19.41	33.88	23.39	0.69	0.57	0.3	0.42	Vn-VN	0.0	77	44000039	%
40	4	179	180	181	0	0	O	On	ON	0	0	7.46	0.0	0.0	0.0	14.92	34.63	10.97	0.316	0.431	0.683	0.569	VN-Nv	0.431	78	44000040	%
40																19.7	34.63	23.65	0.68	0.56	0.31	0.43	Nv-N	0.0	79	44000040	%
41	4	189	190	191	0	0	Y	Yn	YN	0	0	7.3	0.0	0.0	0.0	18.23	34.4	6.3	0.183	0.53	0.816	0.469	M-Mn	0.53	80	44000041	%
41																16.17	34.4	28.09	0.81	0.46	0.18	0.53	Mn-MN	0.0	81	44000041	%

TUB-Registrierung: 20140801-XG50/XG50LONP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation



Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>


N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*vi	SUM	DV*v	DVvr	DVvi	dVvr	dVvi	CODE	VIM	ia	inr	
1	3	1	2	3	0	0	W	CW	C	0	0	6.56	6.54	26.45	26.38	5.68	13.11	6.56	0.5	0.433	0.499	0.566	CW_W	0.433	0	61000001	
2	3	7	8	9	0	0	W	VW	V	0	0	7.23	9.86	29.54	41.94	7.72	17.09	7.23	0.423	0.452	0.576	0.547	VW-W	0.452	1	61000001	
3	3	13	14	15	0	0	W	MW	M	0	0	7.54	7.92	31.0	32.73	6.64	15.47	7.54	0.487	0.429	0.512	0.57	MW-W	0.429	2	61000002	
4	3	19	20	21	0	0	W	OW	O	0	0	6.9	8.95	28.0	37.63	8.82	15.47	7.92	0.51	0.57	0.48	0.42	OW-W	0.0	3	61000002	
5	3	25	26	27	0	0	W	YW	Y	0	0	4.43	3.02	16.98	11.01	9.02	15.86	8.95	0.56	0.56	0.43	0.43	OW-O	0.0	4	61000003	
6	3	31	32	33	0	0	W	LW	L	0	0	6.33	6.98	25.44	28.39	6.39	13.32	6.33	0.475	0.48	0.524	0.52	LW-W	0.48	5	61000003	
7	3	37	38	39	0	0	C	CN	N	0	0	6.41	8.5	25.79	35.46	6.92	13.32	6.41	0.43	0.542	0.569	0.457	CN-C	0.542	6	61000004	
8	3	43	44	45	0	0	V	VN	N	0	0	2.6	4.35	9.3	16.62	6.82	14.92	8.5	0.56	0.45	0.43	0.54	CN-N	0.0	7	61000004	
9	3	49	50	51	0	0	M	MN	N	0	0	6.63	7.26	26.79	29.68	2.76	6.96	4.35	0.62	0.39	0.37	0.6	VN-V	0.602	8	61000004	
10	3	55	56	57	0	0	O	ON	N	0	0	7.46	8.31	30.61	34.58	7.15	13.9	6.63	0.477	0.515	0.522	0.485	MN-M	0.515	9	61000005	
11	3	61	62	63	0	0	Y	YN	N	0	0	7.3	9.82	29.85	41.76	6.74	13.9	7.26	0.52	0.48	0.47	0.51	MN-N	0.0	10	61000005	
12	3	67	68	69	0	0	L	LN	N	0	0	4.85	8.42	18.78	35.11	8.2	15.78	7.46	0.473	0.52	0.526	0.48	ON-O	0.52	11	61000006	
13	3	209	210	211	0	0	W	C	N	0	0	14.35	13.82	64.16	61.49	7.57	15.78	8.31	0.52	0.48	0.47	0.52	ON-N	0.0	12	61000006	
14	3	215	216	217	0	0	W	V	N	0	0	14.91	7.95	67.03	32.9	8.34	17.12	7.3	0.426	0.487	0.573	0.512	YN-Y	0.487	13	61000007	
15	3	221	222	223	0	0	W	M	N	0	0	16.37	13.77	74.47	61.26	8.78	17.12	9.82	0.57	0.51	0.42	0.48	YN-N	0.0	14	61000007	
16	3	227	228	229	0	0	W	O	N	0	0	15.84	14.95	71.76	67.2	6.45	13.27	8.42	0.63	0.48	0.36	0.51	LN-L	0.513	15	61000008	
17	3	233	234	235	0	0	W	Y	N	0	0	8.88	18.6	37.26	86.09	12.72	28.17	14.35	0.509	0.451	0.49	0.548	C-W	0.451	16	61000008	
18	3	239	240	241	0	0	W	L	N	0	0	11.69	12.74	50.88	56.1	15.45	28.17	13.82	0.49	0.54	0.5	0.45	C-N	0.0	17	61000009	
19	3	245	246	247	0	0	C	V	M	0	0	9.8	10.49	41.67	45.01	8.64	22.87	14.91	0.652	0.622	0.347	0.377	V-W	0.622	18	61000009	
20	3	251	252	253	0	0	M	O	Y	0	0	6.98	15.95	28.4	72.31	16.36	30.15	13.77	0.45	0.54	0.54	0.45	W-N	0.0	19	61000010	
21	3	257	258	259	0	0	Y	L	C	0	0	14.47	9.6	64.79	40.72	14.29	30.79	15.84	0.514	0.464	0.485	0.535	O-W	0.464	20	61000010	
22	3	263	264	265	0	0	V	C	L	0	0	9.8	9.6	41.67	40.72	16.49	30.79	14.95	0.48	0.53	0.51	0.46	O-N	0.0	21	61000011	
23	3	269	270	271	0	0	L	Y	O	0	0	14.47	15.95	64.79	72.31	9.52	27.48	8.88	0.323	0.346	0.676	0.653	Y-W	0.346	22	61000011	
24	3	275	276	277	0	0	O	M	V	0	0	6.98	10.49	28.4	45.01	17.96	27.48	18.6	0.67	0.65	0.32	0.34	Y-N	0.0	23	61000012	
25	5	89	90	91	92	93	W	Wc	CW	Cw	C	2.96	3.18	3.08	5.11	12.2	24.44	11.69	0.478	0.499	0.521	0.5	L-W	0.499	24	61000012	
26	5	99	100	101	102	103	W	Wv	CW	Vw	V	3.52	3.54	3.3	4.53	12.23	24.44	12.74	0.52	0.5	0.47	0.49	L-N	0.0	25	61000012	

TUB-Registrierung: 20140801-XG50/XG50LONP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation

Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*vi	SUM	DV*v	DVvr	DVvi	dVvr	dVvi	CODE	VIM	ia	inr	%
%1000*(CIEXYZ & DV) for all colours (a) of experiment, iimp=104, colour difference pairs VA_LV106=VIK_ADJACENT, xchart3=2, xchart4=0 %																											
27	5	109	110	111	112	113	W	Wm	CW	Mw	M	3.78	3.89	3.61	5.07	3.78	16.37	3.78	0.231	0.231	0.768	0.768	W-Wm	0.231	58	61000027	%
(Additional rows for N=27, N=28, N=29, N=30, N=31, N=32, N=33, N=34, N=35, N=36, N=37, N=38, N=39, N=40, N=41 follow similar structure with varying values for DV and SUM)																											

TUB-Registrierung: 20140801-XG50/XG50LONP.PDF /.PS
 Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation
 TUB-Material: Code=rh4ta





N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*vi	SUM	DV*v	DVvr	DVvi	dVvr	dVvi	CODE	VIM	iaa	inr	%	
27	5	109	110	111	112	113	W	Wm	CW	Mw	M	4.18	3.56	3.85	4.76	4.18	16.37	4.18	0.255	0.255	0.744	0.744	W-Wm	0.255	58	62000027	%	
																	3.56	16.37	3.56	0.21	0.21	0.78	0.78	Wm-MW	0.473	57	62000027	%
																	3.85	16.37	3.85	0.23	0.23	0.76	0.76	MW-Mw	0.708	1	62000027	%
																	4.76	16.37	4.76	0.29	0.29	0.7	0.7	Mw-M	0.0	59	62000027	%
28	5	119	120	121	122	123	W	Wo	CW	Ow	O	3.58	3.49	3.84	4.92	3.58	15.84	3.58	0.226	0.226	0.773	0.773	W-Wo	0.226	62	62000028	%	
																	3.49	15.84	3.49	0.22	0.22	0.77	0.77	Wo-OW	0.447	61	62000028	%
																	3.84	15.84	3.84	0.24	0.24	0.75	0.75	OW-Ow	0.689	1	62000028	%
																	4.92	15.84	4.92	0.31	0.31	0.68	0.68	Ow-O	0.0	63	62000028	%
29	5	129	130	131	132	133	W	Wy	CW	Yw	Y	2.08	2.0	2.29	2.49	2.08	8.88	2.08	0.235	0.235	0.764	0.764	W-Wy	0.235	66	62000029	%	
																	2.0	8.88	2.0	0.22	0.22	0.77	0.77	Wy-YW	0.46	65	62000029	%
																	2.29	8.88	2.29	0.25	0.25	0.74	0.74	YW-Yw	0.718	1	62000029	%
																	2.49	8.88	2.49	0.28	0.28	0.71	0.71	Yw-Y	0.0	67	62000029	%
30	5	139	140	141	142	143	W	Wl	CW	Lw	L	2.94	2.47	2.71	3.55	2.94	11.69	2.94	0.251	0.251	0.748	0.748	W-Wl	0.251	70	62000030	%	
																	2.47	11.69	2.47	0.21	0.21	0.78	0.78	Wl-LW	0.463	69	62000030	%
																	2.71	11.69	2.71	0.23	0.23	0.76	0.76	LW-Lw	0.695	1	62000030	%
																	3.55	11.69	3.55	0.3	0.3	0.69	0.69	Lw-L	0.0	71	62000030	%
31	5	149	150	151	152	153	C	Cn	CN	Nc	N	3.94	3.13	3.48	3.26	3.94	13.82	3.94	0.285	0.285	0.714	0.714	C-Cn	0.285	74	62000031	%	
																	3.13	13.82	3.13	0.22	0.22	0.77	0.77	Cn-CN	0.511	73	62000031	%
																	3.48	13.82	3.48	0.25	0.25	0.74	0.74	CN-Nc	0.763	1	62000031	%
																	3.26	13.82	3.26	0.23	0.23	0.76	0.76	Nc-N	0.0	75	62000031	%
32	5	159	160	161	162	163	V	Vn	VN	Nv	N	1.73	2.1	2.41	1.7	1.73	7.95	1.73	0.217	0.217	0.782	0.782	V-Vn	0.217	78	62000032	%	
																	2.1	7.95	2.1	0.26	0.26	0.73	0.73	Vn-VN	0.482	77	62000032	%
																	2.41	7.95	2.41	0.3	0.3	0.69	0.69	VN-Nv	0.785	1	62000032	%
																	1.7	7.95	1.7	0.21	0.21	0.78	0.78	Nv-N	0.0	79	62000032	%
33	5	169	170	171	172	173	M	Mn	MN	Nm	N	4.01	3.17	2.65	3.93	4.01	13.77	4.01	0.291	0.291	0.708	0.708	M-Mn	0.291	82	62000033	%	
																	3.17	13.77	3.17	0.23	0.23	0.76	0.76	Mn-MN	0.521	81	62000033	%
																	2.65	13.77	2.65	0.19	0.19	0.8	0.8	MN-Nm	0.714	1	62000033	%
																	3.93	13.77	3.93	0.28	0.28	0.71	0.71	Nm-N	0.0	83	62000033	%
34	5	179	180	181	182	183	O	On	ON	No	N	4.24	2.96	3.56	4.17	4.24	14.95	4.24	0.284	0.284	0.715	0.715	O-On	0.284	86	62000034	%	
																	2.96	14.95	2.96	0.19	0.19	0.8	0.8	On-ON	0.482	85	62000034	%
																	3.56	14.95	3.56	0.23	0.23	0.76	0.76	ON-No	0.72	1	62000034	%
																	4.17	14.95	4.17	0.27	0.27	0.72	0.72	No-N	0.0	87	62000034	%
35	5	189	190	191	192	193	Y	Yn	YN	Ny	N	5.09	4.05	3.5	5.96	5.09	18.6	5.09	0.273	0.273	0.726	0.726	Y-Yn	0.273	90	62000035	%	
																	4.05	18.6	4.05	0.21	0.21	0.78	0.78	Yn-YN	0.491	89	62000035	%
																	3.5	18.6	3.5	0.18	0.18	0.81	0.81	YN-Ny	0.679	1	62000035	%
																	5.96	18.6	5.96	0.32	0.32	0.67	0.67	Ny-N	0.0	91	62000035	%
36	5	199	200	201	202	203	L	Ln	LN	Nl	N	3.44	2.41	3.5	3.37	3.44	12.74	3.44	0.27	0.27	0.729	0.729	L-Ln	0.27	94	62000036	%	
																	2.41	12.74	2.41	0.18	0.18	0.81	0.81	Ln-LN	0.46	93	62000036	%
																	3.5	12.74	3.5	0.27	0.27	0.72	0.72	LN-Nl	0.735	1	62000036	%
																	3.37	12.74	3.37	0.26	0.26	0.73	0.73	Nl-N	0.0	95	62000036	%
37	3	281	282	283	0	0	C	CV	V	0	0	9.8	0.0	41.67	0.0	4.67	9.8	9.8	0.999	0.476	0.0	0.523	CV-C	0.476	96	62000037	%	
																	5.13	9.8	0.0	0.0	0.52	1.0	0.47	CV-V	0.0	97	62000037	%
38	3	283	284	285	0	0	V	MV	M	0	0	10.49	0.0	45.01	0.0	5.52	10.49	10.49	0.999	0.526	0.0	0.473	VM-V	0.526	98	62000038	%	
																	4.96	10.49	0.0	0.0	0.47	1.0	0.52	VM-M	0.0	99	62000038	%
39	3	291	292	293	0	0	M	MO	O	0	0	6.98	0.0	28.4	0.0	4.24	6.98	6.98	0.999	0.607	0.0	0.392	MO-M	0.607	100	62000039	%	
																	2.74	6.98	0.0	0.0	0.39	1.0	0.6	MO-O	0.0	101	62000039	%
40	3	293	294	295	0	0	O	YO	Y	0	0	15.95	0.0	72.31	0.0	7.97	15.95	15.95	0.999	0.5	0.0	0.5	YO-O	0.5	102	62000040	%	
																	7.97	15.95	0.0	0.0	0.5	1.0	0.5	YO-Y	0.0	103	62000040	%
41	3	301	302	303	0	0	Y	YL	L	0	0	14.47	0.0	64.79	0.0	7.61	14.47	14.47	0.999	0.525	0.0	0.474	YL-Y	0.525	104	62000041	%	
																	6.86	14.47	0.0	0.0	0.47	1.0	0.52	YL-L	0.0	105	62000041	%

Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*vi	SUM	DV*v	DVvr	DVvi	dVvr	dVvi	CODE	VIM	ia	inr	%
1	3	4	5	6	0	0	W	CW	C	0	0	6.56	6.54	26.45	26.38	6.47	13.11	6.56	0.5	0.494	0.499	0.505	CW_W	0.494	0	63000001	%
2	3	10	11	12	0	0	W	VW	V	0	0	7.23	9.86	29.54	41.94	6.63	13.11	6.54	0.49	0.5	0.5	0.49	CW-C	0.0	1	63000001	%
3	3	16	17	18	0	0	W	MW	M	0	0	7.54	7.92	31.0	32.73	7.55	17.09	7.23	0.423	0.441	0.576	0.558	VW-W	0.441	2	63000002	%
4	3	22	23	24	0	0	W	OW	O	0	0	6.9	8.95	28.0	37.63	9.54	17.09	9.86	0.57	0.55	0.42	0.44	VW-V	0.0	3	63000002	%
5	3	28	29	30	0	0	W	YW	Y	0	0	4.43	3.02	16.98	11.01	8.28	15.47	7.54	0.487	0.464	0.512	0.535	MW-W	0.464	4	63000003	%
6	3	34	35	36	0	0	W	LW	L	0	0	6.33	6.98	25.44	28.39	8.49	15.86	6.9	0.435	0.464	0.564	0.535	OW-W	0.464	5	63000004	%
7	3	40	41	42	0	0	C	CN	N	0	0	6.41	8.5	25.79	35.46	3.79	7.46	3.02	0.4	0.5	0.59	0.49	OW-O	0.0	7	63000004	%
8	3	46	47	48	0	0	V	VN	N	0	0	2.6	4.35	9.3	16.62	3.66	7.46	4.43	0.594	0.491	0.405	0.508	YW-W	0.491	8	63000005	%
9	3	52	53	54	0	0	M	MN	N	0	0	6.63	7.26	26.79	29.68	3.79	7.46	3.02	0.4	0.5	0.59	0.49	YW-Y	0.0	9	63000005	%
10	3	58	59	60	0	0	O	ON	N	0	0	7.46	8.31	30.61	34.58	6.31	13.32	6.33	0.475	0.473	0.524	0.526	LW-W	0.473	10	63000006	%
11	3	64	65	66	0	0	Y	YN	N	0	0	7.3	9.82	29.85	41.76	7.01	13.32	6.98	0.52	0.52	0.47	0.47	LW-L	0.0	11	63000006	%
12	3	70	71	72	0	0	L	LN	N	0	0	4.85	8.42	18.78	35.11	7.28	14.92	6.41	0.43	0.488	0.569	0.511	CN-C	0.488	12	63000007	%
13	3	212	213	214	0	0	W	C	N	0	0	14.35	13.82	64.16	61.49	7.63	14.92	8.5	0.56	0.51	0.43	0.48	CN-N	0.0	13	63000007	%
14	3	218	219	220	0	0	W	V	N	0	0	14.91	7.95	67.03	32.9	3.45	6.96	2.6	0.374	0.497	0.625	0.502	VN-V	0.497	14	63000008	%
15	3	224	225	226	0	0	W	M	N	0	0	16.37	13.77	74.47	61.26	3.5	6.96	4.35	0.62	0.5	0.37	0.49	VN-N	0.0	15	63000008	%
16	3	230	231	232	0	0	W	O	N	0	0	15.84	14.95	71.76	67.2	7.44	13.9	6.63	0.477	0.535	0.522	0.464	MN-M	0.535	16	63000009	%
17	3	236	237	238	0	0	W	Y	N	0	0	8.88	18.6	37.26	86.09	6.46	13.9	7.26	0.52	0.46	0.47	0.53	MN-N	0.0	17	63000009	%
18	3	242	243	244	0	0	W	L	N	0	0	11.69	12.74	50.88	56.1	7.93	15.78	7.46	0.473	0.502	0.526	0.497	ON-O	0.502	18	63000010	%
19	3	248	249	250	0	0	C	V	M	0	0	9.8	10.49	41.67	45.01	7.84	15.78	8.31	0.52	0.49	0.47	0.5	ON-N	0.0	19	63000010	%
20	3	254	255	256	0	0	M	O	Y	0	0	6.98	15.95	28.4	72.31	8.0	17.12	7.3	0.426	0.467	0.573	0.532	YN-Y	0.467	20	63000011	%
21	3	260	261	262	0	0	Y	L	C	0	0	14.47	9.6	64.79	40.72	9.11	17.12	9.82	0.57	0.53	0.42	0.42	YN-N	0.0	21	63000011	%
22	3	266	267	268	0	0	V	C	L	0	0	9.8	9.6	41.67	40.72	5.7	13.27	4.85	0.365	0.429	0.634	0.56	LN-L	0.429	22	63000012	%
23	3	272	273	274	0	0	L	Y	O	0	0	14.47	15.95	64.79	72.31	7.57	13.27	8.42	0.63	0.57	0.36	0.42	LN-N	0.0	23	63000012	%
24	3	278	279	280	0	0	O	M	V	0	0	6.98	10.49	28.4	45.01	12.92	28.17	13.82	0.49	0.54	0.5	0.45	C-N	0.0	24	63000013	%
25	5	94	95	96	97	98	W	Wc	CW	Cw	C	3.2	3.63	2.99	4.51	12.92	28.17	13.82	0.49	0.54	0.5	0.45	C-N	0.0	25	63000013	%
26	5	104	105	106	107	108	W	Wv	CW	Vw	V	3.11	3.9	3.64	4.25	15.24	28.17	13.82	0.49	0.54	0.5	0.45	C-N	0.0	26	63000014	%

TUB-Registrierung: 20140801-XG50/XG50LONP.PDF /.PS TUB-Material: Code=rh4ta
 Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation



Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/XG50/XG50L0NP.PDF> / .PS
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

N	S	N1	N2	N3	N4	N5	NA1	NA2	NA3	NA4	NA5	DV*1	DV*2	DV*3	DV*4	DV*vi	SUM	DV*v	DVvr	DVvi	dVvr	dVvi	CODE	VIM	ia	inr	%
%1000*(CIEXYZ & DV) for all colours (a) of experiment, iimp=96, colour difference pairs MA_LV096=MEL_ADJACENT, xchart3=2, xchart4=3 %																											
27	4	109	110	111	0	0	W	Wm	CW	0	0	7.54	0.0	31.0	0.0	3.82	7.54	3.82	0.505	0.505	0.494	0.494	W-Wv	0.505	52	64000027	%
3.72 7.54 3.72 0.49 0.49 0.5 0.5 Wv-VW 0.0 53 64000027 %																											
28	4	119	120	121	0	0	W	Wo	CW	0	0	6.9	0.0	28.0	0.0	3.62	6.9	3.62	0.525	0.525	0.475	0.474	VW-Vw	0.525	54	64000028	%
3.27 6.9 3.27 0.47 0.47 0.52 0.52 Vw-V 0.0 55 64000028 %																											
29	4	129	130	131	0	0	W	Wy	CW	0	0	4.43	0.0	16.98	0.0	2.17	4.43	2.17	0.488	0.489	0.511	0.511	W-Wm	0.489	56	64000029	%
2.26 4.43 2.26 0.51 0.51 0.48 0.48 Wm-MW 0.0 57 64000029 %																											
30	4	139	140	141	0	0	W	Wl	CW	0	0	6.33	0.0	25.44	0.0	3.09	6.33	3.09	0.487	0.488	0.512	0.511	MW-Mw	0.488	58	64000030	%
3.24 6.33 3.24 0.51 0.51 0.48 0.48 Mw-M 0.0 59 64000030 %																											
31	4	91	92	93	0	0	CW	Cw	C	0	0	6.54	0.0	26.38	0.0	3.76	6.54	3.76	0.574	0.575	0.425	0.425	W-Wo	0.575	60	64000031	%
2.78 6.54 2.78 0.42 0.42 0.57 0.57 Wo-OW 0.0 61 64000031 %																											
32	4	101	102	103	0	0	VW	Vw	V	0	0	9.86	0.0	41.94	0.0	4.59	9.86	4.59	0.465	0.466	0.534	0.534	OW-Ow	0.466	62	64000032	%
5.26 9.86 5.26 0.53 0.53 0.46 0.46 Ow-O 0.0 63 64000032 %																											
33	4	111	112	113	0	0	MW	Mw	M	0	0	7.92	0.0	32.73	0.0	4.54	7.92	4.54	0.573	0.574	0.426	0.426	W-Wy	0.574	64	64000033	%
3.37 7.92 3.37 0.42 0.42 0.57 0.57 Wy-YW 0.0 65 64000033 %																											
34	4	121	122	123	0	0	OW	Ow	O	0	0	8.95	0.0	37.63	0.0	5.09	8.95	5.09	0.568	0.569	0.431	0.431	YW-Yw	0.569	66	64000034	%
3.86 8.95 3.86 0.43 0.43 0.56 0.56 Yw-Y 0.0 67 64000034 %																											
35	4	131	132	133	0	0	YW	Yw	Y	0	0	3.02	0.0	11.01	0.0	1.53	3.02	1.53	0.506	0.507	0.493	0.492	W-Wl	0.507	68	64000035	%
1.49 3.02 1.49 0.49 0.49 0.5 0.5 Wl-LW 0.0 69 64000035 %																											
36	4	141	142	143	0	0	LW	Lw	L	0	0	6.98	0.0	28.39	0.0	3.75	6.98	3.75	0.536	0.537	0.463	0.463	LW-Lw	0.537	70	64000036	%
3.23 6.98 3.23 0.46 0.46 0.53 0.53 Lw-L 0.0 71 64000036 %																											
37	4	149	150	151	0	0	C	Cn	CN	0	0	6.41	0.0	25.79	0.0	2.8	6.41	2.8	0.436	0.437	0.563	0.562	C-Cn	0.437	72	64000037	%
3.61 6.41 3.61 0.56 0.56 0.43 0.43 Cn-CN 0.0 73 64000037 %																											
38	4	159	160	161	0	0	V	Vn	VN	0	0	2.6	0.0	9.3	0.0	1.06	2.6	1.06	0.408	0.409	0.591	0.59	CN-Nc	0.409	74	64000038	%
1.54 2.6 1.54 0.59 0.59 0.4 0.4 Nc-N 0.0 75 64000038 %																											
39	4	169	170	171	0	0	M	Mn	MN	0	0	6.63	0.0	26.79	0.0	2.83	6.63	2.83	0.426	0.427	0.573	0.572	V-Vn	0.427	76	64000039	%
3.8 6.63 3.8 0.57 0.57 0.42 0.42 Vn-VN 0.0 77 64000039 %																											
40	4	179	180	181	0	0	O	On	ON	0	0	7.46	0.0	30.61	0.0	3.21	7.46	3.21	0.43	0.431	0.569	0.569	VN-Nv	0.431	78	64000040	%
4.24 7.46 4.24 0.56 0.56 0.43 0.43 Nv-N 0.0 79 64000040 %																											
41	4	189	190	191	0	0	Y	Yn	YN	0	0	7.3	0.0	29.85	0.0	3.86	7.3	3.86	0.53	0.53	0.47	0.469	M-Mn	0.53	80	64000041	%
3.43 7.3 3.43 0.46 0.46 0.53 0.53 Mn-MN 0.0 81 64000041 %																											

TUB-Registrierung: 20140801-XG50/XG50L0NP.PDF /.PS TUB-Material: Code=rh4ta
Anwendung für Messung von Display- oder Drucker-Ausgabe, keine Separation

