

9stufige Grauskalierung zwischen $L^*_{0aN}=14.4$ und $L^*_{0aW}=125$, $Y_{0ref}=3.6$, Normierung: Grau U

$L^*_{0aN}=14.4$, $L^*_{0aU}=69.7$, $L^*_{0aW}=125.1$, $Y_{0aN}=1.8$, $Y_{0aU}=40.4$, $Y_{0aW}=180.0$, $C_{0aY}=Y_{0aW}:Y_{0aN}=100.0$
 $L^*_{tN}=26.6$, $L^*_{taU}=69.7$, $L^*_{taW}=122.0$, $Y_{taN}=4.9$, $Y_{taU}=40.4$, $Y_{taW}=168.5$, $C_{taY}=Y_{taW}:Y_{taN}=34.0$

Regularitätsindex nach ISO/IEC 15775:2022, Anhang G für 5 und 9 Stufen

$$g^* = 100 [\Delta L^*_{min}] / [\Delta L^*_{max}]$$

L^*	$g^*_5=99$, $g^*_9=99$				$g^*_5=71$, $g^*_9=61$					$g^*_5=94$, $g^*_9=91$		
	n0. i	L^*_{0a}	L^*_{0r}	Y_{0a}	Y_{0r}	L^*_{ta}	ΔL^*_{ta}	L^*_{tr}	Y_{ta}	$(L^*_{tr})^{1/1.15}$	L^*_{la}	ΔL^*_{la}
150	9	125.1	1.0	180.0	1.0	122.0	13.2	1.0	168.5	1.0	122.0	11.6
	8	111.3	0.875	132.0	0.731	108.8	13.2	0.861	124.5	0.878	110.4	11.8
100	7	97.4	0.75	93.5	0.514	95.6	13.0	0.723	89.1	0.754	98.6	12.0
	6	83.6	0.625	63.3	0.345	82.6	12.8	0.586	61.4	0.629	86.6	12.2
	5	69.7	0.5	40.4	0.217	69.7	12.5	0.452	40.4	0.501	74.4	12.3
	4	55.9	0.375	23.8	0.124	57.2	11.8	0.321	25.2	0.372	62.1	12.3
50	3	42.1	0.25	12.5	0.06	45.4	10.6	0.197	14.8	0.243	49.8	11.9
	2	28.2	0.125	5.5	0.021	34.8	8.2	0.086	8.4	0.118	37.9	11.3
0	1	14.4	0.0	1.8	0.0	26.6		0.0	4.9	0.0	26.6	

$$\Delta L^*_{ta}=13.8 \quad (i=1,2,\dots,9)$$

Normierung: $Y_{taiU}=Y_{0aU} \frac{Y_{0ai}+Y_{0ref}}{Y_{0aU}+Y_{0ref}}$