

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für D65, Y_N=3,6, Y_W=90, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
0 405 32 561	28.34	48.4	87.6	0.1724	0.2945	0.533	193.8	16 483	37 589	Cm	
6 435 32 562	25.69	48.95	72.52	0.1746	0.3326	0.4927	178.5	17 486	42 610		
10 450 32 563	21.01	49.59	44.25	0.1829	0.4317	0.3852	141.6	19 496	-1 496c		
12 460 33 565	19.15	49.94	29.98	0.1933	0.504	0.3026	124.2	21 505	-1 505c		
12 465 33 567	20.12	51.15	29.99	0.1987	0.5051	0.2961	122.8	21 506	-1 506c		
14 470 33 569	19.94	52.23	19.06	0.2186	0.5724	0.2089	111.1	24 520	-1 520c		
15 475 34 573	21.65	54.1	15.12	0.2382	0.5953	0.1664	105.6	25 528	-1 528c Gm		
16 480 36 580	25.4	57.45	12.12	0.2674	0.6048	0.1276	99.2	27 537	-1 537c		
17 485 39 595	35.62	64.35	9.93	0.3241	0.5855	0.0903	87.4	29 548	-1 548c		
18 490 -1 490c	63.02	76.18	8.3	0.4272	0.5164	0.0562	58.5	33 565	11 459	max	
19 495 -1 495c	62.98	75.01	7.04	0.4342	0.5171	0.0485	57.1	33 566	12 462		
20 500 -1 500c	62.97	73.55	6.07	0.4416	0.5158	0.0425	55.3	33 567	12 464		
22 510 -1 510c	62.87	69.55	4.8	0.4581	0.5068	0.035	50.6	33 569	13 469		
23 520 -1 519c	62.69	66.99	4.43	0.4674	0.4995	0.033	47.7	34 570	14 471	Ym	
25 530 -1 529c	61.81	60.81	3.97	0.4882	0.4803	0.0314	40.7	34 573	15 475		
27 540 -1 539c	60.05	53.7	3.73	0.511	0.4571	0.0318	32.8	35 577	15 478		
28 545 -1 544c	58.8	49.99	3.67	0.5228	0.4445	0.0326	28.7	35 579	15 479		
29 550 -1 549c	57.28	46.21	3.62	0.5347	0.4313	0.0338	24.7	36 582	16 480		
30 555 -1 554c	55.49	42.43	3.6	0.5465	0.4179	0.0354	20.8	36 584	16 481		
32 560 -1 560c	51.12	35.12	3.57	0.5691	0.391	0.0397	13.6	37 589	16 483		
32 561 0 405	57.19	41.59	10.39	0.5238	0.3809	0.0951	13.8	37 589	16 483	Rm	
32 562 6 435	59.84	41.04	25.47	0.4735	0.3248	0.2016	358.5	42 610	17 486		
32 563 10 450	64.52	40.4	53.74	0.4066	0.2546	0.3387	321.6	-1 496c	19 496		
33 565 12 460	66.38	40.05	68.01	0.3805	0.2295	0.3898	304.3	-1 505c	21 505		
33 567 12 465	65.41	38.84	68.01	0.3797	0.2254	0.3947	302.9	-1 506c	21 506		
33 569 14 470	65.59	37.76	78.93	0.3598	0.2071	0.433	291.1	-1 520c	24 520		
34 573 15 475	63.88	35.89	82.87	0.3497	0.1964	0.4537	285.6	-1 528c	25 528	Mm	
36 580 16 480	60.13	32.54	85.87	0.3367	0.1822	0.4809	279.3	-1 537c	27 537		
39 595 17 485	49.91	25.64	88.06	0.305	0.1567	0.5382	267.4	-1 548c	29 548		
-1 490c	18 490	22.51	13.81	89.7	0.1786	0.1096	0.7117	238.5	11 459	33 565	min
-1 495c	19 495	22.55	14.98	90.95	0.1755	0.1166	0.7078	237.1	12 462	33 566	
-1 500c	20 500	22.56	16.44	91.92	0.1723	0.1256	0.702	235.4	12 464	33 567	
-1 510c	22 510	22.66	20.44	93.19	0.1662	0.1499	0.6837	230.7	13 469	33 569	
-1 519c	23 510	22.84	23.0	93.56	0.1638	0.165	0.6711	227.7	14 471	34 570	Bm
-1 529c	25 530	22.72	29.18	94.02	0.1614	0.1986	0.6399	220.7	15 475	34 573	
-1 539c	27 540	25.48	36.29	94.26	0.1633	0.2325	0.604	212.8	15 478	35 577	
-1 544c	28 545	26.73	40.0	94.33	0.1659	0.2483	0.5856	208.8	15 479	35 579	
-1 549c	29 550	28.25	43.78	94.37	0.1697	0.2631	0.567	204.7	16 480	36 582	
-1 554c	30 555	30.04	47.56	94.4	0.1746	0.2765	0.5488	200.8	16 481	36 584	
-1 560c	32 560	34.41	54.87	94.43	0.1873	0.2986	0.5139	193.6	16 483	37 589	
W0	380 770	85.53	90.0	98.0	0.3127	0.329	0.3582	0.0			
N0	380 770	3.42	3.6	3.92	0.3127	0.329	0.3582	0.0			

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für D65, Y_N=3,6, Y_W=90, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A ₂	B _{c2}	C _{AB,2}	a ₂	b _{c2}	h _{xy,2}	i _d , λ _d	i _c , λ _c	Code
0 405 32 561	48.4	-48.88	-12.99	50.58	0.2119	-0.5427	194.8	16 483	37 589	Cm	
6 435 32 562	48.95	-51.61	-1.08	51.62	0.1941	-0.4443	181.2	17 486	42 610		
10 450 32 563	49.59	-55.42	20.8	59.2	0.1689	-0.2676	159.4	19 496	-1 496c		
12 460 33 565	49.94	-56.27	31.88	64.67	0.1652	-0.18	150.4	21 505	-1 505c		
12 465 33 567	51.15	-56.31	33.19	65.36	0.1756	-0.1758	149.4	21 506	-1 506c		
14 470 33 569	52.23	-55.65	42.56	70.06	0.1897	-0.1095	142.5	24 520	-1 520c		
15 475 34 573	54.1	-54.18	47.55	72.09	0.2153	-0.0838	138.7	25 528	-1 528c Gm		
16 480 36 580	57.45	-51.07	53.44	73.92	0.2603	-0.0633	133.6	27 537	-1 537c		
17 485 39 595	64.35	-40.27	62.61	74.44	0.3656	-0.0462	122.7	29 548	-1 548c		
18 490 -1 490c	76.18	-0.33	76.7	76.7	0.6141	-0.0326	90.2	33 565	11 459	max	
19 495 -1 495c	75.01	2.04	76.37	76.4	0.6268	-0.0281	88.4	33 566	12 462		
20 500 -1 500c	73.55	4.93	75.51	75.67	0.6427	-0.0247	86.2	33 567	12 464		
22 510 -1 510c	69.55	12.32	72.11	73.15	0.6867	-0.0207	80.3	33 569	13 469		
23 520 -1 519c	66.99	16.66	69.6	71.57	0.7154	-0.0198	76.5	34 570	14 471	Ym	
25 530 -1 529c	60.81	26.04	63.22	68.38	0.7872	-0.0196	67.6	34 573	15 475		
27 540 -1 539c	53.7	35.08	55.66	65.8	0.8772	-0.0208	57.7	35 577	15 478		
28 545 -1 544c	49.99	39.06	51.67	64.77	0.9284	-0.022	52.9	35 579	15 479		
29 550 -1 549c	46.21	42.56	47.58	63.84	0.9843	-0.0235	48.1	36 582	16 480		
30 555 -1 554c	42.43	45.44	43.49	62.9	1.0443	-0.0254	43.7	36 584	16 481		
32 560 -1 560c	35.12	48.98	35.56	60.52	1.1736	-0.0304	35.9	37 589	16 483		
32 561 0 405	41.59	48.88	37.48	61.6	1.086	-0.0749	37.4	37 589	16 483	Rm	
32 562 6 435	41.04	51.61	25.57	57.6	1.1189	-0.1861	26.3	42 610	17 486		
32 563 10 450	40.4	55.41	3.68	55.53	1.1645	-0.3989	3.8	-1 496c	19 496		
33 565 12 460	40.05	56.25	-7.38	56.73	1.1777	-0.5092	352.5	-1 505c	21 505		
33 567 12 465	38.84	56.29	-8.7	56.96	1.1956	-0.525	351.2	-1 506c	21 506		
33 569 14 470	37.76	55.63	-18.05	58.49	1.2052	-0.6267	342.0	-1 520c	24 520		
34 573 15 475	35.89	54.17	-23.05	58.87	1.2196	-0.6923	336.9	-1 528c	25 528	Mm	
36 580 16 480	32.54	51.05	-28.93	58.68	1.2433	-0.791	330.4	-1 537c	27 537		
39 595 17 485	25.64	40.25	-38.09	55.42	1.2439	-1.0297	316.5	-1 548c	29 548		
-1 490c	18 490	13.81	0.33	-52.17	52.17	0.6255	-1.946	270.3	11 459	33 565	min
-1 495c	19 495	14.98	-2.04	-51.84	51.88	0.5613	-1.8194	267.7	12 462	33 566	
-1 500c	20 500	16.44	-4.93	-50.98	51.22	0.4959	-1.6753	264.4	12 464	33 567	
-1 510c	22 510	20.44	-12.31	-47.59	49.16	0.3749	-1.3665	255.4	13 469	33 569	
-1 519c	23 510	23.0	-16.66	-45.09	48.07	0.3262	-1.2194	249.7	14 471	34 570	Bm
-1 529c	25 530	29.18	-26.04	-38.71	46.66	0.2589	-0.9661	236.0	15 475	34 573	
-1 539c	27 540	36.29	-35.07	-31.16	46.92	0.2292	-0.7789	221.6	15 478	35 577	
-1 544c	28 545	40.0	-39.05	-27.17	47.57	0.2253	-0.7071	214.8	15 479	35 579	
-1 549c	29 550	43.78	-42.55	-23.08	48.41	0.2271	-0.6463	208.4	16 480	36 582	
-1 554c	30 555	47.56	-45.44	-18.99	49.25	0.2337	-0.5951	202.6	16 481	36 584	
-1 560c	32 560	54.87	-48.97	-11.06	50.21	0.2588	-0.5161	192.7	16 483	37 589	
W0	380 770	90.0	0.0	0.0	0.0	0.6159	-0.3265	0.0	B _c =0,750		
N0	380 770	3.6	0.0	0.0	0.0	0.6159	-0.3265	0.0	x _c =0,110		

Technische Information: <http://farbe.li.tu-berlin.de> oder <http://color.li.tu-berlin.de>
 Siehe ähnliche Dateien der ganzen Serie: <http://farbe.li.tu-berlin.de/egus.htm>

TUB-Registrierung: 20230701-egu4/egu4I0na.txt /ps
 Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe
 TUB-Material: Code=rh4ta