

see similar files of the whole serie: <http://farbe.li.tu-berlin.de/fens.htm>
 technical information: <http://farbe.li.tu-berlin.de/A/33872E.htm>
 or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fen2/fen210fa.txt /.ps
 application for evaluation and measurement of display or print output
 TUB material: code=rh4ta

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*
1	0.0	0.0	0.0	0.0	0.01
2	6.36	0.0	0.07	6.36	0.01
3	12.72	0.0	0.13	12.72	0.01
4	19.08	0.0	0.2	19.08	0.01
5	25.44	0.0	0.27	25.44	0.01
6	31.8	0.0	0.33	31.8	0.01
7	38.16	0.0	0.4	38.16	0.01
8	44.52	0.0	0.47	44.52	0.01
9	50.89	0.0	0.53	50.89	0.01
10	57.25	0.0	0.6	57.25	0.01
11	63.61	0.0	0.67	63.61	0.01
12	69.97	0.0	0.73	69.97	0.01
13	76.33	0.0	0.8	76.33	0.01
14	82.69	0.0	0.87	82.69	0.01
15	89.05	0.0	0.93	89.05	0.01
16	95.41	0.0	1.0	95.41	0.01
17	0.0	0.0	0.0	0.0	0.01
18	23.85	0.0	0.25	23.85	0.01
19	47.71	0.0	0.5	47.71	0.01
20	71.56	0.0	0.75	71.56	0.01
21	95.41	0.0	1.0	95.41	0.01


Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps)
 $\Delta E^*_{CIELAB} = 0.0$

Mean lightness difference (5 steps)
 $\Delta L^*_{CIELAB} = 0.0$

Mean colour reproduction index: $R^*_{ab,m} = 100$

fen20-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen21-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{intended}$ (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
$w^* w^* w^*$ setrgb gp=1.0																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*_{CIELAB, r}$ (relative)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0

fen20-7N-130-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

TUB-test chart fen2; fen2: In-output relation according to ISO 9241-306; 1MR, DH000n/w/cmy0/rgb
 Viewing Y contrast $Y_W:Y_N=88,9:0,31$; Y_N range 0,0 to <0,46, L-HDR; $\gamma_R=1,56$ ->rgb*d, 130-2:

see similar files of the whole serie: <http://farbe.li.tu-berlin.de/fens.htm>
technical information: <http://farbe.li.tu-berlin.de/A/33872E.htm>
or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fen2/fen210fa.txt /.ps
application for evaluation and measurement of display or print output
TUB material: code=rh4ta

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*				
1	5.69	0.0	0.0	5.69	0.0	0.0	0.0	0.0	0.01
2	11.67	0.0	0.0	14.73	0.0	0.0	3.06	0.0	3.06
3	17.65	0.0	0.0	21.96	0.0	0.0	4.3	0.0	4.3
4	23.63	0.0	0.0	28.63	0.0	0.0	4.99	0.0	4.99
5	29.62	0.0	0.0	34.96	0.0	0.0	5.34	0.0	5.34
6	35.6	0.0	0.0	41.05	0.0	0.0	5.46	0.0	5.46
7	41.58	0.0	0.0	46.96	0.0	0.0	5.38	0.0	5.38
8	47.56	0.0	0.0	52.72	0.0	0.0	5.16	0.0	5.16
9	53.54	0.0	0.0	58.36	0.0	0.0	4.82	0.0	4.82
10	59.52	0.0	0.0	63.88	0.0	0.0	4.36	0.0	4.36
11	65.5	0.0	0.0	69.32	0.0	0.0	3.82	0.0	3.82
12	71.48	0.0	0.0	74.67	0.0	0.0	3.19	0.0	3.19
13	77.47	0.0	0.0	79.95	0.0	0.0	2.49	0.0	2.49
14	83.45	0.0	0.0	85.16	0.0	0.0	1.72	0.0	1.72
15	89.43	0.0	0.0	90.31	0.0	0.0	0.89	0.0	0.89
16	95.41	0.0	0.0	95.41	0.0	0.0	0.0	0.0	0.01
17	5.69	0.0	0.0	5.69	0.0	0.0	0.0	0.0	0.01
18	28.12	0.0	0.0	33.4	0.0	0.0	5.28	0.0	5.28
19	50.55	0.0	0.0	55.55	0.0	0.0	5.0	0.0	5.0
20	72.98	0.0	0.0	76.0	0.0	0.0	3.02	0.0	3.02
21	95.41	0.0	0.0	95.41	0.0	0.0	0.0	0.0	0.01


Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps)
 $\Delta E^*_{CIELAB} = 3.4$

Mean lightness difference (5 steps)
 $\Delta L^*_{CIELAB} = 2.7$

Mean colour reproduction index: $R^*_{ab,m} = 85$

fen20-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen21-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{intended}$ (absolute)	5.7/0.6	11.7/1.4	17.7/2.4	23.6/4.0	29.6/6.1	35.6/8.8	41.6/12.2	47.6/16.5	53.5/21.5	59.5/27.6	65.5/34.7	71.5/42.9	77.5/52.3	83.4/63.0	89.4/75.1	95.4/88.6
w^*_{setrgb}	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*_{CIELAB, r}$ (relative)	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
$w^*_{intended}$	0,0	0,082	0,155	0,226	0,295	0,362	0,428	0,494	0,559	0,623	0,688	0,75	0,814	0,876	0,938	1,0
w^*_{out}	0,0	0,082	0,155	0,226	0,295	0,362	0,428	0,494	0,559	0,623	0,688	0,75	0,814	0,876	0,938	1,0

fen20-7N-131-2: 16 visual equidistant L^* -grey steps; PS operator: $w^*_{setrgbcolor}$

TUB-test chart fen2; fen2: In-output relation according to ISO 9241-306; 1MR, DH000n/w/cmy0/rgb
Viewing Y contrast $Y_W:Y_N=88,9:0,62$; Y_N range 0,46 to <0,93, L-HDR; $\gamma_R=1,56$ -> $rgb^*_d, 131-2$

see similar files of the whole serie: <http://farbe.li.tu-berlin.de/fens.htm>
 technical information: <http://farbe.li.tu-berlin.de/A/33872E.htm>
 or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fen2/fen210fa.txt /.ps
 application for evaluation and measurement of display or print output
 TUB material: code=rh4ta

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*
1	10.99	0.0	0.0	10.99	0.0
2	16.62	0.0	0.14	22.52	0.0
3	22.25	0.0	0.23	30.18	0.0
4	27.88	0.0	0.31	36.84	0.0
5	33.5	0.0	0.38	42.93	0.0
6	39.13	0.0	0.45	48.63	0.0
7	44.76	0.0	0.51	54.03	0.0
8	50.39	0.0	0.57	59.19	0.0
9	56.02	0.0	0.63	64.17	0.0
10	61.64	0.0	0.69	68.98	0.0
11	67.27	0.0	0.74	73.65	0.0
12	72.9	0.0	0.8	78.2	0.0
13	78.53	0.0	0.85	82.64	0.0
14	84.15	0.0	0.9	86.98	0.0
15	89.78	0.0	0.95	91.23	0.0
16	95.41	0.0	1.0	95.41	0.0
17	10.99	0.0	0.0	10.99	0.0
18	32.1	0.0	0.36	41.45	0.0
19	53.2	0.0	0.6	61.7	0.0
20	74.31	0.0	0.81	79.32	0.0
21	95.41	0.0	1.0	95.41	0.0


Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps)
 $\Delta E^*_{CIELAB} = 6.0$

Mean lightness difference (5 steps)
 $\Delta L^*_{CIELAB} = 4.6$

Mean colour reproduction index: $R^*_{ab,m} = 74$

fen20-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen21-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{intended}$ (absolute)	11.0/1.3	16.6/2.2	22.2/3.6	27.9/5.4	33.5/7.8	39.1/10.7	44.8/14.4	50.4/18.7	56.0/23.9	61.6/30.0	67.3/37.0	72.9/45.0	78.5/54.1	84.2/64.4	89.8/75.8	95.4/88.6
w^*_{setrgb}	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*_{CIELAB, r}$ (relative)	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
$w^*_{intended}$	0.0	0.1	0.18	0.255	0.325	0.393	0.459	0.524	0.586	0.648	0.709	0.768	0.827	0.886	0.943	1.0
w^*_{out}	0.0	0.1	0.18	0.255	0.325	0.393	0.459	0.524	0.586	0.648	0.709	0.768	0.827	0.886	0.943	1.0

fen20-7N-132-2: 16 visual equidistant L^* -grey steps; PS operator: w^*_{setrgb}

TUB-test chart fen2; fen2: In-output relation according to ISO 9241-306; 1MR, DH000n/w/cmy0/rgb
 Viewing Y contrast $Y_W:Y_N=88,9:1,25$; Y_N range 0,93 to <1,87, L-HDR; $\gamma_R=1,56$ ->rgb*d, 132-2:

see similar files of the whole serie: <http://farbe.li.tu-berlin.de/fens.htm>
 technical information: <http://farbe.li.tu-berlin.de/A/33872E.htm>
 or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fen2/fen210fa.txt /.ps
 application for evaluation and measurement of display or print output
 TUB material: code=rh4ta

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*					
1	18.01	0.0	0.0	18.01	0.0	0.0	0.0	0.0	0.01	
2	23.17	0.0	0.0	0.17	31.35	0.0	0.0	8.18	0.0	8.18
3	28.33	0.0	0.0	0.27	38.93	0.0	0.0	10.6	0.0	10.6
4	33.49	0.0	0.0	0.35	45.23	0.0	0.0	11.74	0.0	11.74
5	38.65	0.0	0.0	0.42	50.82	0.0	0.0	12.17	0.0	12.17
6	43.81	0.0	0.0	0.49	55.93	0.0	0.0	12.12	0.0	12.12
7	48.97	0.0	0.0	0.55	60.7	0.0	0.0	11.73	0.0	11.73
8	54.13	0.0	0.0	0.61	65.2	0.0	0.0	11.07	0.0	11.07
9	59.29	0.0	0.0	0.66	69.47	0.0	0.0	10.18	0.0	10.18
10	64.45	0.0	0.0	0.72	73.56	0.0	0.0	9.11	0.0	9.11
11	69.61	0.0	0.0	0.77	77.49	0.0	0.0	7.88	0.0	7.88
12	74.77	0.0	0.0	0.82	81.29	0.0	0.0	6.52	0.0	6.52
13	79.93	0.0	0.0	0.87	84.97	0.0	0.0	5.04	0.0	5.04
14	85.09	0.0	0.0	0.91	88.54	0.0	0.0	3.45	0.0	3.45
15	90.25	0.0	0.0	0.96	92.02	0.0	0.0	1.77	0.0	1.77
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01
17	18.01	0.0	0.0	18.01	0.0	0.0	0.0	0.0	0.0	0.01
18	37.36	0.0	0.0	0.41	49.47	0.0	0.0	12.11	0.0	12.11
19	56.71	0.0	0.0	0.64	67.36	0.0	0.0	10.65	0.0	10.65
20	76.06	0.0	0.0	0.83	82.22	0.0	0.0	6.16	0.0	6.16
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01


Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps)
 $\Delta E^*_{CIELAB} = 7.6$

Mean lightness difference (5 steps)
 $\Delta L^*_{CIELAB} = 5.8$

Mean colour reproduction index: $R^*_{ab,m} = 67$

fen20-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen21-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.4	69.6/40.2	74.8/47.9	79.9/56.6	85.1/66.2	90.2/76.8	95.4/88.6
$w^* w^* w^*$ setrgb	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*_{CIELAB, r}$ (relative)	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
$w^*_{intended}$	0,0	0,123	0,209	0,287	0,359	0,426	0,492	0,554	0,614	0,673	0,731	0,786	0,841	0,895	0,948	1,0
w^*_{out}	0,0	0,123	0,209	0,287	0,359	0,426	0,492	0,554	0,614	0,673	0,731	0,786	0,841	0,895	0,948	1,0

fen20-7N-133-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

TUB-test chart fen2; fen2: In-output relation according to ISO 9241-306; 1MR, DH000n/w/cmy0/rgb
 Viewing Y contrast $Y_W:Y_N=88,9:2,5$; Y_N range 1,87 to <3,75, L-HDR; $\gamma_R=1,56$ ->rgb*d, 133-2:

see similar files of the whole serie: <http://farbe.li.tu-berlin.de/fens.htm>
technical information: <http://farbe.li.tu-berlin.de/A/33872E.htm>
or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fen2/fen210fa.txt /.ps
application for evaluation and measurement of display or print output
TUB material: code=rh4ta

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*	Start output S1
1	26.85	0.0	0.0	26.85	0.0	0.0
2	31.42	0.0	0.21	41.05	0.0	9.63
3	35.99	0.0	0.31	48.1	0.0	12.11
4	40.56	0.0	0.39	53.75	0.0	13.18
5	45.13	0.0	0.46	58.64	0.0	13.51
6	49.7	0.0	0.53	63.05	0.0	13.34
7	54.27	0.0	0.59	67.09	0.0	12.82
8	58.84	0.0	0.64	70.87	0.0	12.02
9	63.41	0.0	0.69	74.42	0.0	11.01
10	67.99	0.0	0.74	77.79	0.0	9.81
11	72.56	0.0	0.79	81.01	0.0	8.46
12	77.13	0.0	0.84	84.1	0.0	6.97
13	81.7	0.0	0.88	87.07	0.0	5.37
14	86.27	0.0	0.92	89.94	0.0	3.67
15	90.84	0.0	0.96	92.71	0.0	1.88
16	95.41	0.0	1.0	95.41	0.0	0.01
17	26.85	0.0	0.0	26.85	0.0	0.01
18	43.99	0.0	0.45	57.47	0.0	13.48
19	61.13	0.0	0.67	72.67	0.0	11.54
20	78.27	0.0	0.85	84.85	0.0	6.58
21	95.41	0.0	1.0	95.41	0.0	0.01


Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps) $\Delta E^*_{CIELAB} = 8.4$

Mean lightness difference (5 steps) $\Delta L^*_{CIELAB} = 6.3$

Mean colour reproduction index: $R^*_{ab,m} = 64$

fen20-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen21-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	26.8/5.0	31.4/6.8	36.0/9.0	40.6/11.6	45.1/14.6	49.7/18.2	54.3/22.2	58.8/26.9	63.4/32.1	68.0/38.0	72.6/44.5	77.1/51.7	81.7/59.7	86.3/68.5	90.8/78.1	95.4/88.6
$w^* w^* w^*$ setrgb																
gp=0.7																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*_{CIELAB, r}$ (relative)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,151	0,244	0,324	0,397	0,463	0,527	0,587	0,644	0,699	0,753	0,805	0,855	0,905	0,953	1,0

fen20-7N-134-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

TUB-test chart fen2; fen2: In-output relation according to ISO 9241-306; 1MR, DH000n/w/cmy0/rgb
Viewing Y contrast $Y_W:Y_N=88,9:5$; Y_N range 3,75 to <7,5, L-HDR; $\gamma_R=1,56$ ->rgb*d, 134-2:

see similar files of the whole serie: <http://farbe.li.tu-berlin.de/fens.htm>
technical information: <http://farbe.li.tu-berlin.de/A/33872E.htm>
or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fen2/fen210fa.txt /.ps
application for evaluation and measurement of display or print output
TUB material: code=rh4ta

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*	Start output S1
1	37.99	0.0	0.0	37.99	0.0	0.0
2	41.81	0.0	0.0	51.79	0.0	9.98
3	45.64	0.0	0.0	57.87	0.0	12.23
4	49.47	0.0	0.0	62.6	0.0	13.13
5	53.3	0.0	0.0	66.63	0.0	13.33
6	57.13	0.0	0.0	70.19	0.0	13.07
7	60.96	0.0	0.0	73.44	0.0	12.48
8	64.78	0.0	0.0	76.44	0.0	11.65
9	68.61	0.0	0.0	79.23	0.0	10.62
10	72.44	0.0	0.0	81.87	0.0	9.43
11	76.27	0.0	0.0	84.37	0.0	8.11
12	80.1	0.0	0.0	86.76	0.0	6.66
13	83.93	0.0	0.0	89.05	0.0	5.12
14	87.75	0.0	0.0	91.24	0.0	3.49
15	91.58	0.0	0.0	93.36	0.0	1.78
16	95.41	0.0	0.0	95.41	0.0	0.01
17	37.99	0.0	0.0	37.99	0.0	0.01
18	52.34	0.0	0.0	65.67	0.0	13.33
19	66.7	0.0	0.0	77.86	0.0	11.16
20	81.05	0.0	0.0	87.34	0.0	6.29
21	95.41	0.0	0.0	95.41	0.0	0.01


Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps) $\Delta E^*_{CIELAB} = 8.2$


Mean lightness difference (5 steps) $\Delta L^*_{CIELAB} = 6.2$

Mean colour reproduction index: $R^*_{ab,m} = 65$

fen20-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen21-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



TUB-test chart fen2; fen2: In-output relation according to ISO 9241-306; 1MR, DH000n/w/cmy0/rgb
Viewing Y contrast $Y_W:Y_N=88,9:10$; Y_N range 7,5 to <15, L-HDR; $\gamma_R=1,56$ -> $rgb^*_d, 135-2$

see similar files of the whole serie: <http://farbe.li.tu-berlin.de/fens.htm>
technical information: <http://farbe.li.tu-berlin.de/A/33872E.htm>
or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fen2/fen210fa.txt /.ps
application for evaluation and measurement of display or print output
TUB material: code=rh4ta

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*
1	52.02	0.0	0.0	52.02	0.0
2	54.91	0.0	0.27	63.82	0.0
3	57.8	0.0	0.38	68.49	0.0
4	60.7	0.0	0.46	72.03	0.0
5	63.59	0.0	0.53	75.0	0.0
6	66.48	0.0	0.59	77.61	0.0
7	69.37	0.0	0.64	79.95	0.0
8	72.27	0.0	0.69	82.1	0.0
9	75.16	0.0	0.74	84.09	0.0
10	78.05	0.0	0.78	85.96	0.0
11	80.95	0.0	0.82	87.72	0.0
12	83.84	0.0	0.86	89.4	0.0
13	86.73	0.0	0.9	91.0	0.0
14	89.62	0.0	0.93	92.53	0.0
15	92.52	0.0	0.97	93.99	0.0
16	95.41	0.0	1.0	95.41	0.0
17	52.02	0.0	0.0	52.02	0.0
18	62.87	0.0	0.51	74.3	0.0
19	73.71	0.0	0.72	83.11	0.0
20	84.56	0.0	0.87	89.81	0.0
21	95.41	0.0	1.0	95.41	0.0


Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps)
 $\Delta E^*_{CIELAB} = 7.0$

Mean lightness difference (5 steps)
 $\Delta L^*_{CIELAB} = 5.2$

Mean colour reproduction index: $R^*_{ab,m} = 70$

fen20-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen21-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	52.0/20.2	54.9/22.8	57.8/25.8	60.7/28.9	63.6/32.3	66.5/36.0	69.4/39.9	72.3/44.1	75.2/48.5	78.1/53.3	80.9/58.4	83.8/63.8	86.7/69.5	89.6/75.5	92.5/81.9	95.4/88.6
$w^* w^* w^*$ setrgb	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*_{CIELAB, r}$ (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
$w^*_{intended}$	0.0	0.226	0.33	0.413	0.484	0.546	0.604	0.658	0.707	0.755	0.8	0.843	0.885	0.925	0.963	1.0
w^*_{out}																

fen20-7N-136-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

TUB-test chart fen2; fen2: In-output relation according to ISO 9241-306; 1MR, DH000n/w/cmy0/rgb
Viewing Y contrast $Y_W:Y_N=88,9:20$; Y_N range 15 to <30, L-HDR; $\gamma_R=1,56$ ->rgb*d, 136-2:

see similar files of the whole serie: <http://farbe.li.tu-berlin.de/fens.htm>
technical information: <http://farbe.li.tu-berlin.de/A/33872E.htm>
or <http://standards.iso.org/iso/9241/306/ed-2/index.html>

TUB registration: 20240301-fen2/fen210fa.txt /.ps
application for evaluation and measurement of display or print output
TUB material: code=rh4ta


i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE^*	Start output S1
1	69.7	0.0	0.0	69.7 0.0 0.0	0.0 0.0 0.0	0.01
2	71.41	0.0	0.3	77.46 0.0 0.0	6.04 0.0 0.0	6.04
3	73.13	0.0	0.41	80.24 0.0 0.0	7.11 0.0 0.0	7.11
4	74.84	0.0	0.49	82.31 0.0 0.0	7.47 0.0 0.0	7.47
5	76.55	0.0	0.56	84.02 0.0 0.0	7.47 0.0 0.0	7.47
6	78.27	0.0	0.62	85.51 0.0 0.0	7.24 0.0 0.0	7.24
7	79.98	0.0	0.67	86.84 0.0 0.0	6.86 0.0 0.0	6.86
8	81.7	0.0	0.71	88.05 0.0 0.0	6.35 0.0 0.0	6.35
9	83.41	0.0	0.76	89.17 0.0 0.0	5.76 0.0 0.0	5.76
10	85.12	0.0	0.8	90.21 0.0 0.0	5.08 0.0 0.0	5.08
11	86.84	0.0	0.84	91.19 0.0 0.0	4.35 0.0 0.0	4.35
12	88.55	0.0	0.87	92.11 0.0 0.0	3.56 0.0 0.0	3.56
13	90.27	0.0	0.91	92.99 0.0 0.0	2.73 0.0 0.0	2.73
14	91.98	0.0	0.94	93.83 0.0 0.0	1.85 0.0 0.0	1.85
15	93.7	0.0	0.97	94.64 0.0 0.0	0.94 0.0 0.0	0.94
16	95.41	0.0	1.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01
17	69.7	0.0	0.0	69.7 0.0 0.0	0.0 0.0 0.0	0.01
18	76.13	0.0	0.54	83.62 0.0 0.0	7.5 0.0 0.0	7.5
19	82.55	0.0	0.74	88.62 0.0 0.0	6.06 0.0 0.0	6.06
20	88.98	0.0	0.88	92.34 0.0 0.0	3.35 0.0 0.0	3.35
21	95.41	0.0	1.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01

Mean lightness difference (16 steps)
 $\Delta E^*_{CIELAB} = 4.6$


Mean lightness difference (5 steps)
 $\Delta L^*_{CIELAB} = 3.4$

Mean colour reproduction index: $R^*_{ab,m} = 80$

fen20-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen21-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



fen20-7N-137-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*_{setrgbcolor}$

TUB-test chart fen2; fen2: In-output relation according to ISO 9241-306; 1MR, DH000n/w/cmy0/rgb
Viewing Y contrast $Y_W:Y_N=88,9:40$; Y_N range 30 to <60, L-HDR; $\gamma_R=1,56$ -> $rgb^*_d, 137-2$